


WEBENCH® Design Report


VinMin = 3.0V VinMax = 4.2V Vout = 3.0V Iout = 0.42A Device = TPS63024YFFR
Topology = Buck_Boost
Created = 2021-07-26 17:41:18.508
BOM Cost = \$1.42
BOM Count = 7
Total Pd = 0.05W


TPS63024YFFR 3V-4.2V to 3.00V @ 0.425A




Electrical BOM

| # | Name | Manufacturer | Part Number | Properties | Qty | Price | Footprint |
|----|-------|-------------------|------------------------------------|---|-----|--------|-----------------------------|
| 1. | Cin | MuRata | GRM188R60J106ME47D Series= X5R | Cap= 10.0 uF ESR= 9.0 mOhm VDC= 6.3 V IRMS= 2.74 A | 1 | \$0.08 | 0603 5 mm ² |
| 2. | Cout | MuRata | GRM31CC80J476KE18L Series= X6S | Cap= 47.0 uF ESR= 3.735 mOhm VDC= 6.3 V IRMS= 4.0522 A | 1 | \$0.20 | 1206_190 11 mm ² |
| 3. | Coutx | MuRata | GRM188R60J106ME47D Series= X5R | Cap= 10.0 uF ESR= 9.0 mOhm VDC= 6.3 V IRMS= 2.74 A | 1 | \$0.08 | 0603 5 mm ² |
| 4. | L1 | Bourns | SRN6045-1R0Y | L= 1.0 μH DCR= 13.9 mOhm | 1 | \$0.20 | SRN6045 64 mm ² |
| 5. | Rfbb | Vishay-Dale | CRCW0603182KFKEA Series= CRCWe3 | Res= 182000.00hm Power= 100.0 mW Tolerance= 1.0% | 1 | \$0.01 | 0603 5 mm ² |
| 6. | Rfbt | Vishay-Dale | CRCW0603499KFKEA Series= CRCWe3 | Res= 499000.00hm Power= 100.0 mW Tolerance= 1.0% | 1 | \$0.01 | 0603 5 mm ² |
| 7. | U1 | Texas Instruments | TPS63024YFFR | Switcher | 1 | \$0.84 | YFF0020AEBA 9 mm² |







Operating Values

| # | Name | Value | Category | Description |
|-----|------------|-------------|-----------|---|
| 1. | Cin IRMS | 6.789 mA | Capacitor | Input capacitor RMS ripple current |
| 2. | Cin Pd | 414.8 nW | Capacitor | Input capacitor power dissipation |
| 3. | Cout IRMS | 55.075 mA | Capacitor | Output capacitor RMS ripple current |
| 4. | Cout Pd | 0.0 W | Capacitor | Output capacitor power dissipation |
| 5. | Coutx IRMS | 9.203 mA | Capacitor | Output capacitor_x RMS ripple current |
| 6. | Coutx Pd | 0.0 W | Capacitor | Output capacitor_x power loss |
| 7. | IC lpk | 459.321 mA | IC | Peak switch current in IC |
| 8. | IC Pd | 48.343 mW | IC | IC power dissipation |
| 9. | IC Tj | 32.601 degC | IC | IC junction temperature |
| 10. | ICThetaJA | 53.8 degC/W | IC | IC junction-to-ambient thermal resistance |
| 11. | lin Avg | 442.05 mA | IC | Average input current |

| # | Name | Value | Category | Description |
|-----|----------------|-----------------------|-------------|--|
| 12. | L lpp | 23.517 mA | Inductor | Peak-to-peak inductor ripple current |
| 13. | L Pd | 2.785 mW | Inductor | Inductor power dissipation |
| 14. | Cin Pd | 414.8 nW | Power | Input capacitor power dissipation |
| 15. | Cout Pd | 0.0 W | Power | Output capacitor power dissipation |
| 16. | Coutx Pd | 0.0 W | Power | Output capacitor_x power loss |
| 17. | IC Pd | 48.343 mW | Power | IC power dissipation |
| 18. | L Pd | 2.785 mW | Power | Inductor power dissipation |
| 19. | Total Pd | 51.136 mW | Power | Total Power Dissipation |
| 20. | BOM Count | 7 | System | Total Design BOM count |
| | | | Information | |
| 21. | Duty Cycle | 1.986 % | System | Duty cycle |
| | | | Information | |
| 22. | Efficiency | 96.144 % | System | Steady state efficiency |
| | | | Information | |
| 23. | FootPrint | 102.0 mm ² | System | Total Foot Print Area of BOM components |
| | | | Information | |
| 24. | Frequency | 2.5 MHz | System | Switching frequency |
| | | | Information | |
| 25. | lout | 425.0 mA | System | lout operating point |
| | | | Information | |
| 26. | Mode | BOOST PWM CCM | System | PWM/PFM Mode |
| | | | Information | |
| 27. | Pout | 1.275 W | System | Total output power |
| | | | Information | |
| 28. | Total BOM | \$1.42 | System | Total BOM Cost |
| | | | Information | |
| 29. | Vin | 3.0 V | System | Vin operating point |
| | | | Information | |
| 30. | Vout Actual | 2.993 V | System | Vout Actual calculated based on selected voltage divider resistors |
| | | | Information | |
| 31. | Vout Tolerance | 1.48 % | System | Vout Tolerance based on IC Tolerance (no load) and voltage divider |
| | | | Information | resistors if applicable |
| 32. | Vout p-p | 105.758 μV | System | Peak-to-peak output ripple voltage |
| | | | Information | |

Design Inputs

| # | Name | Value | Description | | |
|----|-------------|----------|------------------------|--|--|
| 1. | lout | 425.0 m | Maximum Output Current | | |
| 2. | VinMax | 4.2 | Maximum input voltage | | |
| 3. | VinMin | 3.0 | Minimum input voltage | | |
| 4. | VinTyp | 3.7 | Typical input voltage | | |
| 5. | Vout | 3.0 | Output Voltage | | |
| 6. | acFrequency | 60.0 | AC Frequency | | |
| 7. | base_pn | TPS63024 | Base Product Number | | |
| 8. | source | DC | Input Source Type | | |
| 9. | Та | 30.0 | Ambient temperature | | |

Design Assistance

1. TPS63024 Product Folder: http://www.ti.com/product/TPS63024: contains the data sheet and other resources.

Important Notice and Disclaimer

TI provides technical and reliability data (including datasheets), design resources (including reference designs), application or other design advice, web tools, safety information, and other resources AS IS and with all faults, and disclaims all warranties. These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

Providing these resources does not expand or otherwise alter TI's applicable Terms of Sale or other applicable terms available either on ti.com or provided in conjunction with TI products.