

Cisco Packet Tracer - C:\Users\dalib\Downloads\tds.pkt

File Edit Options View Tools Extensions Window Help

Logical Physical x m-y 279

1. Настроить сеть согласно схеме.  
2. Проверить работоспособность соседних сетей между собой командой ping  
3. Обвести синими все broadcast-адреса.  
4. Настроить loop back интерфейсы.

10.0.0.10

Physical Config Desktop Programming Attributes

Command Prompt

Cisco Packet Tracer PC Command Line 1.0

C:\>ping 172.17.0.1

Pinging 172.17.0.1 with 32 bytes of data:

Request timed out.

Request timed out.

Request timed out.

Request timed out.

Ping statistics for 172.17.0.1:

Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\>ping 10.0.0.1

Pinging 10.0.0.1 with 32 bytes of data:

Reply from 10.0.0.1: bytes=32 time=1ms TTL=64

Reply from 10.0.0.1: bytes=32 time=1ms TTL=64

Reply from 10.0.0.1: bytes=32 time=1ms TTL=64

Reply from 10.0.0.1: bytes=32 time=1ms TTL=64

Ping statistics for 10.0.0.1:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milliseconds:

Minimum = 0ms, Maximum = 1ms, Average = 0ms

C:\>

Time: 00:00:10

Realtime Simulation

Scenario 0

Fire Last Status Source Destination Type Color Time(sec) Periodic Num Edit Delete

Toggle PDU List Window

Fiber

16:43 10.08.2023

Cisco Packet Tracer - C:\Users\dalib\Downloads\tds.pkt

File Edit Options View Tools Extensions Window Help

Logical Physical x m-y 279

1. Настроить сеть согласно схеме.  
2. Проверить работоспособность соседних сетей между собой командой ping  
3. Обвести синими все broadcast-адреса.  
4. Настроить loop back интерфейсы.

10.0.0.10

Physical Config Desktop Programming Attributes

Command Prompt

Ping statistics for 192.168.0.1:

Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\>ping 192.168.0.2

Pinging 192.168.0.2 with 32 bytes of data:

Ping statistics for 192.168.0.2:

Packets: Sent = 1, Received = 0, Lost = 1 (100% loss),

Control-C

C:\>ping 192.168.0.1

Pinging 192.168.0.1 with 32 bytes of data:

Request timed out.

Ping statistics for 192.168.0.1:

Packets: Sent = 2, Received = 0, Lost = 2 (100% loss),

Control-C

C:\>ping 192.168.0.1

Pinging 192.168.0.1 with 32 bytes of data:

Reply from 192.168.0.1: bytes=32 time=1ms TTL=64

Reply from 192.168.0.1: bytes=32 time=1ms TTL=64

Reply from 192.168.0.1: bytes=32 time=1ms TTL=64

Reply from 192.168.0.1: bytes=32 time=1ms TTL=64

Ping statistics for 192.168.0.1:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milliseconds:

Minimum = 0ms, Maximum = 1ms, Average = 0ms

C:\>

Time: 00:42:44

Realtime Simulation

Scenario 0

Fire Last Status Source Destination Type Color Time(sec) Periodic Num Edit Delete

Toggle PDU List Window

Fiber

17:25 10.08.2023

