

```

    }
    return true;
  case "ACH":
    if ( _callOnChange_xjal ) {
      set_ACH( ((Number)
      _value_xjal).doubleValue() );
    } else {
      ACH = ((Number) _value_xjal).doubleValue();
    }
    return true;
  case "No_People":
    if ( _callOnChange_xjal ) {
      set_No_People( ((Number)
      _value_xjal).doubleValue() );
    } else {
      No_People = ((Number)
      _value_xjal).doubleValue();
    }
    return true;
  default:
    return super.setParameter( _name_xjal,
    _value_xjal, _callOnChange_xjal );
  }
}

```

Acknowledgement

The authors wish to thank the Department of Building and Real Estate, The Hong Kong Polytechnic University for funding this research.

Appendix

(Table A1 and Table A2)

References

- [1] Jeong W, Kim KH. A performance evaluation of the BIM-based object-oriented physical modeling technique for building thermal simulations: A comparative case study. *Sustainability (Switzerland)* 2016;8(7):1–27. doi: <https://doi.org/10.3390/su07070648>.
- [2] Kassem M, Succar B. Macro BIM adoption: Comparative market analysis. (*Report*). *Autom Constr* 2017;81(286). doi: <https://doi.org/10.1016/j.autcon.2017.04.005>.
- [3] Ng H. The Influence of Building Information Modelling (BIM) towards Return on Investment (ROI) from the Perspective of Malaysian Developers: A Qualitative Approach. *MATEC Web of Conferences* 2019;266. doi: <https://doi.org/10.1051/matecconf/201926605007>.
- [4] Ramli H, Ismail E, Shaza R, Idris N. A Review on Green BIM Potentials in Enhancing the Construction Industry Practice. *MATEC Web of Conferences* 2019;266. doi: <https://doi.org/10.1051/matecconf/201926601023>.
- [5] Thomas A. Modeling Occupant Behavior, Systems Life Cycle Performance, and Energy Consumption Nexus in Buildings Using Multi-Method Distributed Simulation. *Doctor of Philosophy (Civil Engineering), University of Michigan*; 2017.
- [6] Hong T, Langevin J, Sun K. Building simulation: Ten challenges. *Build. Simul.* 2018;11(5):871–98. doi: <https://doi.org/10.1007/s12273-018-0444-x>.
- [7] Hong T, Taylor-Lange SC, D'oca S, Yan D, Corgnati SP. Advances in research and applications of energy-related occupant behavior in buildings. In: *Energy & Buildings*, 116, C; 2016. p. 694–702. doi: <https://doi.org/10.1016/j.enbuild.2015.11.052>.
- [8] Zhang Y, Bai X, Mills FP, Pezzey JCV. Rethinking the role of occupant behavior in building energy performance: A review. *Energy Build* 2018;172:279–94. doi: <https://doi.org/10.1016/j.enbuild.2018.05.017>.
- [9] Yan D et al. Occupant behavior modeling for building performance simulation: Current state and future challenges. *Energy Build* 2015;107:264. doi: <https://doi.org/10.1016/j.enbuild.2015.08.032>.
- [10] Chen Y, Hong T, Xuan Luo. An agent-based stochastic Occupancy Simulator. *Building simulation* 2018;11(1):37–49. doi: <https://doi.org/10.1007/s12273-017-0379-7>.
- [11] Jia M, Srinivasan RS, Ries R, Weyer N, Bharathy G. A systematic development and validation approach to a novel agent-based modeling of occupant behaviors in commercial buildings. *Energy Build* 2019;199:352–67. doi: <https://doi.org/10.1016/j.enbuild.2019.07.009>.
- [12] Ligade J, Sebastian D, Razban A. Challenges of Creating a Verifiable Building Energy Model. *ASHRAE Transactions* 2019;125(1):20.
- [13] Jia M, Srinivasan RS, Raheem AA. From occupancy to occupant behavior: An analytical survey of data acquisition technologies, modeling methodologies and simulation coupling mechanisms for building energy efficiency. *Renew Sustain Energy Rev* 2017;68:525–40. doi: <https://doi.org/10.1016/j.rser.2016.10.011>.
- [14] Carnemanne T et al. Modeling Occupant-Building-Appliance Interaction for Energy Waste Analysis. *Procedia Eng* 2016;145:42–9. doi: <https://doi.org/10.1016/j.proeng.2016.04.012>.
- [15] Chen Y, Luo X, Hong T. An Agent-Based Occupancy Simulator for Building Performance Simulation. LBNL-1004492. eScholarship, University of California; 2016.
- [16] Hong T, Sun H, Chen Y, Taylor-Lange SC, Yan D. An occupant behavior modeling tool for co-simulation. *Energy Build* 2016;117 (C):272–81. doi: <https://doi.org/10.1016/j.enbuild.2015.10.033>.
- [17] Hong T, Koo C, Kim J, Lee M, Jeong K. A review on sustainable construction management strategies for monitoring, diagnosing, and retrofitting the building's dynamic energy performance: Focused on the operation and maintenance phase. *Appl Energy* 2015;155:671–707. doi: <https://doi.org/10.1016/j.apenergy.2015.06.043>.
- [18] Yan D et al. IEA EBC Annex 66: Definition and simulation of occupant behavior in buildings. *Energy Build* 2017;156:258–70. doi: <https://doi.org/10.1016/j.enbuild.2017.09.084>.
- [19] Zou PXW, Xu X, Sanjayan J, Wang J. A mixed methods design for building occupants' energy behavior research. *Energy Build* 2018;166:239–49. doi: <https://doi.org/10.1016/j.enbuild.2018.01.068>.
- [20] Haldi F, Robinson D. The impact of occupants' behaviour on building energy demand. *J Build Perform Simul* 2011;4(4):323–38. doi: <https://doi.org/10.1080/19401493.2011.558213>.
- [21] Feng X, Yan D, Hong T. Simulation of occupancy in buildings. *Energy Build* 2015;87 (C):348–59. doi: <https://doi.org/10.1016/j.enbuild.2014.11.067>.
- [22] Sun K, Hong T. A framework for quantifying the impact of occupant behavior on energy savings of energy conservation measures. In: *Energy & Buildings*, 146, C; 2017. p. 383–96. doi: <https://doi.org/10.1016/j.enbuild.2017.04.065>.

- [23] Ngowtanasuwan G, Hadikusumo BHW. System dynamics modelling for BIM adoption in Thai architectural and engineering design industry. *Construction Innovat* 2017;17(4):457–74. doi: <https://doi.org/10.1108/CI-03-2016-0018>.
- [24] Hajj-Hassan Mohamad, Khoury Hiam. BEHAVIORAL AND PARAMETRIC EFFECTS ON ENERGY CONSUMPTION THROUGH BIM, BEM, AND ABM. Proceedings of the Creative Construction Conference 2018:814–21. doi: <https://doi.org/10.3311/CCC2018-106>.
- [25] Hong T, Chen Y, Belafi Z, D’Oca S. Occupant behavior models: A critical review of implementation and representation approaches in building performance simulation programs. *Build. Simul.* 2018;11(1):1–14. doi: <https://doi.org/10.1007/s12273-017-0396-6>.
- [26] Thompson BP, Bank LC. Use of system dynamics as a decision-making tool in building design and operation. *Build. Environ.* 2010;45(4):1006–15. doi: <https://doi.org/10.1016/j.buildenv.2009.10.008>.
- [27] Paone A, Bacher J-P. The Impact of Building Occupant Behavior on Energy Efficiency and Methods to Influence It: A Review of the State of the Art. *Energies* 2018;11(4):953. doi: <https://doi.org/10.3390/en11040953>.
- [28] Kamaruzzaman SN, Egbu CO, Zawawi EMA, Ali AS, Che-Ani AI. The effect of indoor environmental quality on occupants' perception of performance: A case study of refurbished historic buildings in Malaysia. *Energy Build* 2011;43(2–3):407–13. doi: <https://doi.org/10.1016/j.enbuild.2010.10.003>.
- [29] Langevin J, Wen J, Gurian PL. Simulating the human-building interaction: Development and validation of an agent-based model of office occupant behaviors. *Build. Environ.* 2015;88:27–45. doi: <https://doi.org/10.1016/j.buildenv.2014.11.037>.
- [30] O’Brien W, Gaetani I, Gilani S, Carlucci S, Hoes P-J, Hensen J. International survey on current occupant modelling approaches in building performance simulation. *J Build Perform Simul* 2017;10(5–6):653–71. doi: <https://doi.org/10.1080/19401493.2016.1243731>.
- [31] Lee YS, Malkawi AM. Simulating multiple occupant behaviors in buildings: An agent-based modeling approach. *Energy Build* 2014;69:407–16. doi: <https://doi.org/10.1016/j.enbuild.2013.11.020>.
- [32] Tagliabue LC, Manfren M, Ciribini ALC, De Angelis E. Probabilistic behavioural modeling in building performance simulation—The Brescia eLUX lab. *Energy Build* 2016;128:119–31. doi: <https://doi.org/10.1016/j.enbuild.2016.06.083>.
- [33] Micolier A, Taillandier F, Taillandier P, Bos F. Li-BIM, an agent-based approach to simulate occupant-building interaction from the Building-Information Modelling. *Eng Appl Artif Intell* 2019;82:44–59. doi: <https://doi.org/10.1016/j.engappai.2019.03.008>.
- [34] Mitterhofer M, Schneider GF, Stratbucker S, Steiger S. Semantics for assembling modular components in a scalable building performance simulation. *J Build Perform Simul* 2018;12(2):145–59. doi: <https://doi.org/10.1080/19401493.2018.1492020>.
- [35] Naghshbandi SN. BIM for Facility Management: Challenges and Research Gaps. *Civil Eng J* 2016;2(12):679–84. doi: <https://doi.org/10.28991/cej-2016-0000067>.
- [36] Haider U, Khan U, Nazir A, Humayon M. Cost Comparison of a Building Project by Manual and BIM. *Civil Eng J* 2020;6(1):34–49. doi: <https://doi.org/10.28991/cej-2020-03091451>.
- [37] Putra H, Andrews C, Senick J. An agent-based model of building occupant behavior during load shedding. *Build. Simul.* 2017;10(6):845–59. doi: <https://doi.org/10.1007/s12273-017-0384-x>.
- [38] Anand P, Deb C, Alur R. A simplified tool for building layout design based on thermal comfort simulations. *Front Architect Res* 2017;6(2):218–30. doi: <https://doi.org/10.1016/j foar.2017.03.001>.
- [39] Sánchez-Barroso G, García Sanz-Calcedo J. Application of Predictive Maintenance in Hospital Heating, Ventilation and Air Conditioning Facilities. *Emerg Sci J* 2019;3(5):337–43. doi: <https://doi.org/10.28991/esj-2019-01196>.
- [40] Nikeghbali S, Damavandi A. Analysis of the Challenges and Technical Solutions for Revitalization of Traditional Buildings in Hot and Humid Climate (Case Study: Anthropology Museum of Local Residents in Kish Island). *Civil Eng J* 2018;4(10):2466. doi: <https://doi.org/10.28991/cej-03091173>.
- [41] Sang X, Pan W, Kumaraswamy MM. Informing Energy-efficient Building Envelope Design Decisions for Hong Kong. *Energy Procedia* 2014;62(C):123–31. doi: <https://doi.org/10.1016/j.egypro.2014.12.373>.
- [42] Uddin MN, Wei HH, Chi HL, Ni M. An Inquisition of Envelope Fabric for Building Energy Performance Using Prominent BIM-BPS Tools - A Case Study in Sub-Tropical Climate 2019;354. doi: <https://doi.org/10.1088/1755-1315/354/1/012129>.
- [43] Jung N, Paiho S, Shemeikka J, Lahdelma R, Airaksinen M. Energy performance analysis of an office building in three climate zones. *Energy Build* 2018;158:1023–35. doi: <https://doi.org/10.1016/j.enbuild.2017.10.030>.
- [44] Cheng JCP, Vincent L VJL. Integrating Agent-Based Human Behavior Simulation with Building Information Modeling for Building Design. *IJET* 5 2013;4:473–7. doi: <https://doi.org/10.7763/IJET.2013.V5.600>.
- [45] Kensek KM. Integration of Environmental Sensors with BIM: case studies using Arduino, Dynamo, and the Revit API. *Informes de la Construcción* 2014;66(536). doi: <https://doi.org/10.3989/ic.13.151e044>.
- [46] S. Mengana and T. Mousiadis, "Parametric BIM: Energy Performance Analysis Using Dynamo for Revit," ed, 2016. Available: <https://www.diva-portal.org/smash/get/diva2:1064171/FULLTEXT01.pdf>.
- [47] Givoni B. Effectiveness of mass and night ventilation in lowering the indoor daytime temperatures. Part I: 1993 experimental periods. *Energy & Buildings* 1998;28:1:25–32. doi: [https://doi.org/10.1016/S0378-7788\(97\)00056-X](https://doi.org/10.1016/S0378-7788(97)00056-X).
- [48] R. American Society of Heating and E. Air-Conditioning, 1985. ASHRAE handbook. Fundamentals. ASHRAE handb., Fundam. (SI ed.).
- [49] D. Sundarsingh and D. W. Bearg, "Indoor Air Quality in Schools (IAQ): The Importance of Monitoring Carbon Dioxide Levels," M. M. Design Share, Ed., ed, 2003.
- [50] Krawczyk DA, Żukowski M. Experimental verification of the CO₂ and temperature model. *Int J Vent* 2020;19(2):127–40. doi: <https://doi.org/10.1080/14733315.2019.1592333>.
- [51] Abanda FH, Byers L. An investigation of the impact of building orientation on energy consumption in a domestic building using emerging BIM (Building Information Modelling). *Energy* 2016;97(C):517–27. doi: <https://doi.org/10.1016/j.energy.2015.12.135>.
- [52] R. American Society of Heating and E. Air-Conditioning, Measurement of energy and demand savings. Atlanta, Ga.: ASHRAE, 2002.
- [53] (November, 2015). M&V Guidelines: Measurement and Verification for Performance-Based Contracts, Version 4.0. Available: https://www.energy.gov/sites/prod/files/2016/01/f28/mv_guide_4_0.pdf.
- [54] Ioannou A, Itard L. In-situ and real time measurements of thermal comfort and its determinants in thirty residential dwellings in the Netherlands. *Energy Build* 2017;139:487–505. doi: <https://doi.org/10.1016/j.enbuild.2017.01.050>.
- [55] S. I. u. H. Gilani, M. H. Khan, and W. Pao, 2015. Thermal Comfort Analysis of PMV Model Prediction in Air Conditioned and Naturally Ventilated Buildings. *Energy Procedia* 75:1373–1379. doi:10.1016/j.egypro.2015.07.218.
- [56] B. Arash and F. Steven, "A comparison of calculated and subjective thermal comfort sensation in home and office environment," ed, 2011. doi: 10.13140/2.1.4573.6327.
- [57] Becker R, Paciuk M. Thermal comfort in residential buildings – Failure to predict by Standard model. *Build Environ* 2009;44(5):948–60. doi: <https://doi.org/10.1016/j.buldevn.2008.06.011>.
- [58] Strachan P, Svehla K, Heusler I, Kersken M. Whole model empirical validation on a full-scale building. *J Build Perform Simul* 2016;9(4):331–50. doi: <https://doi.org/10.1080/19401493.2015.1064480>.
- [59] Pivac N, Nizetic S, Zanki V. Occupant behavior and thermal comfort field analysis in typical educational research institution: A case study. *Therm Sci* 2018;22(Suppl. 3):785–95. doi: <https://doi.org/10.2298/TSC170915013P>.
- [60] Prashant Anand Chirag Deb Ramachandraiah A. A simplified tool for building layout design based on thermal comfort simulations. *Frontiers of Architecture and Civil Engineering in China* 2017;62:218–30. doi: <https://doi.org/10.1016/j.foar.2017.03.001>.
- [61] Naramura T, Morikawa J, Ninagawa C. Prediction Model on Room Temperature Side Effect due to FastADR Aggregation for a Cluster of Building Air-Conditioning Facilities. *Electr Eng Jpn* 2017;199(3):17–25. doi: <https://doi.org/10.1002/eej.22946>.
- [62] Smith V, Sookoor T, Whitehouse K. Modeling building thermal response to HVAC zoning. *ACM SIGBED Review* 2012;9(3):39–45. doi: <https://doi.org/10.1145/2367580.2367587>.
- [63] Roberti F, Oberegger UF, Gasparella A. Calibrating historic building energy models to hourly indoor air and surface temperatures: Methodology and case study. *Energy Build* 2015;108:236–43. doi: <https://doi.org/10.1016/j.enbuild.2015.09.010>.
- [64] Royapoor M, Roskilly T. Building model calibration using energy and environmental data. *Energy Build* 2015;94:109–20. doi: <https://doi.org/10.1016/j.enbuild.2015.02.050>.
- [65] Pantazaras A, Lee SE, Santamouris M, Yang J. Predicting the CO₂ levels in buildings using deterministic and identified models. *Energy Build* 2016;127:774–85. doi: <https://doi.org/10.1016/j.enbuild.2016.06.029>.
- [66] A. O. Nesibe YALC, Deniz BALTA, 2018. A modeling and simulation study about CO₂ amount with web-based indoor air quality monitoring. *TURKISH JOURNAL OF ELECTRICAL ENGINEERING & COMPUTER SCIENCES* 26 (3). doi:10.3906/elk-1612-57
- [67] B. Gucyeter, "CALIBRATION OF A BUILDING ENERGY PERFORMANCE SIMULATION MODEL VIA MONITORING DATA" presented at the Building Performance Analysis Conference and SimBuild Chicago, IL September 26–28, 2018. Available: <https://www.ashrae.org/File%20Library/Conferences/Specialty%20Conferences/2018%20Building%20Performance%20Analysis%20Conference%20and%20SimBuild/Papers/C074.pdf>.