

```
root@srv1: /mnt/upload

root@srv1:~#
root@srv1:~# apt list --installed | grep nfs

WARNING: apt does not have a stable CLI interface. Use with caution in scripts.

libnfsidmap1/noble-updates,now 1:2.6.4-3ubuntu5.1 amd64 [installed,automatic]
nfs-common/noble-updates,now 1:2.6.4-3ubuntu5.1 amd64 [installed]
nfs-kernel-server/noble-updates,now 1:2.6.4-3ubuntu5.1 amd64 [installed]
root@srv1:~#
root@srv1:~# ip -br a
lo                UNKNOWN          127.0.0.1/8 ::1/128
enp0s3            UP              192.168.0.111/24 fe80::a00:27ff:fe23:b27a/64
root@srv1:~# showmount -e 192.168.0.110
Export list for 192.168.0.110:
/srv/share 192.168.0.0/24
root@srv1:~# mount -o vers=3 192.168.0.110:/srv/share /mnt
root@srv1:~# ls /mnt/upload/
root@srv1:~# ls -l /mnt/upload/
total 0
root@srv1:~# umount /mnt
root@srv1:~# echo "192.168.0.110:/srv/share/ /mnt nfs vers=3,noauto,x-systemd.automount 0 0" >> /etc/fstab
root@srv1:~# cat /etc/fstab
# /etc/fstab: static file system information.
#
# Use 'blkid' to print the universally unique identifier for a
# device; this may be used with UUID= as a more robust way to name devices
# that works even if disks are added and removed. See fstab(5).
#
# <file system> <mount point> <type> <options>          <dump> <pass>
# / was on /dev/ubuntu-vg/ubuntu-lv during curtin installation
/dev/disk/by-id/dm-uuid-LVM-rBf62w25QuqaIQN6BALHRP6eamaBlS5f6dIYplzCtFs8Oxpqwrwo
aMid4gc1525g / ext4 defaults 0 1
# /boot was on /dev/sda2 during curtin installation
/dev/disk/by-uuid/caca99bb-0ad5-4d9a-885b-5e9c2ec88ff9 /boot ext4 defaults 0 1
/swap.img      none      swap      sw          0          0
#UUID="05e1b359-14dd-4a3b-af8d-2050ea769ff0" /raid/part1 ext4 defaults 0 2
UUID="96f7dbf0-fee6-4819-84f0-fd378ba190e0" /var ext4 defaults 0 0
UUID="22680638-fa21-4446-8527-b9fd5d830fff" /home ext4 defaults 0 0
192.168.0.110:/srv/share/ /mnt nfs vers=3,noauto,x-systemd.automount 0 0
root@srv1:~# systemctl daemon-reload
root@srv1:~# systemctl restart remote-fs.target
root@srv1:~# cd /mnt
root@srv1:/mnt# ls
upload
root@srv1:/mnt# cd upload/
root@srv1:/mnt/upload# ls
```

```
root@srv1: /mnt/upload
root@srv1:~# mount -o vers=3 192.168.0.110:/srv/share /mnt
root@srv1:~# ls /mnt/upload/
root@srv1:~# ls -l /mnt/upload/
total 0
root@srv1:~# umount /mnt
root@srv1:~# echo "192.168.0.110:/srv/share/ /mnt nfs vers=3,noauto,x-systemd.automount 0 0" >> /etc/fstab
root@srv1:~# cat /etc/fstab
# /etc/fstab: static file system information.
#
# Use 'blkid' to print the universally unique identifier for a
# device; this may be used with UUID= as a more robust way to name devices
# that works even if disks are added and removed. See fstab(5).
#
# <file system> <mount point> <type> <options> <dump> <pass>
# / was on /dev/ubuntu-vg/ubuntu-lv during curtin installation
/dev/disk/by-id/dm-uuid-LVM-rBf62w25QuqaIQN6BALHRP6eamaBlS5f6dIYplzCtFs8OxpgwrwoaMid4gc1525g / ext4 defaults 0 1
# /boot was on /dev/sda2 during curtin installation
/dev/disk/by-uuid/caca99bb-0ad5-4d9a-885b-5e9c2ec88ff9 /boot ext4 defaults 0 1
/swap.img none swap sw 0 0
#UUID="05e1b359-14dd-4a3b-af8d-2050ea769ff0" /raid/part1 ext4 defaults 0 2
UUID="96f7dbf0-fee6-4819-84f0-fd378ba190e0" /var ext4 defaults 0 0
UUID="22680638-fa21-4446-8527-b9fd5d830fff" /home ext4 defaults 0 0
192.168.0.110:/srv/share/ /mnt nfs vers=3,noauto,x-systemd.automount 0 0
root@srv1:~# systemctl daemon-reload
root@srv1:~# systemctl restart remote-fs.target
root@srv1:~# cd /mnt
root@srv1:/mnt# ls
upload
root@srv1:/mnt# cd upload/
root@srv1:/mnt/upload# ls
root@srv1:/mnt/upload# cd /
root@srv1:/# mount | grep mnt
systemd-1 on /mnt type autofs (rw,relatime,fd=74,pgrp=1,timeout=0,minproto=5,maxproto=5,direct,pipe_ino=13396)
192.168.0.110:/srv/share/ on /mnt type nfs (rw,relatime,vers=3,rsiz
e=524288,namlen=255,hard,proto=tcp,timeo=600,retrans=2,sec=sys,mountaddr=192.168
.0.110,mountvers=3,mountport=35753,mountproto=udp,local_lock=none,addr=192.168.0
.110)
root@srv1:/# cd /mnt/upload/
root@srv1:/mnt/upload# ls
check_file
root@srv1:/mnt/upload# touch client_file
root@srv1:/mnt/upload# ls
check_file client_file
root@srv1:/mnt/upload# reboot
```


login as: usr1

usr1@192.168.0.111's password:

Welcome to Ubuntu 24.04.3 LTS (GNU/Linux 6.8.0-136-generic x86_64)

* Documentation: <https://help.ubuntu.com>
* Management: <https://landscape.canonical.com>
* Support: <https://ubuntu.com/pro>

System information as of Wed Jul 22 07:41:09 PM UTC 2026

System load:	0.92	Processes:	367
Usage of /home:	0.0% of 1.90GB	Users logged in:	1
Memory usage:	7%	IPv4 address for enp0s3:	192.168.0.111
Swap usage:	0%		

* Strictly confined Kubernetes makes edge and IoT secure. Learn how MicroK8s just raised the bar for easy, resilient and secure K8s cluster deployment.

<https://ubuntu.com/engage/secure-kubernetes-at-the-edge>

Expanded Security Maintenance for Applications is not enabled.

56 updates can be applied immediately.

1 of these updates is a standard security update.

To see these additional updates run: `apt list --upgradable`

Enable ESM Apps to receive additional future security updates.

See <https://ubuntu.com/esm> or run: `sudo pro status`

Last login: Wed Jul 22 19:26:06 2026 from 192.168.0.106

usr1@srv1:~\$ `showmount -e 192.168.0.110`

Export list for 192.168.0.110:

/srv/share 192.168.0.0/24

usr1@srv1:~\$ `showmount -a 192.168.0.110`

All mount points on 192.168.0.110:

usr1@srv1:~\$ `cd /mnt`

usr1@srv1:/mnt\$ `ls`

upload

usr1@srv1:/mnt\$ `showmount -a 192.168.0.110`

All mount points on 192.168.0.110:

192.168.0.111:/srv/share

usr1@srv1:/mnt\$ `cd upload/`

usr1@srv1:/mnt/upload\$ `mount | grep mnt`

systemd-1 on /mnt type autofs (rw,relatime,fd=71,pgrp=1,timeout=0,minproto=5,maxproto=5,direct,pipe_ino=5011)

192.168.0.110:/srv/share/ on /mnt type nfs (rw,relatime,vers=3,rsize=524288,wsiz
e=524288,namlen=255,hard,proto=tcp,timeo=600,retrans=2,sec=sys,mountaddr=192.168
.0.110,mountvers=3,mountport=60003,mountproto=udp,local_lock=none,addr=192.168.0
.110)

usr1@srv1:/mnt/upload\$ `ls`

check_file client_file

usr1@srv1:/mnt/upload\$ `touch final_check`

usr1@srv1:/mnt/upload\$ `ls -l`

total 0

-rw-r--r-- 1 root root 0 Jul 22 19:17 check_file

-rw-r--r-- 1 nobody nogroup 0 Jul 22 19:18 client_file

-rw-rw-r-- 1 usr1 usr1 0 Jul 22 19:42 final_check

usr1@srv1:/mnt/upload\$