

Installing software and writing modules Intro (slides)

In the intro portion of the workshop you will learn:

- About downloading code
 - About compiling code
 - How to build a package from source code
 - configure
 - build
 - install
 - How to write modules
 - simple, elaborate and complex examples (tcl aka *tickle*)
 - `.version` file
 - What are `yum`, `rpm`, `get-apt`, etc
 - how to use `yum` and `rpm`
 - what about `sudo`?
-

Downloading Code

In most cases you are better off downloading the source and building the code (hereafter executable) yourself

Executables

There are instances when available executables will run flawlessly on Hydra, but

1. make sure you trust the origin of the code
2. make sure you get a version compatible with Hydra, *i.e.*, that will run on CentOS 7.x for Intel/AMD CPUs
3. Hydra configuration is specific, hence pre-built code may need other stuff (dependencies) that are not installed on Hydra

Notes

- Since user do not have elevated privileges (root access) you are very unlikely to damage the cluster, but malicious software can still damage your files.
 - In rare cases it may try to install a *trojan horse* that would try to exploit a known vulnerability. So be vigilant and responsible.
 - In case of doubt, never hesitate to contact us.
-

Compiling code

Building from Source Code

If you download source code you will need to build the code. This is usually done in 3 steps

1. **Configure**

- Most packages come with a configuration script, a list of pre-requisites (aka dependencies) and instructions.
- Some packages allow to build the code without some features in case you cannot satisfy some of the pre-requisites.
- You most likely need to load the right module to use the appropriate compiler

2. **Build**

- need to make sure you have loaded the right modules to use the right compiler
- run **make** to compile and link (aka build) the code

3. **Install**

- copy the executable to the right place (usually defined by the configuration)
 - best practice is to separate build from install locations
- This will be illustrated in the hands on section.
-

Module and module files

The `module` command and module files

- The command `module`
 - is a convenient mechanism to configure your Unix/Linux environment.
 - reads a file, aka the “module file”, that holds a set of simple or complex instructions.
 - This is a shell syntax independent way to configure your environment:
 - you use the *same* module file whether you use the `[ba]sh` or `[t]csh` shell.
 - We provide a slew of module files, but users can augment this by writing their own.
 - you are welcome to look at all the module files we wrote, most of them are under `/share/apps/modulefiles/`.
-

Module file syntax and concepts

- Module files can be complex, written following the `tcl` scripting language, *although* you **do not** need to know that language to write simple module files.
 - The `tcl` syntax is augmented by commands specific to help configure your environment.
 - For example a simple module file can just hold a list of modules that must be loaded to to run a given tool.
 - You can write complex module files and leverage the `tcl` syntax.
-

Example of module commands

- Informational

```
module avail
module whatis
module whatis <name>
```

- Configure your environment

```
module load <name>
module unload <name>
module swap <name>
```

- Specific info

```
module list
module help <name>
module show <name>
```

- More help

```
man module
```

Ex-
am-
ple
of a
sim-
ple
mod-
ule
file

```

#%Module1.0
# #
load
two
modules
and
set
the
HEASOFT
env
variable
module
load
gcc/10.1.10
module
load
python/3.8
setenv
HEASOFT
/home/sylvain/heasoft/6.3.1

```

Example of a more elaborate module file: tools/rcclone

```

#%Module1.0
#
# set some internal variables
set ver      1.53.1
set base     /share/apps/bioinformatics
#
# easy way to set up help
proc ModulesHelp { } {
    global helpmsg
    puts stderr "\t$helpmsg\n"
}
#
# what to show for module whatis
module-whatis "System paths to run rclone $ver"
#
# configure the PATH and the MANPATH
prepend-path PATH $base/rcclone/$ver
prepend-path MANPATH $base/rcclone/$ver/man
#
# define the text shown with module help
set helpmsg "

```

Purpose

This module file defines the system paths for rclone \$ver

Documentation

<https://rclone.org/>

Examples of complex module files

```
cd /share/apps/modulefiles
more intel/2022.2
more idl/8.8
more bio/blast2go/1.5.1
more bio/trinity/2.9.1
```

Or-
ga-
ni-
za-
tion
and
Cus-
tomiza-
tion

-
You
can
keep
your
mod-
ule
files
in a
cen-
tral
loca-
tion
(recom-
m-
mended),
us-
ing
a
tree
stuc-
ture,
or if
you
pre-
fer
where
you
need
them.

-
You
can
load
a
mod-
ule
file
us-
ing
the
mod-
ule
file
full
path,
or
tell
module
where
to
look
for
your
cen-
tral
loca-
tion
(rec-
om-
mended).

-
The
rec-
om-
mended
ap-
proach:
- use
a
cen-
tral
loca-
tion
un-
der
you
home
di-
rec-
tory
~/modulefiles
- use
a
tree
struc-
ture
and
use
ver-
sion
num-
bers
if/when
ap-
pli-
ca-
ble

- tell
module
where
to
find
your
mod-
ule
file
with

The yum, rpm, get-apt and sudo soup

Hands-on Section

In the hands-on portion of the workshop you will

- How to find software to install
- How to install software using best-practices
- How to run the software you installed in submitted jobs on Hydra

Log in to Hydra

If you need a reminder about how to log into Hydra and how to change your password, check out our Intro to Hydra tutorial: https://github.com/SmithsonianWorkshops/Hydra-introduction/blob/master/hydra_intro.md
