

P2: Exercise 1 Discussion

Claudio Corrodi

Two approaches

- Custom algorithm
 - Recursive
 - Look at the first character of pattern and filename at a time
- Regular expressions
 - One-liner can cover most cases
 - But: what about special characters?

Custom Algorithm using recursion

```
private boolean match(String pattern, String filename) {  
    ...  
  
    // If there is another character in filename, check if it matches  
    // the current pattern character. If not, the pattern does not match;  
    // otherwise, check the remainder.  
    if (filename.isEmpty() || pattern.charAt(0) != filename.charAt(0)) {  
        return false;  
    } else {  
        return match(pattern.substring(1), filename.substring(1));  
    }  
}
```

match("abc", "abcde.txt") ==
match("bc", "bcde.txt") ==
match("c", "cde.txt") ==
match("", "de.txt") == ...

Custom Algorithm using recursion

```
private boolean match(String pattern, String filename) {  
    ...  
  
    // Question mark. If filename is not empty, match the remainder  
    // of pattern to the remainder of filename.  
    if (pattern.startsWith("?")) {  
        if (filename.isEmpty()) {  
            return false;  
        } else {  
            return match(pattern.substring(1), filename.substring(1));  
        }  
    }  
    ...  
}
```

`match("?oo.txt", "foo.txt") == match("oo.txt", "oo.txt")`

Regular Expressions

```
private boolean matchRegex(String filename) {  
    String regexPattern = pattern;  
    regexPattern = regexPattern.replace("*", ".*");  
    regexPattern = regexPattern.replace("?", ".");  
    return Pattern.matches(regexPattern, filename);  
}
```

“.” matches exactly one character

“.*” matches any number of characters

Regular Expressions

```
private boolean matchRegex(String filename) {  
    String regexPattern = pattern;  
    regexPattern = regexPattern.replace("*", ".*");  
    regexPattern = regexPattern.replace("?", ".");  
    return Pattern.matches(regexPattern, filename);  
}
```

“.” matches exactly one character
“.*” matches any number of characters

- What about special characters?

➔ Read documentation!

```
// escape special character “.”  
regexPattern = regexPattern.replace(".", "\\.");
```

Examples: Encapsulation & names

```
public class FilePattern implements FileFilter {  
  
    public String string;  
  
    public FilePattern(String string) {  
        this.string = string;  
    }  
  
    ...  
}
```

Examples: Encapsulation & names

```
public class FilePattern implements FileFilter {  
    public String string;  
  
    public FilePattern(String string) {  
        this.string = string;  
    }  
  
    ...  
}
```


Examples: Encapsulation & names

```
public class FilePattern implements FileFilter {
```

Make attributes private

```
    private String pattern;
```

Use meaningful names

```
    public FilePattern(String pattern) {  
        this.pattern = pattern;  
    }
```

```
    ...
```

```
}
```

Examples: Useless code

```
private String tempPattern;  
  
public String getTempPattern() {  
    return this.tempPattern;  
}
```

Examples: Useless code

```
private String tempPattern;  
  
public String getTempPattern() {  
    return this.tempPattern;  
}
```

Unused outside of class!

Manual Testing

```
public class TestMain {  
    public static void main(String[] args) {  
        FilePattern a = new FilePattern("fname*");  
        System.out.println(a.accept(new File("")));  
    }  
}
```

Manual Testing

```
public class TestMain {  
    public static void main(String[] args) {  
        FilePattern a = new FilePattern("fname*");  
        System.out.println(a.accept(new File("")));  
    }  
}
```

```
public class FilePatternTest {  
    ...  
  
    @Test  
    public void fnameStarDoesNotMatchEmptyName() {  
        FilePattern a = new FilePattern("fname*");  
        assertFalse(a.accept(new File("")));  
    }  
}
```

add scenario as a
permanent test

P2: Exercise 2

Claudio Corrodi

Exercise 2: Snakes & Ladders

- You are given a skeleton for the Snakes & Ladders game
- Add new types of squares
 - TikTokSquare: “Ladder” with two alternating destinations
 - SwapSquare: When landing here, swap your position with another player
 - ...
- *Test behavior of squares*
 - *Use JUnit and JExample*
- *Write proper documentation*

JUnit, JExample

- Testing frameworks
 - Covered in more detail in lecture 4!
- Goal: Make sure program behaves as expected
- **JUnit**: Individual, independent tests
- **JExample**: Sequences of tests
 - Maintain state between tests
 - No need to reinitialize

JUnit

```
@Test
public void newGame() {
    jack = new Player("Jack");
    jill = new Player("Jill");
    Player[] args = { jack, jill };
    Game game = new Game(12, args);
    game.setSquareToLadder(2, 4);
    game.setSquareToLadder(7, 2);
    game.setSquareToSnake(11, -6);

    assertTrue(game.notOver());
    assertEquals(1, jack.position());
    assertEquals(1, jill.position());
    assertEquals(jack, game.currentPlayer());
}
```

```
@Test
public void initialStrings() {
    jack = new Player("Jack");
    jill = new Player("Jill");
    Player[] args = { jack, jill };
    Game game = new Game(12, args);
    game.setSquareToLadder(2, 4);
    game.setSquareToLadder(7, 2);
    game.setSquareToSnake(11, -6);

    assertEquals("Jack", jack.toString());
    assertEquals("Jill", jill.toString());
    assertEquals("[1<Jack><Jill>]",
        game.firstSquare().toString());
}
```

JUnit

```
@Test
public void newGame() {
    jack = new Player("Jack");
    jill = new Player("Jill");
    Player[] args = { jack, jill };
    Game game = new Game(12, args);
    game.setSquareToLadder(2, 4);
    game.setSquareToLadder(7, 2);
    game.setSquareToSnake(11, -6);

    assertTrue(game.notOver());
    assertEquals(1, jack.position());
    assertEquals(1, jill.position());
    assertEquals(jack, game.currentPlayer());
}
```

```
@Test
public void initialStrings() {
    jack = new Player("Jack");
    jill = new Player("Jill");
    Player[] args = { jack, jill };
    Game game = new Game(12, args);
    game.setSquareToLadder(2, 4);
    game.setSquareToLadder(7, 2);
    game.setSquareToSnake(11, -6);

    assertEquals("Jack", jack.toString());
    assertEquals("Jill", jill.toString());
    assertEquals("[1<Jack><Jill>]",
        game.firstSquare().toString());
}
```

JExample

```
@Test
public Game newGame() {
    jack = new Player("Jack");
    jill = new Player("Jill");
    Player[] args = { jack, jill };
    Game game = new Game(12, args);
    game.setSquareToLadder(2, 4);
    assertTrue(game.firstSquare().isOccupied());
    return game;
}
```

JExample

```
@Test
public Game newGame() {
    jack = new Player("Jack");
    jill = new Player("Jill");
    Player[] args = { jack, jill };
    Game game = new Game(12, args);
    game.setSquareToLadder(2, 4);
    assertTrue(game.firstSquare().isOccupied());
    return game;
}
```

```
@Given("newGame")
public Game initialPositions(Game game) {
    assertEquals(1, jack.position());
    assertEquals(1, jill.position());
    return game;
}
```

JExample

```
@Test
public Game newGame() {
    jack = new Player("Jack");
    jill = new Player("Jill");
    Player[] args = { jack, jill };
    Game game = new Game(12, args);
    game.setSquareToLadder(2, 4);
    assertTrue(game.firstSquare().isOccupied());
    return game;
}
```

```
@Given("newGame")
public Game initialPositions(Game game) {
    assertEquals(1, jack.position());
    assertEquals(1, jill.position());
    return game;
}
```

```
@Given("initialPositions")
public Game move1jack(Game game) {
    game.movePlayer(4);
    assertTrue(game.notOver());
    assertEquals(5, jack.position());
    assertEquals(1, jill.position());
    assertEquals(jill, game.currentPlayer());
    return game;
}
```

JExample

```
@Test
public Game newGame() {
    jack = new Player("Jack");
    jill = new Player("Jill");
    Player[] args = { jack, jill };
    Game game = new Game(12, args);
    game.setSquareToLadder(2, 4);
    assertTrue(game.firstSquare().isOccupied());
    return game;
}
```

More in exercise_02.md

git pull p2ubungen master

```
@Given("newGame")
public Game initia
    assertEquals(1,
    assertEquals(1,
    return game;
}
```

```
@Given("InitialPositions")
public Game move1jack(Game game) {
    game.movePlayer(4);
    assertTrue(game.notOver());
    assertEquals(5, jack.position());
    assertEquals(1, jill.position());
    assertEquals(jill, game.currentPlayer());
    return game;
}
```

License

- <http://creativecommons.org/licenses/by-sa/2.5/>



You are free:

- to copy, distribute, display, and perform the work
- to make derivative works
- to make commercial use of the work

Under the following conditions:



Attribution. You must attribute the work in the manner specified by the author or licensor.



Share Alike. If you alter, transform, or build upon this work, you may distribute the resulting work only under a license identical to this one.

- For any reuse or distribution, you must make clear to others the license terms of this work.
- Any of these conditions can be waived if you get permission from the copyright holder.

Your fair use and other rights are in no way affected by the above.