

Les 2 07/10

07 October 2021 13:59

IF - ELSE

WHILE

★ Relationale operatoren in Python

Table 1 Relational Operators		
Python	Math Notation	Description
>	>	Greater than
>=	≥	Greater than or equal
<	<	Less than
<=	≤	Less than or equal
==	=	Equal
!=	≠	Not equal

💡 "=" kent een waarde toe
"==" kijkt een waarde na
Gebruikt in if of while constructies

Vergelijking van strings: volgorde en hiërarchie!

All UPPERCASE letters come before lowercase

'space' comes before all other printable characters

Digits (0-9) come before all letters

See Appendix A for the Basic Latin (ASCII) Subset of Unicode

Aparte commando's string en number. Zie HB!

💡 Datatypes:

String

Float

Boolean

Twee waarden: true, false

Boolean variabelen: failed = true/false

Operatoren: and, or, not (denk aan waardetabellen!)

Geneste commando's

Vb.: programma discriminant (uitgebreid, les 2)

Vb.: schaal van richter (let op de verschillende interpretaties!)

```
if richter >= 8.0 : # Handle the 'special case' first
    print("Most structures fall")
else:
    if richter >= 7.0 :
        print("Many buildings destroyed")
    else:
        if richter >= 6.0 :
            print("Many buildings damaged, some collapse")
        else:
            if richter >= 4.5 :
                print("Damage to poorly constructed buildings")
            else : # so that the 'general case' can be
                    handled last
                print("No destruction of buildings")
```

=

```
if richter >= 8.0 : # Handle the 'special case' first
    print("Most structures fall")
elif richter >= 7.0 :
    print("Many buildings destroyed")
elif richter >= 6.0 :
    print("Many buildings damaged, some collapse")
elif richter >= 4.5 :
    print("Damage to poorly constructed buildings")
else : # so that the 'general case' can be handled last
    print("No destruction of buildings")
```

!=

```
if richter >= 8.0 :
    print("Most structures fall")
if richter >= 7.0 :
    print("Many buildings destroyed")
if richter >= 6.0 :
    print("Many buildings damaged, some collapse")
if richter >= 4.5 :
    print("Damage to poorly constructed buildings")
```

Vb. Count-controlled loops: Som 1 tot n
berekenen = (n*(n+1))/2

★ Boolean variabels

AND

```
if temp > 0 and temp < 100 :
    print("Liquid")
```

OR

```
if temp <= 0 or temp >= 100 :
    print("Not liquid")
```

NOT

```
if not attending or grade < 60 :
    print("Drop?")
```

```
if attending and not(grade < 60) :
    print("Stay")
```

--> betere versie

```
if attending and grade >= 60 :
    print("Stay")
```

- Count-controlled loops
= while-loop onder invloed van een telopdracht

```
counter = 1      # Initialize the counter
while counter <= 10 :    # Check the counter
    print(counter)
    counter = counter + 1 # Update the loop variable
print("-----")
```

- Event-controlled loops
= while-loop onder invloed van een voorwaarde

```
##
# This program computes the time required to double an investment.
#

# Create constant variables.
RATE = 5.0
INITIAL_BALANCE = 10000.0
TARGET = 2 * INITIAL_BALANCE

# Initialize variables used with the loop.
balance = INITIAL_BALANCE
year = 0

# Count the years required for the investment to double.
while balance < TARGET :
    year = year + 1
    interest = balance * RATE / 100
    balance = balance + interest

# Print the results.
print("The investment doubled after", year, "years.")
```

★ Veel gemaakte programmafouten

Foute voorwaarde, vb.: \geq ipv $>$
 Oneindige loops
 Loop die maar 1x mee gaat

Sentinel values

Gebruikt in een while-loop die een reeks getallen leest en controleert. Er is geen duidelijkheid over wanneer de while-loop moet stoppen, dus voordat deze start wordt er een waarde ingesteld zodat de loop deze leest als 'einde loop'.

Opm.: in het algemeen wordt de waarde -1 hiervoor gebruikt

While getal != -1:	Start je commando op deze manier om de sentinel variabele te installeren
--------------------	--

Vb.: berekening gemiddeld salaris

```
# initialisation
total = 0.0
count = 0
# Initial read - read the first value
salary = float(input("Enter a salary or -1 to
```

0	vraag getal n
1	Som = 0
2	Voor elke " " ≥ 0 and " " ≤ 0 som \leftarrow som + 1
3	Schrijf som uit


```
n=int(input("geefwardevoorn"))
```

```
#startwaarde
som=0
teller=0
```

```
while(teller<n):
teller=teller+1
som=som+teller
```

```
print("desomis",som)
```

💡 Uitvoering loop voorbeeldprogramma event-controlled loop



```
finish: "))
# We will keep on processing values until a
negative value is input
while salary >= 0.0 :
    total = total + salary
    count = count + 1
    # Next read
    salary = float(input("Enter a salary or -1 to
finish: "))
# Compute and print average salary
if count > 0:
    average = total / count
    print("Average salary is", average)
else:
    print("No data was provided...")
```