

Functions

`getSendObjectData()` ⇒ `bytebuffer`

Encodes an object into a Tobject (a bytearray prepended with metadata) to send data to a LaunchLike server.

`getSendCommandData({lCommand,})` ⇒ `bytebuffer`

Encodes data required to send a command to a LaunchLike server.

`getRequestObjectData({lObject,})` ⇒ `bytebuffer`

Encodes data required to make an object request to a LaunchLike server.

`sendCommand({lObject,})` ⇒

Requests a command from a LaunchLike server with the given code.

`sendObject({lObject,})` ⇒

Sends an object from a LaunchLike server with the given code and data.

`requestObject({cData})` ⇒

Requests an object from a LaunchLike server with the given code.

`processBytes(cData, context)` ⇒

Takes a Tobject and parses out a message type definition and length for the data. The function then calls a handler method of the context which was provided to it with the transcribed data.

`getSendObjectData()` ⇒ `bytebuffer`

Encodes an object into a Tobject (a bytearray prepended with metadata) to send data to a LaunchLike server.

Kind: global function

| Param | Type | Description |
|-------|---------------------|---|
| { | <code>object</code> | lObject, lInstanceNumber, lStart, cData } |

`getSendCommandData({lCommand,})` ⇒ `bytebuffer`

Encodes data required to send a command to a LaunchLike server.

Kind: global function

| Param | Type | Description |
|------------|---------------------|------------------|
| {lCommand, | <code>object</code> | lInstanceNumber} |

`getRequestObjectData({lObject,})` ⇒ `bytebuffer`

Encodes data required to make an object request to a LaunchLike server.

Kind: global function

| Param | Type | Description |
|-----------|---------------|-----------------------------------|
| {lObject, | object | lInstanceNumber, lStart, lLength} |

sendCommand({lObject,}) ⇒

Requests a command from a LaunchLike server with the given code.

Kind: global function

Returns: Nothing. This calls a function within the class context provided to it.

| Param | Type | Description |
|-----------|---------------|------------------|
| {lObject, | object | lInstanceNumber} |

sendObject({lObject,}) ⇒

Sends an object from a LaunchLike server with the given code and data.

Kind: global function

Returns: Nothing. This calls a function within the class context provided to it.

| Param | Type | Description |
|-----------|---------------|---------------------------------|
| {lObject, | object | lInstanceNumber, lStart, cData} |

requestObject({cData}) ⇒

Requests an object from a LaunchLike server with the given code.

Kind: global function

Returns: Nothing. This calls a function within the class context provided to it.

| Param | Type | Description |
|---------|---------------|---|
| {cData} | object | An object containing the request code, the instance number, the starting position, and the length. Generally only the data is provided. |

processBytes(cData, context) ⇒

Takes a Tobject and parses out a message type definition and length for the data. The function then calls a handler method of the context which was provided to it with the transcribed data.

Kind: global function

Returns: Nothing. This calls a function within the class context provided to it.

| Param | Type | Description |
|-------|------|-------------|
|-------|------|-------------|

| Param | Type | Description |
|---------|------------|--|
| cData | bytebuffer | The data which you wish to decode |
| context | class | The class context from which you're calling this function. |