1 Moderncode

Title

```c
int main(int ac, char *av[])
{
    printf("Hello, World");
    return 0;
}
```

This title is very very very very very very very very very long

```c
int main(int ac, char *av[])
{
    printf("Hello, World");
    return 0;
}
```

```c
int main(int ac, char *av[])
{
    printf("Hello, World");
    return 0;
}
```

This is a very long code

```c
int main(int ac, char *av[])
{
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    return 0;
}
```

```latex
\documentclass[10pt]{article}
\usepackage[minted]{moderncode}

\begin{document}
\section{Moderncode}

\begin{moderncode}[C][][adjusted title={Title}]
int main(int ac, char *av[])
{
    printf("Hello, World");
    return 0;
}
\end{moderncode}

\begin{moderncode}[C][][adjusted title={This title is very very very very very very very very very long}]
int main(int ac, char *av[])
{
    printf("Hello, World");
    return 0;
}
```

```
\end{moderncode}

\begin{moderncode}[C]
int main(int ac, char *av[])
{
    printf("Hello, World");
    return 0;
}
\end{moderncode}

\begin{moderncode}[C][][adjusted title={This is a very
↪  long code}]
int main(int ac, char *av[])
{
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    return 0;
}
\end{moderncode}

\moderncodeinput[TeX][][breakable=true]{example-minted.tex}

\subsection{Output}

\begin{moderncodeout}
Enter a positive integer: 100
Fibonacci Series: 0, 1, 1, 2, 3, 5, 8, 13, 21, 34, 55,
↪  89
\end{moderncodeout}

\subsection{Inline}
```

```
64
65  \subsubsection{Inline Code}
66
67  This is an inline modern code display:
    ↪  \moderncodeinline{\LaTeX}. It is also possible to
    ↪  define a language: \moderncodeinline[SQL]{SELECT
    ↪  pg_relation_size('title_basics');}.
68
69  \subsection{Inline Key}
70
71  It also supports a key-like-style inline element:
    ↪  \moderncodekey{Ctrl} + \moderncodekey{C}
72
73  \end{document}
```

1.1 Output

```
Enter a positive integer: 100
Fibonacci Series: 0, 1, 1, 2, 3, 5, 8, 13, 21, 34, 55, 89
```

1.2 Inline

1.2.1 Inline Code

This is an inline modern code display: `\LaTeX`. It is also possible to define a language: `SELECT pg_relation_size('title_basics');`.

1.3 Inline Key

It also supports a key-like-style inline element: Ctrl + C