1 Moderncode

Title

```
int main(int ac, char *av[])
{
    printf("Hello, World");
    return 0;
}
```

This title is very very very very very very very very very very long

```
int main(int ac, char *av[])
{
    printf("Hello, World");
    return 0;
}
```

```
int main(int ac, char *av[])
{
    printf("Hello, World");
    return 0;
}
```

This is a very long code

```c
int main(int ac, char *av[])
{
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    printf("Hello, World");
    return 0;
}
```

```latex
\documentclass[10pt]{article}
\usepackage{moderncode}

\begin{document}
\section{Moderncode}

\begin{moderncode}[C][][adjusted title={Title}]
int main(int ac, char *av[])
{
    printf("Hello, World");
    return 0;
}
\end{moderncode}

\begin{moderncode}[C][][adjusted title={This
    ↪ title is very very very very very very
    ↪ very very very long}]
int main(int ac, char *av[])
{
    printf("Hello, World");
```

```
19      return 0;
20  }
21  \end{moderncode}
22
23  \begin{moderncode}[C]
24  int main(int ac, char *av[])
25  {
26      printf("Hello, World");
27      return 0;
28  }
29  \end{moderncode}
30
31  \begin{moderncode}[C][][adjusted title={This is
        ↪ a very long code}]
32  int main(int ac, char *av[])
33  {
34      printf("Hello, World");
35      printf("Hello, World");
36      printf("Hello, World");
37      printf("Hello, World");
38      printf("Hello, World");
39      printf("Hello, World");
40      printf("Hello, World");
41      printf("Hello, World");
42      printf("Hello, World");
43      printf("Hello, World");
44      printf("Hello, World");
45      printf("Hello, World");
46      printf("Hello, World");
47      printf("Hello, World");
48      printf("Hello, World");
49      printf("Hello, World");
50      return 0;
51  }
52  \end{moderncode}
53
54  \moderncodeinput[[LaTeX]TeX][][breakable=true]{
        ↪ example-listings.tex}
55
56  \subsection{Output}
57
58  \begin{moderncodeout}
59  Enter a positive integer: 100
60  Fibonacci Series: 0, 1, 1, 2, 3, 5, 8, 13, 21,
```

```
    ↪ 34, 55, 89
\end{moderncodeout}

\subsection{Inline}

\subsubsection{Inline Code}

This is an inline modern code display: \
    ↪ moderncodeinline{\LaTeX}. It is also
    ↪ possible to define a language: \
    ↪ moderncodeinline[SQL]{SELECT pg_relation_
    ↪ size('title_basics');}.

\subsection{Inline Key}

It also supports a key-like-style inline element
    ↪ : \moderncodekey{Ctrl} + \moderncodekey{C}

\section{Lstlisting}

\begin{lstlisting}[caption=Example in C++,
    ↪ language=c++]
#include <iostream>
using namespace std;

int main() {
    int n, t1 = 0, t2 = 1, nextTerm = 0;

    cout << "Enter the number of terms: ";
    cin >> n;

    cout << "Fibonacci Series: ";

    for (int i = 1; i <= n; ++i) {
        // prints the first two terms.
        if(i == 1) {
            cout << t1 << ", ";
            continue;
        }
        if(i == 2) {
            cout << t2 << ", ";
            continue;
        }
        nextTerm = t1 + t2;
```

```
98          t1 = t2;
99          t2 = nextTerm;
100
101         cout << nextTerm << ", ";
102     }
103     return 0;
104 }
105 \end{lstlisting}
106
107 \subsection{Output}
108
109 \begin{lstlisting}[style=lstoutput]
110 Enter a positive integer: 100
111 Fibonacci Series: 0, 1, 1, 2, 3, 5, 8, 13, 21,
        ↪ 34, 55, 89
112 \end{lstlisting}
113
114 \subsection{Inline}
115
116 \subsubsection{Inline Code}
117
118 \lstinline{\LaTeX}
119
120 \end{document}
```

1.1 Output

```
Enter a positive integer: 100
Fibonacci Series: 0, 1, 1, 2, 3, 5, 8, 13, 21, 34,
   ↪ 55, 89
```

1.2 Inline

1.2.1 Inline Code

This is an inline modern code display: `\LaTeX`. It is also possible to define a language: `SELECT pg_relation_size('title_basics');`.

1.3 Inline Key

It also supports a key-like-style inline element: Ctrl + C

2 Lstlisting

Listing 1: Example in C++

```cpp
#include <iostream>
using namespace std;

int main() {
    int n, t1 = 0, t2 = 1, nextTerm = 0;

    cout << "Enter the number of terms: ";
    cin >> n;

    cout << "Fibonacci Series: ";

    for (int i = 1; i <= n; ++i) {
        // prints the first two terms.
        if(i == 1) {
            cout << t1 << ", ";
            continue;
        }
        if(i == 2) {
            cout << t2 << ", ";
            continue;
        }
        nextTerm = t1 + t2;
        t1 = t2;
        t2 = nextTerm;

        cout << nextTerm << ", ";
    }
    return 0;
}
```

2.1 Output

Output

```
Enter a positive integer: 100
Fibonacci Series: 0, 1, 1, 2, 3, 5, 8, 13, 21, 34,
   ↪ 55, 89
```

2.2 Inline

2.2.1 Inline Code

`\LaTeX`