

**Manufacturer of Customized
Polyol Esters to Fit Your Needs.**

ZONLubeTM

Metal | Quench | Chain | Cutting Esters

Food Grade Esters

Rolling Oil & Rust Preventive Esters

Fire Resistant – Hydraulic Esters

Compressor & Refrigerant Oil Esters

Dielectric Fluid Esters

Drilling Fluid Esters



Products	KV @ 40°C (cst)	Metal Working Fluid	Rolling & Quenching Fluid	Chain Oil	Cutting Oil	Fire Resistance Hydraulic Esters	Grease
ZONLube-105	4-6	✓	✓		✓		
ZONLube-115	7 - 9	✓	✓		✓		✓
ZONLube-119	7.5 -9.5	✓	✓		✓		
ZONLube-120	8.5 -11	✓	✓		✓		
ZONLube-117	13-15						
ZONLube-125	14-18		✓	✓			
ZONLube-129	15 -18	✓					✓
ZONLube-132	18 -21	✓		✓		✓	✓
ZONLube-141	20 -28	✓	✓	✓	✓		✓
ZONLube-175	23-29	✓		✓			✓
ZONLube-154	27 - 34	✓		✓			✓
ZONLube-121	30 -35	✓		✓	✓	✓	
ZONLube-146	30 -44	✓			✓	✓	
ZONLube-131	34 - 38	✓			✓	✓	
ZONLube-146Ultra	41 -48	✓			✓	✓	
ZONLube-116	42 -52	✓	✓	✓	✓	✓	✓
ZONLube-139	42 -52	✓	✓		✓	✓	✓
ZONLube-126	61- 68	✓		✓	✓	✓	✓
ZONLube-140	61 - 74	✓			✓	✓	✓
ZONLube-118	62 - 72	✓	✓	✓	✓	✓	✓
ZONLube-136	62 - 74	✓	✓		✓	✓	✓
ZONLube-155	85-100	✓	✓	✓		✓	✓
ZONLube-137	Min.90	✓			✓	✓	
ZONLube-148	115-150	✓		✓			
ZONLube-181	150 -200	✓	✓	✓	✓	✓	✓
ZONLube-128	200-250	✓	✓	✓	✓	✓	✓
ZONLube-143	295-340	✓		✓			

Biodegradeable Esters	Compressor & Refrigerant Oil	Dielectric Fluid	Marine & Drilling Fluid	Mold Release Oil	Automotive Esters	Food Grade	Description
✓	✓	✓	✓	✓	✓	✓	Monoester
			✓	✓	✓		Ethyl Hexyl Monoester
					✓		Ethyl Hexyl Monoester
					✓		Ethyl Hexyl Monoester
✓		✓				✓	Fully Biodegradable
	✓	✓			✓		Neo Saturated Ester
				✓			Saturated Ester
✓	✓	✓			✓	✓	Saturated Ester
	✓	✓			✓		Neo Ester
	✓	✓			✓		Diester
✓	✓	✓			✓	✓	Saturated Ester
✓	✓	✓		✓		✓	Fully Biodegradable
✓	✓			✓			Neat Cutting Oil
✓	✓			✓	✓	✓	TMP Based Polyol Ester
✓	✓			✓	✓	✓	HSP Neat Cutting Oil
✓	✓		✓	✓	✓	✓	TMP Based Polyol Ester
✓	✓		✓			✓	ISO46 Mining Grade
✓	✓		✓	✓			Pentaerythritol Based
✓	✓		✓				ISO68 Mining Grade
✓	✓		✓		✓		TMP Based Polyol Ester
✓	✓		✓		✓		Complex Low SAP value
	✓	✓					Diester
✓	✓						Pentaerythritol Based
	✓						Trimellitate Ester
✓	✓		✓		✓		Complex Ester
✓	✓		✓		✓		Complex Ester
	✓						Trimellitate Ester

PROPERTIES (CUSTOMISABLE)

Viscosity at 40°C
From 1.5cst to 390cst




Viscosity at 100°C
From 1.2cst to 46cst



Flashpoint
From 90°C to 325°C



Pour Point
From -15°C to -65°C



Head Office & R&D

Plot A-161, Wagle Industrial Estate,
Thane (Mumbai) : 400 604. India.

Site Location

1901 / 1901A, Near Phansa Char Rasta
Sarigam, GIDC, Gujarat : 396 155. India.

+91 22 611 92 700

sales@henichemicals.com

www.henichemicals.com



Scan & Download

Our Certifications:

