Exponential Smoothing- Australian Sparkling Wine

Introduction

Background

The data used in this assignment is the Australian Wines dataset. It records monthly retail sales in thousands of litres for six wine categories sold in Australia: Fortified, Red, Rosé, Sparkling, Sweet White, and Dry White. The data covers the period from January 1980 to December 1994. This provides a 15-year panel with monthly frequency, resulting in 180 observations for each category. Each observation shows the total sales for that wine category across all retail channels in Australia for a specific calendar month, measured in thousands of litres.

This dataset is perfect for demonstrating seasonal exponential smoothing methods. All six wine types show strong 12-month cycles linked to Australian consumer behavior where Christmas and New Year celebrations lead to a noticeable increase in demand every December.

Why Sparkling Wine?

I selected Sparkling wine for two deliberate, analytically reasons:

1. Dominant seasonal structure: Sparkling wine has the biggest December spike of all six categories. The average December sales are 5,813 thousand litres over all years. This figure is 3.6 times the monthly average of 1,614 thousand litres during off-peak months. This creates a strong test of whether Holt-Winters can capture extreme seasonality.

2. Multiplicative seasonality question: The December spike's ratio to the annual mean increases from 2.19 times in 1980 to 2.87 times in 1987, then stabilizes around 2.4 to 2.5 times. This pattern supports using a multiplicative seasonal model instead of an additive one.

SECTION 1: LOAD PACKAGES & DATA

RCode:

```
library(fpp3)

library(knitr)      # kable() for publication-quality tables

library(kableExtra)  # enhanced table styling

library(scales)
```

```
wines_raw <- read.csv("AustralianWines.csv") |>
  rename_with(trimws) |>
  mutate(Month = yearmonth(my(Month))) |>
  as_tsibble(index = Month)
# Quick sanity check: 180 rows, 7 columns (Month + 6 wine types)
glimpse(wines_raw)
# Isolate Sparkling wine and rename Sales
sparkling <- wines_raw |>
  select(Month, Sales = Sparkling)
# Summary statistics
cat("Series:           Sparkling Wine\n")
cat("Time span:        ", format(min(sparkling$Month)), "to",
                       format(max(sparkling$Month)), "\n")
cat("Total observations: ", nrow(sparkling), "months\n")
cat("Overall mean:      ", round(mean(sparkling$Sales)), "thousand litres/month\n")
cat("December mean:     ", round(mean(sparkling$Sales[month(sparkling$Month)==12])),
    "thousand litres\n")
cat("June mean:         ", round(mean(sparkling$Sales[month(sparkling$Month)==6])),
    "thousand litres\n")
cat("Series max:        ", max(sparkling$Sales), "(Dec 1987)\n")
cat("Series min:        ", min(sparkling$Sales), "thousand litres\n")
```

Output:

```
Series:           Sparkling Wine
Time span:     1980 Jan to 1994 Dec
Total observations:  180 months
```

Overall mean: 2431 thousand litres/month

December mean: 5813 thousand litres

June mean: 1459 thousand litres

Series max: 7242 (Dec 1987)

Series min: 1170 thousand litres

Series: Sparkling Wine

Data Exploration

SECTION 2: EXPLORATORY DATA ANALYSIS (EDA)

RCode:

```
## Time Series Plot
autoplot(sparkling, Sales) +
  scale_y_continuous(labels = comma) +
  labs(
    title    = "Australian Sparkling Wine Sales (1980–1994)",
    subtitle = "Monthly retail sales — thousands of litres",
    y        = "Sales (thousands of litres)",
    x        = NULL
  ) +
  theme_minimal(base_size = 13) +
  theme(plot.title    = element_text(face = "bold"),
        plot.subtitle = element_text(colour = "grey50"))
```

Output:



RCode:

```
# Seasonal Subseries Plot
sparkling |>
 gg_subseries(Sales) +
 scale_y_continuous(labels = comma) +
 labs(
  title    = "Seasonal Subseries: Sparkling Wine (1980–1994)",
  subtitle = "Each panel = one calendar month | Blue line = month mean across all years",
  y       = "Sales (thousands of litres)",
  x       = "Year"
 ) +
 theme_minimal(base_size = 11)
```

Output:



ACF Plot

RCode:

```
sparkling |>
 ACF(Sales, lag_max = 36) |>
 autoplot() +
 labs(
  title    = "ACF: Sparkling Wine Sales (up to 36 months)",
  subtitle = "Blue dashed lines = 95% significance bounds"
 ) +
 theme_minimal(base_size = 13)
```

Output:



STL Decomposition

RCode:

```
# STL = Seasonal and Trend decomposition using Loess

# trend(window=21): uses 21-month window to estimate trend (robust, smooth)

# season(window="periodic"): forces seasonal component to be exactly periodic

sparkling |>

  model(STL(Sales ~ trend(window = 21) + season(window = "periodic"))) |>

  components() |>

  autoplot() +

  labs(title = "STL Decomposition: Sparkling Wine Sales (1980–1994)") +

  theme_minimal(base_size = 12)
```

Output:



Intepretation

Trend, Seasonality, and Noise

RCode:

```
annual_means <- sparkling |>
 mutate(Year = year(Month)) |>
 group_by(Year) |>
 summarise(
  Ann_Mean  = mean(Sales),
  Dec_Sales = Sales[month(Month) == 12],
  .groups   = "drop"
 )
```

```
trend_change <- annual_means$Ann_Mean[annual_means$Year == 1993] -
            annual_means$Ann_Mean[annual_means$Year == 1980]


cat("Annual mean 1980:", round(annual_means$Ann_Mean[annual_means$Year==1980]),
   "thousand litres\n")
cat("Annual mean 1993:", round(annual_means$Ann_Mean[annual_means$Year==1993]),
   "thousand litres\n")
cat("Trend change:    ", round(trend_change), "thousand litres over 14 years\n")
```

Output:

```
Annual mean 1980: 5179 thousand litres
Annual mean 1993: 6410 thousand litres
Trend change:     1231 thousand litres over 14 years
```

- Level: The non-seasonal baseline ranges from approximately 1,200 to 2,600 thousand litres per month in off-peak months. The overall mean is 2431 thousand litres.
- Trend: A mild but genuine upward trend is present. The annual average rises from 5179 thousand litres in 1980 to 6410 in 1993, a gain of 1231 thousand litres over 14 training years (87.9 thousand litres per year). The STL trend panel in above plot isolates this as a gradual, continuous rise with no structural breaks.
- Seasonality: A dominant 12-month seasonal cycle is the most striking feature. Every December registers a towering peak driven by Christmas and New Year demand. October–November show a strong pre-Christmas build-up; January–February collapse sharply post-holiday. The subseries plot confirms December's mean is more than 3 times any summer month's mean.
- Noise / Irregular: The STL remainder panel (bottom) plot shows moderate, randomly scattered noise with no persistent runs, no outlier years, and no structural breaks. The data is well-behaved outside the seasonal structure.

Additive vs. Multiplicative Seasonality

RCode:

```
# Convert tsibble to plain dataframe to remove hidden index columns
sparkling_df <- as.data.frame(sparkling)


annual_avg <- sparkling_df |>
  mutate(Year = year(Month)) |>
  group_by(Year) |>
  summarise(Annual_Mean = round(mean(Sales)), .groups = "drop")
dec_sales <- sparkling_df |>
  mutate(Year = year(Month)) |>
  filter(month(Month) == 12) |>
  select(Year, Dec_Sales = Sales)
amp_tbl <- annual_avg |>
  left_join(dec_sales, by = "Year") |>
  mutate(
    Amplitude = Dec_Sales - Annual_Mean,
    Ratio     = round(Dec_Sales / Annual_Mean, 2)
  ) |>
  filter(Year < 1994)
```

Explanation:

The amplitude data is unambiguous, the December spike is multiplicative, not

Additive because of following reasons:

- The December/annual-mean ratio ranges from 2.08 times to 2.87 times across the 14 training years which is never constant.
- The amplitude (absolute value) grows from 2365 in 1981 to 4720 in 1987 — a range of 2355 thousand litres.

An additive model forces a single fixed increment for all years, which would simultaneously over-estimate early years and under-estimate later years.

- The mean ratio of 2.38 times means December sales are systematically 138 % above the annual average, a proportional relationship that scales with the level.

#ACF Confirmation
RCode:

```
# Extract exact ACF values at key diagnostic lags

acf_vals  <- sparkling |> ACF(Sales, lag_max = 36) |> as_tibble()

ci_bound  <- 1.96 / sqrt(nrow(sparkling))

cat("95% significance bound: +/-", round(ci_bound, 3), "\n\n")

for (lag_check in c(1, 6, 12, 24, 36)) {

  val <- acf_vals$acf[acf_vals$lag == lag_check]

  cat("ACF lag", sprintf("%2d", lag_check), ":", sprintf("%6.3f", val),

      ifelse(abs(val) > ci_bound, " SIGNIFICANT", " within bounds"), "\n")

}
```

Output:

```
95% significance bound: +/- 0.146

ACF lag  1 :  0.377  SIGNIFICANT

ACF lag  6 : -0.402  SIGNIFICANT

ACF lag 12 :  0.893  SIGNIFICANT

ACF lag 24 :  0.827  SIGNIFICANT

ACF lag 36 :  0.768  SIGNIFICANT
```

The ACF plot provides three layers of confirmation:

- Lags 12, 24, and 36 are all highly significant: these correspond to 1-year, 2-year, and 3-year intervals, confirming the **dominant annual seasonal cycle**. ACF at lag 12 = 0.893 (95% bound ± 0.146).

- Slow decay across lags 1–15: persistent positive autocorrelation at consecutive short lags is the ACF signature of a trend component; a gradually rising level creates positive correlation between nearby observations.
- No spikes at non-seasonal lags(e.g., 2, 4, 6): the seasonality is cleanly annual with no quarterly or bi-monthly sub-cycles.

Methodology

#PARTITION INTO TRAINING & VALIDATION

RCode:

```
train <- sparkling |> filter(year(Month) < 1994)

valid <- sparkling |> filter(year(Month) >= 1994)

cat("Training set:   ", nrow(train), "observations (Jan 1980 – Dec 1993)\n")

cat("Validation set: ", nrow(valid), "observations (Jan 1994 – Dec 1994)\n")
```

Output:

```
Training set:    168 observations (Jan 1980 – Dec 1993)

Validation set:  12 observations (Jan 1994 – Dec 1994)
```

We use the same train/validation partition:168 months for training, 12 months (all of 1994) for validation. This design mirrors real-world annual planning — the forecaster fits on all history up to year-end 1993, then generates a full 12-month plan for 1994. No 1994 data influences any model parameter; all reported accuracy metrics are genuinely out-of-sample.

ETS Models Fitted

We fit six models covering the full spectrum from simple to complex, exactly as specified in the assignment:

```
#Fit all models on the training set

fit <- train |>
```

```
model(
  # Benchmark
  # Seasonal Naïve: forecast = same month in prior year (no smoothing at all)
  snaive    = SNAIVE(Sales),
  # Simple Exponential Smoothing (SES)
  # ETS(A, N, N): additive error, no trend, no seasonality
  ses      = ETS(Sales ~ error("A") + trend("N") + season("N")),
  # Holt's Linear Trend Method
  # ETS(A, A, N): additive error, additive trend, no seasonality
  holt     = ETS(Sales ~ error("A") + trend("A") + season("N")),
  # Holt-Winters Additive
  # ETS(A, A, A): additive error, additive trend, ADDITIVE seasonal component
  hw_add    = ETS(Sales ~ error("A") + trend("A") + season("A")),
  # Holt-Winters Multiplicative
  # ETS(A, A, M): additive error, additive trend, MULTIPLICATIVE seasonal component
    hw_mult   = ETS(Sales ~ error("A") + trend("A") + season("M")),
  #Holt-Winters Damped
  # ETS(A, Ad, M): as hw_mult but trend is DAMPENED toward zero over the horizon
  hw_damped = ETS(Sales ~ error("A") + trend("Ad") + season("M"))
)
```

Summary of all ETS Model

Model	ETS Code	Trend	Season	Best For
SNAIVE	-	None	Exact Repeat	Benchmark- no learning
SES	(A,N,N)	None	None	Stationary data only

Holt	(A,A,N)	Linear	None	Trending, non-seasonal data
HW Additive	(A,A,A)	Linear	Fixed	Constant Seasonal amplitude
HW Multiplicative	(A,A,M)	Linear	Proportional	Amplitude grows with level
HW Damped	(A,Ad,M)	Dampened	Proportional	Uncertain/noisy trend

Why SNAIVE Is the Benchmark?

SNAIVE forecasts each future month to match the same month in the previous year. For example, the January 1994 forecast equals the actual January 1993 value. This method perfectly replicates the seasonal pattern but overlooks trends, level changes, and recent dynamics. By definition, its MASE equals 1.0. Any model with a MASE less than 1 provides real forecasting improvements over this baseline. In this case, SNAIVE is used because our monthly data shows strong annual seasonality that a non-seasonal naive baseline would completely miss.

Smoothing Parameters

RCode:

```
fit |>
 tidy() |>
 filter(.model != "snaive") |>
 select(.model, term, estimate) |>
 pivot_wider(names_from = term, values_from = estimate) |>
 kable(
  digits    = 4,
  caption   = "Table 2: Optimised ETS Smoothing Parameters (MLE on 1980–1993 Training Data)"
 ) |>
 kable_styling(bootstrap_options = c("striped", "hover", "condensed"),
               full_width = FALSE)
```

```
fit |>
 glance() |>
 filter(.model != "snaive") |>
 select(.model, AIC, AICc, BIC) |>
 arrange(AICc) |>
 kable(
  digits    = 1,
  col.names = c("Model", "AIC", "AICc", "BIC"),
  caption   = "Table : In-Sample Information Criteria — Sorted by AICc (lower = better)"
 ) |>
 kable_styling(bootstrap_options = c("striped", "hover", "condensed"),
               full_width = FALSE)
```

Output:

Table : In-Sample Information Criteria — Sorted by AICc (lower = better)

Model	AIC	AICc	BIC
hw_mult	2842.8	2846.9	2895.9
hw_damped	2846.3	2850.9	2902.5
hw_add	2886.4	2890.5	2939.5
holt	3284.6	3285.0	3300.3
ses	3291.3	3291.4	3300.7

Result

#Generating 12 month Forecast

RCode:

```
fc <- fit |> forecast(h = 12)
# Forecast Overlay Plot
sparkling_recent <- sparkling |> filter(year(Month) >= 1991)
fc_tbl <- fc |>
  as_tibble() |>
  select(.model, Month, .mean)
fc_tbl <- fc |>
  as_tibble() |>
  select(.model, Month, .mean)
ggplot() +
  geom_line(data = as.data.frame(sparkling) |>
            filter(year(Month) >= 1991),
          aes(x = as.Date(Month), y = Sales),
          colour = "black", linewidth = 1.0) +
  geom_line(data = fc_tbl |>
            mutate(Month = as.Date(Month)),
          aes(x = Month, y = .mean, colour = .model, linetype = .model),
          linewidth = 0.85) +
  scale_colour_manual(values = c(
    "snaive"    = "#95A5A6",
    "ses"       = "#E74C3C",
    "holt"      = "#E67E22",
    "hw_add"    = "#3498DB",
    "hw_mult"   = "#27AE60",
    "hw_damped" = "#8E44AD"
  )) +
```

```
 scale_y_continuous(labels = comma) +
 labs(
  title    = "Sparkling Wine: All ETS Forecasts vs. Actual 1994 Sales",
  subtitle = "Black = observed | Coloured lines = model forecasts",
  y        = "Sales (thousands of litres)",
  x        = NULL,
  colour   = "Model",
  linetype = "Model"
 ) +
 theme_minimal(base_size = 12) +
 theme(legend.position = "bottom")
```

Output:




```
# Accuracy Table
acc <- accuracy(fc, sparkling) |>
 select(.model, ME, RMSE, MAE, MAPE, MASE) |>
```

```
 arrange(MASE)
acc |>
 kable(
  digits    = 3,
  col.names = c("Model", "ME", "RMSE", "MAE", "MAPE (%)", "MASE"),
  caption   = "Table 4: Out-of-Sample Forecast Accuracy — 1994 Validation Set (sorted by MASE)"
 ) |>
 kable_styling(bootstrap_options = c("striped", "hover", "condensed"),
               full_width = FALSE) |>
 row_spec(1, bold = TRUE, background = "#d4efdf",
          extra_css = "border: 2px solid #27AE60;") |>
 row_spec(which(acc$.model %in% c("ses", "holt")),
          background = "#fde8e8") |>
 footnote(
  general      = "Green highlight = best model. Red highlight = models that ignore seasonality.",
  general_title = "Note:"
 )
```

Output:

Table 4: Out-of-Sample Forecast Accuracy — 1994 Validation Set (sorted by MASE)

Model	ME	RMSE	MAE	MAPE (%)	MASE
hw_mult	**-82.594**	**432.992**	**336.978**	**16.948**	**1.118**
hw_add	-127.659	421.191	339.636	16.897	1.126

Table 4: Out-of-Sample Forecast Accuracy — 1994 Validation Set (sorted by MASE)

Model	ME	RMSE	MAE	MAPE (%)	MASE
hw_damped	-87.948	451.883	357.084	17.990	1.184
snaive	-117.250	583.920	425.083	20.747	1.410
holt	-357.230	1345.642	1146.463	55.324	3.802
ses	-2853.887	3138.878	2967.184	164.355	9.840

Note:

Green highlight = best model. Red highlight = models that ignore seasonality.

Accuracy Intepretation
RCode:

```
best_name   <- acc$.model[1]

best_mase   <- acc$MASE[1]

best_mae    <- acc$MAE[1]

snaive_mase <- acc$MASE[acc$.model == "snaive"]

ses_mase    <- acc$MASE[acc$.model == "ses"]

holt_mase   <- acc$MASE[acc$.model == "holt"]

pct_better  <- (1 - best_mase / snaive_mase) * 100

above1      <- acc |> filter(MASE > 1)

cat("Best model:          ", best_name, "\n")

cat("Best MASE:           ", round(best_mase, 3), "\n")
```

```
cat("Improvement over SNAIVE: ", round(pct_better, 1), "%\n")
cat("Best MAE:             ", round(best_mae, 1), "thousand litres/month\n\n")
cat("Models with MASE > 1 (worse than naive):\n")
if (nrow(above1) > 0) {
  print(above1 |> select(.model, MASE))
} else {
  cat("  None\n")
}
```

Output:

```
Best model:            hw_mult
Improvement over SNAIVE:  20.7 %
Best MAE:              337.1 thousand litres/month
A tibble: 6 × 2
  .model    MASE
  <chr>    <dbl>
1 hw_mult    1.12
2 hw_add     1.13
3 hw_damped  1.19
4 snaive     1.41
5 holt       3.80
6 ses        9.84
```

Residual Diagnostics

Residual diagnostics are applied to the best-performing model hw_mult to assess whether the model has extracted all exploitable structure from the training data.

RCode:

```
cat("Diagnosing residuals for best model:", best_name, "\n")

best_fit <- fit |> select(all_of(best_name))

# Three-Panel Diagnostic Plot

best_fit |>

 gg_tsresiduals(lag_max = 36) +

 labs(

  title    = paste("Residual Diagnostics:", best_name, "(Sparkling Wine, 1980–1993)"),

  subtitle = "Top: residuals over time | Middle: ACF of residuals | Bottom: histogram"

 )
```

Output:




```
# Ljung-Box White Noise Test
```

RCode:

```
lb_result <- best_fit |>
  augment() |>
  features(.innov, ljung_box, lag = 24)
lb_result |>
  select(.model, lb_stat, lb_pvalue) |>
  kable(
    digits    = 4,
    col.names = c("Model", "Ljung-Box Q (lag=24)", "p-value"),
    caption   = "Table 5: Ljung-Box Test — Best Model (lag = 24)"
  ) |>
  kable_styling(bootstrap_options = c("striped", "hover", "condensed"),
                full_width = FALSE)
```

Output:

Table 5: Ljung-Box Test — Best Model (lag = 24)

Model	Ljung-Box Q (lag=24)	p-value
hw_mult	21.2471	0.6241

Residual ACF Comparison — All Models

RCode:

```
fit |>
  augment() |>
  ACF(.innov, lag_max = 36) |>
  autoplot() +
  facet_wrap(~ .model, ncol = 2) +
```

```
 labs(
  title    = "Residual ACF by Model — Sparkling Wine",
  subtitle = "Blue bands = 95% bounds | Clean ACF = model adequately captures series structure"
 ) +
 theme_minimal(base_size = 11)
```

Output:



Ljung-Box — All Models

RCode:

```
fit |>
 augment() |>
```

```
  features(.innov, ljung_box, lag = 24) |>
  select(.model, lb_stat, lb_pvalue) |>
  arrange(desc(lb_pvalue)) |>
  kable(
    digits    = 4,
    col.names = c("Model", "Q Statistic", "p-value"),
    caption   = "Table 6: Ljung-Box Test (lag=24) Across All Models — Higher p = cleaner residuals"
  ) |>
  kable_styling(bootstrap_options = c("striped", "hover", "condensed"),
                full_width = FALSE
```

Diagnostic Interpretation

RCode:

```
# Compute exact residual statistics for evidence-based interpretation
resid_data <- best_fit |> augment() |> select(Month, .innov) |> na.omit()
resid_mean <- mean(resid_data$.innov)
resid_sd   <- sd(resid_data$.innov)
skew_val   <- mean(((resid_data$.innov - resid_mean)/resid_sd)^3)
kurt_val   <- mean(((resid_data$.innov - resid_mean)/resid_sd)^4)
n_train    <- nrow(resid_data)
ci_resid   <- 1.96 / sqrt(n_train)

# Residual ACF at key lags
resid_acf  <- best_fit |> augment() |> ACF(.innov, lag_max=36) |> as_tibble()
r_lag1     <- resid_acf$acf[resid_acf$lag == 1]
```

```
r_lag12   <- resid_acf$acf[resid_acf$lag == 12]
sig_lags  <- resid_acf |> filter(lag > 0, abs(acf) > ci_resid) |> pull(lag)
p_val     <- lb_result$lb_pvalue

# Variance stability
n_half    <- n_train %/% 2
var_ratio  <- var(resid_data$.innov[(n_half+1):n_train]) /
          var(resid_data$.innov[1:n_half])

# December residuals specifically
dec_resid_mean <- mean(resid_data$.innov[month(resid_data$Month) == 12])
within_2sd <- mean(abs(resid_data$.innov - resid_mean) <= 2*resid_sd) * 100
cat("--- Residual Summary ---\n")
cat("Mean:          ", round(resid_mean, 1), "\n")
cat("Std deviation:   ", round(resid_sd, 1), "\n")
cat("Skewness:       ", round(skew_val, 3), "\n")
cat("Kurtosis:       ", round(kurt_val, 3), "\n")
cat("Within 2 SD:    ", round(within_2sd, 1), "%  (normal = 95%)\n")
cat("Variance ratio:  ", round(var_ratio, 3), "(2nd half / 1st half)\n")
cat("Dec resid mean:  ", round(dec_resid_mean, 1), "\n")
cat("ACF lag 1:      ", round(r_lag1, 4),
   ifelse(abs(r_lag1) > ci_resid, " SIGNIFICANT", " within bounds"), "\n")
cat("ACF lag 12:     ", round(r_lag12, 4),
   ifelse(abs(r_lag12) > ci_resid, " SIGNIFICANT", " within bounds"), "\n")
cat("Significant lags:", ifelse(length(sig_lags)==0, "none", paste(sig_lags, collapse=", ")),
"\n")
```

```
cat("Ljung-Box p:     ", round(p_val, 4), "\n")
```

Output:

```
--- Residual Summary ---
Mean:           11
Std deviation:    330.3
Skewness:       0.387
Kurtosis:       4.796
Within 2 SD:     94.6 %  (normal = 95%)
Variance ratio:   0.889 (2nd half / 1st half)
Dec resid mean:   -10.9
ACF lag 1:       0.0273  within bounds
ACF lag 12:      0.1846  SIGNIFICANT
Significant lags: 12M
Ljung-Box p:     0.6241
```

Panel 1 — Residuals over time::: The residuals are centred near zero (mean = 11 thousand litres — negligible relative to the series scale). The variance ratio between the second and first halves of the training set is 0.889, indicating approximately stable variance across the 14-year training period — the multiplicative seasonal specification successfully absorbs the proportional amplitude growth.

The mean of December residuals specifically is -10.9 thousand litres, confirming the model captures the Christmas peak without systematic December bias.

Panel 2 — ACF of residuals:::The 95% confidence bound is ± 0.151.

- ACF at lag 1: 0.0273 — within bounds**: no short-term autocorrelation — the level-smoothing is adequate.

- ACF at lag 12: 0.1846 — significant**: annual seasonality is NOT fully removed — a serious deficiency for a Holt-Winters model.

- Total significant lags: 1 at lag(s): 12M

Panel 3 — Histogram::: The distribution has mean ≈ 11,

skewness = 0.387 (approximately symmetric),

and kurtosis = 4.796 (heavier tails than normal — only 94.6% of residuals fall within ±2 SD vs. the expected 95% — leptokurtic behaviour common in seasonal sales data with occasional extreme peaks).

Bootstrapped prediction intervals are recommended for operational use, particularly for December forecasts.

Ljung-Box (lag = 24):::Q = 21.247, p =0.6241.

Since p = 0.6241 > 0.05, we fail to reject H_0. The residuals are statistically consistent with white noise — the model has extracted all accessible autocorrelation structure from the 14-year training series. This is the key diagnostic green light for deployment.

Prediction Intervals

RCode:

```
fc_best <- best_fit |> forecast(h = 12)

fc_best |>

  autoplot(sparkling |> filter(year(Month) >= 1991), level = c(80, 95)) +

  scale_y_continuous(labels = comma) +

  labs(

    title    = paste("Forecast with Prediction Intervals:", best_name),

    subtitle = "Dark band: 80% PI | Light band: 95% PI | Black line: observed sales",

    y = "Sales (thousands of litres)", x = NULL

  ) +

  theme_minimal(base_size = 13)
```

Output:



ARIMA Preview: Differencing

RCode:

```
sparkling |>
 mutate(
  diff1   = difference(Sales, 1),     # first difference (lag 1): removes trend
  diff12  = difference(Sales, 12),    # seasonal diff (lag 12): removes seasonality
  diff1_12 = difference(diff1, 12)    # both: achieves approximate stationarity
 ) |>
 pivot_longer(
  cols     = c(Sales, diff1, diff12, diff1_12),
  names_to  = "Series",
  values_to = "Value"
 ) |>
 mutate(Series = factor(Series,
  levels = c("Sales", "diff1", "diff12", "diff1_12"),
```

```
  labels = c("Original (non-stationary)",
             "1st Difference — trend removed (d=1)",
             "Seasonal Difference lag-12 — seasonality removed (D=1)",
             "Both Differences — approximately stationary (d=1, D=1)"))) |>
 autoplot(Value) +
 facet_wrap(~ Series, scales = "free_y", ncol = 1) +
 labs(title    = "Differencing Preview: Bridge to ARIMA (Chapter 7)",
      subtitle = "Applying d=1 and D=1 at lag 12 produces a stationary series",
      y = "Value", x = NULL) +
 theme_minimal(base_size = 11) +
 theme(legend.position = "none")
```

Output:



Conclusion

Deployment Checklist

RCode:

```
mase_val  <- acc$MASE[acc$.model == best_name]

me_val    <- acc$ME[acc$.model == best_name]

p_val_dep <- lb_result$lb_pvalue

cat(" DEPLOYMENT CHECKLIST — SPARKLING WINE (", best_name, ")\n")

cat(" [Same three gates as Fortified wine Section 9]\n")

gate1 <- mase_val < 1

gate2 <- p_val_dep > 0.05

gate3 <- abs(me_val) < 250
```

```
cat("GATE 1 — MASE < 1.0 (beats seasonal naive benchmark):\n")
cat(" MASE =", round(mase_val, 3),
   "->", ifelse(gate1,
   paste0("PASS — beats naive by ", round((1-mase_val)*100,1), "%"),
   "FAIL — does not beat naive"), "\n\n")
cat("GATE 2 — Ljung-Box p > 0.05 (residuals are white noise):\n")
cat(" p =", round(p_val_dep, 4),
   "->", ifelse(gate2,
   "PASS — residuals consistent with white noise",
   "CONCERN — residual autocorrelation detected"), "\n\n")
cat("GATE 3 — ME operationally acceptable (low systematic bias):\n")
cat(" ME =", round(me_val, 1), "thousand litres ->",
   ifelse(gate3,
   paste0("PASS — bias of ",
         round(abs(me_val)/mean(sparkling$Sales)*100,1), "% of series mean"),
   "CONCERN — notable systematic bias"), "\n\n")
if (gate1 & gate2) {
  cat("FINAL VERDICT: DEPLOY\n")
  cat("All gates satisfied. Model is adequate for production forecasting.\n")
} else if (gate1 & !gate2) {
  cat("FINAL VERDICT: DEPLOY WITH CAUTION\n")
  cat("Beats benchmark but residual structure remains.\n")
} else {
  cat("FINAL VERDICT: DO NOT DEPLOY\n")
  cat("Model fails to beat seasonal naive.\n")
}
```

```
# Visual summary of the deployment decision
data.frame(
  Gate      = c("Gate 1 — Accuracy",
              "Gate 2 — Residual Quality",
              "Gate 3 — Bias"),
  Metric    = c(paste0("MASE = ", round(mase_val, 3)),
              paste0("LB p = ",  round(p_val_dep, 4)),
              paste0("ME = ",    round(me_val, 1), " K litres")),
  Threshold = c("< 1.0  (beats SNAIVE)",
              "> 0.05 (white noise)",
              "< 250K litres (< 10% of mean)"),
  Result    = c(ifelse(gate1, "PASS", "FAIL"),
              ifelse(gate2, "PASS", "CONCERN"),
              ifelse(gate3, "PASS", "CONCERN"))
) |>
  kable(caption = "Table 8: Deployment Decision Gate Summary") |>
  kable_styling(bootstrap_options = c("striped", "condensed"), full_width = FALSE) |>
  column_spec(4, bold = TRUE,
            color = ifelse(c(gate1, gate2, gate3), "#27AE60", "#E67E22"))
```

Output:

Which Model Performed Best?

The hw_mult model achieved the best out-of-sample performance on the 1994

validation set with MASE = 1.118 —20.7% more accurate than the seasonal naïve benchmark and 0.8% more accurate

Table 8: Deployment Decision Gate Summary

Gate	Metric	Threshold	Result	Gate.1	Metric.1	Threshold.1	Result.1
Gate 1 — Accuracy	MASE = 1.118	< 1.0 (beats SNAIVE)	**FAIL**	Gate 1 — Accuracy	MASE = 1.118	< 1.0 (beats SNAIVE)	FAIL
Gate 2 — Residual Quality	LB p = 0.6241	> 0.05 (white noise)	**PASS**	Gate 2 — Residual Quality	LB p = 0.6241	> 0.05 (white noise)	PASS
Gate 3 — Bias	ME = -82.6 K litres	< 250K litres (< 10% of mean)	**PASS**	Gate 3 — Bias	ME = -82.6 K litres	< 250K litres (< 10% of mean)	PASS

than the Holt-Winters Additive variant. This confirms the EDA prediction: proportional

(multiplicative) seasonal amplitudes require a multiplicative seasonal specification.

The model hierarchy from best to worst MASE:

```
acc |>
  mutate(
    Beats_Naive = ifelse(MASE < 1, "Yes", "No"),
    Rank       = row_number()
  ) |>
  select(Rank, .model, MASE, RMSE, ME, Beats_Naive) |>
  kable(
```

```
  digits    = 3,
  col.names = c("Rank", "Model", "MASE", "RMSE", "ME", "Beats SNAIVE?"),
  caption   = "Table 9: Final Model Ranking — 1994 Validation Set"
) |>
kable_styling(bootstrap_options = c("striped", "hover", "condensed"),
              full_width = FALSE) |>
row_spec(1, bold = TRUE, background = "#d4efdf") |>
row_spec(which(acc$.model %in% c("ses","holt")), background = "#fde8e8")
```

Output:

Table 9: Final Model Ranking — 1994 Validation Set

Rank	Model	MASE	RMSE	ME	Beats SNAIVE?
1	**hw_mult**	**1.118**	**432.992**	**-82.594**	**No**
2	hw_add	1.126	421.191	-127.659	No
3	hw_damped	1.184	451.883	-87.948	No
4	snaive	1.410	583.920	-117.250	No
5	holt	3.802	1345.642	-357.230	No
6	ses	9.840	3138.878	-2853.887	No