



JAI MARUTHI POLYMERS

AN ISO 9001:2005 CERTIFIED COMPANY



Unit 1: Survey No.160/2, Durainallur Village,
Puduvoyal Post, Ponneri Taluk, Thiruvallur District,
Tamilnadu, India - 601206.

Unit 2 : Survey No.408/6, Kongal Road, Melpakkam Village,
Eguvarpalayam Post, Gummidipoondi Taluk, Thiruvallur District,
Tamilnadu, India - 601201.

E-Mail: jaimaruthipolymers@gmail.com
Phone No: 9380505265 | 8110037464

Our Company Profile

- ❖ JAI MARUTHI POLYMERS was established in the year 2009 as a Basic Plastic Scrap Sorting and Recycling company.
- ❖ With the growth of Automotive and Home Appliances Industries in Tamilnadu from the Year 2000, there is significant increase in demand for Recycled and Reprocessed Polymers.
- ❖ Jai Maruthi Polymers utilized its Knowledge and Experience in the Plastics Recycling and Reprocessing of Various Polymers and expanded its market as a leading Manufacturer and Trading of Recycled / Reprocessed Polypropylene Granule, Regrinds and Engineering Polymers (PA6, PA66, PC, ABS, PC/PBT, PC/ABS, ASA, HIPS, PET).
- ❖ The Company has a Strong Functional Core Team expertise in Technical, Production and Quality Management.
- ❖ Presently, We are processing 3600 MT of Polymers annually.

Mission

To Achieve Excellence In Recycling & Reprocessing Of Plastic Industry By Benefitting The Customer by Modifying the Properties by Value Addition.

Polymers- We Recycle & Reprocess

- Polypropylene
- Polycarbonate (PC)
- PC/PBT
- PC/ABS
- PA6 / Pa66
- ASA
- PET
- HIPS
- LDPE
- LLPDE





GOALS

- ❖ 100% Recycling | ❖ Value Addition to the Polymer Scrap
- ❖ Sustainability | ❖ Save our Earth from Plastic Waste

POLYPROPYLENE

Properties	UOM	PPCP-1	PPCP-2	PPCP-3	PPCP-4	PPHP - 1
Filler Content	%	Max 5	Max 5	Max 5	Max 5	Max 5
MFI	g/10 min	8 to 15	25 to 35	Min 0.50	Min 8	8 to 15
Tensile Strength	Kg/Sq.cm	Min 200	Min 200	Min 180	Min 200	Min 250
Impact Strength	Kg-cm/cm	Min 6	Min 6	Min 20	Min 12	Min 2.50

ENGINEERING POLYMERS

Properties	UOM	PC	Nylon (Unfilled)	Nylon (Glass Filled)	PC/PBT	PC/ABS	PBT
Filler Content	%	Max 3	Max 5	30	Max 3	Max 3	Max 3
MFI	g/10 min	15 to 35	---	---	15 to 35	15 to 35	15 to 35
Tensile Strength	Kg/Sq.cm	Min 500	Min 450	Min 1000	Min 450	Min 500	Min 500
Impact Strength	Kg-cm/cm	Min 20	5 to 25	6 to 12	10 to 30	10 to 30	2 to 5



Thank You.....