

Logbook

RTOS Q4
(Linux Device Driver)

Contents

1. Before we start	3
2. Trying out the sample	4
2.1. The sample driver from Apriorit	4
2.1.1. <code>pr_notice</code> fun fact :	6
2.2. The Conclutions with Apriorit	10
3. Making my own device driver.	12
3.1. Driver, In the making	12
3.1.1. Modifying <code>main.c</code>	12
3.1.2. Modifying <code>device_file.c</code>	12
3.1.3. First run	15
3.2. C kernel reader, In the making	17
3.3. Conclutions	19
3.3.1. Commands that is used	19
3.3.2. Core Concepts	19
3.3.2.1. Character Device Registration and The Mall Analogy	19
3.3.2.2. Memory Isolation and Data Transfer Functions	20
4. Trying the GPIO	21
4.1. LED Controlling	21
4.1.1. GPIO Headers and Module Parameters	21
4.1.2. Device Write Handler	21
4.1.3. File Operations Mapping	22
4.1.4. GPIO Lifecycle Management	22
4.2. Nokia Screen SPI	23
4.2.1. Planning	23
4.2.2. SPI research in the making	23

1. Before we start

This is the second logbook for RealTime Operating System. This assignment goals is to make us understand more about making a Linux Driver.

And this is my logbook of trying to make things work

2. Trying out the sample

2.1. The sample driver from Apriorit

from the assignment, we have to try out the sample linux driver from Apriorit. And this is what i get from the first simple driver explanation in the web (also in GitHub).

```
#include "device_file.h"
#include <linux/init.h>      /* module_init, module_exit */
#include <linux/module.h>    /* version info, MODULE_LICENSE, MODULE_AUTHOR
*/

MODULE_DESCRIPTION("Simple Linux driver");
MODULE_LICENSE("GPL");
MODULE_AUTHOR("Apriorit, Inc");

static int simple_driver_init(void)
{
    int result = 0;
    pr_notice("Simple-driver: Initialization started\n");

    result = register_device();
    if (result)
    {
        pr_notice("Simple-driver: Failed to register character device\n");
    }
    return result;
}

static void simple_driver_exit(void)
{
    pr_notice("Simple-driver: Exiting\n");
    unregister_device();
}

module_init(simple_driver_init);
module_exit(simple_driver_exit);
```

Let me explain a bit of what is happening here :

- **module_init** → This is the function that tell the driver module loader (`insmod`, insert module) the function to run. In this case it would run the `simple_driver_init` function
- **module_exit** → This is the function that tell the driver module remover (`rmmod`, remove module) the function to run. In this case it would run the `simple_driver_exit` function
- **MODULES (anything with this in front)** → This is the module descriptor, so if you do `modinfo` you can see the description listed there.

- **pr_notice** → This is basically like the printf of your normal c file, but this print the notice in your dmesg (fun fact about pr_notice after this)

2.1.1. `pr_notice` fun fact :

```
printk(KERN_NOTICE "Simple-driver: Initialization started\n");  
pr_notice("Simple-driver: Initialization started\n");
```

this two are the same thing, so `pr_notice` is just `printk` with `KERN_NOTICE`. For me personally, i would just use `printk` because of muscle memory to type `printf`

But then after some searching, there is actually more to put in the `printk` function

- `KERN_EMERG` ⇒ System is unusable.
- `KERN_ERR` ⇒ Error conditions (usually used if `register_device()` fails).
- `KERN_WARNING` ⇒ Warning flags.
- `KERN_INFO` ⇒ Informational messages tracking healthy runtime behaviors.
- `KERN_NOTICE` ⇒ Normal but significant operational alerts.

The code is too long for me to put it here, so you can just open the code from https://github.com/apriorit/SimpleLinuxDriver/blob/master/device_file.c

Let me break it down for you :

```
int register_device(void) {  
    int result = 0;  
  
    pr_notice("Simple-driver: register_device() is called.\n");  
  
    unsigned baseminor = 0;  
    unsigned minor_count_required = 1;  
    result = alloc_chrdev_region(&g_devno, baseminor, minor_count_required,  
device_name);  
    if (result)  
    {  
        pr_err("Simple-driver: alloc_chrdev_region failed: %d\n", result);  
        goto err_out;  
    }  
  
    cdev_init(&g_cdev, &simple_driver_fops);  
    g_cdev.owner = THIS_MODULE;  
    result = cdev_add(&g_cdev, g_devno, minor_count_required);  
    if (result)  
    {  
        pr_err("Simple-driver: cdev_add failed: %d\n", result);  
        goto err_unregister_chrdev_region;  
    }  
  
    g_class = class_create(class_name);  
    if (IS_ERR(g_class))  
    {
```

```
        result = PTR_ERR(g_class);
        pr_err("Simple-driver: class_create failed: %d\n", result);
        goto err_cdev_del;
    }

    g_device = device_create(g_class, NULL, g_devno, NULL, device_name);
    if (IS_ERR(g_device))
    {
        result = PTR_ERR(g_device);
        pr_err("Simple-driver: device_create failed: %d\n", result);
        goto err_class_destroy;
    }

    pr_notice("Simple-driver: Registered character device with major number =
%i, minor number = %i\n", MAJOR(g_devno), MINOR(g_devno));
    return 0;

err_class_destroy:
    if (!IS_ERR_OR_NULL(g_class))
    {
        class_destroy(g_class);
        g_class = NULL;
    }

err_cdev_del:
    cdev_del(&g_cdev);

err_unregister_chrdev_region:
    if (g_devno)
    {
        unsigned minor_count_allocated = 1;
        unregister_chrdev_region(g_devno, minor_count_allocated);
        g_devno = 0;
    }

err_out:
    return result;
}
```

This function is set for the module_init calling. In this function there is :

- 1. Allocate the identification (`alloc_chrdev_region`)
- 2. Initialize the internal kernel structure (`cdev_add`)
- 3. Create the system class functions (`class_create`)
- 4. Mount the user interface device file for I/O (`device_create`)

But then why is the code so long ? **Because of the fallback that we have**

Imagine if the code is crashing in step 4, you cannot just stop there, you have to clear all the steps before. Therefore you use a `goto` functions and make `err_` functions to handle the clear up for you. So this initializer function really make sure that you didn't leak any memory or anything bad that we don't want.

```
void unregister_device(void)
{
    pr_notice("Simple-driver: unregister_device() is called\n");

    if (!IS_ERR_OR_NULL(g_device))
    {
        device_destroy(g_class, g_devno);
        g_device = NULL;
    }

    if (!IS_ERR_OR_NULL(g_class))
    {
        class_destroy(g_class);
        g_class = NULL;
    }

    cdev_del(&g_cdev);

    if (g_devno)
    {
        unsigned minor_count_allocated = 1;
        unregister_chrdev_region(g_devno, minor_count_allocated);
        g_devno = 0;
    }
    pr_info("Simple-driver: Unregistered\n");
}
```

This is the function that was called to remove the kernel module from the loaded kernel module (in other word `rmmod`). Here there is not much thing to explain. Just the same way like when you do the error handling in the `register_device` on top.

And the rest of the code

```
static const char g_s_Hello_World_string[] = "Hello world from kernel mode!\n";
static const ssize_t g_s_Hello_World_size = sizeof(g_s_Hello_World_string);

static ssize_t device_file_read(
    struct file *file_ptr, char __user *user_buffer, size_t count, loff_t
    *position)
{
```



```
pr_notice("Simple-driver: Read from device file offset = %i, read bytes
count = %u\n", (int)*position, (unsigned int)count);

if (*position ≥ g_s_Hello_World_size)
    return 0;

if (*position + count > g_s_Hello_World_size)
    count = g_s_Hello_World_size - *position;

if (copy_to_user(user_buffer, g_s_Hello_World_string + *position, count) !
= 0)
    return -EFAULT;

*position += count;
return count;
}
```

When analyzing the runtime behavior using the `dmesg` tool, I noticed the driver outputs two lines showing the offset and read bytes count. I broke down what these numbers actually mean during the file access loop:

- **Read Bytes Count:** This value represents the maximum size of the memory buffer that the application (in this case, the `cat` command) has allocated to hold incoming data. The system defaults this to `4096` bytes because that is the standard size of a single memory page in Linux. The utility requests this full amount even though our message is much smaller, simply because it does not know the file's size in advance.
- **Offset:** This serves as a positional tracking cursor or bookmark. It tells the driver exactly which byte index to start reading from inside the kernel string array. An offset of `0` means reading starts at the first character.
- **The Dual-Read Loop Mechanism:** The log records two distinct access attempts because of how the reading loop operates in the background:
 1. **First Pass (`offset = 0`):** The tool requests data from the beginning. The driver copies the 30-byte message over and shifts the tracking offset position directly to index 30.
 2. **Second Pass (`offset = 30`):** The tool loops back to verify if more text exists. It requests more data starting at position 30. The driver checks the boundaries, sees the offset has reached the end of the text, and returns a value of `0`. This zero return acts as the standard End-of-File signal, telling the reading tool to stop and exit safely.

But, how to tell the operating system which code to execute when we run the kernel ?

To explain how the operating system knows which code to execute when we run commands, we have to look at the `simple_driver_fops` structure.

```
static const struct file_operations simple_driver_fops =
{
    .owner = THIS_MODULE,
    .read = device_file_read,
};

static const char device_name[] = "simple-driver";
static const char class_name[] = "simple-driver-class";
dev_t g_devno = 0;
struct cdev g_cdev = {};
static struct class *g_class = NULL;
static struct device *g_device = NULL;
```

To make this mechanism easy to visualize, think of this structure as a **Standardized Services Menu** at a bank counter:

- A customer walking up to the bank window represents a User Space program (like the `cat` command).
- The customer cannot just walk into the secure vault or tell the bank tellers to run custom errands. They have to choose a standard operation directly from the laminated service menu sitting on the counter.

I broke down how this structure maps those menu choices to our actual backend driver instructions:

- **The VFS Bridge (Treating Devices like Files):** In Linux, there is a core design rule: “Everything is a file.” When a terminal command tries to talk to our device path at `/dev/simple-driver`, it passes through a system boundary called the Virtual File System (VFS). The VFS picks up the request and instantly checks our `file_operations` structure to see what specific rules and actions this custom device file is allowed to support.
- **Module Safety Allocation (`.owner = THIS_MODULE`):** This line acts as a building safety lock. It tells the operating system exactly which module owns this operational menu
- **Function Redirection (`.read = device_file_read`):** This is the literal line that glues the standard operating system read action to our custom C function. When the user selects the “Read” option from the system menu, the VFS looks at this pointer and redirects the execution straight down into our `device_file_read` function. Because we did not define any `.write` or `.open` pathways on this menu, the Linux kernel automatically handles those missing choices with built-in safety rejections. This completely blocks any write requests by default and turns our code into a secure, read-only device.

2.2. The Conclutions with Apriorit

Basically, when we compile it we will get like a `.ko` file and that is the one that you can do `insmod`. The github that we can pull from apriorit actually have this in the cmake

```
TARGET_MODULE:=simple-module

# If we running by kernel building system
ifneq ($(KERNELRELEASE),)
    $(TARGET_MODULE)-objs := main.o device_file.o
    obj-m := $(TARGET_MODULE).o

# If we are running without kernel build system
else
    BUILDSYSTEM_DIR:=/lib/modules/$(shell uname -r)/build
    PWD:=$(shell pwd)

all :
# run kernel build system to make module
$(MAKE) -C $(BUILDSYSTEM_DIR) M=$(PWD) modules

clean:
# run kernel build system to cleanup in current directory
$(MAKE) -C $(BUILDSYSTEM_DIR) M=$(PWD) clean

load:
    insmod ./$(TARGET_MODULE).ko

unload:
    rmmod ./$(TARGET_MODULE).ko

endif
```

See the load and unload part, its using insmod and rmmod.

And from that, after we are done compiling it, it will make a `.ko` file which we can use for loading it to the active kernel module it will load the main.c (the first code that i gave on top), and it will utilize the module init in the device_file.c

3. Making my own device driver.

3.1. Driver, In the making

In this part of the logbook, i will continue with the assignment 1b which is to change the name to my own name `bastian-driver`

3.1.1. Modifying `main.c`

I will start from the main, here i change everything that says simple to NW1728 (my alias is `nw1728@np1770`) this is the full main code

```
#include "device_file.h"
#include <linux/init.h> /* module_init, module_exit */
#include <linux/module.h> /* version info, MODULE_LICENSE, MODULE_AUTHOR */

MODULE_DESCRIPTION("BastianEthan Linux Driver");
MODULE_LICENSE("GPL");
MODULE_AUTHOR("NW1728@NP1770");

static int NW1728_driver_init(void) {
    int result = 0;
    pr_notice("NW1728-driver: Initialization started\n");

    result = register_device();
    if (result) {
        pr_notice("NW1728-driver: Failed to register character device\n");
    }
    return result;
}

static void NW1728_driver_exit(void) {
    pr_notice("NW1728-driver: Exiting\n");
    unregister_device();
}

module_init(NW1728_driver_init);
module_exit(NW1728_driver_exit);
```

3.1.2. Modifying `device_file.c`

Now i am going to do the other part, which is `device_file.c`.

```
#include "device_file.h"
#include <linux/cdev.h>
#include <linux/device.h>
#include <linux/errno.h> /* error codes */
#include <linux/fs.h> /* file stuff */
#include <linux/module.h> /* THIS_MODULE */
```

```
#include <linux/printk.h> /* pr_* */
#include <linux/uaccess.h> /* copy_to_user() */

static const char g_s_Hello_World_string[] = "Hello world from kernel mode!
\n";
static const ssize_t g_s_Hello_World_size = sizeof(g_s_Hello_World_string);

static ssize_t device_file_read(struct file *file_ptr, char __user
*user_buffer,
                                size_t count, loff_t *position) {
    pr_notice("NW1728-driver: Read from device file offset = %i, read bytes "
              "count = %u\n",
              (int)*position, (unsigned int)count);

    if (*position ≥ g_s_Hello_World_size)
        return 0;

    if (*position + count > g_s_Hello_World_size)
        count = g_s_Hello_World_size - *position;

    if (copy_to_user(user_buffer, g_s_Hello_World_string + *position, count) ≠
0)
        return -EFAULT;

    *position += count;
    return count;
}

static const struct file_operations nw1728_driver_fops = {
    .owner = THIS_MODULE,
    .read = device_file_read,
};

static const char device_name[] = "nw1728-driver";
static const char class_name[] = "nw1728-driver-class";
dev_t g_devno = 0;
struct cdev g_cdev = {};
static struct class *g_class = NULL;
static struct device *g_device = NULL;

int register_device(void) {
    int result = 0;

    pr_notice("NW1728-driver: register_device() is called.\n");

    unsigned baseminor = 0;
    unsigned minor_count_required = 1;
```

```
result = alloc_chrdev_region(&g_devno, baseminor, minor_count_required,
                             device_name);
if (result) {
    pr_err("NW1728-driver: alloc_chrdev_region failed: %d\n", result);
    goto err_out;
}

cdev_init(&g_cdev, &nw1728_driver_fops);
g_cdev.owner = THIS_MODULE;
result = cdev_add(&g_cdev, g_devno, minor_count_required);
if (result) {
    pr_err("NW1728-driver: cdev_add failed: %d\n", result);
    goto err_unregister_chrdev_region;
}

g_class = class_create(class_name);
if (IS_ERR(g_class)) {
    result = PTR_ERR(g_class);
    pr_err("NW1728-driver: class_create failed: %d\n", result);
    goto err_cdev_del;
}

g_device = device_create(g_class, NULL, g_devno, NULL, device_name);
if (IS_ERR(g_device)) {
    result = PTR_ERR(g_device);
    pr_err("NW1728-driver: device_create failed: %d\n", result);
    goto err_class_destroy;
}

pr_notice("NW1728-driver: Registered character device with major number = "
          "%i, minor number = %i\n",
          MAJOR(g_devno), MINOR(g_devno));
return 0;

err_class_destroy:
if (!IS_ERR_OR_NULL(g_class)) {
    class_destroy(g_class);
    g_class = NULL;
}

err_cdev_del:
cdev_del(&g_cdev);

err_unregister_chrdev_region:
if (g_devno) {
    unsigned minor_count_allocated = 1;
    unregister_chrdev_region(g_devno, minor_count_allocated);
}
```

```
    g_devno = 0;
}

err_out:
    return result;
}

void unregister_device(void) {
    pr_notice("NW1728-driver: unregister_device() is called\n");

    if (!IS_ERR_OR_NULL(g_device)) {
        device_destroy(g_class, g_devno);
        g_device = NULL;
    }

    if (!IS_ERR_OR_NULL(g_class)) {
        class_destroy(g_class);
        g_class = NULL;
    }

    cdev_del(&g_cdev);

    if (g_devno) {
        unsigned minor_count_allocated = 1;
        unregister_chrdev_region(g_devno, minor_count_allocated);
        g_devno = 0;
    }
    pr_info("NW1728-driver: Unregistered\n");
}
```

3.1.3. First run

Nice, now everything is under my name. Lets try to run it with `make all` commands in the RPI 2B.

```
BASH
make -C /lib/modules/6.12.75+rpt-rpi-v7/build M=/home/nw1728/study/kernel/
SimpleLinuxDriver modules
make[1]: Entering directory '/usr/src/linux-headers-6.12.75+rpt-rpi-v7'
  CC [M] /home/nw1728/study/kernel/SimpleLinuxDriver/main.o
  CC [M] /home/nw1728/study/kernel/SimpleLinuxDriver/device_file.o
  LD [M] /home/nw1728/study/kernel/SimpleLinuxDriver/simple-module.o
  MODPOST /home/nw1728/study/kernel/SimpleLinuxDriver/Module.symvers
  CC [M] /home/nw1728/study/kernel/SimpleLinuxDriver/simple-module.mod.o
  CC [M] /home/nw1728/study/kernel/SimpleLinuxDriver/.module-common.o
  LD [M] /home/nw1728/study/kernel/SimpleLinuxDriver/simple-module.ko
make[1]: Leaving directory '/usr/src/linux-headers-6.12.75+rpt-rpi-v7'
```

But wait, why the name is SimpleLinuxDriver ?? Oh yeah, **THE MAKE FILE**, Aight im going to change the make file. I think i have to change the target.

```
TARGET_MODULE:=nw1728-module

# If we running by kernel building system
ifneq ($(KERNELRELEASE),)
    $(TARGET_MODULE)-objs := main.o device_file.o
    obj-m := $(TARGET_MODULE).o

# If we are running without kernel build system
else
    BUILDSYSTEM_DIR:=/lib/modules/$(shell uname -r)/build
    PWD:=$(shell pwd)

all :
# run kernel build system to make module
    $(MAKE) -C $(BUILDSYSTEM_DIR) M=$(PWD) modules

clean:
# run kernel build system to cleanup in current directory
    $(MAKE) -C $(BUILDSYSTEM_DIR) M=$(PWD) clean

load:
    insmod ./$(TARGET_MODULE).ko

unload:
    rmmod ./$(TARGET_MODULE).ko

endif
```

Okay, Now lets try to compile this one.

```
RPI-2B - ཨོཾ་མ་ཎི་པདྨེ་ཧཱུྃ་ OM MANI PADME HUM ཨེམ་ཎི་པདྨེ་ཧཱུྃ་
→ SimpleLinuxDriver git:(master) × make clean
make -C /lib/modules/6.12.75+rpt-rpi-v7/build M=/home/nw1728/study/kernel/
SimpleLinuxDriver clean
make[1]: Entering directory '/usr/src/linux-headers-6.12.75+rpt-rpi-v7'
CLEAN /home/nw1728/study/kernel/SimpleLinuxDriver/Module.symvers
make[1]: Leaving directory '/usr/src/linux-headers-6.12.75+rpt-rpi-v7'
RPI-2B - ཨོཾ་མ་ཎི་པདྨེ་ཧཱུྃ་ OM MANI PADME HUM ཨེམ་ཎི་པདྨེ་ཧཱུྃ་
→ SimpleLinuxDriver git:(master) × make all
make -C /lib/modules/6.12.75+rpt-rpi-v7/build M=/home/nw1728/study/kernel/
SimpleLinuxDriver modules
make[1]: Entering directory '/usr/src/linux-headers-6.12.75+rpt-rpi-v7'
CC [M] /home/nw1728/study/kernel/SimpleLinuxDriver/main.o
CC [M] /home/nw1728/study/kernel/SimpleLinuxDriver/device_file.o
```



```
LD [M] /home/nw1728/study/kernel/SimpleLinuxDriver/nw1728-module.o
MODPOST /home/nw1728/study/kernel/SimpleLinuxDriver/Module.symvers
CC [M] /home/nw1728/study/kernel/SimpleLinuxDriver/nw1728-module.mod.o
CC [M] /home/nw1728/study/kernel/SimpleLinuxDriver/.module-common.o
LD [M] /home/nw1728/study/kernel/SimpleLinuxDriver/nw1728-module.ko
make[1]: Leaving directory '/usr/src/linux-headers-6.12.75+rpt-rpi-v7'
```

Okay, now lets load it

```
RPI-2B - ཨོ་སྐྱོད་མཁུ་གུ་ལྟ་བུ་ OM MANI PADME HUM ཨམ་མཁུ་ལྟ་བུ་
→ SimpleLinuxDriver git:(master) × sudo make load
insmod ./nw1728-module.ko
RPI-2B - ཨོ་སྐྱོད་མཁུ་གུ་ལྟ་བུ་ OM MANI PADME HUM ཨམ་མཁུ་ལྟ་བུ་
→ SimpleLinuxDriver git:(master) × dmesg | tail -n 3
[141564.857824] NW1728-driver: Initialization started
[141564.857859] NW1728-driver: register_device() is called.
[141564.866247] NW1728-driver: Registered character device with major number =
239, minor number = 0
```

Okay lets check if its working or not

```
RPI-2B - ཨོ་སྐྱོད་མཁུ་གུ་ལྟ་བུ་ OM MANI PADME HUM ཨམ་མཁུ་ལྟ་བུ་
→ SimpleLinuxDriver git:(master) × ls -la /dev/* | grep 'driver'
crw----- 1 root root 239, 0 Jun 18 15:09 /dev/nw1728-driver
lrwxrwxrwx 1 root root 16 Jun 18 15:09 239:0 -> ../nw1728-driver
RPI-2B - ཨོ་སྐྱོད་མཁུ་གུ་ལྟ་བུ་ OM MANI PADME HUM ཨམ་མཁུ་ལྟ་བུ་
→ SimpleLinuxDriver git:(master) × sudo cat > /dev/nw1728-driver
zsh: permission denied: /dev/nw1728-driver
RPI-2B - ཨོ་སྐྱོད་མཁུ་གུ་ལྟ་བུ་ OM MANI PADME HUM ཨམ་མཁུ་ལྟ་བུ་
→ SimpleLinuxDriver git:(master) × sudo chmod 666 /dev/nw1728-driver
RPI-2B - ཨོ་སྐྱོད་མཁུ་གུ་ལྟ་བུ་ OM MANI PADME HUM ཨམ་མཁུ་ལྟ་བུ་
→ SimpleLinuxDriver git:(master) × sudo cat < /dev/nw1728-driver
Hello world from kernel mode!
```

Great Success, -borat

3.2. C kernel reader, In the making

The wise one once typed

“Make also a small test programme in C where you open the device as a file, read from it character for character and displaying them using printf.”

So i am going to do exactly what the wise one told me to do

C

```
#include <stdio.h>
#include <stdlib.h>
#include <fcntl.h>
#include <unistd.h>
#include <errno.h>

#define DEVICE_PATH "/dev/nw1728-driver"

int main(void)
{
    // Open the device file in read-only mode
    int fd = open(DEVICE_PATH, O_RDONLY);
    if (fd < 0)
    {
        perror("Error: Cannot open device file. Did you load the module and
are you root?");
        return EXIT_FAILURE;
    }

    printf("Successfully opened %s\n", DEVICE_PATH);
    printf("--- Reading contents character by character ---\n");

    char ch;
    ssize_t bytes_read;

    // Read exactly 1 byte at a time until end-of-file (0) or error (-1)
    while ((bytes_read = read(fd, &ch, 1)) > 0)
    {
        // Flush stdout immediately to see character-by-character progression
        printf("%c", ch);
        fflush(stdout);
    }

    if (bytes_read < 0)
    {
        perror("\nError occurred while reading from device");
        close(fd);
        return EXIT_FAILURE;
    }

    printf("\n--- End of File reached ---\n");

    // Clean up resource descriptor
    close(fd);
    return EXIT_SUCCESS;
}
```

And now lets try to compile and run it

```
RPI-2B - ཨོ་མ་ཎི་པདྨ་ཧུཾ་ OM MANI PADME HUM ཨོ་མ་ཎི་པདྨ་ཧུཾ་
→ SimpleLinuxDriver git:(master) × gcc test_client.c -o test_client
RPI-2B - ཨོ་མ་ཎི་པདྨ་ཧུཾ་ OM MANI PADME HUM ཨོ་མ་ཎི་པདྨ་ཧུཾ་
→ SimpleLinuxDriver git:(master) × ./test_client
Successfully opened /dev/nw1728-driver
--- Reading contents character by character ---
Hello world from kernel mode!

--- End of File reached ---
```

Nice, it works again.

Now lets play with GPIO Pins (or what Raspberry call HAT+)

3.3. Conclutions

3.3.1. Commands that is used

- Compilation : `make`
 - **Why it is used:** Compiles the source files (`main.c` and `device_file.c`) and generates the kernel module object file (`nw1728-module.ko`).
- Installation: `sudo insmod nw1728-module.ko`
 - **Why it is used:** “Insert Module” dynamically loads our `.ko` module into the running kernel.
- Execution/Testing: Writing and Reading the Device File
 - **Why it is used:** We use standard file utilities like `echo` and `tee` to write control signals to the driver, or `cat` to read from it.
 - **Commands:**
 - To Turn LED ON: `echo "1" | sudo tee /dev/nw1728-driver`
 - To Turn LED OFF: `echo "0" | sudo tee /dev/nw1728-driver`
 - To Read Hello Message: `cat /dev/nw1728-driver`
- Uninstallation: `sudo rmmod nw1728-module`
 - **Why it is used:** “Remove Module” unloads the driver from the kernel.

3.3.2. Core Concepts

3.3.2.1. Character Device Registration and The Mall Analogy

In older Linux drivers, developers used `register_chrdev()`, which locked down an entire major number and all 256 minor numbers at once.

Modern drivers fix this waste by splitting the setup into a 3-step dynamic process, which can be compared to opening a new business kiosk inside a **Massive Shopping Mall**.

- **The Old Way (`register_chrdev`) Renting a Whole Floor:** This legacy function is like renting an entire mall floor just to set up one small information desk. It completely blocks all 256 shop slots on that floor, quickly running out of available major numbers.

- **Step 1: `alloc_chrdev_region` Reserving Your Room Number:** This modern function dynamically requests a single, unique room address (Major and Minor number combination) from the kernel. In our analogy, mall management checks their database and assigns you to **Floor 240, Room 0**, leaving the other rooms open.
- **Step 2: `cdev_init` & `cdev_add` Building the Service Counter:** This step initializes your character device structure and binds it to your file operations code map. This is like physically assembling your desk inside your assigned room and training your staff, though the public hallway doors are still locked.
- **Step 3: `class_create` & `device_create` Adding to the Mall Directory:** These functions create a class directory in sysfs and generate the active device file node at `/dev/nw1728-driver`. This acts like listing your business on the main lobby directory board and carving a physical service window through the lobby wall for customers.

3.3.2.2. Memory Isolation and Data Transfer Functions

Linux splits system memory into two isolated zones to keep the operating system secure. To understand this separation, we can imagine Kernel-Space as a **High-Security Government Vault** and User-Space as the **Public Lobby outside the building**.

- **User-Space Memory:** This is where normal programs run in their own isolated bubbles. If a user application crashes, it only kills that single program without hurting the rest of the system.
- **Kernel-Space Memory:** This zone has absolute control over the hardware, CPU, and physical RAM blocks. If code here encounters a bad memory pointer, the entire operating system crashes instantly into a Kernel Panic.
- **The Privilege Barrier:** Because of this strict barrier, kernel code cannot directly read or write to pointers handed over by user apps. The system requires specialized, secure transfer windows to pass data safely across the line.
- **`copy_to_user()` — Exporting Data to the Public Lobby:** This function securely copies data out of privileged kernel memory and hands it to a user-space application buffer. In our driver's read function, it acts like a secure tray passing the "Hello world..." string out to the terminal command.
- **`copy_from_user()` — Importing Data into the Vault:** This function pulls data from an untrusted user-space application and places it safely into a kernel memory buffer. For our upcoming write functions, it checks and imports the user's input command byte to toggle the hardware state safely.

4. Trying the GPIO

Okay now lets do the extra part, lets keep thing simple first, only controlling 1 led at a time.

4.1. LED Controlling

All modification is done only in device_file.c

4.1.1. GPIO Headers and Module Parameters

We import the kernel's GPIO header and define a module parameter. One cool thing, i am using a parameter that allows me to specify which GPIO pin to use dynamically when inserting the module (e.g., `insmod nw1728-module.ko gpio_pin=X`).

```
#include <linux/gpio.h> /* gpio_request, gpio_set_value, etc. */

static unsigned int gpio_pin = 533; /* Default GPIO 21 (base 512 + 21) */
module_param(gpio_pin, uint, 0644);
MODULE_PARM_DESC(gpio_pin, "GPIO pin number to control (default 21)");
```

4.1.2. Device Write Handler

I implemented `device_file_write` to process data written to the device file `/dev/nw1728-driver`. It reads the first character from the user-space buffer, parses it, and drives the GPIO state.

```
static ssize_t device_file_write(struct file *file_ptr, const char __user
*user_buffer,
                                size_t count, loff_t *position) {
    char value_char;

    if (count == 0)
        return 0;

    // Copy data safely from user-space to kernel-space
    if (copy_from_user(&value_char, user_buffer, 1) != 0) {
        return -EFAULT;
    }

    // Toggle GPIO pin voltage levels
    if (value_char == '1') {
        gpio_set_value(gpio_pin, 1); // High (3.3V)
        pr_notice("NW1728-driver: LED turned ON (GPIO %u)\n", gpio_pin);
    } else if (value_char == '0') {
        gpio_set_value(gpio_pin, 0); // Low (GND)
        pr_notice("NW1728-driver: LED turned OFF (GPIO %u)\n", gpio_pin);
    } else {
        pr_notice("NW1728-driver: Invalid write value '%c' (only '1' or '0'
accepted)\n", value_char);
    }
}
```

```
    }  
  
    return count;  
}
```

4.1.3. File Operations Mapping

I updated the `file_operations` structure so that the driver knows what to do if we put something to the Driver File (the `/dev/nw1728-driver`)

```
static const struct file_operations nw1728_driver_fops = {  
    .owner = THIS_MODULE,  
    .read = device_file_read,  
    .write = device_file_write, // New write mapping  
};
```

4.1.4. GPIO Lifecycle Management

I allocate and initialize the GPIO pin inside the `register_device` function and free it inside the `unregister_device` function (as well as inside the error labels of `register_device`).

Initialization (`register_device`):

```
// Validate if the requested pin is valid  
if (!gpio_is_valid(gpio_pin)) {  
    pr_err("NW1728-driver: Invalid GPIO pin %u requested\n", gpio_pin);  
    result = -EINVAL;  
    goto err_out;  
}  
  
// Request GPIO ownership from the kernel  
result = gpio_request(gpio_pin, "nw1728-led");  
if (result) {  
    pr_err("NW1728-driver: gpio_request failed for pin %u: %d\n", gpio_pin,  
result);  
    goto err_out;  
}  
  
// Set the pin direction to output (and initialize it to OFF / Low state)  
result = gpio_direction_output(gpio_pin, 0);  
if (result) {  
    pr_err("NW1728-driver: gpio_direction_output failed for pin %u: %d\n",  
gpio_pin, result);  
    goto err_free_gpio;  
}
```

Cleanup & Error Paths:

```
// Inside unregister_device and error handler labels:  
gpio_free(gpio_pin);
```

4.2. Nokia Screen SPI

With the LED being done now, lets cook some stuff

From The wise man (the one that tell me to do a C file to interact with the kernel driver), he lended me a very unique stuff. Its a Nokia 5110 Screen, but with an SPI breakout board, made by Adafruit.

<https://github.com/adafruit/Adafruit-PCD8544-Nokia-5110-LCD-library.git>

Its a neat little screen. Also very retro looking. But now we have work to do, which is to make the screen work

4.2.1. Planning

Let's do the planning. Here is some of my plan :

- I want the screen to be connected with SPI to the GPIO (Pi Hat+)
- I want the SPI screen to be initialized when we load the module (then initializer in the register device func)
- I want the Buffer to change as well (whats on the screen = whats on the buffer)
- I want the backlit to turn on when the RPI turn on, and turn off when the RPI turned off (power indicator logic)
- I want when i do `echo` something to the driver, the screen update immediately

I think this enough for Planning. Now lets cook.

4.2.2. SPI research in the making