

## **MACHINE LEARNING**

### In Q1 to Q8, only one option is correct, Choose the correct option:

1. The computational complexity of linear regression is:

A)  $O(n^{2.4})$  B) O(n) C)  $O(n^2)$  D)  $O(n^3)$ 

Answer- D)  $O(n^3)$ 

2. Which of the following can be used to fit non-linear data?

A) Lasso Regression
C) Polynomial Regression

B) Logistic RegressionD) Ridge Regression

**Answer- C) Polynomial Regression** 

3. Which of the following can be used to optimize the cost function of Linear Regression?

A) Entropy

B) Gradient Descent

C) Pasting

D) None of the above.

**Answer- B) Gradient Descent** 

4. Which of the following method does not have closed form solution for its coefficients?

A) extrapolation

B) Ridge

C) Lasso

D) Elastic Nets

Answer- C) Lasso

5. Which gradient descent algorithm always gives optimal solution?

A) Stochastic Gradient Descent

B) Mini-Batch Gradient Descent

C) Batch Gradient Descent

D) All of the above

Answers- D) All of the above

6. Generalization error measures how well a model performs on training data.

A) True

B) False

Answer- A) True

7. The cost function of linear regression can be given as  $J(w, w) = \frac{1}{2} \left( w + w x^{(i)} - y^{(i)} \right)^2$ .

The half term at start is due to:

- A) scaling cost function by half makes gradient descent converge faster.
- B) presence of half makes it easy to do grid search.
- C) it does not matter whether half is there or not.
- D) None of the above.

#### Answer- C) it does not matter whether half is there or not

8. Which of the following will have symmetric relation between dependent variable and independent variable?

A) Regression

B) Correlation

C) Both of them

D) None of these

**Answers - B) Correlation** 

## In Q9 to Q11, more than one options are correct, Choose all the correct options:

- 9. Which of the following is true about Normal Equation used to compute the coefficient of the Linear Regression?
  - A) We don't have to choose the learning rate.



## **MACHINE LEARNING**

- B) It becomes slow when number of features are very large.
- C) We need to iterate.
- D) It does not make use of dependent variable.

Answer- A),B) & C)

- 10. Which of the following statement/s are true if we generated data with the help of polynomial features with 5 degrees of freedom which perfectly fits the data?
  - A) Linear Regression will have high bias and low variance.
  - B) Linear Regression will have low bias and high variance.
  - C) Polynomial with degree 5 will have low bias and high variance.
  - D) Polynomial with degree 5 will have high bias and low variance

Answer- A) Linear Regression will have high bias and low variance.

- 11. Which of the following sentence is false regarding regression?
- A) It relates inputs to outputs.
- B) It is used for prediction.
- C) It discovers causal relationship.
- D) No inference can be made from regression line Linear Regression will have high bias and low variance..

Answer- C) & D)

#### Q12 and Q13 are subjective answer type questions, Answer them briefly.

12. Which Linear Regression training algorithm can we use if we have a training set with millions of features?

Answer- If you have a training set with millions of features you can use Stochastic Gradient Descent or Mini-batch Gradient Descent, and perhaps Batch Gradient Descent if the training set fits in memory. But you cannot use the Normal Equation because the computational complexity grows quickly (more than quadratically) with the number of features.

13. Which algorithms will not suffer or might suffer, if the features in training set have very different scales?

Answer-

The normal equations method does not require normalizing the features, so it remains unaffected by features in the training set having very different scales.

The Gradient Descent suffers from features of different scales, because the model will take a longer time to reach the global maximum. We can always scale the features to eliminate this problem.



# **MACHINE LEARNING**