ENGG1003 - Lab 2

Brenton Schulz

1 Introduction

Project: ENGG1003 - Lab 2, February 24, 2020

This set of programming exercises leaves you to perform a series of tasks on your own. This can be daunting at first, but your ability to remain resolute and resourceful in an atmosphere of extreme pessimism¹ will be a useful skill when studying Engineering². (In truth, I hope you don't find it *that* hard and gain satisfaction and confidence from getting programs to work).

The example tasks are mostly "toy" programs. They don't do anything particularly useful because most "real-world" problems are too advanced for this stage of the course. Things will get more interesting in the coming weeks (I hope...).

Do not expect programs to compile (let alone *work*) first go. It is totally normal, even for experienced programmers, for multiple lines of hand typed code to generate several errors the first time compilation is attempted. You will then find *more* errors when the code is executed and found to produce the wrong output.

In time you will learn to interpret and deal with error messages quickly. Typically they will be a syntax error due to a missing parenthesis, semicolon, or double quote. Don't be afraid to ask for help from demonstrators and work with other students in the lab.

In short: almost all of your time spent programming will be fixing problems because as soon as all the (known) problems are fixed you stop programming and ship the software to your customer.

Generally speaking, the development process follows repeated application of the following steps:

- 1. Make a code change
- 2. Compile
- 3. Fix compile errors, repeat until code compiles
- 4. Test program with known correct input-output data
- 5. Repeat whole process until correct output is generated for multiple test inputs

Very few students will complete all these tasks within the lab time.

Yes, this is a reference to the computer game Portal (2007).

²Talk to your demonstrators about how true this is. I write it only partially in jest. I've found it a necessary skill for life.

2 Pseudocode to C Conversion Examples

Project: ENGG1003 - Lab 2, February 24, 2020

Pseudocode is any rough working out which you write (or are given) which describes a computer algorithm in the most human-readable form practical. It will *not* run when typed into a C compiler. It only exists to document algorithms and assist in helping you convert a "real world" problem into computer code.

The table below covers the flow control structures seen so far. The first entry is what I consider to be the *absolute minimum* required for all code in this course. The main() function is required, it is where program execution begins.

Pseudocode	C Code
BEGIN // do things END	<pre>#include <stdio.h> int main() { // do things return 0; }</stdio.h></pre>
<pre>IF condition // do things ENDIF</pre>	<pre>if(condition) { // do things }</pre>
<pre>IF condition // do things ELSE // do things ENDIF</pre>	<pre>if(condition) { // do things } else { // do things }</pre>
IF condition // do things ELSE IF condition // do things ELSE // do things ENDIF	<pre>if(condition) { // do things } else if(condition) { // do things } else { // do things }</pre>
WHILE condition // do things ENDWHILE	<pre>while(condition) { // do things }</pre>

3 Data Type Subset and Format Specifiers

Although C contains many data types you only need to consider the following subset when completing this lab:

Type	Value Range	Format Specifier
int	-2 147 483 647 to +2 147 483 647	%d
float	1.2×10^{-38} to 3.4×10^{38}	%f

The Value Range indicates the maximum and minimum values which can be stored in each type. For the float data type both positive and negative numbers can be stored. If an arithmetic statement causes an int to exceed the value range the result will "wrap around"; a behaviour known as overflow or underflow. If you type in a number which is too big and read it with scanf("%d", &x); the number stored will be different to that which you typed in.

The format specifier is the text which goes inside scanf(); and printf(); when reading or printing numbers, respectively. It tells the compiler how ASCII text should be converted into a number (and back again).

Eg, to read and print an int:

```
int value;
scanf("%d", &value);
printf("You entered: %d\n", value);
```

Change the two %d's to %f to read and print a float. Always consider what data type is being read or written when typing format specifiers.

If you write the wrong format specifier it will result in garbage. For example, the following code uses %f inside scanf(); when it should have been %d:

```
#include <stdio.h>

int main() {
   int x;
   printf("Enter an integer: ");
   scanf("%f", &x); // %f is incorrect!
   printf("You entered: %d\n", x);
   return 0;
}
```

It exhibits the following behaviour on when executed:

```
Enter an integer: 1
You entered: 1065353216
```

The compiler, gcc, produces a warning when the code is compiled:

4 Usage of printf(); and scanf();

The basic usage of printf(); and scanf(); when working with single integers is:

```
scanf("%d", &x); // Read an integer, store it in x
printf("%d \n", x); // Print the value of x followed by a new line
```

If using float or double "fractional" numbers the %d gets replaced with %f.

They can, however, be used to read or print arbitrarily many variables. To do this you:

- 1. Use multiple format specifiers (%d and %f) inside the format string
- 2. List multiple variables, separated by commas, after the format string

The format string is everything between the pair of double quotes:

```
printf("This is the format string.\n")
```

For example, to read three integers, x, y, and z from the console:

```
int x,y,z; // This declares three int variables on one line scanf("%d %d %d", &x, &y, &z);
```

The integers you type need to be separated by spaces (note that spaces are present inside the format string) and <enter> typed to end the line. The scanf(); function won't process any data until an end of line is read.

Note that the order is crucial; the numbers you type will go into x, y and z in the the same order that the variable names are listed in scanf();.

You don't need to separate the input with spaces. You can, for example, read an hh:mm time with:

```
scanf("%d:%d", &hours, &minutes);
```

and scanf(); will match the integer-colon-integer pattern with the input and extract hours and minutes.

scanf(); even supports incredibly advanced "pattern matching" but it is well beyond the scope of ENGG1003.

Note that the numbers don't all need to be integers. You can mix integers and, say, doubles:

```
int x,y; // This declares three int variables on one line
double z;
scanf("%d %d %f", &x, &y, &z);
```

Likewise, the printf(); function can print multiple numbers in arbitrary locations. You can write a mixture of %d and %f anywhere inside the format string and values will be pulled from the list of variables in order.

For example:

will print:

```
1 is an integer, 2 is an integer, have some more numbers: 1.23 8.2
```

Lastly, if you get this compiler warning:

```
main.c:6:13: warning: format %d expects argument of type int *, but argument
3 has type float * [-Wformat=] scanf("%d:%d", &h, &m);
```

it means that the data type and format specifier don't match. You have made a mistake, fix it.

5 Getting Started Questions

Project: ENGG1003 - Lab 2, February 24, 2020

These problems are *not* meant to be executed in a C compiler. Read through them and write your answers on paper (or Word etc). Solutions can be found on the last page of this document.

1. What are the values of x, y, v, and z after execution of each line? On which lines are each variable undeclared (ie: their value is known)? You don't need to run this code, only read and think about it.

```
int x = 2;
int y, v, r;
float z;
x = x+5;
y = 2*x + 3;
v = y/x; // NB: integer division
r = y%x;
z = (float)y/x; // Forced to floating point division
```

2. What is printed to the console if the user enters 13<enter>? You don't need to run this code, only read and think about it.

```
1 float k;
2 printf("Enter a number: ")
3 scanf("%f", &k);
4 k = 1.43*k + 84;
5 printf("%f\n", k);
6 printf("%d\n", (int)k); // Integer truncation
```

3. Write a printf(); statement which takes an integer variable temp and prints:

```
The temperature reading of <temp> is dangerous
```

to the screen (with <temp> replaced with the actual value, ie: write the %d format specifier in that spot).

- 4. A variable is required which stores integers with a maximum possible value of ten billion. What C data type is required? Why can't you use an int? See Section 10.6 for a list of C data types.
- 5. A variable is required to store a real number with 10 significant figures. What C data type is required? See Section 10.6 for a list of C data types.
- 6. Write a C "code snippet" which implements the following pseudocode (decrement implies a subtraction by 1):

```
IF x is not equal to zero
  decrement x
ENDIF
```

A "code snippet" is just the code required to implement the pseudocode, you don't need to write a full program. In this case, you are only converting the pseudocode IF..ENDIF into something that looks like:

```
if(condition) {
   /* stuff */
}
```

7. Write a C code snippet which implements the following pseudocode:

```
WHILE x is greater than 1
  y = y*x;
  x = x-1;
ENDWHILE
```

8. Write a C code snippet which implements the following pseudocode:

```
BEGIN
  integer result
  integer x
  READ x from the console
  IF x is zero
    result = -1
  ELSEIF x is -1
    result = 0
  ELSE
    result = 1
  ENDIF
```

6 Input-Processing-Output Exercises

These exercises all require the use of scanf(); to read data, some arithmetic to process data, and printf(); to print results to the console.

Every task requires the following steps:

- 1. Work out what variables are required
- 2. What type do the variables need to be?
- 3. Convert an equation to C code. Do we need to be careful with data types?
- 4. Write a scanf (); statement to read the user's input
- 5. Write a printf(); statement to print the result
- 6. (Optional) Do you want the user to be *prompted*? This is when text appears in the console telling the user what to enter. This requires a printf(); prior to the scanf();
- 7. (Optional) Does the output need to be in a human sentence? Write the printf(); statement.
- 8. (Optional) Should you limit the precision of the printed result? Are 6 decimal places appropriate? Should it only be 1? Use the %.nf format specifier to limit floating point precision to n decimal places

The following template can be used for all these exercises:

```
#include <stdio.h>
  int main() {
     // Declare the required variables
     // eg: int x; float y; etc
     // Get input from the user
     // eg: printf("Enter a number: ");
             scanf("%f", &y);
     // Do the calculation
     // x = ....whatever
12
13
     // Print result to user
14
     // eg: Printf("%d times %d is %d\n", x, y, z);
16
     return 0;
17
18
```

6.1 Example

Write a C program which calculates a miles to kilometres conversion with the following formula:

$$km = 1.60934 \times miles. \tag{1}$$

Going through the steps above:

- 1. We need a variable miles and another km
- 2. We are multiplying by a fractional number so they need to be of type float (or double)
- 3. In C, the equation is implemented with: km = 1.60934 * miles;
- 4. To read a float from the user we need the %f format specifier in scanf();. To store the read value in miles, we can use: scanf("%f", &miles);
- 5. To print the result of type float we need the %f format specifier, so we can print it with: printf("%f\n", km);

To make the above "code snippets" *actually run* they need to be written inside main() { } and we need to write #include <stdio.h> at the top. Putting it all together, the following code will implement the problem:

```
#include <stdio.h>
int main() {
    float km;
    float miles;

    scanf("%f", &miles);
    km = 1.60934 * miles;
    printf("%f\n", km);

    return 0;
}
```

All the Tasks in this section can be implemented by modifying the above template.

6.2**Tasks**

Task 1: Temperature Conversion

Project: ENGG1003 - Lab 2, February 24, 2020

The formula for converting temperatures in Farenheit, F to Celsius, C, is:

$$C = \frac{5}{9}(F - 32). \tag{2}$$

Given the C template, write a program which performs this conversion. It should read the Farenheit temperature from stdin and print the result to stdout. The program should correctly handle any practical real values (eg: 19.38) as input. Print the result to 2 decimal places.

Test your code with several values calculated with Google.

Task 2: Variance Calculation

From statistics, the sample variance, s^2 , of N samples, $X_1, X_2, ..., X_N$, can be calculated as:

$$s^{2} = \frac{1}{N-1} \sum_{k=1}^{N} (X_{k} - mean(X))^{2}.$$
 (3)

Write a C program which reads **four** numbers and outputs their sample variance.

Given that N=4 (and some algebra) Equation 3 can be expanded into two steps:

- 1. Calculate the sample mean: $\text{mean} = \frac{1}{4} \times (X_1 + X_2 + X_3 + X_4)$ 2. Calculate the variance: $\text{var} = \frac{1}{3} \times ((X_1 \text{mean})^2 + (X_2 \text{mean})^2 + (X_3 \text{mean})^2 + (X_4 \text{mean})^2)$ Your program will have to declare four float variables to store the four input values. To read four numbers in one instance of scanf(); you can do this:
- float x1, x2, x3, x4; scanf("%f %f %f %f", &x1, &x2, &x3, &x4);

Test your program given that the variance of the set (1, 2, 3, 4) = 1.6667

NB 1: Be careful with the $\frac{1}{4}$ and $\frac{1}{3}$ constants in the equations above. They may experience integer division problems. If in doubt, convert them to floating point literals.

Observation: Did you find programming this task is really tedious? What if you had 100 samples? Or a million? In later weeks we will learn about arrays. These are a C language feature which greatly simplify the code when you need to keep track of a lot of data.

Task 3: Linear Interpolation

Project: ENGG1003 - Lab 2, February 24, 2020

There are many instances in science and engineering when data needs to be *interpolated*. Informally, this is the process of predicting a quantity's value somewhere between two (or more) data points.

In this task you will be using the *two-point formula* (you saw this in high school, right?) to interpolate between two data points. You can imagine these data points to be measurements of temperature / brightness / sound intensity / pressure / etc as a function of time.

The two-point formula states that the equation of a line passing through two points (x_1, y_1) and (x_2, y_2) is:

$$y = \frac{y_2 - y_1}{x_2 - x_1}(x - x_1) + y_1. \tag{4}$$

The value of y at some given x can then be estimated. For the purposes of interpolation x will always be in between the given data points. ie, assuming $x_2 > x_1$:

$$x_2 > x > x_1. \tag{5}$$

Note that y is only an *estimate* of the true value. You will often see this notated as \hat{y} , especially in statistics.

The process of estimating values outside the $[x_1, x_2]$ interval is known as $extrapolation^a$ and is beyond the scope of this task.

Given the above, write a C program which implements the following pseudocode:

```
BEGIN
READ x1 and y1 from the console
READ x2 and y2 from the console
READ a point x from the console
Estimate the value of y at x using linear interpolation
PRINT y
END
```

To understand this problem you will find it useful to draw some sketches. Draw an x-y axis, dot two points and draw a line between them. If you pick two neat integer points (eg: 0,0 and 5,5) then the linear interpolation will be easy to see by eye. Perform several tests with known-correct sets of values to confirm that your code is correct.

Program implementation notes:

• Reading a pair of points can be done with:

```
float x1, y1;
printf("Enter point 1: ");
scanf("%f %f", &x1, &y1);
```

you would then type two numbers into the console, separated by a space, and press enter.

• Keep all variables as float or double. It doesn't really matter which, just be consistent.

ahttps://xkcd.com/605/

7 Flow Control Exercises

Project: ENGG1003 - Lab 2, February 24, 2020

A template is not explicitly provided for these tasks. You can, however, use the "hello world" template provided by OnlineGDB or the code written for previous tasks as a starting point.

This first task presents you with all the required building blocks to implement a simple algorithm. All this program will do is read in 2 integers, perform a division, then print the result. A check is performed to make sure a division by zero does not occur.

Task 4

Write a program which implements the following pseudocode:

```
integer a
integer b
integer q
integer r
Read an integer from standard input, store it in a
Read an integer from standard input, store it in b
IF b is zero
   PRINT "Division by zero error"
ELSE
   q = a/b
   r = a%b
   PRINT "a divided by b is" <the value of q>
   PRINT "and the remainder is" <the value of r>
ENDIF
```

Notes:

• Reading each integer can be done with: scanf("%d", &a); (with an appropriate substitution for the variable name). You may prompt the user by placing a printf(); without newline character prior to scanf();, eg:

```
printf("Enter an integer: ");
scanf("%d", &a);
```

• Note that <the value of c> in the pseudocode is implying that a number should be printed there, ie:

```
printf("a divided by b is %d\n", c);
```

- The condition "b is zero" needs to be implemented with the == (two equals symbols) operator.
- You may start with the default code listing provided by OnlineGDB

In 2019 77% of students reported running out of time here.

Task 5: Calculating Square Roots

Project: ENGG1003 - Lab 2, February 24, 2020

The square root of a number, $x = \sqrt{n}$, can be calculated with the iterative formula:

$$x_{k+1} = \frac{1}{2} \left(x_k + \frac{n}{x_k} \right) \tag{6}$$

Task: Write a C program which implement this formula to calculate square roots of real numbers. The value of n is to be read from the console with scanf(); and the result printed with printf();.

The choice of x_0 is somewhat arbitrary, the algorithm should *converge* $(x_n$ will move towards the result, not away) given any sane value (eg: not infinity), but will converge faster (ie: in fewer iterations) if x_0 is closer to the true value of \sqrt{n} . You may play with this value and observe how accurate the result is after a fixed number of iterations (say, 5). Common choices for x_0 would be $x_0 = n$ or $x_0 = 1$.

The algorithm will require a loop. The exit condition could be one of several choices. In order of difficulty:

- 1. Exit after a fixed number of iterations (eg: 10)
- 2. Exit when $|x_k x_{k-1}| < e$ where e is some pre-defined precision of your choosing
- 3. Exit when either of the above conditions are met

To calculate precision you will need to explicitly save x_k and x_{k-1} in different variables.

Sketch out pseudocode (either on actual dead tree paper or in Word/text editor/in code comments) before attempting to write the C program.

Hint: You can place printf(); statements inside the loop to help you debug. Calculate the series of x_n 's for a particular value (eg: $\sqrt{2} = 1.4142$) by hand (with the same value for x_0) so that you can compare your program's output with an output you have confidence in.

7.1

Project: ENGG1003 - Lab 2, February 24, 2020

Else-If

The C syntax for an IF .. ELSEIF .. ENDIF flow control structure is:

```
if( condition ) {
    // Statements
} else if( condition ) {
    // Statements
}
```

There are many variants, for more examples see Section 10.10.1.

Please be aware of a common mistake: a semicolon should *not* be placed after an if () statement. Doing so tells the compiler "if this condition is true, do nothing". C will always do exactly what you tell it to, even if you tell it to do something that appears to be useless.

Task 6: Quadratic Equation Analysis

The Friday Week 1 lecture introduced the following pseudocode for solving quadratic equations:

```
BEGIN
   INPUT: a, b, c
   D = b^2 - 4ac
   IF D < 0
      N = 0
   ELSEIF D == 0
      N = 1
      x1 = -b/(2a)
   ELSEIF D > 0
      N = 2
      x1 = (-b + sqrt(D))/(2a)
      x2 = (-b - sqrt(D))/(2a)
   ENDIF
   OUTPUT: N, x1, x2
```

Everyone: Write a C program which takes the a, b, and c values and outputs the number of real valued solutions which exist (ie: 0, 1, or 2).

Everyone: Introduce a "temporary" variable (ie: short lived, one we stop caring about soon after it is used) which explicitly removes the requirement to calculate sqrt (D) twice.

Advanced: Using the square root algorithm in Equation 6, implement the full quadratic equation solution algorithm.

8 Random Numbers

Project: ENGG1003 - Lab 2, February 24, 2020

The following tasks involve generating and using random numbers. The standard C library (glibc, in Linux and MinGW, provided by the <u>GNU project</u>) contains a function called rand(); which creates a random number between 0 and a constant called RAND_MAX. In glibc RAND_MAX is 2147483647, or the maximum value an int can store. It may vary between implementations (older systems may use 32767, for example).

Because rand(); is part of a "library" and not built into the C language you need to include a header file which describes to the compiler what rand(); is before it is used. To do this, type the following line at the top of your source listing (anywhere above main()):

```
#include <stdlib.h>
```

The rand(); function can then be included in your code. You can write it in all the same places that you would write a variable or literal. All of the following statements are valid:

```
1 x = rand();
2 y = 10 + rand() % 5;
3 printf("A random number is: %d\n", rand() );
```

Generally you aren't after a random number between 0 and RAND_MAX. To limit the rand of integers generated we can use the modulus (%) operator. For the purposes of this course the following methods can be used to generate:

• A number between 0 and MAX:

```
x = rand() % (MAX + 1);
```

• A number between 1 and MAX:

```
x = rand() % MAX + 1;
```

• A floating point number between 0 and MAX:

```
x = (float)rand()/RAND_MAX * MAX;
```

NB: rand(); becomes an int so an explicit cast to float (or double) is required to avoid integer division errors.

IMPORTANT: The rand(); function is what's known as "pseudo-random". Repeated use of rand(); will generate a sequence of random numbers but the *same sequence* will be generated every time the program is run.

To change the sequence you can use the srand(); function (known as "seed-rand") with a manually chosen random number:

```
srand(233534);
```

Every different number given to srand(); will cause a different random sequence to be generated by rand();. You only need to include srand(); once, somewhere before rand(); is used.

In the future, we will learn how to "seed" random number generation with the current time. That way the sequence will automatically change each time the program is run.

Example:

```
#include <stdio.h>
#include <stdlib.h>
int main() {
   int x;
   srand(2323423);
   x = rand();
   printf("A random number is: %d\n", x);
}
```

Task 7: Rolling Dice

Project: ENGG1003 - Lab 2, February 24, 2020

Using the rand(); function, write a C program which estimates the probability that, when two dice are thrown, at least one of the dice rolled a 3. This can be done with the following algorithm:

```
BEGIN

counter = 0;
aThreeHappened = 0

WHILE counter < 1000

a = random number between 1 and 6

b = random number between 1 and 6

IF (a == 3) OR (b == 3)

aThreeHappened = aThreeHappened + 1

END

counter = counter + 1

ENDWHILE

PRINT aThreehappened / counter

END

The theoretical value is \frac{11}{36} = 0.3055
```

Task 8: Arithmetic Tutor

Write a C program which can be used to teach basic arithmetic to primary school children.

Your program should follow the following algorithm:

```
BEGIN
  integer max
READ max from the user
  integer a = a random number between 1 and max
  integer b = a random number between 1 and max
  integer c = a + b
  PRINT What is a + b? // a and b the numerical values
READ an integer d
  IF c == d
    PRINT "Correct!"
  ELSE
    PRINT "Wrong : (. The correct answer is " c
  ENDIF
```

Extension 1: Modify the algorithm so that it keeps generating problems until the user gets one wrong. (ie: Chuck a while() around the appropriate lines, create a variable which records if the answer was wrong or correct, and test that variable in the while() condition).

Extension 2: Add a variable which keeps score and prints the number of correctly answered questions on program exit.

Advanced: Add a menu to the start of the program which allows the user to select between addition, subtraction, multiplication, and division. Implement integer division where the user must enter the result as quotient and remainder.

Task 9: Calculating Pi

Project: ENGG1003 - Lab 2, February 24, 2020

Implement the π calculation algorithm talked about during lectures. The pseudocode is:

NB: If running this on OnlineGDB use a "small" value for the maximum loop count. Try one million. If this takes longer than around 10 seconds to execute use a smaller value. You are occupying OnlineGDB's shared CPU resources when running this program.

9 Mandelbrot Set - Advanced

This problem is presented for students interested in mathematics. It may take several lab sessions to correctly implement this task. If you do not understand anything here, do not be troubled. Do not feel the need to attempt this task. The mathematics is beyond the scope of ENGG1003.

Demonstrators are not to help you solve this problem. It is intended for students who have advanced beyond expectations, doing it alone is part of the challenge.

A complex number, C, exists within the Mandelbrot set if, when iterated with the formula:

$$z_{n+1} = z_n^2 + C, (7)$$

with initial condition $z_0 = 0$, the value of $|z_n|$ stays bounded (ie: doesn't "blow off to infinity") as n becomes "very large". It's calculation can be used to create <u>mathematical artwork</u>. Hanging in my office is a piece of art known as a <u>Buddahbrot</u>. Calculation took several days on an R9 270X gaming graphics card. Come check it out some time. I have an unhealthy love of this branch of mathematics.

Purely real examples:

• C = 0.1 is *inside* the Mandelbrot set, as:

$$z_1 = 0 + 0.1 \tag{8}$$

$$z_2 = 0.1^2 + 0.1 = 0.11 \tag{9}$$

$$z_3 = 0.11^2 + 0.1 = 0.1121 \tag{10}$$

$$\dots$$
 (11)

$$z_{14} = 0.112701665^2 + 0.1 = 0.112701665 \tag{12}$$

$$z_{15} = 0.112701665^2 + 0.1 = 0.112701665 \tag{13}$$

...and it just sits at 0.112701665 forever.

• C = 1 is *outside* the Mandelbrot set, as:

$$z_1 = 0 + 1 \tag{14}$$

$$z_2 = 1^2 + 1 = 2 \tag{15}$$

$$z_3 = 2^2 + 1 = 5 \tag{16}$$

$$z_4 = 5^2 + 1 = 26 \tag{17}$$

$$z_5 = 26^2 + 1 = 677 \tag{18}$$

$$\dots$$
 (19)

$$z_{11} = (3.79 \times 10^{90})^2 + 1 = 1.4 \times 10^{181}$$
(20)

...and it just keeps getting bigger. Fast.

Task 10

Write a C program which tests a single point, C, for inclusion in the Mandelbrot set. This code can be expanded to draw an image in a later lab.

To do this you will be need to know that:

- \bullet z and C are complex numbers with real and imaginary parts
- Introducing some notation:

$$z_n = x_n + iy_n \tag{21}$$

$$C = x_0 + iy_0 \tag{22}$$

Where x denotes a real part and y the imaginary.

• Using rules of complex arithmetic it can be shown that:

$$z_{n+1} = z_n^2 + C (23)$$

$$=x_n^2 + i2x_ny_n - y_n^2 + x_0 + iy_0 (24)$$

• To evaluate this on a computer which only deals with *real* numbers it has to be split into real and imaginary parts:

$$Re(z_{n+1}) = x_{n+1} = x_n^2 - y_n^2 + x_0$$
 (25)

$$Im(z_{n+1}) = y_{n+1} = 2x_n y_n + y_0 (26)$$

• A complex number's norm (or absolute value, informally its "size") can be calculated as:

$$|z| = \sqrt{x^2 + y^2} \tag{27}$$

and is needed to test if z_n is getting "too big". For this problem, "too big" is typically defined as "outside a circle of radius 2". To avoid having to calculate the square root (which can be slow) you can take the so-called *escape condition* as:

$$x^2 + y^2 > 4 (28)$$

In code, this will go inside a loop's exit condition. Either as a "NOT $(x^*x+y^*y>4)$ " or, more simply, " $x^*x+y^*y<4$ " as loop conditions need to remain TRUE for the loop to continue.

- The loop which implements the iterative equation needs to keep track of the iteration count but does not need to record a full history of z_n 's. You only need the "next" and "current' values of x_n and y_n . At some point an assignment causes the "next" to become the "current".
- An iteration limit needs to be set. A point, C, is considered "inside" the set if the iteration limit is hit without $|z_n|$ exceeding 2.
- If $|z_n| > 2$ before the iteration limit is hit the point, C, is inside the Mandelbrot set
- Full, somewhat optimised, pseudocode for this problem can be found on <u>Wikipedia</u>. Independent research may be required to implement this problem.
- For testing purposes here are some test points with an iteration limit of 1000:
 - -C = 0 + i0 takes 1000 iterations
 - -C = 0.5 + i0 takes 5 iterations
 - -C = 0.4 + i0.1 takes 8 iterations
 - -C = 0.38 + i0.1 takes 36 iterations
 - -C = -0.38 + i0.1 takes 1000 iterations
 - If all these test points take an iteration count which is offset by 1 from my solution your code is probably fine. This kind of error happens all the time due to < Vs <= and the like.

10 C Summary

Project: ENGG1003 - Lab 2, February 24, 2020

This section will be included in all future lab documents and lists a summary of C language features taught prior to the lab session. It will grow each week.

Not everything listed in this section is required to complete a particular lab.

10.1 Basic Structure

This is the absolute minimum amount of code you need to make a C program compile, run, and interact with the user via a console:

```
#include <stdio.h>
int main() {
    // Your program goes here
    return 0;
}
```

10.2 Comments

```
1 // This is a comment to end of line

2
3 /* this is a block comment
4 which could span
5 multiple
6 lines
7 */
```

10.3 Code Blocks

Any section of code encompassed by $\{\ldots\}$ is a *block*.

10.4 Operators

Operation	C Symbol
Addition	+
Subtraction	_
Multiplication	*
Division	/
Modulus	왕
Increment	++
Decrement	
Less than	<
Less than or equal to	<=
Greater than	>
Greater than or equal to	>=
Equal to	==
Not equal to	!=
Boolean AND	& &
Boolean OR	
Boolean NOT	!

Table 1: Arithmetic operators in C

10.5 Operator Shorthand

Many arithmetic operators support the following shorthand syntax. The left and right columns present equivalent statements.

x = x + y;	x += y;
x = x - y;	x -= y;
x = x * y;	x *= y;
x = x / y;	x /= y;

10.6 Data Types

Type	Bytes	Value Range
char	1	-128, +127
unsigned char	1	0, 255
short	2	-32768, 32767
unsigned short	2	0, 65535
int	4	$\approx \pm 2.1 \times 10^9$
unsigned int	4	0, 4294967296
long	8	$\approx \pm 9.2 \times 10^{18}$
unsigned long	8	$0, 1.8 \times 10^{19}$
float	4	$1.2 \times 10^{-38} \text{ to } 3.4 \times 10^{38}$
double	8	2.3×10^{-308} to 1.7×10^{308}

Type	Precision
float	6 sig. figs.
double	15 sig. figs

10.7 Standard i/o

Read a single variable from stdin with scanf(); scanf("format specifier", &variable);

Write a single variable to stdout with printf(); printf("format specifier", variable);

You can use printf(); without a newline (\n) to create an input prompt:

```
printf("Enter a number: ");
scanf("%d", &variable);
```

This prints:

Enter a number:

where _ indicates the terminal prompt (ie: where typed characters will appear).

Format Specifiers 10.8

The following table is weefully incomplete. The compiler may generate warnings if %d is given something other than int and %f is given something other than float. An attempt will be made to ensure these are sufficient.

Data Type	Format Specifier
Integers	%d
Floating point	%f
Float with n decimal places	%.nf

Table 2: Basic format specifiers

10.9 Type Casting

Placing the syntax (type) before a variable name performs a type cast (ie: data type conversion).

eg: convert float to an int prior to using its value. This forces a rounding-down to the nearest integer.

```
1 float a;
2 // ...
y = (int)a * z;
```

NB: This does **not** modify the original variable.

Data type "upgrades" are done automatically by the compiler but sometimes it is desired to downgrade or force esoteric behaviour. Adding it unnecessarily doesn't have any negative impact. Applications in ENGG1003 will be limited but it comes up regularly in embedded systems and nobody else explicitly teaches type casting. I have used it extensively if (condition) { in the low-level art of bit banqing: manual manipulation of binary data. This is, unfortunately, beyond 3 } else { ENGG1003.

10.10 Flow control

Flow control allows selected blocks of code to execute 1 if (condition) { multiple times or only under a specified condition. 2 // Do stuff

10.10.1 if()

The if () statement executes a block of code only if the *condition* is true. The condition is an arithmetic statement which evaluates to either zero (false) or non-zero (true).

```
if () Syntax:
```

```
if(condition) {/* other code */}
```

Full if () example:

```
if(x > 10) {
   // Do stuff
```

Condition Examples:

- if(x) // if(x is not zero)
- if (x+y) //if ((x+y) is not zero)
- if (y >= 5)
- if(1) // Always executes
- if(0) // Never executes
 - Can be used for debugging. Might be easier than a block comment /* */

NB: NEVER place a semicolon after an if (), that stops it from having any effect. The block after it will always execute. This bug can take days to find.

If there is only *one* statement after an if () the { } braces are optional:

```
if(x > 10)
  printf("x is greater than 10\n");
```

```
10.10.2 if() ...
```

The C syntax for IF ... ELSE is:

```
// Do stuff
```

IF ... ELSEIF takes the form:

```
3 } else if(condition) {
    // Do stuff
```

Multiple "layers" of else if () can be written. You don't have to stop at two.

NB: NEVER place a semicolon directly after the else if (). Semicolons only go after the statements inside the if () block (ie: between the curly braces { }).

10.10.3 while()

The while () flow control statement executes a block of code so long as a condition is true. The condition is checked before the block is executed and before every repeated execution.

The condition rules and examples are the same as for those listed under the if () statement.

Syntax:

```
while (condition) {/* other code */}
```

Example:

Evaluate the infinite sum:

```
\sum_{n=0}^{\infty} \frac{1}{n^2} \tag{29}
```

to a precision of 1×10^{-6}

```
1 float sum = 0.0;
2 int x = 0;
3 while(1/(x*x) > 1e-6) {
4    sum = sum + 1.0/(x*x);
5    x++
6 }
```

NB: *NEVER* place a semicolon directly after a while () line. Semicolons only go after the statements inside the loop.

10.10.4 for(;;)

As of week 2 this has not yet been covered in lectures.

The for (;;) loop syntax is:

```
for( initial ; condition ; increment )
{
    // Do stuff
}
```

The three sub-parts have the following behaviour:

- **Initial:** Code which is executed *once*, before the loop is entered
- Condition: A condition which is tested *before* every loop iteration
- **Increment:** Code which is executed *after* every iteration

for (;;) Example:

```
int x;
for(x = 0; x < 10; x++) {
   printf("%d ", x);
4 }</pre>
```

will print:

```
0 1 2 3 4 5 6 7 8 9
```

The for (;;) loop example doesn't print 10 because the condition is "strictly less than 10". When x is incremented to 10 the condition fails and the loop exits. It prints 0 because the increment is only applied *after* the loop has run once.

10.11 Library Functions

10.11.1 rand()

To generate a random number between 0 and MAX:

```
#include <stdlib.h> // For rand()
2 // ...
3 x = rand() % (MAX + 1);
```

For all work in this course you may assume that the above method works well enough.

For more crucial work (eg: cryptography, serious mathematics) this method is considered problematic. Very advanced discussion Here.

10.12 Glossary of Terms

I'll sort these alphabetically later, just a brain dump for now. Sorry.

- Compiler: The software package which converts source code into a binary.
- **Source Code:** The text which you type into a programming environment (eg: OnlineGDB) which is sent to the *compiler*.
- **Binary:** A program data file which can be executed on a computer.
- Variable: A "thing" which remembers a number within your program. In C they have a type, a name, (optionally) an initial value, and (for future reference) a memory address. Variables change when they are on the left side of an assignment.
- **Pseudocode:** Any hand-written or typed notes which document the behaviour of a computer program. Pseudocode is for humans to read, not computers.
- Flow Control: Any algorithmic statement which breaks the "top-to-bottom, line-by-line" execution pattern of a computer program.

- Project: ENGG1003 Lab 2, February 24, 2020
 - Statement: A line of C code which performs a task and ends with a semicolon. Arithmetic lines, printf();, scanf();, and rand(); are all examples of statements.
 - Assignment: The process of changing a variable's value as your program executes. In C, this is typically performed with the = symbol. Eg: x = y + 5 calculates the value of "y + 5" then allocates the result to the variable x.
- Block: A section of code "grouped together" by curly braces { ... }. Typically applies to flow control, where a single, say, if () controls a block of code listed inside { and }.
- Literal: Any numerical constant written in your code. Eg: In x < 2.0 the "2.0" is a literal. Unless otherwise stated, integer literals are treated as int data types (ie: they inherit the int's value range limit) and real valued literals are treated as doubles.

Page 22 of 24 Brenton Schulz

11 Getting Started Question Solutions

1. What are the values of x, y, v, and z execution of each line? On which lines are each variable undeclared (ie: their value is known)?

```
int x = 2; // x = 2, all others unknown
int y, v, r; // x = 2, y v r still unknown

float z; // x = 2, y v r z still unknown

x = x + 5; // x = 7

y = 2 + x + 3; // y = 17

v = y / x; // v = 17

v = y / x; // v = 17

v = y / x; // v = 17

v = y / x; // v = 17

v = y / x; // v = 17

v = y / x; // v = 17

v = y / x; // v = 17

v = y / x; // v = 17

v = y / x; // v = 17

v = y / x; // v = 17

v = y / x; // v = 17

v = y / x; // v = 17

v = y / x; // v = 17

v = y / x; // v = 17
```

2. What is printed to the console if the user enters 13<enter>?

3. Write a printf(); statement which takes an integer variable temp and prints:

The temperature reading of 123 is dangerous

to the screen (with 123 replaced with the actual value).

4. A variable is required which stores integers with a maximum possible value of ten billion. What C data type is required?

long. An int only stores up to approx 2.1 billion so it can't be used. Some C documentation claims that long is the same size as int. On some systems that is true, but not for the systems you are compiling on. OnlineGDB (and, later, Eclipse Che) are running on 64-bit machines on which long is an 8-byte data type consistent with the table in Section 10.6.

- 5. A variable is required to store a real number with 10 significant figures. What C data type is required? double. A float only has about 6 significant figures of precision
- 6. Write a C code snippet which implements the following pseudocode (decrement implies a subtraction by 1):

```
IF x is not equal to zero
   decrement x
ENDIF

if(x != 0)
{
    x--; // --x will also work. As would x = x - 1 or x -= 1
}
```

7. Write a C code snippet which implements the following pseudocode:

```
WHILE x is greater than 1
  y = y*x;
  x = x-1;
ENDWHILE
```

```
while(x > 1) {
    y = y * x;
    x = x - 1;
} // end while()
```

8. Write a C code snippet which implements the following pseudocode:

```
BEGIN
   integer result
   integer x
   READ x from the console
   IF x is zero
     result = -1
   ELSEIF x is -1
     result = 0
   ELSE
     result = 1
   ENDIF
 END
int result;
2 int x;
scanf("%d", &x);
_{4} if (x == 0) {
result = -1;
_{6} } else if(x == -1) {
result = 0;
8 } else {
9 result = 1;
10 }
```