# **Device Programming**

Tuur Vanhoutte

October 19, 2020

# **Contents**

1	.NE						
	1.1	Languages					
	1.2	Applications					
		1.2.1 Desktop					
		1.2.2 Web & Server					
		1.2.3 Mobile					
		1.2.4 Gaming					
		1.2.5 loT					
	4.0	1.2.6 Al					
	1.3	Xamarin					
		1.3.1 Xamarin - UI Technology					
		1.3.2 Xamarin - Code Sharing strategy					
	1.4	Summary					
_							
2	C# S	Syntax 4					
	2.1	Python vs C#					
	2.2	Datatypes					
	2.3	Collections					
		2.3.1 Arrays					
		2.3.2 Dictionary <tkey, tvalue=""></tkey,>					
		2.3.3 List <t></t>					
	2.4	Selections					
	2.5	Loops					
	2.6	Classes					
	2.7						
		•					
	2.8	Properties					
		2.8.1 Fields vs properties					
		2.8.2 Default values for properties					
	2.9	Constructor					
_							
3		amreader 8					
	3.1	Namespaces					
	3.2	System.Reflection					
	3.3	System.IO					
	3.4	Embedded files					
		3.4.1 Read an embedded file in Xamarin					
		3.4.2 Processing the file's content					
	3.5	Summary					
		·					
4	Nav	igation 9					
	4.1	Modal vs Modeless					
	4.2	Navigate forward					
	4.3	Navigate back					
		4.3.1 Go back - Modeless page					
		4.3.2 Go back - Modal page					
	4.4	Navigation stack					
	4.5	Page types					
	4.6	Exchanging data					
	4./	Summary					

5	Obje	ect Orientation	13					
	5.1	Inheritance	13					
		5.1.1 Constructor	14					
		5.1.2 Access modifiers						
		5.1.3 Properties/methods: VIRTUAL and OVERRIDE	14					
		5.1.4 Properties/methods: ABSTRACT and OVERRIDE	15					
	5.2	Polymorphisme	16					
		5.2.1 Disadvantage	17					
	5.3	Interfaces	17					
		5.3.1 Summary	17					
		5.3.2 Example	18					
	5.4	Composition	18					
		5.4.1 Example	19					
		5.4.2 Interfaces in Xamarin(.Forms)	19					
	5.5	Summary						
		•						
6	Asy	Asynchronous programming: async and await keywords						
	6.1	Why?						
	6.2	Example: newspaper app	20					
		6.2.1 Problem	20					
		6.2.2 Solution	21					
	6.3	Creating an asynchronous function	21					
		6.3.1 With void-functions: use Task	21					
		6.3.2 With a function that returns a type T	22					
	6.4	Calling an asynchronous function						
	6.5	Summary						

### **1** .NET

.NET is a free, cross-platform, open source developer platform (\*) for building many different types of applications.

\* languages + libraries




Figure 1: .NET ecosystem

### 1.1 Languages

- Syntax very similar to C, C++, Java & JavaScript
- · Functional programming language, cross-platform, open source
- · Approachable English-like language for OOP

### 1.2 Applications

- desktop
- · web & server
- · mobile
- gaming
- IoT
- Al

#### 1.2.1 Desktop

- UWP (Universal Windows Project)
- · Xamarin.Mac
- WPF (Windows Presentation Foundation)
- WinForms (Windows Forms)

#### 1.2.2 Web & Server

- ASP.NET
- ASP.NET Core

#### 1.2.3 Mobile

- UWP (Universal Windows Project)
- Xamarin

### 1.2.4 Gaming

- Unity
- CryEngine

### 1.2.5 loT

- UWP
- · .NET Core IoT

### 1.2.6 AI

- Cognitive Services
- · Azure Machine Learning
- · Machine Learning and Al Libraries
- F# for Data Science and ML

#### 1.3 Xamarin

- 'Target all platforms with a single, shared codebase for Android, iOS, Windows'.
- Developen van Mobile devices lastig: verschillende platformen, verschillende talen voor elk device.
- · Oplossing: Xamarin
- Extensie op Visual Studio.



Figure 2: Xamarin Logo

### 1.3.1 Xamarin - UI Technology




Figure 3: Native vs Xamarin.Forms

#### 1.3.2 Xamarin - Code Sharing strategy



Figure 4: .NET Standard vs Shared (Assets) Project

Met Shared Assets Project maken we de UI voor elk platform apart. Wij gaan vooral werken met .NET Standard.

### 1.4 Summary

- What devices, platforms, etc. can we target using .NET, and what programming languages can we use?
- · What is the basic difference between .NET Standard and Shared Assets projects in Xamarin?
- What is the difference between Xamarin native and Xamarin. Forms? What are the advantages and disadvantages?
- How to set up and understand the structure of a Xamarin project for the labs in this course, and how to debug on the different platforms.

# 2 C# Syntax

### 2.1 Python vs C#

• curly brackets { } in plaats van indenting

### 2.2 Datatypes

Туре	Omschrijving	Waarde	
Gehele getallen		Minimum	Maximum
int	integer	-231	2 <sup>31</sup>
long	long integer	-2 <sup>63</sup>	2 <sup>63</sup>
Reële getallen			
float	Kommagetal (positief / negatief)	1,5 x 10 <sup>-45</sup>	3,4 x 10 <sup>38</sup>
double	Preciezer kommagetal (positief / negatief)	5 x 10 <sup>-324</sup>	1,7 x 10 <sup>308</sup>
decimal	Geldbedragen		
Tekst			
string	Tekenreeks		
Andere types			
char	1 teken		
bool	Booleaanse waarde	Onwaar (0)	Waar(1)

Figure 5: Datatypes in C#

### 2.3 Collections

- Array
- · Dictionary<TKey, TValue>
- List<T>

Collection type = fixed!  $\Rightarrow$  Je kan alleen objecten van het gekozen type toevoegen aan een collection

```
// collections of type Person:
Person[] teacherArr = new Person[10];
List < Person > teacherList = new List < Person > ();
// You can only add Person objects to these collections!
```

### 2.3.1 Arrays

= meerdere variabelen van hetzelfde type

```
//initialize int array with 10 positions:
int[] numbers = new int[10];
//save number 13 in the first position
numbers[0] = 13;
//print the value of the first number in the array:
Debug.WriteLine("The_first_number_is:" +numbers[0]);
//intialize and fill another array with 4 numbers:
int[] startPositions = { 4, 1, 9, 3 };
```

### 2.3.2 Dictionary <TKey, TValue>

```
//declare dictionary with key type & value type
Dictionary < string, int > studentScores = new Dictionary < string, int >();
//add two elements (key value pairs)
studentScores.Add("Jean-Jacques", 13);
studentScores.Add("Jean-Louis", 4);
//get the score of Jean-Jacques
int score = studentScores["Jean-Jacques"];
```

#### 2.3.3 List<T>

```
//declare list, fill one by one:
List < string > emailList = new List < string > ();
emailList.Add("stijn.walcarius@howest.be");
emailList.Add("frederik.waeyaert@howest.be");
//get elements out (two ways):
string first = emailList.ElementAt(0);
string second = emailList[1];
//declare + fill list:
List < string > teacherList = new List < string > { "SWC", "FWA" };
```

#### 2.4 Selections

if / else if / else / switch

```
if (findTheoryTeacher == true) {
    email1 = "frederik.waeyaert@howest.be";
    email2 = null;
}
else if (findLabTeachers == true) {
    email1 = "stijn.walcarius@howest.be";
    email2 = "_frederik.waeyaert@howest.be";
} else {
    email1 = email2 = null;
}
```

```
switch (teacher){
    case "SWC":
        email = "stijn.walcarius@howest.be";
        break;
    case "FWA":
        email = "frederik.waeyaert@howest.be";
        break;
    default:
        email = "info@howest.be";
        break;
}
```

### 2.5 Loops

for / foreach / while / do while

```
for(int i = 0; i < 100; i++) {
    //do something 100 times
}</pre>
```

```
List < string > teacherList = new List < string > { "SWC", "FWA" };
foreach(string teacher in teacherList) {
    //do something
}
```

```
while(endOfClass == false){
    //might never be executed
}
```

```
do {
    //executed at least once!
} while(endOfClass == false);
```

#### 2.6 Classes

```
public class Person
{
    //property
    public string Name {
        get {...};
        set {...};
    }

    //constructor
    public Person(string name) {
        this.Name = name;
    }

    //method
    public void Subscribe() {
        //do something
    }
}
```

### 2.7 Instantiate objects

```
Persons p1 = new Person("Stijn");

// Based on the following constructor in the Person class:
public Person (string name) {
    this.Name = name;
}
```

### 2.8 Properties

#### 2.8.1 Fields vs properties

- · Fields store the actual data
- · Properties are used to access those fields
- · Auto-implemented properties have a hidden field
- · Use properties to control field access
- · Enhance input/output control using get & set
- · Calculated properties build on other properties
  - No field required
  - Reusability

```
//private field
private int _id;

//property (zetten we altijd public)
public int ld {
      // getter
      get { return _id; }
      // setter
      set { _id = value; }
}
```

### 2.8.2 Default values for properties

- · Setting default values can be useful
- Default values can be set...
  - ... with full properties
  - ... with auto-implemented properties
  - ... in the constructor

#### 2.9 Constructor

- · A constructor is called every time you create an instance of a class
- It is used to allow / force the user to provide certain values
- · Default constructor is (only) added if a model has no constructors
- Constructor overloading = multiple constructors with either . . .
  - ... a different number of parameters, or
  - ... a different type of paramters, or
  - ... the same parameters in a different order
- Constructors should call each other for enhanced efficiency
- · Constructors in inheriting classes call the constructors of the base class

### 3 Streamreader

- Namespaces
- · System.Reflection
- · Embedded Files
- · System.IO

### 3.1 Namespaces

```
    using Xamarin.Forms;
    namespace
    System.Diagnostics.Debug.WriteLine("DEVPROG");
    namespace class
```

Figure 6: Namespaces

### 3.2 System.Reflection

"The classes in the System.Reflection namespace, together with System.Type, enable you to obtain information about loaded assemblies and the types defined within, such as classes, interfaces, and value types. You can also use **reflection** to create type instances at run time and to invoke them."

### 3.3 System.IO

- = Input/Output https://developer.xamarin.com/api/namespace/System.IO/
  - StreamReader https://developer.xamarin.com/api/type/System.IO.StreamReader/
  - StreamWriter https://developer.xamarin.com/api/type/System.IO.StreamWriter/

#### 3.4 Embedded files

- · Textfiles, images, etc.
- · Generates a ResourceID for the file




Figure 7: Embedded files inladen in een Visual Studio project: rechtermuisknop op 1 of meerdere files  $\Rightarrow$  properties  $\Rightarrow$  build action = Embedded resources

#### 3.4.1 Read an embedded file in Xamarin

Figure 8

•

#### 3.4.2 Processing the file's content

```
using (var reader = new System.IO.StreamReader(stream))
{
    reader.ReadLine(); //ignore title row
    string line = reader.ReadLine(); //read first line
    while (line != null)
    {
        //process line
        //...
        //read the next line
        line = reader.ReadLine();
    }
}
```

Figure 9

### 3.5 Summary

- You understand the importance of namespaces, and the techniques of using them in your own projects.
- You can explain the very basics of the **System.IO** and **System.Reflection** namespaces, and what they have to do with reading an embedded file in Xamarin.
- You understand the how and why of the ResourceID that's being generated for an embedded file.

# 4 Navigation

### 4.1 Modal vs Modeless

Modal page: requires user input to continue

· Modeless page: user can go back any time he wants; no input required




Figure 10: Modal page vs Modeless page

### 4.2 Navigate forward

```
Navigation.PushAsync(new FooPage());
Navigation.PushModalAsync(new FooPage());
// FooPage is hier de XAML page waar we willen naar navigeren
```

- PushAsync vs PushModalAsync
- · Navigation object: controls the navigation stack

### 4.3 Navigate back

#### 4.3.1 Go back - Modeless page




Figure 11

### 4.3.2 Go back - Modal page




Figure 12

# 4.4 Navigation stack



Figure 13: Pushen op de stack



Figure 14: Pop'en van de stack



Figure 15: InsertPageBefore



Figure 16: RemovePage



Figure 17: PopToRoot

## 4.5 Page types

- ContentPage
- MasterDetailPage (zie Demo\_MasterDetail)
- NavigationPage (zie Demo\_Navigation)
- TabbedPage (zie Demo\_TabbedPage)
- TemplatedPage
- · CarouselPage



Figure 18

# 4.6 Exchanging data

How to exchange data between several pages:

- 1. Constructor (Demo\_MasterDetail)
- 2. Properties (Demo\_TabbedPage)

### 4.7 Summary

- The different **page types** and how to use them.
- The difference between **Modal** and **Modeless** pages, and how to manage navigation for both.
- You know how to **exchange data** between pages in the navigation process.
- You understand the navigation stack and how you can manipulate it.
- You can explain the concept of a master-detail relation with an example

# 5 Object Orientation

#### 5.1 Inheritance

= klasses nemen methods en properties over van een andere klasse.

Er ontstaat een hi"erarchie.

```
// the base class:

public class Advisor
{
    // properties
    public string Name { get; set; }

    // methods
    public void Advise() { }
}

// the deriving class
// notice the : between the base class and deriving class

public class MinisterOfDefense : Adviser {
    // code here
}
```

All C# classes, of any type, are treated as if they ultimately derive from System. Object




Figure 19

- Generalize properties (equal for all) by putting them in the base class
- Specify properties (specific for one) by putting them in the deriving class

#### 5.1.1 Constructor

- · Constructors are not inherited!
- · Constructor without parameter in base class?
  - → Automatically called by deriving class
- · No constructor without parameters in base class?
  - ⇒ Explicitly call it in deriving classes

Figure 20: Inheritance: constructor example

#### 5.1.2 Access modifiers

public is the default access modifier.

MODIFIER	APPLIES TO	DESCRIPTION
public	Any type or members	The item is visible to any other code
protected	Any member of a type, also the any nested type	The item is only visible in class and subclasses
private	Any type or members	The item is only visible in the class
internal	Any member of a type, also the any nested type	The item is only visible in it's containing assembly

Figure 21: Inheritance: access modifiers

### 5.1.3 Properties/methods: VIRTUAL and OVERRIDE

When you want to override a method from the base class, use the virtual keyword in the base method, and the override method in the derived method.

Virtual properties/methods:

- · Default implementation in base class
- 'virtual' keyword, to replace the way an object behaves
- CAN be overriden in subclasses, only if necessary.

```
public class Vliegtuig
    public virtual void Vlieg()
        Console.WriteLine("Het vliegtuig vliegt rustig door de wolken.");
    }
}
public class Raket : Vliegtuig
    public override void Vlieg()
        Console.WriteLine("De raket verdwijnt in de ruimte.");
    }
}
Vliegtuig f1 = new Vliegtuig();
Raket spaceX1 = new Raket();
f1.Vlieg();
spaceX1.Vlieg();
[0:] Het vliegtuig vliegt rustig door de wolken.
[1:] De raket verdwijnt in de ruimte.
```

Figure 22

### 5.1.4 Properties/methods: ABSTRACT and OVERRIDE

Abstract properties/methods:

- · No default implementation possible in base class
- 'abstract' keyword, to **extend** the way an object behaves
- MUST be present in each deriving class

Figure 23

### 5.2 Polymorphisme

= Objects of a derived class can be treated like objects of the base class at runtime

**Example:** say we have a class Animal, and two classes Cat and Dog that inherit the Animal class. Then, this is possible:

```
List < Animal > animals = new List < Animal > ();
Animal dog = new Dog();
Animal cat = new Cat();
animals. Add(dog);
animals. Add(cat);
```

```
public abstract class Animal
    public abstract string MakeNoise();
}
public class Horse : Animal
    public override string MakeNoise()
       return "Hinnikhinnik";
}
public class Pig : Animal
    public override string MakeNoise()
       return "Oinkoink";
    }
}
Animal someAnimal = new Pig();
Animal anotherAnimal = new Horse();
Debug.WriteLine(someAnimal.MakeNoise()); //Oinkoink
Debug.WriteLine(anotherAnimal.MakeNoise()); //Hinnikhinnik
```

Figure 24: Polymorphism example

#### 5.2.1 Disadvantage

!!! Multiple inheritance is NOT allowed through classes in C# !!!

#### 5.3 Interfaces

- Interfaces can be seen as contracts for classes
- Implementing = applying the contract
- An interface forces all implementing classes to implement all properties and/or methods
- An interface has no default implementation on its own (=you can't create an instance from an interface)

#### 5.3.1 Summary

- Contract + NO implementations = interface
- Contract + SOME implementations = abstract (base) class
- Implementation for all properties & methods = normal (base) class

#### 5.3.2 Example

- The IAdvisor interface has an Advice() method (notice that method has no default implementation)
- Every class that implements this interface also must have its own Advice() method
- · A class can implement multiple interfaces (see the MicrosoftCEO class)
- In the PrimeMinister class:
  - A list is created with the same type as the interface
  - Every element in that list is of a class that implements the interface
  - Can therefore also be used in a foreach() loop

```
public class MicrosoftCEO : CEO, IAdvisor
{
    public void Advise()
         Console.WriteLine("I think you should allow our monopoly.");
                                                                                               public class PrimeMinister
    public void EarnBigBucks()
                                                                                                    // properties
                                                                                                   public string Name { get; set; }
         Console.WriteLine("I'm getting rich!!!");
                                                                                                   // public methods
    public void FireDepartement()
                                                                                                   public void RunTheCountry()
                                                                                                        List<IAdvisor> allAdvisors = new List<IAdvisor>();
allAdvisors.Add(new MinisterOfDefense());
allAdvisors.Add(new MinisterofHealthcare());
allAdvisors.Add(new CoronaCommissioner());
allAdvisors.Add(new MicrosoftCEO());
         Console.WriteLine("You're all fired!");
                                                                       interface IAdvisor
}
                                                                            void Advise();
public class MinisterOfDefense : IAdvisor
    public void Advise() { }
                                                                                                        //Ask advise from each:
                                                                                                         foreach (IAdvisor advisor in allAdvisors)
public class MinisterofHealthcare : IAdvisor
                                                                                                             advisor.Advise();
                                                                                                 0
    public void Advise() { }
public class CoronaCommissioner : IAdvisor
    public void Advise() { }
```

Figure 25: Interfaces example

### 5.4 Composition

= Creating an instance of an object from a class in another class.

#### 5.4.1 Example

```
public class PC
{
     private Disk _disk;
}

public class Disk
{
}
```

Figure 26: How can we make an instance of '\_disk'?

#### Option 3 **Option 2** Option 1 public class PC public class PC public class PC private Disk \_disk = new Disk(); private Disk \_disk; private Disk \_disk; public Disk Disk public PC(bool parameter) get { return \_disk; } if (parameter) set { disk = value; } \_disk = new Disk(); //else \_disk == null } // somewhere in code Disk myDisk = new Disk(); myPC.Disk = myDisk;

Figure 27: Solution: 3 options

**Option 1:** creating it at the start of the class (=composition)

**Option 2:** using the constructor (=composition)

**Option 3:** Outside of the class, by creating a new object an assigning that object to the '\_disk' property in the class.

The 3rd option is called **Aggregation**. Unlike the other options, the 'myDisk' object keeps existing even if the PC class stops existing.

#### 5.4.2 Interfaces in Xamarin(.Forms)

Interfaces in Xamarin(.Forms) is extremely useful:

Say you need to get data from a specific sensor on your Android/iOS/UWP device. We can create an interface in our project, and implement that interface in each device's code. Once we need to get that data, we can automatically call the correct method for the correct device, by just calling the interface's method.

#### 5.5 Summary

- You are convinced by the advantages of inheritance and polymorphism, and can explain using an example
- You understand the usage and consequences of the virtual and abstract keywords for properties and methods.

- You know when to use abstract classes and/or interfaces, and can explain the difference between those two.
- You understand the specific importance of interfaces in **Xamarin**(.Forms)

# 6 Asynchronous programming: async and await keywords

### 6.1 Why?

To make the app continue to respond to use interaction while. . . :

- · Reading from or writing to a database or file
- · Accessing a web service
- · Performing data processing

### 6.2 Example: newspaper app

- · Load the trending newspaper items
- · Load user preferences
- Load newspaper items based on preferences ⇒ needs to wait until user preferences are set
  - LoadTrendingNews() while...
  - LoadUserPrefs ()wait for it...
    - LoadNewsItems(UserPreferences prefs)

Figure 28

#### 6.2.1 Problem

```
public async Task LoadNewsItemsAsync()
{
    LoadTrendingNewsAsync();
    LoadUserPrefsAsync();
    LoadNewsItemsAsync(prefs);
}

This function needs the user preferences that are being loaded in LoadUserPrefsAsync()
however since this function is async this will not wait for it!
```

Figure 29: LoadNewsItemsAsync(prefs) needs to wait

#### 6.2.2 Solution

```
public async Task LoadNewsItemsAsync()
{
    LoadTrendingNewsAsync();
    var prefs = await LoadUserPrefsAsync();
    LoadNewsItemsAsync(prefs);
}
```

Figure 30: Solution: use the 'await' keyword

Figure 31

### 6.3 Creating an asynchronous function

#### 6.3.1 With void-functions: use Task

```
public static void SavePreferences()

{
    //save preferences synchronously

public static async Task SavePreferencesAsync()

{
    //save preferences asynchronously

}
```

Figure 32: Turning a void function asynchronous

#### 6.3.2 With a function that returns a type T

```
public static List<NewsItem> GetNewsItems()
{
    //load some news items synchronously
}

public static async Task<List<NewsItem>> GetNewsItemsAsync()
{
    //load some news items asynchronously
}
```

Figure 33: Turning a type function asynchronous

### 6.4 Calling an asynchronous function

- · 'async' in both the function you call it in, and the function you are calling
- · await when calling the function

Figure 34

### 6.5 Summary

- The difference between synchronous and asynchronous programming
- The what and the why of asynchronous programming
- The meaning and usage of the async keyword
- · The meaning and usage of the await keyword
- The return type of async functions