

Euclid's Algorithm for Greatest Common Divisor

Under The Supervision of
Dr. Swapnil Lokhande

Group Members:

Name: PRASAD KAPURE	ID:202151115
Name: SNEHAL NALAWADE	ID: 202151160
Name: BARAIYA POOJAN	ID:202151185
Name: PATEL UTKARSH	ID:202152329
Name: SHIVANI MEENA	ID: 202152340



Contents:

1. Introduction
2. Divisor

Divisor definition

Code: find out divisors of given number

Code: find out number of divisors

3. Common divisor

Common divisor definition

Code: find out common divisor

Code: find out number of common divisor

4. Greatest Common divisors(GCD)

GCD definition

Code: find out GCD using different algorithms

Euclid's GCD algorithm

Proof of Euclid's GCD algorithm

Time complexity analysis of Euclid's GCD algorithm

Introduction

In this Project, we discuss about greatest common Divisor of two numbers and what are the efficient techniques to calculate the GCD of two numbers . One of those techniques is Euclid's GCD algorithm, which was invented by Euclid of Alexandria , who was a Greek mathematician born in 300 BC. We also compute the time complexity of Euclid's GCD algorithm . We will compare the time complexity of brute force algorithm vs Euclid's GCD algorithm.

Divisor


What is Divisor?

A divisor is a number that divides another number either completely or with a remainder.

A divisor is represented in a division equation as:

Dividend \div Divisor = Quotient.

On dividing 20 by 4, we get 5. Here 4 is the number that divides 20 completely into 5 parts and is known as the divisor. Its division equation is



Similarly, if we divide 20 by 5, we get 4. Thus, both 4 and 5 are divisors of 20.

For an integer P, we say set S is a set of all divisors of N if

$$S = \{ x \mid P \bmod x = 0 \ \&\& \ x \leq P \ \&\& \ x \in \mathbb{N} \}$$

For examples

$\text{divisors}(144) = \{ 1, 2, 3, 4, 6, 8, 9, 12, 16, 18, 24, 36, 48, 72, 144 \}$

Code 1: Print all divisors of given number(Brute force)

```
int n;  
cin>>n;  
for(int i=1;i<=n;i++)  
{  
    if(n%i==0)  
        printf("%d ",i);  
}
```

Input: 36

Output: 1 2 3 4 6 9 12 18 36

Time complexity: **O(n)**

Code 2: Print all divisors of given number

```
int n;  
cin>>n;  
for(int i=1;i<=sqrt(n);i++)  
{  
    if(n%i==0)  
    {  
        if(i*i != n)  
            printf("%d ",i);  
        else  
            printf("%d %d ",i,n/i);  
    }  
}
```

Input : 36

Output: 1 36 2 18 3 12 4 9 6

Time complexity : **$O(n^{1/2})$**

	Code 1	Code 2
Advantage	Give a all divisors in sorted order	It takes only \sqrt{n} steps. Suppose $n=36$ steps=6.
Disadvantage	It take n steps. Suppose $n=36$ steps=36.	Give a all divisors in non-sorted order

Code 3: Print number of divisor

```

int a;
cin>>a;
int answer=0;
for(int i=1;i<=sqrt(a);i++)
{
    if(a%i==0)
    {
        if(i*i!=a)
            answer=answer+2;
        else
            answer++;
    }
}

```

```
printf("%d",answer);
```

Input : 12

Output : 6

Time complexity : **$O(n^{1/2})$**

Common divisors

For two number a and b we say x is a common divisor of a and b if

$a \bmod x = 0$ and $b \bmod x = 0$

For example

$\text{Divisor}(12) = \{1, 2, 3, 4, 6, 12\}$

$\text{Divisor}(18) = \{1, 2, 3, 6, 9, 18\}$

$\text{Common Divisor}(12, 18) = \{1, 2, 3, 6\}$

Code 1: Print all common divisors of given number (Brute force)

```
int a,b;  
cin>>a>>b;  
for(int i=1;i<=min(a,b);i++)  
{  
    if(a%i==0 && b%i==0)  
        printf("%d ",i);  
}
```

Input : 12 and 18

Output: 1 2 3 6

Time complexity : **$O(n)$**

Code 2: Print all common divisors of given number

```
int a,b;  
cin>>a>>b;  
map<int,bool>mp1;
```

```
map<int,bool>mp2;  
if(a>b)  
swap(a,b);  
for(int i=1;i<=sqrt(a);i++)  
{  
    if(a%i==0)  
    {  
        mp1[i]=true;  
        mp1[a/i]=true;  
    }  
}  
for(int i=1;i<=sqrt(b);i++)  
{  
    if(b%i==0)  
    {  
        mp2[i]=true;  
        mp2[b/i]=true;  
    }  
}
```

```

    }
}
for(int i=1;i<=sqrt(a);i++)
{
    if(mp1[i])
    {
        if(mp2[i])
            printf("%d ",i);
        if(i*i!=a && mp1[a/i] && mp2[a/i])
            printf("%d ",a/i);
    }
}
}

```

Input : 12 and 18

Output: 1 2 6 3

Time complexity : **$O(n^{1/2})$**

	Code 1	Code 2
Advantage	Give a all common divisors in sorted order	It takes only $\sqrt{\max(a,b)}$ steps.
Disadvantage	It take $\min(a,b)$ steps.	Give a all common divisors in non-sorted order

Code 3: Print number of common divisor

```

int    a,b;

cin>>a>>b;

map<int,bool>mp1;
map<int,bool>mp2;

if(a>b)
swap(a,b);

for(int i=1;i<=sqrt(a);i++)
{
    if(a%i==0)

```

```
{  
    mp1[i]=true;  
    mp1[a/i]=true;  
}  
}  
for(int i=1;i<=sqrt(b);i++)  
{  
    if(b%i==0)  
    {  
        mp2[i]=true;  
        mp2[b/i]=true;  
    }  
}  
int answer=0;  
for(int i=1;i<=sqrt(a);i++)  
{  
    if(mp1[i])
```

```
{  
    if(mp2[i])  
        answer++;  
    if(i*i!=a && mp1[a/i] && mp2[a/i])  
        answer++;  
}  
}  
Printf("%d",answer);
```

Input : 12 and 18

Output: 4

Time complexity : **$O(n^{1/2})$**

Greatest Common divisors

For two numbers a and b let S be the set of common divisors of a and b then

- G = maximum integer in set S is called the GCD of a and b .
- $G = \max(s)$, where $\max(s)$ is the greatest integer in set S .
- In short, the greatest among common divisors of a and b is called a Greatest common divisors of a and b .

If $a = 12$ and $b = 8$, then $\text{GCD}(12,8) = 4$.

Code 1: Find GCD (divisor method)

```
int a,b;  
  
cin>>a>>b;  
  
if(a>b)  
  
swap(a,b);
```

```
map<int,bool>mp1;
map<int,bool>mp2;
for(int i=1;i<=sqrt(a);i++)
{
    if(a%i==0)
    {
        mp1[i]=true;
        mp1[a/i]=true;
    }
}
for(int i=1;i<=sqrt(b);i++)
{
    if(b%i==0)
    {
        mp2[i]=true;
        mp2[b/i]=true;
    }
}
```



```
}  
  
int GCD=1;  
for(int i=1;i<=sqrt(a);i++)  
{  
    if(mp1[i])  
    {  
        if(mp2[i])  
        {  
            if(i>GCD)  
            GCD=i;  
        }  
        if(i*i!=a && mp1[a/i] && mp2[a/i])  
        {  
            if(a/i>GCD)  
            GCD=a/i;  
        }  
    }  
}
```

```
}  
printf("%d",GCD);
```

Input: 45 and 30

Output: 15

Time complexity : $O(n^{1/2})$

Code 2 : Brute Force

```
int a,b;  
cin>>a>>b;  
int GCD=1;  
for(int i=1;i<=min(a,b);i++)  
{  
    if(a%i==0 && b%i==0)  
        GCD=i;  
}  
printf("%d",GCD);
```

Input: 45 and 30

Output: 15

Time complexity : **$O(n)$**

Code 3 : Find GCD (using prime Factors)

$$18=2*3*3$$

$$12=2*2*3$$

$$\text{GCD}(12,18)=2*3=6$$

```
int a,b;
```

```
cin>>a>>b;
```

```
vector<int>v1;
```

```
vector<int>v2;
```

```
while(a%2==0)
```

```
{
```

```
    v1.push_back(2);
```

```
    a=a/2;
```

```
}  
for(int i=3;i<=sqrt(a);i=i+2)  
{  
    while(a%i==0)  
    {  
        v1.push_back(i);  
        a=a/i;  
    }  
}  
if(a>2)  
v1.push_back(a);  
while(b%2==0)  
{  
    v2.push_back(2);  
    b=b/2;  
}  
for(int i=3;i<=sqrt(b);i=i+2)
```

```
{  
    while(b%i==0)  
    {  
        v2.push_back(i);  
        b=b/i;  
    }  
}  
if(b>2)  
v2.push_back(b);  
int GCD=1;  
int pointer1=0;  
int pointer2=0;  
int size1=v1.size();  
int size2=v2.size();  
while(pointer1<size1 && pointer2<size2)  
{  
    if(v1[pointer1]==v2[pointer2])
```

```
{  
    GCD=GCD*v1[pointer1];  
    pointer1++;  
    pointer2++;  
}  
else if(v1[pointer1]<v2[pointer2])  
    pointer1++;  
else  
    pointer2++;  
}  
printf("%d",GCD);
```

Input: 96 and 144

Output: 48

Time complexity : **$O(n)$**

GCD property1 : $\text{GCD}(a,b)=\text{GCD}(a-b,b)$ ($a \geq b$)

: $\text{GCD}(a,b)=\text{GCD}(a,b-a)$ ($b \geq a$)

Code 4 : Find GCD (using property1)

If a and b both are same stop using property1

This number is GCD

$\text{GCD}(12,18)=\text{GCD}(12,6)$

$\text{GCD}(12,6)=\text{GCD}(6,6)$ (STOP)

GCD=6

```
int a,b;
```

```
cin>>a>>b;
```

```
while(a!=b)
```

```
{
```

```
    if(a>b)
```

GCD property2 : $\text{GCD}(a,b)=\text{GCD}(a \% b,b)$ ($a \geq b$)
 : $\text{GCD}(a,b)=\text{GCD}(a,b \% a)$ ($b \geq a$)

Euclid's GCD algorithm :

- Input : two integers x and y .
 - Output : $\text{GCD}(x,y)$
1. let $x > y$ and if $x < y$ then swap x and y .
 2. while b is not zero do as follows –

- a. `Temporary_variable = x mod y;`
- b. `x = y;`
- c. `y = Temporary_variable;`
- d. finally x is nothing but a GCD of input values of x and y

CODE:

```
int a,b;
cin>>a>>b;
while(a!=0 && b!=0)
{
    if(a>b)
        a=a%b;
    else
        b=b%a;
}
if(a==0)
```

```
printf("%d",b);
```

```
else
```

```
printf("%d",a);
```

Input: 96 and 144

Output: 48

Time complexity : **$O(\log(\min(a,b)))$**

Proof of Euclid's GCD Algorithm :

For two integers a and b Euclid's algorithms works as follows

$$a > b$$

$$a = b * q + r_0 \text{ (by division algorithm)}$$

$$b = r_0 * q_1 + r_1$$

$$r_0 = r_1 * q_2 + r_2$$

..

$$r_n = (r_{n+1} * q_{n+2}) + 0 \text{ (algorithm terminates)}$$

- First we show that the algorithm terminates.

Since $r_{i+2} < r_{i+1}$, we have

- $r_0 > r_1 > r_2 > \dots > r_n > r_{n+1} = 0$.
- This shows that the remainders are monotonically strictly decreasing positive integers until the last one, which is $r_{n+1} = 0$.

Therefore the algorithm stops after no more than b divisions.

- We prove by induction the claim that for each i in $0 \leq i \leq n$ we have $\gcd(a, b) = \gcd(r_i, r_{i+1})$.

- For the base step $i = 0$, we have $\gcd(a, b) = \gcd(r_0, r_1)$ by definition of $r_0 = a$ and $r_1 = b$.

For each i in $0 \leq i < n$ we have $\gcd(r_i, r_{i+1}) = \gcd(r_{i+1}, r_{i+2})$.

- This shows that if $\gcd(a, b) = \gcd(r_i, r_{i+1})$, then $\gcd(a, b) = \gcd(r_{i+1}, r_{i+2})$, which is the induction step.

- This ends the proof of the claim. Now use the

claim with $i = n$: $\gcd(a, b) = \gcd(r_n, r_{n+1})$. But $r_{n+1} = 0$ and r_n is a positive integer by the way the Euclidean algorithm terminates. Every positive integer divides 0. If r_n is a positive integer, then the greatest common divisor of r_n and 0 is r_n . Thus, the Euclidean algorithm correctly computes the greatest common divisor of its input a and b as $\gcd(a, b) = r_n$.

Time Complexity of Euclid's algorithm :

The time complexity of this algorithm is

$$O(\log(\min(a, b)));$$

The time complexity of brute force algorithm is

$$O(\min(a, b));$$

a	b	Brute force algorithm (steps)	Euclid's algorithm (steps)
10	20	10	2
100	16563	100	6
1000	165156	1000	9
10000	1561627	10000	14
100000	56167466	100000	17

This table clearly shows how efficient Euclid's algorithm is !