

MTS-Vision Plugin

Overview

MTS-Vision is an OpenTAP plugin used for TCP/IP communication with the Keyence Vision Camera system.

The plugin supports:

- Opening TCP/IP communication
- Sending commands to the Vision system
- Receiving responses from the Vision system
- Validating received responses
- Closing communication
- Saving Vision communication logs into CSV files

Instrument Configuration

Add the instrument:

MTS-Vision

The following parameters must be configured:

Parameter	Description
IP Address	IP address of the Keyence Vision system
Port	TCP/IP communication port
Vision_Log	Enable/Disable Vision communication logging
Vision_Log_Path	Full path where Vision logs will be stored

Example log path:

D:\MTS.TEST.0001.v1.0.2\Autorun\Logs\Vision

Communication Flow

The plugin communication sequence should follow this order:

1. Open Communication

First, open the TCP/IP connection with the Vision system.

Example:

ServiceStr = Open

2. Send Command

Send the required command to the Vision system.

Example:

ServiceStr = Send
DATA = RUN

3. Receive Response

Receive the response from the Vision system.

Example response format:

RT,00898,OK,01,OK,0000096

The plugin validates only the **3rd position** value from the received response.

Example:

Position	Value
1	RT
2	00898
3	OK
4	01
5	OK
6	0000096

In this example:

3rd Position = OK

The comparison result is determined only by the 3rd position value.

The value is not fixed to "OK" only.
It can be any expected value such as:

OK
01
NG
PASS
FAIL

The plugin compares the configured expected response with the received 3rd position value.

4. Close Communication

After communication is completed, close the TCP/IP connection.

Example:

ServiceStr = Close

Vision Logging

If Vision_Log is enabled:

- All Vision communication logs will be stored automatically.
- Logs are saved in CSV format.
- The plugin automatically creates folders based on:
 - Year
 - Month
 - Date

Example structure:

```
Vision
├── 2026
│   ├── 05
│   │   ├── 19-05-26
│   │   │   └── 19-05-26_12-30-15.csv
```

Example log file:

19-05-26_12-30-15.csv

Notes

- The IP Address and Port must match the Keyence Vision system configuration.
- Always follow the correct communication sequence:

Open → Send → Receive → Close

- The plugin supports timeout handling and socket error detection.
- If communication fails or timeout occurs, the test verdict will be marked as FAIL.