EXPERIMENT 5

(Exercise on retrieving records from the table)
EMPLOYEES (Employee_Id, First_Name, Last_Name, Email, Phone_Number, Hire_Date, Job_Id, Salary, Commission_Act, Manager_Id, Department_Id)

(a) Find out the employee id, names, salaries of all the employees

```
mysql> SELECT Employee_Id, First_Name, Last_Name, Salary
    -> FROM EMPLOYEES;
+-------------+------------+-----------+--------+
| Employee_Id | First_Name | Last_Name | Salary |
+-------------+------------+-----------+--------+
|         101 | Rahul      | Sharma    |   5000 |
|         102 | Priya      | Verma     |   6000 |
|         103 | Amit       | AUSTIN    |   4500 |
|         104 | Neha       | Gupta     |   7000 |
|         105 | Ravi       | Kumar     |   4800 |
+-------------+------------+-----------+--------+
5 rows in set (0.00 sec)
```

(b) List out the employees who works under manager 100

```
mysql> SELECT *
    -> FROM EMPLOYEES
    -> WHERE Manager_Id = 100;
+------------+-----------+----------+----------------+-------------+------------+---------+--------+----------------+------------+---------------+
| Employee_Id | First_Name | Last_Name | Email          | Phone_Number | Hire_Date  | Job_Id  | Salary | Commission_Act | Manager_Id | Department_Id |
+------------+-----------+----------+----------------+-------------+------------+---------+--------+----------------+------------+---------------+
|        101 | Rahul      | Sharma   | rahul@gmail.com | 9999999999  | 2020-01-10 | IT_PROG |   5000 |           NULL |        100 |            60 |
|        102 | Priya      | Verma    | priya@gmail.com | 8888888888  | 2019-02-15 | HR      |   6000 |           NULL |        100 |            70 |
|        105 | Ravi       | Kumar    | ravi@gmail.com  | 5555555555  | 2022-05-30 | HR      |   4800 |           NULL |        100 |            90 |
+------------+-----------+----------+----------------+-------------+------------+---------+--------+----------------+------------+---------------+
3 rows in set (0.00 sec)
```

(c) Find the names of the employees who have a salary greater than or equal to 4800

```
mysql> SELECT First_Name, Last_Name
    -> FROM EMPLOYEES
    -> WHERE Salary >= 4800;
+------------+-----------+
| First_Name | Last_Name |
+------------+-----------+
| Rahul      | Sharma    |
| Priya      | Verma     |
| Neha       | Gupta     |
| Ravi       | Kumar     |
+------------+-----------+
4 rows in set (0.00 sec)
```

(d) List out the employees whose last name is ‘AUSTIN’

```
mysql> SELECT * FROM EMPLOYEES WHERE LAST_NAME='AUSTIN';
+-------------+------------+-----------+---------------+--------------+------------+--------+--------+----------------+-----------+---------------+
| Employee_Id | First_Name | Last_Name | Email         | Phone_Number | Hire_Date  | Job_Id | Salary | Commission_Act | Manager_Id | Department_Id |
+-------------+------------+-----------+---------------+--------------+------------+--------+--------+----------------+-----------+---------------+
|         103 | Amit       | AUSTIN    | amit@gmail.com | 7777777777   | 2021-03-20 | SALES  |   4500 |           NULL |       101 |            80 |
+-------------+------------+-----------+---------------+--------------+------------+--------+--------+----------------+-----------+---------------+
1 row in set (0.02 sec)
```

(e) Find the names of the employees who works in departments 60,70 and 80

```
mysql> SELECT First_Name, Last_Name
    -> FROM EMPLOYEES
    -> WHERE Department_Id IN (60, 70, 80);
+------------+-----------+
| First_Name | Last_Name |
+------------+-----------+
| Rahul      | Sharma    |
| Priya      | Verma     |
| Amit       | AUSTIN    |
| Neha       | Gupta     |
+------------+-----------+
4 rows in set (0.00 sec)
```

(f) Display the unique Manager_Id.

```
mysql> SELECT DISTINCT Manager_Id
    -> FROM EMPLOYEES;
+------------+
| Manager_Id |
+------------+
|        100 |
|        101 |
|        102 |
+------------+
3 rows in set (0.02 sec)
```

EXPERIMENT 6

(Exercise on updating records in table)
Create Client_master with the following fields (ClientNO, Name, Address, City, State, bal_due)
(a) Insert five records

```
mysql> CREATE TABLE Client_master (
    ->     ClientNO VARCHAR(10) PRIMARY KEY,
    ->     Name VARCHAR(50),
    ->     Address VARCHAR(100),
    ->     City VARCHAR(50),
    ->     State VARCHAR(50),
    ->     bal_due INT
    -> );
Query OK, 0 rows affected (0.05 sec)

mysql> INSERT INTO Client_master VALUES
    -> ('C101', 'Rahul Sharma', 'Street 1', 'Delhi', 'Delhi', 4000),
    -> ('C102', 'Priya Verma', 'Street 2', 'Mumbai', 'Maharashtra', 6000),
    -> ('C123', 'Amit Singh', 'Street 3', 'Kolkata', 'West Bengal', 4500),
    -> ('C104', 'Neha Gupta', 'Street 4', 'Chennai', 'Tamil Nadu', 7000),
    -> ('C105', 'Ravi Kumar', 'Street 5', 'Bangalore', 'Karnataka', 3000);
Query OK, 5 rows affected (0.01 sec)
Records: 5  Duplicates: 0  Warnings: 0
```

(b) Find the names of clients whose bal_due> 5000 .

```
mysql> SELECT Name
    -> FROM Client_master
    -> WHERE bal_due > 5000;
+-------------+
| Name        |
+-------------+
| Priya Verma |
| Neha Gupta  |
+-------------+
2 rows in set (0.00 sec)
```

(c) Change the bal_due of ClientNO “ C123” to Rs. 5100

```
mysql> UPDATE Client_master
    -> SET bal_due = 5100
    -> WHERE ClientNO = 'C123';
Query OK, 1 row affected (0.02 sec)
Rows matched: 1  Changed: 1  Warnings: 0
```

(d) Change the name of Client_master to Client12.

```
mysql> ALTER TABLE Client_master RENAME TO Client12;
Query OK, 0 rows affected (0.05 sec)
```

(e) Display the bal_due heading as “BALANCE”

```
mysql> SELECT bal_due AS BALANCE
    -> FROM Client12;
+---------+
| BALANCE |
+---------+
|    4000 |
|    6000 |
|    7000 |
|    3000 |
|    5100 |
+---------+
5 rows in set (0.02 sec)
```