

ASSIGNMENT

Name: Sneha Talukdar

Institute of Engineering and Management, New Town

B.Tech CSE(AI & ML)

SAE LEVELS OF AUTONOMOUS VEHICLES (L0 – L5)

1. INTRODUCTION –

Autonomous vehicles (AVs) are vehicles which use sensors, software, computing systems, and vehicle controls to assist or perform driving tasks. Depending on how much of the driving task is performed by the vehicle and how much remains the responsibility of the human driver, autonomous driving is classified into different levels.

The Society of Automotive Engineers (SAE) defines six levels of driving automation, from Level 0 to Level 5.

2. SAE Levels of Driving Automation-

- **Level 0 – No Driving Automation**

At level 0, the driver is completely responsible for driving. The vehicle may provide warnings or momentary assistance, but it does not continuously control the vehicle.

Examples: Forward collision warning, parking sensors, lane-departure warning.

Sensors/Technology: Cameras, radar, ultrasonic sensors.

Human Role: Full responsibility for driving.

- **Level 1 – Driver Assistance**

At level 1, the vehicle can assist the driver with either steering or acceleration/braking, but not both simultaneously.

- Examples: Adaptive Cruise Control or Lane Keeping Assistance.
- Sensors/Technology: Cameras, radar, ultrasonic sensors.
- Human Role: Driver continuously monitors the vehicle and surroundings.
- **Level 2 – Partial Driving Automation**

At Level 2, the vehicle can simultaneously control steering and acceleration/braking under certain conditions. However, the driver must continuously monitor the driving environment.

- Examples: Advanced driver-assistance systems (ADAS) that combine lane centering with adaptive cruise control.
- Sensors/Technology: Cameras, radar, LiDAR in some systems, GPS and other vehicle sensors.
- Human Role: Driver remains responsible and must be ready to take control.
- **Level 3 – Conditional Driving Automation**

At Level 3, the automated driving system can perform the driving task under specific conditions. The human driver does not need to continuously monitor the environment but must be able to take control when requested.

- Example: Automated highway driving systems designed for specific conditions.
- Sensors/Technology: Cameras, radar, LiDAR, GPS/IMU and high-definition maps.
- Human Role: Take over when the system requests.
- **Level 4 – High Driving Automation**

At Level 4, the vehicle can perform the complete driving task within a defined operational area or specific conditions without human intervention.

If the system operates outside its supported conditions, it must reach a safe state rather than simply expecting the human to take over.

- Example: Driverless robotaxi services operating in defined areas.
- Sensors/Technology: Multiple cameras, LiDAR, radar, GPS/IMU, HD maps and advanced computing systems.
- Human Role: Not required to drive while the system operates within its defined conditions.

- **Level 5 – Full Driving Automation**

At Level 5, the automated driving system can perform the complete driving task under all roadway and environmental conditions in which a human driver could reasonably operate.

No human driving is required.

- Example: A fully automated vehicle capable of operating without a driver in all suitable driving conditions.
- Sensors/Technology: Highly capable multi-sensor systems, advanced AI, localization and vehicle-control systems.
- Human Role: No driving responsibility

3. COMPARISON OF SAE LEVELS-

<u>SERIAL NUMBER</u>	<u>LEVEL</u>	<u>AUTOMATION</u>	<u>HUMAN DRIVER</u>	<u>TYPICAL TECHNOLOGY</u>
1.	L0	None	Drives	Warnings/Sensors
2.	L1	Driver Assistance	Monitors	Camera/Radar
3.	L2	Partial	Continuously monitors	Camera/Radar/ADAS
4.	L3	Conditional	Takes over when requested	Camera/Radar/LiDAR
5.	L4	High	Not required in defined conditions	Multi-sensor + AI
6.	L5	Full	Not required	Advanced multi-sensor + AI

4. SENSORS AND SOFTWARE REQUIREMENTS-

Autonomous vehicles use different sensors to understand their surroundings.

- Camera: Detects lanes, signs, vehicles and pedestrians.
- Radar: Measures object distance and speed.
- LiDAR: Provides detailed 3D information.
- Ultrasonic sensors: Used mainly for short-range detection.

- GPS/IMU: Helps with vehicle localization and movement.

The main software functions are- perception, localization, prediction, path planning and vehicle control.

5. REAL-WORLD APPLICATIONS-

- L0-L2: Common in modern vehicles with ADAS features.
- L3: Used in selected vehicles and specific driving conditions.
- L4: Used in some driverless mobility and robotaxi services within defined areas.
- L5: Fully autonomous driving in all suitable conditions is still a future goal.

6. ADVANTAGES AND CHALLENGES-

ADVANTAGES:

- Improved driving assistance
- Reduced driver workload
- Potential safety improvements
- Increased mobility

CHALLENGES:

- Difficult weather and road conditions
- Reliable object detection
- High technology cost
- Safety and regulatory requirements

7. CONCLUSION –

SAE (Society of Automotive Engineers) Levels L0-L5 describes the gradual transition from human-driven vehicles to highly automated vehicles. Higher levels require increasingly advanced sensors, software and control systems. Level 4 is an important stage because the vehicle can operate without human driving within its defined conditions.

8. REFERENCES-

- SAE International – Driving Automation Systems.
- National Highway Traffic Safety Administration (NHTSA) – Automated Vehicles.