

PRACTICAL QUERIES 21

Create EMP Table

```
CREATE TABLE EMP (  
    EMPNO NUMBER PRIMARY KEY,  
    ENAME VARCHAR2(50),  
    SAL NUMBER(10,2)  
);
```

Insert Sample Records

```
INSERT INTO EMP VALUES (101, 'Amit', 25000);  
INSERT INTO EMP VALUES (102, 'Neha', 40000);  
INSERT INTO EMP VALUES (103, 'Rahul', 35000);  
INSERT INTO EMP VALUES (104, 'Sneha', 50000);  
INSERT INTO EMP VALUES (105, 'Karan', 30000);
```

```
COMMIT;
```

Program to Display Top N Salaries using Explicit Cursor

```
SET SERVEROUTPUT ON;
```

```
ACCEPT P_N NUMBER PROMPT 'Enter Value of N : '
```

```
DECLARE
```

```
-----  
-- Cursor Declaration  
-----
```

```
CURSOR C_EMP IS  
SELECT EMPNO, ENAME, SAL  
FROM EMP  
ORDER BY SAL DESC;
```

```
-----  
-- Variable Declaration  
-----
```

```
V_EMPNO EMP.EMPNO%TYPE;  
V_ENAME EMP.ENAME%TYPE;  
V_SAL EMP.SAL%TYPE;
```

```
COUNT_EMP NUMBER := 0;
```

```
BEGIN
```

```
-----  
-- Open Cursor  
-----
```

```
OPEN C_EMP;
```

```
LOOP
```

```
-----  
-- Fetch Records  
-----
```

```
FETCH C_EMP INTO V_EMPNO, V_ENAME, V_SAL;
```

```
EXIT WHEN C_EMP%NOTFOUND  
        OR COUNT_EMP = &P_N;
```

```
-----  
-- Display Records  
-----
```

```
DBMS_OUTPUT.PUT_LINE(  
    'EMPNO : ' || V_EMPNO ||  
    ' ENAME : ' || V_ENAME ||  
    ' SALARY : ' || V_SAL  
);
```

```
COUNT_EMP := COUNT_EMP + 1;
```

```
END LOOP;
```

```
-----  
-- Close Cursor  
-----
```

```
CLOSE C_EMP;
```

```
END;  
/
```