

# Rajalakshmi Engineering College

Name: Sneha Raju R  
Email: 240701519@rajalakshmi.edu.in  
Roll no: 240701519  
Phone: 7550004064  
Branch: REC  
Department: CSE - FE  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 4\_COD\_Question 4

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

In an office setting, a print job management system is used to efficiently handle and process print jobs. The system is implemented using a queue data structure with an array.

The program provides the following operations:

Enqueue Print Job: Add a print job with a specified number of pages to the end of the queue. Dequeue Print Job: Remove and process the next print job in the queue. Display Queue: Display the print jobs in the queue

The program should ensure that print jobs are processed in the order they are received.

##### **Input Format**

The input consists of integers corresponding to the operation that needs to be performed:

Choice 1: Enqueue the print job into the queue. If the choice is 1, the following input is a space-separated integer, representing the pages to be enqueued into the queue.

Choice 2: Dequeue a print job from the queue.

Choice 3: Display the print jobs in the queue.

Choice 4: Exit the program.

### ***Output Format***

The output displays messages according to the choice and the status of the queue:

If the choice is 1:

1. Insert the given page into the queue and display "Print job with [page] pages is enqueued." where [page] is the number of pages that are inserted.
2. If the queue is full, print "Queue is full. Cannot enqueue."

If the choice is 2:

1. Dequeue a page from the queue and display "Processing print job: [page] pages" where [page] is the corresponding page that is dequeued.
2. If the queue is empty without any elements, print "Queue is empty."

If the choice is 3:

1. The output prints "Print jobs in the queue: " followed by the space-separated pages present in the queue.
2. If there are no elements in the queue, print "Queue is empty."

If the choice is 4:

1. Exit the program and print "Exiting program"

If any other choice is entered, the output prints "Invalid option."

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 1

10

1

20

1

30

1

40

1

50

1

60

3

2

3

4

Output: Print job with 10 pages is enqueued.

Print job with 20 pages is enqueued.

Print job with 30 pages is enqueued.

Print job with 40 pages is enqueued.

Print job with 50 pages is enqueued.

Queue is full. Cannot enqueue.

Print jobs in the queue: 10 20 30 40 50

Processing print job: 10 pages

Print jobs in the queue: 20 30 40 50

Exiting program

### **Answer**

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
#define max 5
```

```
int queue[max];
```

```
int front=-1;
```

```
int rear=-1;
```

```

void enqueue(int data){
    if(rear==max-1){
        printf("Queue is full. Cannot enqueue.\n");
        return;
    }
    else{
        if(front==-1){
            front=0;
        }
        rear=rear+1;
        queue[rear]=data;
        printf("Print job with %d pages is enqueued.\n",data);
    }
}

```

```

void dequeue(){
    if(front==-1){
        printf("Queue is empty.\n");
        return;
    }
    else{
        printf("Processing print job: %d pages\n",queue[front]);
        if(front==rear){
            front=rear=-1;
        }else{
            front=front+1;
        }
    }
}

```

```

void display(){
    if(front==-1){
        printf("Queue is empty.\n");
        return;
    }
    else{
        printf("Print jobs in the queue: ");
        for(int i=front;i<=rear;i++){
            printf("%d ",queue[i]);
        }
        printf("\n");
    }
}

```

```
}  
}  
int main(){  
    int ch,data;  
    while(1){  
        scanf("%d",&ch);  
        switch(ch){  
            case 1:  
                scanf("%d",&data);  
                enqueue(data);  
                break;  
            case 2:  
                dequeue();  
                break;  
            case 3:  
                display();  
                break;  
            case 4:  
                printf("Exiting program\n");  
                exit(0);  
            default:  
                printf("Invalid option.\n");  
                break;  
        }  
    }  
    return 0;  
}
```

**Status :** Correct

**Marks :** 10/10