# Rajalakshmi Engineering College

Name: Sneha  Raju R
Email: 240701519@rajalakshmi.edu.in
Roll no: 240701519
Phone: 7550004064
Branch: REC
Department: CSE - FE
Batch: 2028
Degree: B.E - CSE

Scan to verify results

## NeoColab_REC_CS23231_DATA STRUCTURES

## REC_DS using C_Week 5_COD_Question 3

Attempt : 1
Total Mark : 10
Marks Obtained : 10

## Section 1 : Coding

1.  Problem Statement

You are required to implement basic operations on a Binary Search Tree (BST), like insertion and searching.

Insertion: Given a list of integers, construct a Binary Search Tree by repeatedly inserting each integer into the tree according to the rules of a BST.

Searching: Given an integer, search for its presence in the constructed Binary Search Tree. Print whether the integer is found or not.

Write a program to calculate this efficiently.

*Input Format*

The first line of input consists of an integer n, representing the number of nodes

in the binary search tree.

The second line consists of the values of the nodes, separated by space as integers.

The third line consists of an integer representing, the value that is to be searched.

### Output Format

The output prints, "Value <value> is found in the tree." if the given value is present, otherwise it prints: "Value <value> is not found in the tree."

Refer to the sample output for formatting specifications.

### Sample Test Case

Input: 7
8 3 10 1 6 14 23
6
Output: Value 6 is found in the tree.

### Answer

```c
#include <stdio.h>
#include <stdlib.h>
struct node{
    int data;
    struct node *left;
    struct node *right;
};
typedef struct node Node;

Node *create(int key){
    Node *newnode=(Node *)malloc(sizeof(Node));
    newnode->data=key;
    newnode->left=NULL;
    newnode->right=NULL;
    return newnode;
}

Node *insert(Node *root,int key){
    if(root==NULL)
```

```c
        return create(key);
    else if(key < root->data)
        root->left=insert(root->left,key);
    else if(key > root->data)
        root->right=insert(root->right,key);
    return root;
}

void search(Node *root,int value){
    if(root==NULL){
        printf("Value %d is not found in the tree.",value);
        return;
    }
    else if(value < root->data)
        search(root->left,value);
    else if(value > root->data)
        search(root->right,value);
    else if(value==root->data)
        printf("Value %d is found in the tree.",value);
}

int main(){
    Node *root=NULL;
    int n,key,value;
    scanf("%d",&n);
    for(int i=0;i<n;i++){
        scanf("%d",&key);
        root=insert(root,key);
    }
    scanf("%d",&value);
    search(root,value);
    return 0;
}
```

*Status :* Correct                                    *Marks : 10/10*