Subj-Android Pratical Name - Suraj Nathani Univ. roll no - 1921186 Student Id - 19041008 Course - BCA Sem - V Section - A Oues1 - Implicit (i) XML main file <?xml version = "1.0" encoding = "Wf=8"?)</pre> xmins: cinclosid = "http:// schemas. cindroid. Com/ < Relative Layout ap K/res/android "Xmins: app= "http://schemas. android. com/apk/res-auto "Xmins: tools = "http: 1100 hemas. andsoid.com/ tools "android: layout width = "moth-parent" android: layout height = "match-parent" tools: context = " main Activity)

(Edit Text android: Layout _ width = "match-parent"

android: Layout - height = "wrap-content

android: Id = "@tid/et.1" android: input Typ(=

"tent' android: padding = "30dp"

android: layout - maryinTop = "30dp"/7

(Button android: Layout width = "woap-Content" android:

(Button android: Layout width = "woop- Content" android!

dayout - height = "wrap- Content"

android. text = "Click here" android! id = "Otid/btn-1"

android: textsi31 = "30dp"

android: background = "@ Color/teal-700" android: dayout_below = "@ +id/et-7"

android: layout_marginleft = "80 dp" and roid: layout, marginTop = "40 dp"/>

(/Relative Layout)

SUIA

```
Java Code:
Rate Package Com. example. implicit-intent;
      import android X. app Compat. app. App Compat
       Activity; import android. Content. Intent;
     import android. net. Uri; import android. OS.
      Bundle; import android view. View;
     import android widget, Button;
    import android. Widget: EditText,
 Public Class main Activity extends App Compat Activity
    ¿ Edit Text e1;
         Button ben; @ Override
        Protected void on Create (Bundle Saved Instance State)
           ¿ Super. On Create (Saved In Dtan a State);
        Set Content View (R. layout- Activity-main),
            e1 = find view By Id (R.id. et-1);
        bt n= find View By 1d (R.id.btn-1); btn. sed On click Listener
            (new View. Ondick Listner()[
           Public void onclick (view v) & String S=elget Textl)

to String()
        override
            Intent i = new Intent (intent. Action_ UIEW,
                                Uxi. parse (s)); Start Activity
 3),
                                                 SUPS
```

Scanned by CamScanner

```
Java (odi
 Package Com example explicit intent;
 import android x. applompat. app. Applom put Activity
 import android. Content. intent; import android. OS.
        Bundle; import android view view; import
  android . widget . Button'
  import android. widget. Text view
   Public Class Main Activity extends.
   App Compat Activity & Text view to;
    Button
     Protected Void on Cleate (Bundle Saved Instance State)
       ¿ Super. On Create (Saved Instana State), Set Contentière
          (R. layout-activity_main)
      to = find view by Id (R. Id. tu-1)' bt n = find view By Id (Rid stri)
        Hm. Set Onclick Listener ( Cinew View. Onclick Listener ()(
      (d) Override
        Public word ondick (via v) {
          intent i = new Intent (get Application Continued (),
           Activity 2. Class); Start Acitivity (1)
```

Main Activity-2 Code

<! Xml version = "1.0" encoding = "Utf-8"?)</pre>

< Relative layout xmlns: android = "http://schemas.android.com lapk lies landroid "xmlns: app. "http://schemas.android.com /apx / res-auto"

Xmlnsitools: "http://schemas. android. Com/tools" android: layord - width = "match - parent" android, layout high = "match-parent" tools: Contend = ". Activity 2">

Ctent View android: layout-width = "match-parent" android: layout _ height = "wrap: Content" android: +ent=" Hello This is Activity 2" and soid: tent Size: "hodp" android ! layout - Center Horizontal = "true" condroick ! layout - Center Vertical = "true" condroid: test Colos: "@Colos Heal 200/

</kelative layout >

SurAs