

MAJOR PROJECT REPORT

ON

“SPECIOUS - Spectral Perturbation Engine for Contrastive Inference Over Universal Surrogates”

**submitted in partial fulfilment of the requirements
for the award of the degree of**

**Bachelor of Technology
In
Artificial Intelligence and Machine Learning
[2021-25]**

Submitted By:
Name: Harshveer Singh
Enrollment No: 07519011621

Supervised By:
Dr. Himani Tyagi
Assistant Professor, USAR

UNIVERSITY SCHOOL OF AUTOMATION AND ROBOTICS, GGSIPU



GURU GOBIND SINGH INDRAPRASTHA UNIVERSITY
EAST DELHI CAMPUS, SURAJMAL VIHAR, DELHI-11009

DECLARATION BY THE CANDIDATE

I hereby declare that the work, which is being presented in this project entitled **“SPECIOUS (Spectral Perturbation Engine for Contrastive Inference Over Universal Surrogates)”**, is an authentic record of my own work carried out by me under the supervision and guidance of **Ms. Himani Tyagi, Assistant Professor, University School of Automation of Robotics, GGSIPU.**

This project was undertaken as a part of the major project report for the partial fulfillment of B.Tech. (AI&ML).

I have not submitted the matter embodied here in this project for the award of any other Degree/Diploma.

harsh

Harshveer Singh


Enrollment No.: 07519011621

BTech (AI&ML)

CERTIFICATE

This is to certify that this MAJOR PROJECT REPORT “**SPECIOUS (Spectral Perturbation Engine for Contrastive Inference Over Universal Surrogates)**” is submitted by **Harshveer Singh**, who carried out the project work under my supervision. I approve this project for submission of the Bachelor of Technology (B.Tech., AI&ML) in the University School of Automation and Robotics (USAR), Guru Gobind Singh Indraprastha University, Delhi.


Date: 20.05.2025


Ms. Himani Tyagi
Assistant Professor
USAR, GGSIPU EDC

Dhruv kumar

“Ghiblification”

 Revolutionizing Healthcare: Exploring the Applications of 4D Printing in Medical Advancements

 Advanced Production, Manufacturing Engineering

 GGS IP University Delhi

Document Details

Submission ID

trn:oid:::1:3254045087

Submission Date

May 19, 2025, 10:03 AM GMT+5:30

Download Date

May 19, 2025, 10:41 AM GMT+5:30

File Name

Final_Report.pdf

File Size

1.8 MB

31 Pages

5,704 Words

34,166 Characters





8% Overall Similarity

The combined total of all matches, including overlapping sources, for each database.




Exclusions

▸ 10 Excluded Matches

Match Groups

-  **25 Not Cited or Quoted 7%**
Matches with neither in-text citation nor quotation marks
-  **4 Missing Quotations 1%**
Matches that are still very similar to source material
-  **1 Missing Citation 0%**
Matches that have quotation marks, but no in-text citation
-  **0 Cited and Quoted 0%**
Matches with in-text citation present, but no quotation marks

Top Sources

- 6%  Internet sources
- 6%  Publications
- 5%  Submitted works (Student Papers)

Integrity Flags

0 Integrity Flags for Review

No suspicious text manipulations found.

Our system's algorithms look deeply at a document for any inconsistencies that would set it apart from a normal submission. If we notice something strange, we flag it for you to review.

A Flag is not necessarily an indicator of a problem. However, we'd recommend you focus your attention there for further review.

Dhruv kumar

“Ghiblification”

 Revolutionizing Healthcare: Exploring the Applications of 4D Printing in Medical Advancements

 Advanced Production, Manufacturing Engineering

 GGS IP University Delhi

Document Details

Submission ID

trn:oid:::1:3254045087

Submission Date

May 19, 2025, 10:03 AM GMT+5:30

Download Date

May 19, 2025, 10:42 AM GMT+5:30

File Name

Final_Report.pdf

File Size

1.8 MB

31 Pages

5,704 Words

34,166 Characters

0% detected as AI

The percentage indicates the combined amount of likely AI-generated text as well as likely AI-generated text that was also likely AI-paraphrased.

Caution: Review required.

It is essential to understand the limitations of AI detection before making decisions about a student's work. We encourage you to learn more about Turnitin's AI detection capabilities before using the tool.

Detection Groups



0 AI-generated only 0%

Likely AI-generated text from a large-language model.



0 AI-generated text that was AI-paraphrased 0%

Likely AI-generated text that was likely revised using an AI-paraphrase tool or word spinner.

Disclaimer

Our AI writing assessment is designed to help educators identify text that might be prepared by a generative AI tool. Our AI writing assessment may not always be accurate (it may misidentify writing that is likely AI generated as AI generated and AI paraphrased or likely AI generated and AI paraphrased writing as only AI generated) so it should not be used as the sole basis for adverse actions against a student. It takes further scrutiny and human judgment in conjunction with an organization's application of its specific academic policies to determine whether any academic misconduct has occurred.

Frequently Asked Questions

How should I interpret Turnitin's AI writing percentage and false positives?

The percentage shown in the AI writing report is the amount of qualifying text within the submission that Turnitin's AI writing detection model determines was either likely AI-generated text from a large-language model or likely AI-generated text that was likely revised using an AI-paraphrase tool or word spinner.

False positives (incorrectly flagging human-written text as AI-generated) are a possibility in AI models.

AI detection scores under 20%, which we do not surface in new reports, have a higher likelihood of false positives. To reduce the likelihood of misinterpretation, no score or highlights are attributed and are indicated with an asterisk in the report (*%).

The AI writing percentage should not be the sole basis to determine whether misconduct has occurred. The reviewer/instructor should use the percentage as a means to start a formative conversation with their student and/or use it to examine the submitted assignment in accordance with their school's policies.

What does 'qualifying text' mean?

Our model only processes qualifying text in the form of long-form writing. Long-form writing means individual sentences contained in paragraphs that make up a longer piece of written work, such as an essay, a dissertation, or an article, etc. Qualifying text that has been determined to be likely AI-generated will be highlighted in cyan in the submission, and likely AI-generated and then likely AI-paraphrased will be highlighted purple.

Non-qualifying text, such as bullet points, annotated bibliographies, etc., will not be processed and can create disparity between the submission highlights and the percentage shown.



ACKNOWLEDGEMENT

I would like to express my sincere gratitude to all those who have supported and guided me throughout the course of this project. First and foremost, I am deeply thankful to **Prof. A. K. Saini, Director**, East Campus, GGSIPU, for providing the necessary academic environment and resources that made this project possible. I would also like to extend my heartfelt gratitude to **Prof. Arvinder Kaur**, Dean USAR, for her constant encouragement and support during this academic journey.

I sincerely thank to **Prof. Dr. Abha Agarwal**, Program Coordinator, for his/her valuable guidance in structuring the project and ensuring smooth progress. I am especially grateful to **Assistant Prof. Dr. Manisha Parlewar**, Teacher-in-Charge, for the consistent academic supervision, helpful insights, and feedback that significantly enhanced the quality of my work.

A very special thanks to my project mentor, **Ms. Himani Tyagi**, for her unwavering support, expert guidance, and constant motivation throughout every phase of this project. Their dedication and mentoring were crucial to the completion of this work. Lastly, I would like to thank all my faculty members, friends, and family who contributed in any way toward the success of this project.

Thanking You,
Harshveer Singh
Enrollment No.: 07519011621

TABLE OF CONTENTS

S.No.	TITLE	PAGE NO.
1	Abstract	1
2	Introduction 2.1 Background and Problem Statement 2.2 Limitations of Existing Defenses 2.3 Our Approach	2
3	Literature Survey 3.1 Style-Cloaking and Dataset-Poisoning Attacks 3.2 Frequency-Domain Adversarial Perturbations 3.3 Perceptual Metrics in Adversarial Optimization 3.4 Y-Channel Specific Attacks 3.5 Universal and Multi-Model Attacks 3.6 Adversarial Patches and Physical-World Attacks 3.7 Object-Detection Patch Attacks 3.8 Certified Robustness via Randomized Smoothing 3.9 Extending Certification to Transformations	5

	3.10 Feature De-Noising Networks	
4	Materials and Proposed Methodology 4.1 Data Preparation 4.2 Model Architecture 4.3 Frequency Domain Perturbation Block 4.4 Specious Loss: Joint Perceptual-Feature Objective	9
5	Experiments & Results 5.1 Training Dynamics 5.2 CLIP Cosine Similarity Drop Distribution 5.3 ResNet-50 Classification Results 5.4 CLIP Zero shot Classification 5.5 Summary of Findings 5.6 Simulation and User-Friendly Website Screenshots	17
6	Conclusion	26
7	References	27
8	Annexure	30

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE NO.
4.1	Working Flow Diagram of SPECIOUS	9
5.1.1	Plot of the smoothed LPIPS, feature loss, and total loss over $\approx 7,200$ training steps (rolling window = 100)	17
5.1.2	Zoomed in LPIPS over training steps	18
5.2	The histogram and KDE of similarity drops	19
5.3	Scatter plot of the data points showcasing whether they got fooled or not, along with their LPIPS and Confidence Drop, and a bar plot showcasing the Fooling Rate when got tested on ResNet50	20
5.4	Scatter plot of the data points showcasing whether they got fooled or not, along with their LPIPS and Confidence Drop, and a bar plot showcasing the Fooling Rate when tested on CLIP Zero Shot Prediction on the CIFAR-100 test dataset	21

5.6.1	Home Page	22
5.6.2	Website How It Works Section	22
5.6.3	Detailed Flow Diagram of Specious on the Website	23
5.6.4	Comparison of SPECIOUS with Glaze and Nightshade	23
5.6.5.1	Use it Tab on Website	24
5.6.5.2	SPECIOUS in Action on Website	24
5.6.6	Meet the team	25

ROLES AND RESPONSIBILITIES

S.No	NAME	ROLES AND RESPONSIBILITIES
1	Dhruv Kumar	Research, Planning, Methodology, Execution, Drafting
2	Deepanshu Singh	Research, Methodology, Execution, Drafting
3	Harshveer Singh	Data Curation and Processing, Validation, Execution, Drafting

ABSTRACT

Generative AI models trained on large uncured image corpora often appropriate artists' copyrighted work without consent. We introduce **SPECIOUS** (Spectral Perturbation Engine for Contrastive Inference Over Universal Surrogates), a universal, multi-model defensive technique that embeds imperceptible high-frequency perturbations into the **luminance (Y) channel** of YCbCr representations. At inference time, these perturbations remain invisible to humans but systematically degrade feature embeddings across multiple surrogate models (ResNet-50, CLIP ViT-B/32, etc.), preventing downstream generative or classification tasks from reproducing the protected style. Our **U-Net-based generator** works in the Fourier domain, with a learnable high-pass mask, while our novel **SpeciousLoss** simultaneously minimizes LPIPS perceptual distance and maximizes the surrogate model's feature distortion under a strict perceptual threshold. We demonstrate that S.P.E.C.I.O.U.S. effectively fools zero-shot predictions and classifications, generalizes across resolutions, and preserves visual fidelity.

Chapter - 1

INTRODUCTION

1. Background and Problem Statement

The recent “Ghiblification” phenomenon, more like a social media trend—in which users transform images into a Studio Ghibli style via ChatGPT’s image model [1][2][3]—has reignited urgent debates about copyright and artist rights in AI-generated art. Studio Ghibli itself has weighed legal action against OpenAI [4], but trademark and copyright statutes offer only partial recourse because “visual style” per se often falls outside traditional infringement claims. Meanwhile, AI companies continue to scrape public and private image repositories—often including copyrighted works—without artists’ consent [5][6], allowing models like DALL·E 2, Midjourney, Stable Diffusion, etc, to reproduce distinctive styles in seconds. Authors and illustrators worldwide report moral injury, as their life’s work is co-opted without credit or compensation [7].

Adversarial perturbations offer a pathway for **self-defence** [8]: small, model-imperceptible modifications that disrupt downstream inference. Empirical studies demonstrate that such perturbations concentrate in **high-frequency** components (sharp edges and textures)—that deep networks exploit to build feature representations [9][10], while leaving low-frequency content (soft edges and textures) intact. Furthermore, perturbations applied in the **YCbCr color space** show that changes in chrominance (Cb, Cr) are less salient to humans, but the most effective adversarial distortions actually arise in the **luminance (Y) channel** [11].

2. Limitations of Existing Defences

Although tools like **Glaze** and **Nightshade** represent important steps toward protecting artists, they exhibit several key shortcomings that hinder their broader applicability:

1. **Model-Specific Targeting:** Both Glaze and Nightshade focus narrowly on Stable Diffusion–style pipelines rather than offering a general defence. Glaze’s perturbations are designed specifically to mislead diffusion-based generators (e.g., Stable Diffusion or Midjourney) and may not transfer to other architectures or tasks [12][13]. Nightshade likewise tailors its poisoning attack

to prompt-specific vulnerabilities in text-to-image diffusion models, requiring intimate knowledge of a single target model’s training data and concept sparsity [14]. In contrast, SPECIOUS can incorporate any number of surrogate models—from ResNet-50 classifiers to CLIP encoders—via its dynamic loss function, making it universal across architectures [15].

2. **Dependence on a Target Label:** Nightshade’s prompt-specific poisoning hinges on choosing exactly which concept or class to corrupt [16]. You must supply a **target label** that directs the model’s latent representation into an unwanted state. Glaze similarly bakes in perturbations aimed at derailing the model’s style mimicry for a predefined artist. SPECIOUS, however, functions as a **label-agnostic perturbation engine** [17]: it crafts **universal changes** that degrade feature embeddings broadly, without needing to specify any particular downstream label or prompt.
3. **Single-Metric Penalty:** Both prior defences apply only an **LPIPS penalty** [18] to control perceptual visibility, so they minimize human-noticeable changes but do not actively push feature representations apart. SPECIOUS’s **SpeciousLoss**, by contrast, is a **bi-objective** function: it simultaneously *minimizes* LPIPS and *maximizes* distortion in multiple surrogate feature spaces. This balanced approach guarantees both stealth and efficacy, rather than sacrificing one for the other.
4. **Neglect of Y-Channel Perturbations:** Glaze and Nightshade operate solely in the **RGB pixel domain** [19], dispersing small cloaks uniformly across red, green, and blue channels. Yet perceptual and adversarial research shows that the **luminance (Y) channel in YCbCr** carries the most potent perturbations—human vision is less sensitive to chrominance, but deep networks leverage brightness variations heavily. SPECIOUS exploits this by concentrating all changes in the Y channel, preserving color fidelity while attacking the model-relevant signal.
5. **Overlooking Frequency-Domain Structure:** Neither Glaze nor Nightshade uses **frequency-domain filtering** [20], neglecting the fact that adversarial deltas predominantly occupy **high-frequency bands**—edges and textures—that classification and generative models rely on. SPECIOUS embeds a **learnable high-pass mask** in the Fourier domain, adaptively isolating precisely

those spectral regions where perturbations inflict maximum damage, ensuring minimal perceptual impact.

Taken together, these limitations underscore why a **universal, multi-model defence**—one that works at inference time, requires no specific label, balances perceptual and feature distortion, targets only the Y channel, and leverages frequency analysis—is essential for protecting creative content in the age of generative AI.

3. Our Approach: SPECIOUS

We propose **SPECIOUS** (Spectral Perturbation Engine for Contrastive Inference Over Universal Surrogates), which integrates four key innovations:

1. **Frequency-Domain Perturbation on Y Channel:** We transform only the Y channel into the Fourier domain [11][21], apply a **learnable high-pass mask** to isolate sharp edges and textures, then invert back to the spatial domain. This focuses perturbations on features that both classification (ResNet-50) and zero-shot (CLIP ViT-B/32) models rely on.
2. **U-Net Generator with FFT/IFFT Blocks:** A bespoke U-Net architecture [22] ingests the high-frequency component and outputs a single-channel perturbation, ensuring the capacity to learn complex spatial patterns while maintaining low inference cost.
3. **Specious Loss: Joint Perceptual and Feature Distortion Objective:** To train this, we designed Specious Loss, which balances two goals:
 1. Perceptual fidelity, by minimizing LPIPS (a learned measure of human-perceived similarity) under a strict threshold.
 2. Model disruption, by maximizing the difference in feature representations extracted by several pre-trained networks.An exponential formulation keeps the loss positive and smoothly balances these pressures, while a penalty term ensures we never exceed our perceptual budget.
4. **Universal Multi-Model Defence:** By training against multiple surrogate models simultaneously, SPECIOUS generates perturbations that generalize across architectures and tasks, unlike prior single-model attacks [15][24].

We demonstrate that SPECIOUS preserves visual fidelity while achieving high fooling rates ($> 70\%$) on both classification and zero-shot generative benchmarks.

Chapter - 2

LITERATURE SURVEY

1. Style-Cloaking and Dataset-Poisoning Attacks

1. **Glaze’s Style Cloaks:** Glaze crafts tiny RGB perturbations (“style cloaks”) that artists can apply before sharing images, so that diffusion models trained on these cloaked versions learn a skewed style representation rather than the true artistic style. In a large-scale user study involving over 1,000 professional illustrators [12][13], surveyed artists found the visual changes acceptable, and automated CLIP-based metrics confirmed over 92% disruption of style mimicry under normal conditions and still above 85% under adaptive counter-attacks. However, Glaze’s effectiveness hinges on models fine-tuned on cloaked data and does not extend to inference-time scenarios.
2. **Nightshade’s Prompt-Specific Poisoning:** Nightshade takes a data-poisoning route [14] by injecting carefully crafted image–text pairs into the Stable Diffusion training set, such that fewer than 100 poisoned samples can hijack a model’s response to a specific prompt (e.g., making “a cat” generate flowers instead). These poison images are visually indistinguishable from authentic samples and can even “bleed through” to semantically related prompts. Yet because Nightshade requires access to and modification of the training pipeline, it cannot defend images shared against black-box, inference-only attacks.

2. Frequency-Domain Adversarial Perturbations

Early work revealed that gradient-based adversarial deltas concentrate in **high-frequency bands** [9][25]—the fine edges and textures that convolutional networks heavily weight. Building on this, researchers have embedded **spectral filtering layers** inside defences to emphasize low-frequency content for robust recognition, effectively “damping” model sensitivity to perturbations. Other defences apply **input transformations in the Fourier domain**, such as mixing or removing select frequencies, to neutralize adversarial noise before classification. These techniques underscore the power of frequency analysis, but most target single architectures or rely on fixed, hand-crafted filters rather than learnable, adaptive masks.

3. Perceptual Metrics in Adversarial Optimization

To achieve “stealthy” attacks, perceptual fidelity is critical. The **Learned Perceptual Image Patch Similarity (LPIPS)** metric [18] aligns deep feature distances with human judgments, mapping differences onto a **0–1 scale**. LPIPS has been used both as an evaluation metric and as a **loss term** during adversarial example generation, ensuring perturbations remain below human-noticeable thresholds. The **Perceptual Sensitive Attack** further integrates LPIPS constraints to maximize downstream task disruption under tight perceptual budgets, illustrating how perceptual losses can guide more effective black-box attacks. However, existing methods seldom **jointly optimize** LPIPS and multi-model feature distortion under a strict threshold.

4. Y-Channel Specific Attacks

Pestana et al. demonstrated that adversarial perturbations “prevail” in the **luminance (Y) channel** [11] of YCbCr space, achieving higher fooling rates for the same perturbation budget compared to RGB-space attacks. Their **ResUpNet** defence uses a Y-channel de-noising network to remove adversarial noise (from FGSM, PGD, DDN) while leaving chrominance untouched, thereby preserving color fidelity. This work highlights how human sensitivity to chrominance changes is lower, making Y-focused perturbations more “efficient”—yet most RGB-based defences ignore this channel specificity.

5. Universal and Multi-Model Attacks

Most adversarial studies focus on a **single target architecture** [24] under white-box assumptions. Transfer-based attacks create perturbations in pixel space that sometimes generalize to other networks, but typically only at fixed resolutions and without perceptual guarantees. Very few methods optimize simultaneously against **multiple surrogate models** (e.g., ResNet-50, CLIP ViT-B/32) under perceptual constraints. This gap motivates **universal defences** that operate at inference time, require no retraining of downstream systems, and maintain visual fidelity while disrupting a range of black-box encoders.

6. Adversarial Patches and Physical-World Attacks

Universal adversarial patches, introduced by Brown et al., can be printed or worn in the real world [22][26] yet still mislead classifiers toward a chosen label, demonstrating that perturbations need not be pixel-budget-limited to be effective. These patches remain robust under varied transformations—lighting, scale, viewpoint—making them a potent threat in safety-critical applications. Thys et al. later extended this idea to object detectors, showing that simple printouts affixed to clothing can hide pedestrians from surveillance systems like YOLOv2, confirming the real-world viability of patch attacks.

7. Object-Detection Patch Attacks

Liu et al. proposed **DPatch**, an adversarial patch attack [27] specifically targeting object detectors (Faster R-CNN, YOLO). Unlike earlier work focused on classifiers, DPatch simultaneously disrupts bounding-box regression and class scores, driving mAP on state-of-the-art detectors below 1% in a purely black-box setting. Its location independence and cross-model transferability highlight the vulnerability of modern detection architectures to patch-style attacks.

8. Certified Robustness via Randomized Smoothing

Cohen et al. introduced **randomized smoothing** [28], a technique that wraps any base classifier with Gaussian noise to produce a “smoothed” model that comes with a **provable ℓ_2 -norm robustness certificate**. This approach scales to ImageNet, delivering, for instance, 49% top-1 certified accuracy under perturbations of size 0.5 (127/255)—the first certified defence at full ImageNet scale.

9. Extending Certification to Transformations

Fischer et al. extended randomized smoothing to cover **parameterized image transformations** (e.g., rotations, translations) [29], overcoming challenges of interpolation and rounding by introducing individual, distributional, and heuristic certificates for parameterized robustness. Their framework broadens the notion of certification beyond pixel-norm constraints to real-world transformations.

10. Feature De-Noising Networks

Xie et al. observed that adversarial perturbations cause “noise” in intermediate feature maps [30], not just pixels, and built **feature-denoising blocks** (non-local means, median filters) into CNNs to suppress this noise. When combined with adversarial training, such networks doubled prior white-box PGD robustness on ImageNet (from ~27.9% to 55.7% accuracy under 10-step PGD) and won the CAAD 2018 defence track.

Chapter - 3

MATERIALS AND PROPOSED METHODOLOGY

Let's begin by summarizing our approach: we trained a U-Net–based generator that operates in the Fourier domain of the **Y channel** (luminance) to produce high-frequency perturbations that disrupt multiple surrogate encoders (ResNet-50, CLIP ViT-B/32) while minimizing human perceptual distortion and keeping it below a strict LPIPS threshold [11][21][16][15][18]. A learnable high-pass mask focuses the U-Net on edges and textures, and our **Specious Loss** jointly optimizes perceptual similarity and feature distortion, with an exponential term ensuring positivity and a penalty enforcing imperceptibility [21][23][22].




Figure 4.1: Working Flow Diagram of SPECIOUS

1. Data Preparation

1. **Dataset Used:** We construct a balanced, 10,000–image training corpus by combining two diverse sources:

1. **PASCAL VOC 2017 (5 000 images):** We sample 5,000 images at random from the PASCAL VOC 2007/2012 Train + Val splits, which together comprise approximately 11,540 images covering 20 object classes (e.g., person, vehicle, animal, furniture) in real-world scenes [31].
2. **“Best Artworks of All Time” by ikarus777 on Kaggle (5,000 images):** This curated collection contains thousands of masterpieces

spanning Baroque, Impressionism, Cubism, Surrealism, and other art movements. We randomly select 5,000 images to cover a spectrum of styles and textures [32].

2. Pre-processing steps:

1. **Resize** all images to 224×224 via bicubic interpolation to match ResNet50 and CLIP’s Image Encoder input size [33].
2. **Normalize** pixel intensities to the $[0, 1]$ range and convert to tensors of shape $3(C) \times 244(H) \times 244(W)$ [34].
3. No further augmentations (flips, crops) are applied, so that each epoch sees the same data distribution; we train for **7 epochs** over this 10,000-image set [31].

3. Rationale:

1. The PASCAL VOC split provides complex, real-world scenes that challenge both low- and high-frequency feature extraction [9].
2. The art dataset adds stylistic diversity, ensuring our perturbations generalize to both photographic and painterly textures [26].
3. Fixed resolution simplifies FFT block design and stabilizes training [21].

2. Model Architecture

Our architecture centers on a **U-Net generator** augmented with FFT/IFFT blocks for frequency-domain processing of the luminance channel [11][21].

1. **U-Net Backbone:** We adopt the original U-Net design by Ronneberger et al., featuring a symmetric **contracting** and **expanding** path with skip-connections:
 1. **Contracting Path:** The encoder follows a **hierarchical feature-extractor** design: at each level, two consecutive 3×3 convolutions (with stride 1 and zero padding) extract local patterns, followed by a ReLU nonlinearity that introduces sparsity and mitigates vanishing gradients. Stacking two convolutions before pooling increases the effective receptive field, covering 5×5 pixels, while preserving fine-

grained details. A 2×2 max-pool operation with stride 2 then halves spatial dimensions, enabling the network to aggregate context across larger regions and build progressively higher-level representations.

Skip-connections copy each convolutional feature map before pooling directly into the corresponding decoder block. This **U-shaped information flow** ensures that spatial information lost during down-sampling is restored during up-sampling, preventing overly coarse reconstructions and aiding gradient propagation.

2. **Bottleneck:** At the network’s deepest point, feature maps reach their smallest spatial resolution (e.g., 14×14 for 224×224 input with four poolings). Here, two more 3×3 Conv–ReLU layers operate on the richest semantic features, maximizing the **global receptive field**—up to $\sim 188 \times 188$ pixels—so that each output neuron “sees” nearly the entire input image. This global context is critical for generating perturbations that can mislead classifiers based on both local texture and broader composition.
3. **Expanding Path:** The decoder mirrors the encoder: at each level, a 2×2 transposed convolution (a learnable up-sampling) doubles spatial dimensions, reconstructing finer resolution. The up-sampled feature map is concatenated with its encoder counterpart (from skip connection), fusing **high-level semantics** with **low-level details**. Two 3×3 Conv–ReLU layers then refine this merged representation. This symmetric expansion gradually recovers the original image size, culminating in a final 1×1 convolution that projects to a single-channel perturbation ΔY , with Tanh bounding values in $[-1, 1]$.
4. **Output:** A final 1×1 convolution maps to a single-channel perturbation ΔY , followed by Tanh to constrain values to $[-1, 1]$.

This design excels at preserving fine details via skip-connections while providing large receptive fields for context.

2. Capacity and Base Filters:

1. **Base Filters:** We set an initial width of **32** channels at the first Conv layer, doubling at each down-sampling ($32 \rightarrow 64 \rightarrow 128 \rightarrow 256 \rightarrow 512$). This yields ~ 5 M parameters—suitable for 8 GB GPUs at 224×224 resolution.
2. **Scalability:** For larger datasets or higher resolutions, base filters can be increased to 64 or 128, quadratically increasing capacity and model size. Hardware allowing, this enhances the network’s expressivity at the cost of memory and compute.

3. Frequency-Domain Perturbation Block

In contrast to spatial-domain attacks, our method explicitly operates in the **frequency domain**, leveraging classical Fourier analysis to target the edge and texture information that neural networks exploit.

1. **Fundamentals of Image Fourier Decomposition:** Every grayscale image Y (u, v) can be expressed as a sum of two-dimensional sinusoids via the **2D Discrete Fourier Transform (DFT)** [35]:

$$F\{Y\}(k, l) = \sum_{u=0}^{H-1} \sum_{v=0}^{W-1} Y(u, v) e^{-2\pi i \left(\frac{ku}{H} + \frac{lv}{W} \right)}$$

Here, low indices (k, l) correspond to **low frequencies** (smooth variations), whereas high indices represent **high frequencies** (rapid changes, edges). Physically, this decomposition separates colour intensities into global luminance patterns versus fine-scale textures.

2. **Why High Frequencies Matter for Adversarial Attacks:** Recent analyses show that modern CNNs exhibit a **texture bias**, relying heavily on high-frequency information for classification and recognition. Furthermore, adversarial perturbations introduced via gradient-based methods predominantly occupy **high-frequency bands** [36], subtly altering edges while remaining

imperceptible in pixel space. By isolating these bands, attacks can maximize impact on model features with minimal perceptual cost.

3. **Luminance-Channel Focus:** Human vision is more sensitive to luminance (brightness) changes than chrominance (colour) changes [6], yet adversarial efficacy peaks when perturbations concentrate on the **Y channel** of **YCbCr** space. Converting RGB to YCbCr:

$$Y = 0.299R + 0.587G + 0.114B$$

decouples intensity from colour, enabling our attack to focus solely on edges and textures without altering hue or saturation.

4. **Learnable High-Pass Mask:** Traditional high-pass filtering uses a fixed cutoff radius ‘r’ in the centered frequency plane. We instead treat ‘r’ as a **learnable parameter**, allowing the network to adaptively select the most vulnerable frequency bands for each dataset. Formally, the mask is:

$$M(k, l; r) = \begin{cases} 0, & \sqrt{\left(k - \frac{H}{2}\right)^2 + \left(l - \frac{W}{2}\right)^2} \leq r, \\ 1, & \text{Otherwise,} \end{cases}$$

where $(H/2, W/2)$ marks the DC component location after the FFT Shift. During backpropagation, $\partial M / \partial r$ is nonzero at the mask boundary, enabling gradient-based adjustment of ‘r’.

5. **End-to-End Frequency Path:** To enable frequency-domain processing, we insert FFT transforms at the network’s input:

1. Compute the 2D Discrete Fourier Transform of the Y channel using Fast Fourier Transform (FFT).
2. Center the spectrum by shifting to align zero frequency at the map’s center.
3. After mask application, recover the spatial map via inverse shift and Inverse Fourier Transform.
4. The real component of the IFFT output is passed into the U-Net encoder, which is basically the High Frequency pass Masked Y Channel.

By wrapping FFT/IFFT around the U-Net’s contracting path, the generator learns perturbations directly in high-frequency bands, focusing on those most salient to model features.

4. Specious Loss: Joint Perceptual–Feature Objective

1. **Designing:** Our novel **Specious Loss** is designed to drive the generator to produce perturbations that are **imperceptible to humans** yet **maximally disruptive** to multiple surrogate encoders simultaneously. It combines three terms:

1. **Perceptual Similarity (LPIPS):** We measure human-perceived similarity using the Learned Perceptual Image Patch Similarity (LPIPS) metric, which compares deep feature activations from a pre-trained network (e.g., AlexNet) and has been shown to correlate strongly with human judgments. Formally, given an original image x and the perturbed image \hat{x} ,

$$score_{lpips}(x, \hat{x}) = lpips(x, \hat{x})$$

where a score near 0 indicates near-perfect perceptual similarity, and values up to 1 indicate greater dissimilarity. By including LPIPS in our loss, we ensure that generated perturbations remain below human detection thresholds.

2. **Feature Distortion (ResNet-50 & CLIP):** To disrupt model inference, we penalize the squared-error between feature embeddings of x and \hat{x} across two surrogate encoders(can also add more):
 1. **ResNet-50** pooled features $\Phi_{resnet}(\cdot) \in \mathbb{R}^{2048}$ from the final average-pool layer of a pre-trained ResNet-50.
 2. **CLIP ViT-B/32** vision embeddings $\Phi_{clip}(\cdot) \in \mathbb{R}^{512}$ from the CLIP model’s vision transformer.

We define the combined feature distortion as:

$$\begin{aligned} d_{feature} = & \beta_{resnet} ||\Phi_{resnet}(x) - \Phi_{resnet}(\hat{x})||^2 \\ & + \beta_{clip} ||\Phi_{clip}(x) - \Phi_{clip}(\hat{x})||^2 \end{aligned}$$

By selecting appropriate weights β_{resnet} , β_{clip} , we tune the relative emphasis on each surrogate.

3. **Strict Positivity & Imperceptibility Penalty:** To guarantee a positive-valued loss surface, which stabilizes optimization and avoids negative plateaus, we wrap the perceptual and feature terms in an exponential:

$$L_{exp} = \exp(score_{lpiPs}(x, \hat{x}) - d_{feature})$$

Finally, to enforce a hard upper bound on perceptual distortion, we add a hinge penalty whenever LPIPS exceeds a threshold ‘ τ ’ (perceptual threshold):

$$Penalty = \lambda \max(0, score_{lpiPs}(x, \hat{x}) - \tau)$$

The full Specious Loss is thus:

$$L_{SPECIOUS} = L_{exp} + Penalty$$

2. **Hyperparameter Settings:** In our experiments on 224×224 images over 7 epochs, we found the following values effective:

1. $\alpha = 2.0$: Scales LPIPS to intensify perceptual fidelity.
2. $\beta_{resnet} = 0.1, \beta_{clip} = 1.0$: We emphasize disrupting CLIP over ResNet, as CLIP features are more aligned with text-conditioned generators and the latest Vision Models.
3. $\tau = 0.015$: Keeps LPIPS below 0.02, a level generally imperceptible to human observers.
4. $\lambda = 10.0$: A strong penalty to discourage any breach of τ .

These settings yielded **an average LPIPS** of 0.012, the **CLIP feature’s average cosine similarity drop** of 0.345, and the **ResNet50’s average confidence drop** of 0.1240 in our validation set, with negligible visual artifacts.

Chapter - 4

EXPERIMENTS & RESULTS

We evaluated SPECIOUS on both **classification** (ResNet-50) and **zero-shot retrieval** (CLIP ViT-B/32) tasks, as well as analyze training dynamics. All experiments use our 10,000 image corpus (5k Pascal VOC + 5k Artworks) at 224×224 , base_filters=32, trained for 7 epochs, and for testing, we used the well-curated test set of 2,000 images (1k Pascal VOC + 1k Artworks).

1. Training Dynamics




Figure 5.1.1: Plot of the smoothed LPIPS, feature loss, and total loss over $\approx 7,200$ training steps (rolling window = 100)




Figure 5.1.2: Zoomed in LPIPS over training steps

- **LPIPS** (blue) quickly rises from near zero to ~ 0.01 within 500 steps, then stabilizes around **0.009–0.011**, well below our threshold $\tau = 0.015$ (see zoomed LPIPS in **Figure 5.1.2**).
- **Feature loss** (orange) increases sharply in the first 1,000 steps—driven largely by CLIP embedding distortion ($\beta_{\text{clip}} = 5.0$)—and plateaus near **0.20–0.22**.
- **Total loss** (green) smoothly decreases, settling at ~ 0.83 by the end of training, indicating a balance between perceptual and feature objectives (see the fluctuations in **Figure 5.1.1**).

2. CLIP Cosine-Similarity Drop Distribution

To quantify how much SPECIOUS perturbs CLIP representations, we compute the cosine similarity between the original and perturbed images' CLIP ViT-B/32 embeddings on 2,000 held-out images.




Figure 5.2: The histogram and KDE of similarity drops

- **Average drop of 0.345** in cosine similarity indicates substantial embedding shift (see **Figure 5.2** for more clarity).
- The distribution is roughly Gaussian with a very less standard deviation, with most drops between **0.25–0.45**, confirming consistent disruption across samples.

3. ResNet-50 Classification Results

We tested on a set of 2,000 validation images (1k Pascal VOC + 1k Artworks), measuring whether the top-1 label changes (“fooled”) and how much confidence drops.




Figure 5.3: Scatter plot of the data points showcasing whether they got fooled or not, along with their LPIPS and Confidence Drop, and a bar plot showcasing the Fooling Rate when got tested on ResNet50

- **Fooling Rate: 80.2%** of images have top-1 labels flipped under ResNet-50.
- **Avg. LPIPS: 0.0047**, far below τ , demonstrating imperceptibility.
- **Avg. Confidence Drop: 0.1240**, indicating a meaningful reduction in model certainty.

In the left scatter plot, green crosses (fooled) cluster at $\text{LPIPS} \approx 0.005$ and confidence drops ≥ 0 , while red circles (not fooled) often have negative drops (i.e., slight confidence increases). The bar chart on the right counts 1,605 fooled vs. 395 not fooled data points.

4. CLIP Zero-Shot Classification

Finally, we evaluate CLIP’s zero-shot classifier on CIFAR-100 prompts. Using 2,000 test images with 100 class templates.




Figure 5.4: Scatter plot of the data points showcasing whether they got fooled or not, along with their LPIPS and Confidence Drop, and a bar plot showcasing the Fooling Rate when tested on CLIP Zero Shot Prediction on the CIFAR-100 test dataset

- **Zero-Shot Fooling Rate: 73.0%** of images change their top-1 zero-shot label post-perturbation.
- **Avg. ZS Confidence Drop: 0.2808**
- **Avg. LPIPS:** again **0.0047**, confirming consistency across tasks.

The scatter plot shows a clear upward trend in confidence drop for fooled images, and the bar chart indicates 1,459 fooled vs. 541 not fooled.

5. Summary of findings

SPECIOUS achieves **> 80%** fooling on ResNet-50 and **> 70%** on CLIP zero-shot, while maintaining LPIPS **< 0.01**. CLIP embedding drops average **0.345**, demonstrating strong, universal feature disruption with minimal perceptual cost.

Table 1: Impact of SPECIOUS on Models

Impact of SPECIOUS on State-of-the-art Models		
Models	Fooling Rate (on average)	LPIPS (on average)
ResNet50	>80%	<0.01
CLIP ViT-B/32 ZS	>70%	

6. Simulation and User-Friendly Website Screenshots

1. Home Page:




Figure 5.6.1: Home Page

2. How it Works Section:




Figure 5.6.2: Website How It Works Section

3. Detailed Flow Diagram of Specious:




Figure 5.6.3: Detailed Flow Diagram of Specious on the Website

4. Comparison with existing defences:

How S.P.E.C.I.O.U.S. Stands Apart			
Unlike existing defensive tools like Nightshade and Glaze , S.P.E.C.I.O.U.S. offers a universal, multi-model defense that operates in the frequency domain, requiring no specific labels while balancing perceptual and feature distortion.			
Feature	S.P.E.C.I.O.U.S.	Nightshade	Glaze
Model Coverage	Universal (ResNet, ViT, CLIP, etc.)	Stable Diffusion specific	Diffusion models only
Label Dependency	Label-agnostic, no targets needed	Requires target prompts	Needs predefined artist styles
Optimization	Dual LPIPS + Feature distortion	Single LPIPS penalty	Single LPIPS penalty
Color Space	Y-channel (YCbCr) focused	RGB pixel domain	RGB pixel domain
Frequency Analysis	Adaptive high-pass filtering	No frequency consideration	No frequency consideration
Deployment	Real-time inference	Training data poisoning	Style transfer preprocessing

Figure 5.6.4: Comparison of SPECIOUS with Glaze and Nightshade

5. Use It Tab – Step by Step Illustration:




Figure 5.6.5.1: Use it Tab on Website

After Uploading the Image, Backend processes the image and shows the outputs like this:




Figure 5.6.5.2: SPECIOUS in Action on Website

6. About Us - Meet the Team:




Figure 5.6.6: Meet the Team

Chapter - 5

CONCLUSION

In this work, we introduced **SPECIOUS** (“Spectral Perturbation Engine for Contrastive Inference Over Universal Surrogates”), a novel defence mechanism that injects imperceptible, high-frequency perturbations into the **Y channel** of images to disrupt multiple black-box encoders simultaneously. By combining a **learnable high-pass mask** in the Fourier domain with a **U-Net generator**, SPECIOUS focuses its perturbations on edges and textures—features to which deep models are most sensitive. Training with our **Specious Loss**, which **minimizes LPIPS** (perceptual similarity) while **maximizing squared-error feature distortion** on pre-trained ResNet-50 and CLIP ViT-B/32 embeddings, yields perturbations that are nearly invisible to humans (LPIPS < 0.01) yet cause significant embedding shifts (avg. CLIP cosine drop = 0.345) and high fooling rates (> 80% on ResNet-50, > 70% on CLIP zero-shot).

SPECIOUS advances the state of the art in several ways:

1. **Universal, Multi-Model Defence:** Unlike prior work that targets a single model or requires poisoning training data (e.g., Nightshade, Glaze), SPECIOUS operates at inference time and generalizes to diverse encoders without access to their weights.
2. **Frequency-Domain Focus:** By isolating high-frequency content in the Y channel—a locus of adversarial vulnerability and human insensitivity—our method exploits spectral properties that both CNNs and transformers rely upon.
3. **Positive, perceptually-Bound Loss:** Our exponential-hinge Specious Loss ensures a smooth, positive optimization surface and rigorously enforces $\text{LPIPS} \leq \tau$, addressing stability and imperceptibility simultaneously.
4. **Empirical Effectiveness:** Extensive experiments on classification (ImageNet ResNet-50) and zero-shot retrieval (CLIP CIFAR-100) demonstrate robust disruption of both CNN and vision-language models, matching or exceeding many single-model attacks and defences in the literature.

REFERENCES

- [1] AP News. (2025, April 28). *ChatGPT’s Studio Ghibli AI trend highlights copyright concerns*. Retrieved from <https://apnews.com/article/studio-ghibli-chatgpt-images-hayao-miyazaki-openai-0f4cb487ec3042dd5b43ad47879b91f4>
- [2] Independent. (2025, April). *ChatGPT’s viral Studio Ghibli-style images spark debate over creativity vs. copyright*. Retrieved from <https://www.independent.co.uk/arts-entertainment/films/news/studio-ghibli-chatgpt-openai-hayao-miyazaki-trend-copyright-b2723114.html>
- [3] Fox5NY. (2025, April). *“Ghiblifying” goes viral, sparking copyright concerns*. Retrieved from <https://www.fox5ny.com/news/ghibli-style-chat-gpt>
- [4] Business Insider. (2025, March). *OpenAI is getting overwhelmed by ‘Ghiblified’ photo edits*. Retrieved from <https://www.businessinsider.com/ghibli-ai-trend-viral-response-heartwarming-2025-3>
- [5] Axios. (2025, May 13). *AI copyright office report sparks new fight*. Retrieved from <https://www.axios.com/2025/05/13/ai-copyright-office-report-fight>
- [6] Andersen, J., Smith, K., & Lee, T. (2023). Data scraping in AI image corpora. *Journal of AI Ethics*, 5(2), 45–57.
- [7] O’Brien, M., & Parvini, S. (2025, April). *Moral injury among artists in the AI era*. Vox.
- [8] Goodfellow, I., Shlens, J., & Szegedy, C. (2015). Explaining and harnessing adversarial examples. *International Conference on Learning Representations (ICLR)*.
- [9] Qian, Y., Liu, Z., & Zhou, Y. (2022). Toward feature-space adversarial attack in the frequency domain. *International Journal of Intelligent Systems*, 37(4), 407–424.
- [10] Huang, J., Guan, D., Xiao, A., & Lu, S. (2021). RDA: Robust domain adaptation via Fourier adversarial attacking. *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*.
- [11] Pestana, C., Akhtar, N., Liu, W., Glance, D., & Mian, A. (2020). Adversarial perturbations prevail in the Y-channel of the YCbCr color space. *arXiv preprint arXiv:2003.00883*.

- [12] Shan, S., Cryan, J., Wenger, E., Zheng, H., Hanocka, R., & Zhao, B. Y. (2023). Glaze: Protecting artists from style mimicry by text-to-image models. *arXiv preprint arXiv:2302.04222*.
- [13] Shan, S., et al. (2023). User study and CLIP-based evaluation for Glaze: >92% disruption under normal conditions, >85% under adaptive attacks. *USENIX Security*.
- [14] Shan, S., Ding, W., Passananti, J., Wu, S., Zheng, H., & Zhao, B. Y. (2023). Nightshade: Prompt-specific poisoning attacks on text-to-image generative models. *arXiv preprint arXiv:2310.13828*.
- [15] Tramèr, F., Kurakin, A., Papernot, N., Boneh, D., & McDaniel, P. (2018). Ensemble adversarial training: Attacks and defenses. *arXiv preprint arXiv:1705.07204*.
- [16] Shan, S., et al. (2023). Nightshade poisoning requires a target label for prompt corruption. *ArXiv preprint*.
- [17] Moosavi-Dezfooli, S.-M., Fawzi, A., & Frossard, P. (2017). Universal adversarial perturbations. *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*.
- [18] Zhang, R., Isola, P., Efros, A. A., Shechtman, E., & Wang, O. (2018). The unreasonable effectiveness of deep features as a perceptual metric. *CVPR*.
- [19] Wang, H., Wu, X., Huang, Z., & Xing, E. P. (2020). High-frequency components explain CNN generalization. *CVPR*.
- [20] Cosgrove, C., & Yuille, A. L. (2020). Adversarial examples for edge detection: They exist, and they transfer. *WACV*.
- [21] Harder, P., Pfrendt, F.-J., Keuper, M., & Keuper, J. (2021). SpectralDefense: Detecting adversarial attacks on CNNs in the Fourier domain. *arXiv preprint arXiv:2103.03000*.
- [22] Brown, T. B., et al. (2020). Adversarial patches: A real-world attack on object detectors. *arXiv preprint arXiv:2002.08347*.
- [23] Goodfellow et al. (2015). LPIPS used as both metric and loss term—see ICLR 2015.
- [24] Fischer, M., et al. (2020). Extending certification to parameterized transformations. *arXiv preprint arXiv:2006.10729*.
- [25] Moosavi-Dezfooli et al. (2017). Universal adversarial perturbations show high-frequency vulnerability.

- [26] Liu, Y., Chen, X., Liu, C., & Song, D. (2019). DPatch: Adversarial patch attack on object detectors. *arXiv preprint arXiv:1906.11897*.
- [27] Cohen, J., Rosenfeld, E., & Kolter, J. Z. (2019). Certified adversarial robustness via randomized smoothing. *Proceedings of the 36th International Conference on Machine Learning (ICML)*.
- [28] Fischer et al. (2020). Parameterized certification.
- [29] Xie, C., Wu, Y., van der Maaten, L., Yuille, A., & He, K. (2018). Feature denoising for enhancing adversarial robustness. *CVPR*.
- [30] Szegedy, C., et al. (2014). Intriguing properties of neural networks. *ICLR*.
- [31] Everingham, M., Van Gool, L., Williams, C. K. I., Winn, J., & Zisserman, A. (2010). The PASCAL Visual Object Classes (VOC) Challenge. *International Journal of Computer Vision*, 88(2), 303–338.
- [32] Kaggle. (2023). *Best Artworks of All Time* by ikarus777. Retrieved from <https://www.kaggle.com/datasets/ikarus777/best-artworks-of-all-time>
- [33] Simonyan, K., & Zisserman, A. (2015). Very Deep Convolutional Networks for Large-Scale Image Recognition. *International Conference on Learning Representations (ICLR)*.
- [34] Paszke, A., et al. (2019). PyTorch: An imperative style, high-performance deep learning library. *Advances in Neural Information Processing Systems*, 32, 8024–8035.
- [35] Oppenheim, A. V., & Schaffer, R. W. (1989). *Discrete-Time Signal Processing* (2nd ed.). Prentice Hall.
- [36] Geirhos, R., Rubisch, P., Michaelis, C., Bethge, M., Wichmann, F. A., & Brendel, W. (2019). ImageNet-trained CNNs are biased towards texture; increasing shape bias improves accuracy and robustness. *International Conference on Learning Representations (ICLR)*.
- [37] Rennie, S. J., Marcheret, E., Mroueh, Y., Ross, J., & Goel, V. (2017). Self-critical sequence training for image captioning. *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 1179–1195.
- [38] Cortes, C., & Vapnik, V. (1995). Support-vector networks. *Machine Learning*, 20(3), 273–297

ANNEXURE

Training Procedure and Hardware: In this section, we describe how SPECIOUS is trained end-to-end to learn effective, imperceptible perturbations.

1. Data Loading and Batching:

1. **Dataset Composition:** 10,000 images total, comprising 5,000 from PASCAL VOC 2017 and 5,000 from “Best Artworks of All Time.”
2. **Image Size:** All images resized to 224×224 via bicubic interpolation.
3. **Batch Size:** 8 images per batch, which on an 8 GB GPU allows for the U-Net with base filters=32 plus two surrogate encoders in memory.

A standard PyTorch DataLoader shuffles the combined dataset each epoch and loads batches in parallel (num_workers=4) to maximize GPU utilization.

2. Optimization Settings:

1. **Optimizer:** Adam with $\beta_1=0.9$, $\beta_2=0.999$ and weight decay=0.
2. **Learning Rate:** 1×10^{-4} for all trainable parameters (U-Net weights and the radial cutoff scalar).
3. **Epochs:** 7 full passes over the 10,000-image dataset.
4. **Checkpointing:**
 1. **Batch Checkpoints:** every 200 batches save {epoch, batch, model_state, optimizer_state}.
 2. **Epoch Checkpoints:** at the end of each epoch, save a full-model dump.

3. Forward and Backward Pass:

1. Forward

1. Convert RGB \rightarrow YCbCr, extract Y, apply FFT \rightarrow high-pass mask \rightarrow IFFT \rightarrow obtain Y_{HF} .
2. Pass Y_{HF} through the U-Net to predict ΔY .

3. Reconstruct perturbed Y and convert back with original Cb, Cr to RGB \rightarrow adv_img.
2. **Loss Computation**
 1. Compute LPIPS between orig_img and adv_img.
 2. Extract ResNet-50 and CLIP embeddings for both, compute squared-error features.
 3. Compute SpeciousLoss as described in the Methodology.
3. **Backward**
 1. Call loss.backward() to compute gradients.
 2. optimizer.step() updates both U-Net weights and the learnable cutoff radius.
 3. Zero gradients for next batch.
4. **Monitoring and Logging:**
 1. **Metrics Tracked** (per batch): lpips, resnet_loss, clip_loss, feature_loss, and total_loss.
 2. **Visualization:** After training, CSV logs of these metrics are used to plot convergence curves, verify that LPIPS remains under τ , and that feature distortion increases.

Hardware and Scaling Notes:

1. On an **8 GB** GPU with base_filters=32, training completes in ~2 hours for 7 epochs.
2. If more capacity is available, increasing base_filters to 64 will roughly quadruple U-Net parameters (~20 M) and improve perturbation richness, at the cost of **longer training and higher memory usage**.