Accepted Manuscript

Survey of Green Vehicle Routing Problem: Past and future trends

Canhong Lin, K.L. Choy, G.T.S. Ho, S.H. Chung, H.Y. Lam

Survey of Green Vehicle Routing Problem: Past and future trends

Canhong Lin, K.L. Choy, G.T.S. Ho, S.H. Chung, H.Y. Lam
Department of Industrial and Systems Engineering, The Hong Kong Polytechnic
University, Hong Kong

Abstract

Green Logistics has emerged as the new agenda item in supply chain management. The traditional objective of distribution management has been upgraded to minimizing system-wide costs related to economic and environmental issues. Reflecting the environmental sensitivity of vehicle routing problems (*VRP*), an extensive literature review of *Green Vehicle Routing Problems (GVRP)* is presented. We provide a classification of *GVRP* that categorizes *GVRP* into *Green-VRP*, *Pollution Routing Problem*, *VRP in Reverse Logistics*, and suggest research gaps between its state and richer models describing the complexity in real-world cases. The purpose is to review the most up-to-date state-of-the-art of *GVRP*, discuss how the traditional *VRP* variants can interact with *GVRP* and offer an insight into the next wave of research into *GVRP*. It is hoped that OR/MS researchers together with logistics practitioners can be inspired and cooperate to contribute to a sustainable industry.

Keywords: vehicle routing, green vehicle routing, reverse logistics, green logistics, literature review.

1. Introduction

Green Logistics has recently received increasing and close attention from governments and business organizations. The importance of Green Logistics is motivated by the fact that current production and distribution logistics strategies are not sustainable in the long term. Thus environmental, ecological and social effects are taken into consideration when designing logistics policies, in addition to the conventional economic costs. The environmentally sensitive logistic policy itself requires changing the transportation scheme and shifting it onto a sustainable distribution network with fewer negative impacts on the environment and the ecology, owing to the undeniable fact that transportation accounts for the major part of logistics. There is a wide variety of problems concerning Green Transportation, such as the promotion of alternative fuels, next-generation electronic vehicles, green intelligent transportation systems, and other eco-friendly infrastructures. A better utilization of vehicles and a cost effective vehicle routing solution would more directly achieve sustainable transportation schemes. In this context, designing a green distribution network by means of vehicle routing models is the major task. Bloemhof-Ruwaard et al. (1995) and Daniel et al. (1997) specified the close interaction and the contributions of Operations Research methods to environmental

1

management and addressed some environmental issues related to routing, such as the reverse logistics in product recovery management and the routing of waste collection.

In the traditional *Vehicle Routing Problem (VRP)*, the focus is concentrated on the economic impact of vehicle routes on the organization that carries out the distribution service. Consideration of wider objectives and more operational constraints that are concerned with sustainable logistics issues pose new vehicle routing models and new application scenarios, which naturally lead to more complex combinatorial optimization problems. Green Logistics deals with the activities of measuring the environmental effects of different distribution strategies, reducing the energy consumption, recycling refuse and managing waste disposal (Sbihi and Eglese 2007a). Based on these dominating activities, we attempt to identify the *VRP* variants regarding these sustainable transportation issues in the literature from an operations research perspective and denote them as *Green Vehicle Routing Problems (GVRP)*. *GVRP* are characterized by the objective of harmonizing the environmental and economic costs by implementing effective routes to meet the environmental concerns and financial indexes. As they have just arisen in the literature in recent years, there is a continuing need to enrich related studies either through theoretical contributions or by real applications. Sbihi and Eglese (2007a, 2007b) presented some research gaps that link the *VRP* with Green Logistics issues, such as employing the *Time-dependent VRP* as an approach to deal with the minimization of emissions during traveling. Salimifard et al. (2012) reported several recent articles published in 2010 and 2011 with direct consideration of environmental impact in the objective functions and stated that this topic is still at the beginning of being studied and is rather attractive. Despite their attempt of surveying relevant literature, they confined *VRP* with green transportation consideration to only those problems with explicit objectives of environmental costs. It seems that there is still room for investigation to explore *GVRP* in the area of energy consumption, emission control, and reverse logistics.

The contribution of this paper is to give an exhaustive literature review and clear classification of *GVRP*. More importantly, we have highlighted the lack of the existing studies and point out the future research directions for the *GVRP*. For academic purposes, a landscape of literature on *GVRP* is shown to shed light on this topic and help researchers find potential areas of further and deeper study. In particular, the classification of the traditional *VRP* variants is also summarized to inspire researchers to find out how these traditional variants can be related to the *GVRP*. For practical purposes, it is hoped that these idealized models can help governments, non-profit organizations, and companies to evaluate the possible economic and environmental significance of real-world transportation problems and to take action at different levels to contribute to Green Logistics.

The remaining part of this paper is organized as follows. Section 2 concerns the survey methodology of this paper. A review of the traditional *VRP* variants, with a brief

introduction and sub-categories for each variant, is presented in Section 3 to show the evolution of *VRP* literature. Section 4 gives an overview of the most important *VRP* variant, *VRP with Time Windows*. A brief introduction to the algorithms and main benchmark test instances for *VRP* is presented in Section 5. In Section 6, we review the existing research on *GVRP* in depth, with a classification categorizing *GVRP* into *Green-VRP*, *Pollution Routing Problem*, and *VRP in Reverse Logistics*. The future research opportunities for each *GVRP* category are also suggested. Section 7 contains a summary of important trends and perspectives of the future development of the research into *GVRP*. Finally, a conclusion is drawn in Section 8.

2. Survey methodology

2.1. Source of the literature

The literature surveyed in this paper was majorly selected from three sources: (1) a wide set of academic databases such as *Science Direct*, *Springer Link*, *EBSCO*, etc., accessed from the university library by using keywords such as vehicle routing, time windows, green, reverse logistics, etc.; (2) bibliographies of survey papers and book chapters on *VRP*; (3) additional articles that are addressed in the initial articles in (1) and (2). The literature we searched is normally scattered at different times ranging from 1959 to 2012. As we intend to survey the studies on *GVRP*, we mainly confined our search to articles published from 2006 to 2012. The searching process was conducted in two dimensions: horizontal and vertical. In the horizontal dimension, attention was paid to the evolution of *VRP* on the timeline, especially when finding *VRPs* of sustainability issues (i.e. *GVRP*). In the vertical dimension, different classes of *VRP* are employed to distinguish each article. The majority of the literature falls into journal articles in terms of operations research, management science, and transportation, in such journals as the *European Journal of Operational Research, Computers and Operations Research, Transportation Science, Transportation Research (Part A, B, C, D, E), Networks, Operations Research, Journal of the Operational Research Society*, etc. A small number of proceeding papers, working papers, technical reports and dissertations are also included in this overview as they were also taken as good references for some most up-to-date research directions or for the foundation of further study. In this study, about 280 papers were reviewed, which are shown in Fig. 1 and Table 1.

The fourth column of Table 1 summarizes the *VRP* variants that were studied in each year in our review work. It can be found that the research efforts before 2006 focused on the traditional *VRP*. Few studies on Green *VRP* had been conducted during this time period. After 2006, Green *VRP* covering energy consumption (*G-VRP*), pollution emissions (*PRP*), as well as recycling and reverse logistics (*VRPRL*) started to draw researchers' close attention and became a hot topic in the past several years. To explore the past and new trends of *VRP* in order to better understand its evolution, our review

work was performed from categorizing the traditional *VRP* to summarizing the Green *VRP*, which formed the fundamental philosophy of our review work.

Fig. 1 The distribution of papers by year

Table 1

The papers reviewed in this study

Year	Number of papers	The list of the papers	The studied VRP variants
1959	1	Dantzig and Ramser;	CVRP
1964	1	Clark and Wright;	CVRP
1966	1	Cooke and Halsey;	TDVRP
1967	1	Wilson and Weissberg;	PDP
1969	1	Tillman;	SVRP, MDVRP
1973	1	Watson-Gandy and Dohm;	LRP
1974	1	Beltrami and Bodin;	PVRP
1976	1	Speidel;	DVRP
1977	1	Russell;	VRPTW
1978	2	Cook and Russell; Golden and Stewart;	SVRP
1979	1	Christofides et al.;	
1980	1	Psaraftis;	DVRP
1981	2	Fisher and Jaikumar; Schrage;	VRPTW, CVRP
1983	2	Bell et al.; Bodin et al.;	IRP, TSP
1984	2	Golden et al.; Tsiligirides;	FSMVRP, Generalized VRP

1985	3	Christophides; Dror et al.; Jézéquel;	MCVRP, SVRP
1986	2	Dror and Levy; Nag;	IRP, Site-dependent VRP
1987	4	Dror and Ball; Jaillet; Sculli et al.; Solomon;	IRP, SVRP, VRPTW
1988	3	Jaillet and Odoni; Powell; Psaraftis;	SVRP, DVRP
1989	2	Balas; Dror and Trudeau;	Generalized VRP, SDVRP
1990	1	Laporte and Martello;	Generalized VRP
1992	5	Bertsimas; Laporte; Laporte et al.; Malandraki and Daskin; Min et al.;	SVRP, MDVRP, TDVRP
1993	4	Dror et al.; Lambert et al.; Semet and Tailard; Taillard;	SVRP, Site-dependent VRP
1994	2	Fisher; Rochat and Semet;	Site-dependent VRP
1995	8	Bloemhof-Ruwaard et al.; Cheng et al.; Frizzell and Giffin; Gelinas et al.; Gendreau et al.; Madsen et al.; Psaraftis; Russell;	FVRP, SDVRP, SVRP, PDP, DVRP, VRPTW
1996	7	Bertsimas and Simchi-Levi; Chao et al.; Gendreau et al.; Renaud et al.; Salhi and Fraser; Speranza; Teodorović and Pavković;	Generalized VRP, SVRP, MDVRP, FSMVRP, IRP, FVRP, DVRP
1997	3	Daniel et al.; Fleischmann et al.; Salhi and Sari;	MDVRP
1998	6	Cater and Ellram; Gendreau and Potvin; Golden et al.; Hadjiconstantinou and Baldacci; Mansini and Speranza; Min et al.;	PVRP, MCVRP, LRP, DVRP
1999	4	Fagerholt; Gendreau et al.; Liu and Shen; Salhi and Nagy;	FSMVRP, **G-VRP**, MDVRP, DVRP
2000	5	Ghiani and Improta; Irnich; Laporte et al.; Pronello and André; Sariklis and Powell;	Generalized VRP, FSMVRP, OVRP
2001	4	Cordeau et al; Dethloff; Ioannou et al.; Li and Lim;	**VRPRL**, VRPTW
2002	7	Angelelli and Speranza; Bertazzi and Speranza; Cordeau et al.; Giosa et al.; Toth and Vigo; Wassan and Osman; Wu et al.;	MDVRP, IRP, FSMVRP
2003	4	Blakeley et al.; Chajakis and Guignard; Ghiani et al.; Iori et al.;	PVRP, MCVRP, VRPLC, DVRP
2004	10	Beullens et al.; Brandão; Campbell and Savelsbergh; Dekker et al.; Ho and Haugland; Moura and Oliveira; Polacek et al.; Sambracos et al.; Wasner and Zäpfel; Yang et al.;	SDVRP, VRPLC, MDVRP, OVRP, IRP, **G-VRP**, DVRP
2005	7	Chao and Liou; Feillet et al.; Kallehauge et al.; Li; Nagy and Salhi; Bräysy and Gendreau (a); Bräysy and Gendreau (b)	Site-dependent VRP, Generalized VRP, MDVRP, VRPTW
2006	18	Archetti et al.; Bélanger et al.; Blanc et al.; Bukchin and Sarin; Chen et al.; Chen and Xu; Dell'Amico et al. (a); Dell'Amico et al. (b); Francis and Smilowitz; Francis et al.; Gendreau et al.(a); Gendreau et al.(b); Jang et	**VRPRL**, SDVRP, PVRP, MCVRP, FSMVRP, VRPLC, MEVRP, FVRP, TDVRP, DVRP

		al.; Lee et al.; Min et al.; Privé et al.; Schultmann et al.; Zheng and Liu;	
2007	24	Alegre et al.; Alshamrani et al.; Archetti et al.; Cordeau et al.; Carrabs et al.; Crevier et al.; Doerner et al.; Dondo and Cerdá; Ichoua et al.; Iori et al.; Kara et al.; Laporte; Li et al. (a); Li et al. (b); Marinakis and Migdalas; McKinnon; Nagy and Salhi; Palmer; Repoussis et al.; Ropke et al.; Sbihi and Eglese (a); Sbihi and Eglese (b); Zhang and Tang; Zhao et al.;	**G-VRP**, **PRP**, **VRPRL**, Site-dependent VRP, IRP, MDVRP, VRPLC, FSMVRP, OVRP, LRP, DVRP, PDP, VRPTW
2008	25	Alonso et al.; Apaydin and Gonullu; Baldacci et al. (a); Baldacci et al. (b); Bräysy et al.; Cheung et al.; El Fallahi et al.; Gendreau et al. (a); Gendreau et al.(b); Golden et al.; Gribkovskaia et al.; Kallehauge; Krikke et al.; Krumke et al.; Malapert et al.; Marasš; Moura; Nanthavanij et al.; Oppen and Løkketangen; Paraskevopoulos et al.; Parragh et al. (a); Parragh et al. (b); Srivastava; Taveares et al.; Zhao et al.;	**G-VRP**, **VRPRL**, Site-dependent VRP, FSMVRP, MCVRP, VRPLC, VRPTW, IRP, PDP, IRP, DVRP
2009	25	Baldacci and Mingozzi; Baldacci et al.; Bräysy et al.; Crainic et al.; Erbao and Mingyong; Figliozzi; Fuellerer et al.; Khebbache et al.; Kim et al.; Laporte; Li et al.(a); Li et al.(b); Liu et al.; Pirkwieser and Gunther; Potvin; Prescott-Gagnon et al.; Prins; Qureshi et al.; Soler et al.; Tang et al.; Tarantilis et al; Wang and Lu; Wen et al.; Yu et al.; Zachariadis et al.;	**VRPRL**, FSMVRP, MEVRP, FVRP, VRPLC, DVRP, PVRP, MEVRP, VRPTW, OVRP, TDVRP
2010	23	Andersson et al.; Angelelli et al.; Azi et al.; Baldacci et al. (a); Baldacci et al. (b); Bauer et al.; Çatay; Christensen and Rousøe; Erbao and Mingyong; Fagerholt et al.; Figliozzi; Fuellerer et al.; Gajpal and Abad; Li et al.; Liao et al.; Maden et al.; Mendoza et al.; Muyldermans and Pang; Polimeni and Vitetta; Qureshi et al.; Rei et al.; Repoussis and Tarantilis; Kuo;	**G-VRP**, **VRPRL**, **PRP**, IRP, Generalized VRP, Site-dependent VRP, VRPLC, FVRP, SVRP, MEVRP, MCVRP, FSMVRP, DVRP, VRPTW, PDP
2011	26	Aras et al.; Archetti et al.; Baldacci et al.; Bektaş and Laporte; Belenguer et al.; Bortfeldt; Brandão; Cappanera et al.; Derigs et al.; Duhamel et al.; Faulin et al.; Leung et al.; Mar-Ortiz et al.; Mu and Eglese; Mu et al.; Pang; Perboli et al.; Ramos and Oliveira; Salani and Vacca; Tasan and Gen; Tricoire et al.; Ubeta et al.; Wen et al.; Xu et al.; Yu and Yang; Zachariadis et al.;	**VRPRL**, **PRP**, SDVRP, LRP, MDVRP, VRPLC, Site-dependent VRP, MCVRP, DVRP, MEVRP, FVRP, FSMVRP, VRPTW, PVRP
2012	23	Baldacci et al.; Coelho et al.; Cordeau and	**G-VRP**, **PRP**, IRP, OVRP,

| | | Maischbergr; Demir et al.; ErdoÄŸan and Miller-Hooks; Figliozzi; Hemmelmayr et al.; Hong; Jin et al.; Kok et al.; Kritzinger et al.; Kuo and Wang; Li et al.; Marinakis; Mingozzi et al.; Moccia et al.; Pillac et al.; Qureshi et al.; Ribeiro and Laporte; Salimifard et al.; Schneider et al.; Vidal et al.; Xiao et al.; | MDVRP, TDVRP, MEVRP, DVRP, VRPTW, PVRP |
| 2013 | 10 | Baldacci et al.; Baños et al.; Berbotto et al.; Dondo and Cerdá; Lecluyse et al.; Nguyen et al.; Polimeni and Vitetta; Salhi et al.; Stenger et al.; Vidal et al.; | MEVRP, VRPTW, SDVRP, TDVRP, MDVRP |

Note. CVRP, Capacitated VRP; TDVRP, Time-dependent VRP; PDP, Pickup and Delivery Problem; MDVRP, Multi-depot VRP; SVRP, Stochastic VRP; LRP, Location Routing Problem; PVRP, Periodic VRP; DVRP, Dynamic VRP; VRPTW, VRP with Time Windows; IRP, Inventory Routing Problem; FSMVRP, Fleet Size and Mix Vehicle Routing Problem; MCVRP, Multi-compartment VRP; SDVRP, Split-delivery VRP; FVRP, Fuzzy VRP; OVRP, Open VRP; VRPLC, VRP with Loading Constraints; MEVRP, Multi-echelon VRP; G-VRP, Green-VRP; PRP, Pollution Routing Problem; VRPRL, VRP in Reverse Logistics.

2.2. *The philosophy of the review work*

As shown in Fig. 2, our review work includes three steps. Step 1 covers a review of the traditional *VRP* variants in the literature. It aims at providing a landscape of how different classes of problems evolved and varied in diverse application domains and operational constraints. In Step 2, the state-of-the-art of *GVRP* is summarized and criticized. Based on the traditional *VRP* variants we defined in Step 1, we discuss how the *GVRP* interacts with the traditional *VRP* variants to formulate more practical and complex models in Step 3 so as to suggest the next wave of research on *GVRP*.

2.3. *Classification schemes*

A comprehensive and feasible taxonomy of *VRP* is no doubt a tool to get the hang of the nature of the problem of *VRP* and to identify the future directions. There exist various classification schemes in the literature to categorize *VRP*. Using different algorithms (e.g. exact algorithm, heuristics, metaheuristics) and distinct characteristics of elements of the problem (e.g. time window structure, vehicle heterogeneity, quality of information) are the most common schemes in previous efforts by other researchers to produce a *VRP* taxonomy. Since we herein attempt to focus on the nature of the problem and application of *VRP*, our classification scheme is based on the problem characteristics and their application scenarios rather than the algorithms. One advantage of this scheme is that it enables in-depth classification of the problem, that is, sub-categories of each class can be revealed, which provides a much wider and clearer horizon to the scientific progress of this problem. Using this scheme, we identified the *GVRP* and its sub-categories.

Note. CVRP, Capacitated VRP; TDVRP, Time-dependent VRP; PDP, Pickup and Delivery Problem; MDVRP, Multi-depot VRP; SVRP, Stochastic VRP; LRP, Location Routing Problem; PVRP, Periodic VRP; DVRP, Dynamic VRP; VRPTW, VRP with Time Windows; IRP, Inventory Routing Problem; FSMVRP, Fleet Size and Mix Vehicle Routing Problem; MCVRP, Multi-compartment VRP; SDVRP, Split-delivery VRP; FVRP, Fuzzy VRP; OVRP, Open VRP; VRPLC, VRP with Loading Constraints; MEVRP, Multi-echelon VRP; G-VRP, Green-VRP; PRP, Pollution Routing Problem; VRPRL, VRP in Reverse Logistics.

Fig. 2 The philosophy of the review work

3. A review of traditional VRP variants

At the outset, we present the traditional *VRP* variants that have been summarized and fruitfully studied in the literature, in order to demonstrate the evolution of *VRP*. One should note that although the variants are distinguishable they often stand closely related. An extensive survey of every variant would require very long paragraphs; we summarily introduce the definition, application, classification and related remarkable articles of each variant, on the basis of their first arrival on the timeline (see Fig. 5).

Since the seminal article of *VRP* by Dantzig and Ramser (1959), *VRP* has enjoyed close and extensive research attention for nearly 50 years. A variety of survey papers were published at different times to report the state-of-the-art up to that date (the latest surveys are by Toth and Vigo, 2002; Li, 2005; Cordeau et al., 2007; Laporte, 2007; Marinakis and Migdalas, 2007; Golden et al., 2008; Krumke et al., 2008; Potvin, 2009; Laporte, 2009). With its intrinsic relevance to the real-life applications and its growing complexity subject to operational constraints, concerns with *VRP* are still increasing and efforts are continually being made to develop more practical mathematical models and higher performance algorithms. Various classes of *VRP* have been identified and each class has received diverse scientific study. Some new *VRP* variants, such as *Multi-*

echelon VRP, *VRP with Loading Constraints*, etc., have recently appeared. They incorporate new operational considerations into the problem, some of which even alter the structure of the nature of the problem.

3.1. Capacitated VRP (since 1959)

The vehicle routing problem was first introduced by Dantzig and Ramser (1959). They describe a real-world problem concerning dispatching gasoline delivery trucks between a bulk terminal and large numbers of service stations. When the number of the service stations becomes larger, options of routes increase dramatically, which thus makes the work of testing and finding an improved route to yield an optimal solution, a great burden. In order to replace this inapplicable procedure, they proposed an algorithm approach based on integer linear formulation to obtain a near optimal solution. In their truck dispatching problem, the capacity of each truck is explicitly considered (*Capacitated VRP*, *CVRP*). In the light of the properties of cost in the matrix of distance, *CVRP* can be further partitioned into *Symmetrical CVRP* (*SCVRP*) and *Asymmetrical CVRP* (*ACVRP*) (Toth and Vigo, 2002). An integer programming model of *CVRP* is presented in the appendix.

3.2. Time-dependent VRP (since 1966)

Traditional *VRP* assumes Euclidean distance as a constant. However, this contradicts the real conditions where the vehicles are moving on a real road network. The cost estimation is therefore unconvincing because the cost variability in relation to time is largely neglected (Polimeni and Vitetta, 2013). The distinctive characteristic of *Time-dependent VRP* (*TDVRP*) is that the travel time between any pair of points (customers and depots) depends on the distance between the points or on the time of day (e.g. rush hours, weather conditions). The feature of fluctuating traveling duration enables *VRP* to account for the actual conditions such as urban congestion, where the traveling speed is not constant due to variation in traffic density. As a consequence, *TDVRP* is a relevant and useful model to reveal the recurring traffic congestion problems (Lecluyse et al., 2013) and to explore how to avoid them (Kok et al., 2012).

The very early work related to time-dependent traveling duration includes Cooke and Halsey (1966), which extended the classical shortest path problem with static internodal time to consider varying internodal time. Nevertheless, multiple vehicles were not considered in this study. Malandraki and Daskin (1992) gave the mixed integer linear programming mathematical model of *TDVRP* and its special case, *TDTSP*. The variation of travel time was formulated as a step function within the period of a day. The travel time step function was then discussed in terms of how it influences the final solution. Two nearest neighbor heuristics were presented for solving *TDVRP* and *TDTSP* respectively. The extension of *TDVRP*, *TDVRP with Time Windows* (*TDVRPTW*), has gained great attention in the *TDVRP* literature. Based on the classical benchmark

instances given by Solomon (1987), Figliozzi (2012) introduced the benchmark problems in *TDVRPTW* for evaluating and comparing the solution quality and computational time of the algorithms in this field. An Iterative Route Construction and Improvement algorithm (IRCI) was also developed to universally tackle either constant or time-dependent speed problems with hard or soft time windows. Other research of *TDVRPTW* includes Chen et al. (2006), Soler et al. (2009), Kritzinger et al. (2012).

TDVRP describes more real network optimization problems. More importantly, it makes it possible to use *VRP* to study the green issues in transportation, such as fuel consumption and emission, as the measurement of fuel consumption and emission is closely associated with the time-varying real-time speed in urban areas. We categorize these studies into the new variants of *VRP*: *Green-VRP* and the *Pollution Routing Problem*, which are summarized in Section 6.

3.3. *Pickup and Delivery Problem (since 1967)*

The *Pickup and Delivery Problem* (*PDP*) dates back to a dial-a-ride problem examined by Wilson and Weissberg (1967). In the research field of *VRP*, there are masses of studies in terms of *VRP with backhauls*, *VRP with pickup and delivery*, *VRP with simultaneously pickup and delivery*, *dial-a-ride problem*, etc. Some of them share a very similar structure of the nature of the problem but have slight differences that are difficult to distinguish and thus often cause confusion. In fact, all of these classes should be regarded as sub-categories of *PDP*. To distinguish different sub-categories of *PDP*, Parragh et al. (2008a; 2008b) provided a literature synthesis for *PDP* and gave a very reasonable classification of *PDP*. According to their summary, the problem classes are shown in Fig. 3.

Fig. 3 Classification of the Pickup and Delivery Problem

3.4. Multi-depot VRP (since 1969)

Multi-depot VRP (*MDVRP*), which was firstly studied by Tillman (1969), contains more than one depot and each customer is visited by a vehicle that is assigned to one of these depots (i.e. every vehicle route must start and end at the same depot). *MDVRP* naturally originates from a variety of physical distribution problems such as the delivery of meals, chemical products, soft drinks, machines, industrial gases, packaged food, etc. and previous studies have shown the substantial economic savings in these cases achieved by the use of optimization techniques (Renaud et al., 1996). Various extensions of *MDVRP* are discussed in the literature, including *MDVRP with Time Windows* (Giosa et al., 2002; Polacek et al., 2004; Dondo and Cerdá, 2007), *MDVRP with Backhauls* (Min et al., 1992; Salhi and Nagy, 1999), *MDVRP with Pickup and Delivery* (Nagy and Salhi, 2005), *MDVRP with Mix Fleet* (Salhi and Sari, 1997; Salhi et al., 2013), *Multi-depot Location Routing Problem* (Wu et al., 2002; Wasner and Zäpfel, 2004), *MDVRP with Loading Cost* (Kuo and Wang, 2012), *MDVRP with Inter-depots* (Angelelli and Speranza, 2002; Crevier et al., 2007) where the intermediate depots act as either warehouses for replenishment in a distribution system, or as recycling facilities for vehicles to unload in a collection system.

3.5. Stochastic VRP (since 1969)

Stochastic VRP (*SVRP*) arises whenever some elements like customer demand, travel times, and even the set of customers in the routing problem are random (Gendreau et al., 1996). Probability theory is the main tool to represent the uncertainty in mathematical models in this context. Gendreau et al. (1996) provided an extensive survey on *SVRP*. Based on the nature of different stochastic components, *SVRP* can be categorized into different variants: *VRP with Stochastic Demand* (Tillman, 1969; Golden and Stewart, 1978; Jaillet and Odoni, 1988; Dror et al., 1993; Rei et al. 2010; Mendoza et al., 2010), *VRP with Stochastic Customers* (Jézéquel, 1985; Jaillet, 1987; Bertsimas, 1992), *VRP with Stochastic Customers and Demands* (Jézéquel, 1985; Gendreau et al., 1995;), *VRP with Stochastic Travel Time* (Lambert et al., 1993), *VRP with Stochastic Demand and Travel Time* (Cook and Russell, 1978), *VRP with Stochastic Travel Time and Service Time* (Laporte et al., 1992; Li et al., 2010).

3.6. Location Routing Problem (since 1973)

It is observed that the separated design of depot location and vehicle routing often yields a suboptimal solution and generates extra cost, which motivates the advent of a *Location Routing Problem* (*LRP*) (Watson-Gandy and Dohrn, 1973). In *LRP*, the joint decisions consist of opening a single or a set of depots and designing a number of routes for each opened depot, with the objectives of minimizing the overall cost comprising the fixed costs of opening the depots and the costs of the routes. The application of *LRP* can

be found in waste collection, postbox location, parcel delivery, mobile communications access networks, and grocery distribution (Baldacci et al., 2011). *LRP* is the generalization of *CVRP* (with single depot) or the *MDVRP* without addressing the location aspect (Belenguer et al., 2011). Min et al. (1998) provided a classification of *LRP* from different perspectives including deterministic or stochastic demand, capacitated or incapacitated depots, capacitated or incapacitated vehicles, etc. Another more recent review of *LRP* is referred to Nagy and Salhi (2007).

3.7. *Periodic VRP (since 1974)*

Beltrami and Bodin (1974) developed algorithms to solving routing problems for municipal waste collection with time constraints, in which locations (customers) required different numbers of visits and different day combinations for visits in a week. Given this visiting schedule requested by customers, the classical *VRP* is extended not only to determine a shortest route but also to assign the tours to certain days of the week. The objective is to find a feasible routing solution such that the total cost of the routes over the time horizon (week) is minimized. This problem is donated as the *Periodic Vehicle Routing Problem* (*PVRP*). The significance of studying *PVRP* is motivated by many real-world applications, such as waste collection, industrial gas distribution, grocery industry, picking up raw materials from suppliers (Alegre et al., 2007), and even the allocation of workforce (Blakeley et al., 2003; Jang et al., 2006). In the literature, extensions of *PVRP* includes *Multi-depot PVRP* (Hadjiconstantinou and Baldacci, 1998), *PVRP with Service Choice* (Francis and Smilowitz, 2006; Francis et al., 2006), *PVRP with Time Windows* (Bélanger et al., 2006; Pirkwieser and Gunther, 2009). *Site-dependent Multi-trip PVRP* (Alonso et al., 2008).

3.8. *Dynamic VRP (since 1976)*

The traditional *VRP* deals with a deterministic operational environment where all information is known (offline) before routes are constructed and remains static during the execution of the routing plan. However, the circumstances in the real-world is not always deterministic and static because uncertainty, such as breakdown of vehicles, traffic control, and continually arriving customer requests, frequently takes place. Reflecting such uncertainty in a dynamic operational environment, *Dynamic VRP* (*DVRP*), which dates back to Speidel (1976) and Psaraftis (1980), is featured by the on-going fashion in which the information such as vehicle locations, customer orders are revealed over time. The typically studied *DVRP* concerns a dynamic operation in which the customer requests are released during the planning period (online requests) and should be assigned in real time to appropriate vehicles. It is motivated by a variety of real-life applications such as dynamic fleet management, vendor-managed distribution systems, courier service, repair or rescue service, dial-a-ride service, emergency service, as well as taxi cab service (Ghiani et al., 2003). So far, various classes of *DVRP* with different aspects of

operational constraints have been investigated and reported in the literature, which fall into the main categories: *DVRP with Time Windows* (Madsen et al., 1995; Gendreau et al., 1999; Chen and Xu, 2006; Hong, 2012) and *DVRP with Pickup and Delivery and Time Windows* (Yang et al., 2004; Gendreau et al., 2006a; Cheung et al., 2008). The overview of *DVRP* with regards to its application and algorithm is presented by Powell (1988), Psaraftis (1988), Psaraftis (1995), Bertsimas and Simchi-Levi (1996), Gendreau and Potvin (1998), Ghiani et al. (2003), Ichoua et al. (2007), Angelelli et al. (2010), and very recently by Pillac et al. (2012).

Disrupted VRP is a variant of *DVRP* with real-time rerouting and rescheduling (Li et al., 2009a; Mu et al., 2011). Disruption to the original vehicle routing plans is sometimes caused by unforeseen events, such as traffic jams, breakdowns, or the postponed departure from depots or customer points (Mu and Eglese, 2011). As the original plans may not remain optimal due to the disruption, it needs timely adjustment to minimize the inevitable and negative effects. *Disrupted VRP* concerns disruption management during the execution stage of a dispatching plan.. With the time window constraints, the problem aims at not only the least weighted sum of total distance, but also the minimization of deviations from the predefined time windows (Zhang and Tang, 2007).

3.9. *Inventory Routing Problem (since 1984)*

The *Inventory Routing Problem* (*IRP*) was first considered by Bell et al. (1983) to deal with the distribution of air products in terms of integrated inventory management and vehicle dispatching. A distinguishing feature of *IRP* is to guarantee that there are no stockouts at each customer. Several early studies (Dror and Ball, 1987; Speranza, 1996; Bertazzi and Speranza, 2002) addressed *IRP* of only a single vehicle or a single customer, which cannot entirely describe the complexity in real-world problems and do not match the nature of *VRP*. Archetti et al. (2007) proposed the first exact algorithm for *IRP* in the context of Vender-managed Inventory (VMI). They used a branch-and-cut algorithm to successfully tackle the problem with up to 50 customers when the time horizon was equal to 3. Coelho et al. (2012) very recently considered more practical cases in VMI in which the goods can be transshipped from supplier to customer or from customer to customer. They employed the large neighborhood search heuristic combined with a network flow algorithm to simultaneously decide the optimal inventory and routing solution. However, both of these 2 studies only handled a single vehicle case in the VMI system. Zhao et al. (2007) and Zhao et al. (2008) took into account multi-vehicle cases in VMI and employed different approaches to tackle the inventory/routing problem. Another interesting study by Campbell and Savelsbergh (2004) was motivated by an industrial gases company which implements VMI with their customers. Considering a long planning horizon and customer consumption rates in the vehicle routing model, the study determined the timing, sizing, and routing of the deliveries so that the average distribution cost during the planning period is minimized and no stockouts occur. By

leveraging a two-phase algorithm that is composed of an integer program in phase 1 and an insertion heuristic in phase 2, large-scale real-life instances (up to 100 customers) were tested.

3.10. Fleet Size and Mix Vehicle Routing Problem (since 1984)

In reality, the common problem that bothers the logistics decision makers is: How many and what size of vehicles are necessary to accommodate the demand at the least expense (Golden et al., 1984)? The *Fleet Size and Mix VRP* (*FSMVRP*) (Liu et al., 2009; Baldacci et al., 2009) is to solve this question to determine the most economic combination of vehicles in the fleet when considering the trade-off between the fixed vehicle costs and the variable costs proportional to the distance travelled. A more complex case in the fleet size problem is to consider heterogeneous vehicles with different capacities and traveling cost. *FSMVRP with Time Windows* (Liu and Shen (1999), Wassan and Osman, 2002; Dell'Amico et al., 2006a; Li et al., 2007a; Paraskevopoulos et al., 2008; Bräysy et al., 2008; Bräysy et al., 2009; Repoussis and Tarantilis, 2010) has been well studied as an extension of *FSMVRP*. *FSMVRP with Multi-depot* (Salhi and Fraser, 1996; Salhi and Sari, 1997; Irnich, 2000) is another natural extension of *FSMVRP* to determine which customers are to be associated with different depots in addition to the optimum fleet composition and routes. Dondo and Cerdá (2007) considered a combined multi-depot and time window version in *FSMVRP*.

3.11. Generalized VRP (since 1984)

In *Generalized VRP* (Ghiani and Improta, 2000), the customers are partitioned into clusters and vehicles are obligated to visit only one customer in each cluster (i.e. each cluster should be visited exactly once). The prototype of *Generalized VRP* dates back to the orienteering problem introduced by Tsiligirides (1984) and extended as a team orienteering problem by Chao et al. (1996). They are characterized by the case that visiting customers is associated with different scores (or profits) and due to the time limitation, it is impossible to traverse all of the customers. What subset of the customers is to be visited, how to assign these selected customers to vehicles, and how to dispatch the vehicles so as to achieve maximum total profit become the objectives and thus make a multi-level optimization problem concerning routing. Very similar problems and studies in the literature include prize collecting traveling salesman problems (Balas, 1989), the selective traveling salesman problem (Laporte and Martello, 1990), the traveling salesman problem with profits (Feillet et al., 2005), *VRP* with selective backhauls (Privé, 2006; Gribkovskaia et al., 2008). Baldacci et al. (2010a) provided an exhaustive survey on *Generalized VRP* and its applications.

3.12. Multi-Compartment VRP (since 1985)

VRP with multiple compartments (*MCVRP*) (Christophides, 1985) differs from the traditional *VRP* in that goods in *MCVRP* are inhomogeneous and non-intermixable in the sense that they have to be delivered in multiple compartments on the same vehicle. In *MCVRP*, each customer requests one or more types of products; each product required by a customer must be delivered by only one vehicle (i.e. the demand of a customer for one given product cannot be split); however, multiple visits are allowed to deliver different requested products so as to fulfill the demand set of products. *MCVRP* naturally arises in several industries, such as delivery of food to convenience stores and fuel distribution. Chajakis and Guignard (2003) proposed optimization models with the consideration of two possible cargo space layouts. Bukchin and Sarin (2006) attempted to determine a loading policy which minimizes the number of required shipments per unit of time, by the comparison between two loading policies: the continuous and static loading policy and the discrete and dynamic loading policy. El Fallahi et al. (2008) developed a genetic algorithm hybridized with a local search procedure, namely, the Memetic Algorithm, and a tabu search for solving *MCVRP*. Mendoza et al. (2010) introduced uncertainty of customer demands to *MCVRP* and developed the optimization model as *MCVRP with Stochastic Demand*s. Other applications in co-collecting different types of waste, collecting milk of different types and qualities can be found in the work of Muyldermans and Pang (2010), Oppen and Løkketangen (2008). An overview of *MCVRP*, including a benchmark suite of 200 instances and a discussion of heuristics for *MCVRP*, is provided by Derigs et al. (2011).

3.13. Site-dependent VRP (since 1986)

In *Site-dependent VRP* (Nag, 1986), there are compatible independencies between customers (sites) and vehicle types. Each customer is allowed to be visited by only one set of vehicle types rather than by all types. One customer has to select only one type of this set of allowable vehicle types. A comprehensive definition and illustration can be found in the work of Chao and Liou (2005). Many real-life application problems, such as refuse collection (Sculli et al., 1987), grocery delivery (Semet and Taillard, 1993), pet food and flour distribution (Rochat and Semet, 1994), can be formulated as *Site-dependent VRP* models. A survey of the studies of *Site-dependent VRP* before 2005 is provided in Chao and Liou (2005). *Site-dependent VRP* was mentioned as a variant of the general heterogeneous *VRP* in Baldacci et al. (2008a, 2010b). The *Skill VRP*, which originates from a real-world problem concerning dispatching technicians with different skill levels to conduct the after-sales service, is a special case of *Site-dependent VRP* (Cappanera et al., 2011). Alonso et al. (2008) presented an explicit and direct research on *Site-dependent VRP*.

3.14. Split-delivery VRP (since 1989)

In the majority of the aforementioned *VRP*, each customer is assumed to be visited by a vehicle exactly only once. However, this confinement is not always realistic because sometimes the customer demand exceeds the vehicle capacity. In this case, this constraint should be relaxed to allow each customer to be serviced by more than one vehicle. *Split-delivery VRP* (*SDVRP*), the extension of *VRP* that deals with this real-life operation, was first introduced by Dror and Trudeau (1989) who demonstrated that remarkable cost savings with regard to the number of vehicles utilized and the total traveling distance can be achieved by split deliveries. Archetti et al. (2006) showed that these savings can reach up to 50%. The research in this field mainly focuses on algorithms for tackling this complex problem. *SDVRP with Time Windows* (Frizzell and Giffin, 1995; Ho and Haugland, 2004; Salani & Vacca, 2011; Archetti et al., 2011) is the main extension of *SDVRP* in the literature.

3.15. Fuzzy VRP (since 1995)

In real-life application, time windows and customer demand are frequently set by ambiguous linguistic statements like "14:00 to 16:00 is highly preferred", "approximately between 200 and 300 items are needed". In this context, fuzzy logic is used in *VRP* to formulate the uncertain, subjective, ambiguous, and vague elements. *VRP with Fuzzy Time Windows* (*VRPFTW*) directly investigates how service time preference influences the logistics service level. Cheng et al. (1995) replaced fixed time window with a fuzzy due-time, the fuzzy membership function of which is correlative to the degree of customer satisfaction of service time. They used genetic algorithm to find the maximum average satisfaction as well as other traditional objectives of *VRP*. To cope with the fuzziness of time windows, Tang et al. (2009) considered linear and concave fuzzy membership functions for the fuzzy soft time window and formulated a multi-objective model for the *VRPFTW* so as to minimize the routing cost and to maximize the overall customer satisfaction level. A two-stage algorithm is proposed to decompose *VRPFTW* into a traditional vehicle routing problem with time window and a service improvement problem and then solve these two sub-problems sequentially. Xu et al. (2011) proposed a global-local-neighbor particle swarm optimization with exchangeable particles to tackle a very similar problem. Other versions of *FVRP* include *VRP with Fuzzy Demand* (Teodorović and Pavković, 1996; Erbao and Mingyong, 2009; Erbao and Mingyong, 2010) and *VRP with Fuzzy Travel Time* (Zheng and Liu, 2006).

3.16. Open VRP (since 2000)

In *Open VRP* (*OVRP*), which was firstly introduced by Sariklis and Powell (2000), each route is Hamiltonian path rather than a Hamiltonian cycle as vehicles are not required to return to the depot after servicing all the affiliated customers. It is naturally

encountered in the newspaper or mail delivery service. In particular, this problem is faced by the companies that outsource the deliveries to the third party logistics provider (3PL) as the external vehicles are not obligated to return to the depot. Brandão (2004) proposed a tabu search for *OVRP*. The initial solution was derived by using a nearest neighbor heuristic and a pseudo lower bound based approach, while the solution was improved by using the nearest neighbor method and the unstringing and stringing procedure. The extensive computational experiments showed that the proposed tabu search was very competitive in its ability to find very good solutions within a very short computation time, remarkably outperforming Sariklis and Powell's (2000) algorithm. Li et al. (2007b) provided a survey on the algorithms for solving the *OVRP*. Repoussis et al. (2007) addressed *OVRP with Time Windows* and conducted a survey on the related studies in real-world cases, such as the delivery of school meals, school bus routing, the plans of passing through tunnels of trains, etc. Very recently, Li et al. (2012) studied a heterogeneous fixed fleet *OVRP*, in which vehicles are heterogeneous and of a limited number and with different costs per unit distance. This problem more closely describes the real situation of the transportation in outsourcing carriers. A multi-start adaptive memory programming meta-heuristic combined with modified tabu search was proposed to solve the problem.

3.17. *VRP with Loading Constraints (since 2003)*

VRP with Loading Constraints (*VRPLC*) jointly determines the optimal routes and packing patterns (Zachariadis et al., 2011). Ladany and Mehrez (1984) presented a traveling salesman problem with pickup and delivery and Last-In-First-Out (LIFO) loading constraint. The most frequently studied problem in the literature is the *Two-dimensional Capacitated VRP* (*2L-CVRP*) (Iori et al., 2003, 2007; Gendreau et al., 2008a; Fuellerer et al., 2009; Zachariadis et al., 2009; Khebbache et al., 2009; Duhamel et al., 2011; Leung et al., 2011). In *2L-CVRP*, customer demand consists of rectangular two-dimensional weighted items. The problem calls for the minimization of total cost of routes, with a feasible orthogonal packing pattern of the items onto the two-dimensional loading surface of each vehicle, without exceeding the vehicle weight capacity. Other extensions of *VRPLC* include *Two-dimensional Pickup and Delivery Routing Problem* (Malapert et al., 2008), *Three-dimensional Capacitated VRP* (Gendreau et al., 2006b; Tarantilis et al., 2009; Fuellerer et al., 2010; Christensen and Rousøe, 2010; Bortfeldt, 2011;), *Vehicle Routing with Time Windows and Loading Problem* (Moura and Oliveira, 2004; Moura, 2008), *Multi-Pile Routing Problem* (Doerner et al., 2007; Tricoire et al., 2011;), *The Pallet-Packing Vehicle Routing Problem* (Zachariadis et al., 2011), *Pickup and Delivery TSP with LIFO Loading* (Carrabs et al., 2007).

3.18. Multi-echelon VRP (since 2009)

Multi-echelon VRP (*MEVRP*) is to study the movement of flows in a multi-echelon distribution strategy, where the delivery of freight from the origin to the customers is compulsorily delivered through an intermediate depot (Perboli et al., 2011). It aims at minimizing the total transportation cost of the vehicles involved at all levels. Multi-echelon transportation systems naturally originate from many different real-world industries, such as newspaper and press distribution, e-commerce and home delivery service, and express postal service. The most common instance is *Two-echelon VRP (2EVRP)* with the first level linking the depot to the intermediate depots (named satellites) and the second level connecting the satellites to the customers, which is also known as cross-docking (Lee et al., 2006; Wen et al., 2009; Liao et al., 2010). Crainic et al. (2009) investigated *Two-echelon Capacitated VRP* (*2E-CVRP*) in a two-tier distribution facility structure in the context of city logistics planning. Multiple trips, multiple depots, multiple products, heterogeneous vehicles, soft time windows (at customers) and hard time windows (at satellites) were considered. In Perboli et al. (2011), *2E-CVRP* was explicitly examined by a flow-based mathematical model and two math-based heuristics were derived from the model. An instance with the size of 50 customers and 4 satellites was tested.

4. VRP with Time Windows (since 1977)

Heuristic approaches for *VRP* didn't consider service time intervals or due dates as constraints of the model until Russell (1977) presented an effective heuristic for the M-tour traveling salesman problem. He accommodated the time window restrictions in his model and extended Lin and Kernighan's heuristic to propose a MTOUR heuristic that could give better-quality solutions. Before Russell's study, *VRP* with time windows had dealt mainly with case studies (Solomon, 1987). Generally, there are two types of time windows that are extensively studied in the literature:

1) Hard Time Windows, where a vehicle must arrive and be ready to serve the customer before or right before the specified time interval. Late arrival is not allowed. If the vehicle arrives earlier than the time window, it has to wait.
2) Soft Time Window, where the violation of the time window constraint is acceptable at the price of some penalty (Kallehauge, 2008).

The hard time window constraint seems to naturally describe the real-world situation, but sometimes no feasible or executable solution can be obtained if all time window constraints need to be satisfied. Relaxing this strict restriction might result in a better solution with respect to total distance or to the total number of vehicles. Furthermore, a tiny deviation from the customer-specified time window is acceptable in real life (Tang et al., 2009). The adoption of soft time window constraints deals with this practical

violation and it receives close attention in many practical scenarios. Relaxing hard time windows might lead to lower cost without significantly hurting customer satisfaction (Figliozzi, 2010). In particular, Semi Soft Time Windows (Qureshi et al., 2009; Qureshi et al., 2010), as a variant of Soft Time Windows, refers to the scenario where early arrival is allowed at no cost while late arrival incurs a penalty cost.

VRP with Time Windows (VRPTW) is the most common variant in the literature. The introduction of time windows has led to the growth of research interest in various real scenarios concerning routing. Recent surveys of *VRPTW* have been conducted by Bräysy and Gendreau (2005a), Bräysy and Gendreau (2005b), Kallehauge et al. (2005), Kallehauge (2008). A typical mathematical model of *VRPTW* is presented in the appendix. Recent studies of *VRPTW* tend to not merely focus on the minimization of transportation cost. A variety of new research angles have been pursued to keep pace with the new service strategies (e.g. make-to-order) of the growing industry. Figliozzi (2009) reflected how time window constraints and customer demand levels influence the average distance of *VRP*, which is an important indicator associated with the decisions in network design, facility location and fleet sizing, especially for delivering high value-high time sensitive products. Instead of using traditional optimization heuristics, the study developed a probabilistic modeling approach to approximate the average length of the routes traveled. Polimeni et al. (2010) integrated a demand model (commodity flow) and a routing model (vehicle flow) with time windows so as to present a macro-architectural view of goods movement in the context of city logistics. Door-to-door delivery, which is a growing industry of city logistics, often suffers from the great pressure from both the customer-defined service time intervals and the unexpected disruption of traffic conditions in urban places. To cope with the dynamic re-routing problems caused, Qureshi et al. (2012) proposed a *Dynamic Vehicle Routing Problem with Soft Time Windows* model to help freight carriers avoid extra cost as well as lateness of goods delivery.

5. Algorithms and main benchmark test instances

VRP is a NP-hard combinatorial optimization problem. The optimal or near-optimal solution is generally obtained by using *exact algorithms* or *approximate algorithms*. *Exact algorithms* can only tackle problems of a relatively small scale. According to Laporte (1992), *exact algorithms* for *VRP* are classified into three broad categories: (1) direct tree search methods; (2) dynamic programming; (3) integer linear programming. The related papers in these three categories were also discussed to present the rationale of the algorithms.

Approximate algorithms are able to find very near-optimal solutions for large-scale problems within a very satisfactory computation time, and thus commonly used in practice. A variety of *approximate algorithms*, including *classical heuristics* and *metaheuristics* since 1980s, are proposed in the literature to efficiently solve different variants of *VRP*. Based on the survey by Laporte et al. (2000) and Cordeau et al. (2002), there are mainly several categories of *classical heuristics*: (1) Saving algorithms; (2)

Sequential improvement algorithms; (3) Sweep algorithms; (4) Petal algorithms; (5) Fisher and Jaikumar two-phase algorithms; (6) Improvement heuristics. Compared with the *classical heuristics*, *metaheuristics* carry out a more thorough search of the solution space, allowing inferior and sometimes infeasible moves, in addition to re-combining solutions to create new ones. As a result, *metaheuristics* are capable of consistently producing high quality solutions, in spite of its greater computation time than early *heuristics*. (Cordeau et al., 2002). *Metaheuristics* can be categorized into two main types:

1) *Local search*. Local search based methods keep exploring the solution space by iteratively moving from the current solution to another promising solution in its neighborhood. The main local search based metaheuristics for *VRP* include: (1) tabu search (TS); (2) simulated annealing (SA); (3) Greedy Randomized Adaptive Search Procedure (GRASP); (4) Variable Neighborhood Search (VNS); (5) Large Neighborhood Search (LNS)
2) *Population search*. Population search based methods maintain a pool of good parent solutions, by continually selecting parent solutions to produce promising offspring so as to update the pool. Typical examples are: (1) Genetic Algorithms (GA); (2) Ant Colony Optimization (ACO).

Fig. 4 summarizes the relation among the above-mentioned algorithms. Table 2 lists the papers related to the exact and approximate algorithms for *VRP* in the recent decade, with a focus on *metaheuristics*. For the research work of metaheuristics, Gendreau et al. (2008b) have listed the bibliography of metaheuristics for solving *VRP* and its extensions. Only the papers since 2008 are cited in this table.

Fig. 4 The algorithms for *VRP* and their relation

Table 2

The algorithms for *VRP* and recent related papers

Algorithms	Papers
Exact algorithms	Baldacci et al., 2008b; Baldacci and Mingozzi, 2009; Qureshi et al., 2009; Azi et al., 2010; Baldacci et al., 2012; Mingozzi et al., 2012; Baldacci et al., 2013
Classical heuristics	Li et al., 2007a; Gajpal and Abad, 2010; Figliozzi, 2010; Pang, 2011; Dondo and Cerdá, 2013
TS	Brandão, 2011; Cordeau and Maischberger, 2012; Jin et al., 2012; Moccia et al., 2012; Nguyen et al., 2013; Berbotto et al., 2013
SA	Kuo, 2010; Baños et al., 2013
GRASP	Prins, 2009; Marinakis, 2012
VNS	Paraskevopoulos et al., 2008; Wen et al., 2011; Kuo and Wang, 2012; Stenger et al., 2013; Salhi et al., 2013
LNS	Prescott-Gagnon et al., 2009; Hemmelmayr et al., 2012; Ribeiro and Laporte, 2012
GA	Liu et al., 2009; Wang and Lu, 2009; Vidal et al., 2012; Vidal et al., 2013
ACO	Yu et al., 2009; Fuellerer et al., 2009; Li et al., 2009b; Yu and Yang, 2011

In the literature, benchmark test instances for various *VRP* variants have been created. These instances provide a data set for a variety of solution methods that solve a certain *VRP* variant and conduct extensive computational experiments. In this way, the performance of different algorithms and the solution results can be evaluated and compared. Table 3 presents the main benchmark instances for *VRP*.

Table 3

The main benchmark instances for *VRP*

VRP variants	Benchmark test instances
Capacitated VRP	Christofides et al., 1979
	Taillard, 1993
	Fisher, 1994
	Golden et al., 1998
VRP with Time Windows	Solomon, 1987
	Russell, 1995
Pickup and Delivery Problem with Time Windows	Li and Lim, 2001
	Ropke et al., 2007
Multi-depot VRP with Time Windows	Cordeau et al., 2001
Periodic VRP with Time Windows	Cordeau et al., 2001
VRP with Backhauls and Time Windows	Gelinas et al., 1995

Though the *VRP* variants discussed above have covered a large number of subjects, few studies of them investigated the environmental and ecological impact that is caused in the real-world vehicle routing problems. The recent advent of a limited number of papers on *VRP* that concerns the optimization of green impact bridges the gap, which is discussed in the next section.

6. Green Vehicle Routing Problem (since 2006)

Fig. 5 provides a landscape of the state-of-the-art of *VRP*, which renews the existing taxonomy of *VRP* by adding the *GVRP* variants. The *GVRP*, which was mainly investigated since 2006, are reviewed and criticized in this section. Based on the classification scheme, we define three major categories of *GVRP*, including *Green-VRP*, *Pollution Routing Problem*, and *VRP in Reverse Logistics*. We also discuss their future interesting research areas for those who are dedicated to research into *GVRP*.

6.1. *Green-VRP*

The research on *Green-VRP* (*G-VRP*) deals with the optimization of energy consumption of transportation. The review begins with illustrating (i) transportation and energy consumption, followed by the survey on (ii) the current studies on *G-VRP* during 2007-2012. (iii) The future research directions in *G-VRP* are then suggested.

6.1.1. *Transportation and energy consumption*

As the overuse of energy and air pollution have imposed a threat on our ecological environment, governments, non-profit organizations, as well as private companies have started to take the initiative to participate in this green campaign. The US government has made some energy policies for reducing fossil fuel consumption and for supporting alternative fuel, though barriers to implementing these sustainable solutions still exist. Private companies have started to make some changes at the operational level in their business to prevent too much damage to the environment. Logistics activities, such as product development, production process, transportation, waste management, can have a great impact on the environment and thus call for more environmentally-friendly practices.

Transportation, which is one of the most important parts of logistics, is the irreplaceable fundamental infrastructure for economic growth. However, it is also one of the hugest petroleum consumers and accounts for a large part of the overall pollutants (Salimifard et al., 2012). Researchers and entrepreneurs tend to pay close attention to the role that transportation will play in achieving positive environmental effects. The new green transportation solution may clash with the designated economic objectives. Exploring the relationship between environmental effect and transportation through route planning will be able to provide practical and valuable suggestions regarding this green campaign.

Note. CVRP, Capacitated VRP; TDVRP, Time-dependent VRP; PDP, Pickup and Delivery Problem; MDVRP, Multi-depot VRP; SVRP, Stochastic VRP; LRP, Location Routing Problem; PVRP, Periodic VRP; DVRP, Dynamic VRP; VRPTW, VRP with Time Windows; IRP, Inventory Routing Problem; FSMVRP, Fleet Size and Mix Vehicle Routing Problem; MCVRP, Multi-compartment VRP; SDVRP, Split-delivery VRP; FVRP, Fuzzy VRP; OVRP, Open VRP; VRPLC, VRP with Loading Constraints; MEVRP, Multi-echelon VRP; G-VRP, Green-VRP; PRP, Pollution Routing Problem; VRPRL, VRP in Reverse Logistics.

Fig. 5 A landscape of the state-of-the-art of *VRP*

6.1.2. The current studies on G-VRP during 2007-2012

G-VRP is the vehicle routing problems concerning energy consumption. Fuel cost accounts for a significant part of the total cost of the petroleum-based transportation (Xiao et al., 2012). Reducing the fuel consumption and improving the transportation efficiency at an operational level would be the most straightforward course of action. It is also desirable that a decrease petroleum-based fuel consumption can correspondingly reduce the greenhouse gas emission significantly (ErdoÄŸan and Miller-Hooks, 2012; Xiao et al., 2012). Therefore, fuel consumption is an important index in the *G-VRP* (Kuo, 2010). In order to include the fuel consumption in the routing model, the formulation of computing fuel consumption with respect to the condition of a traveling vehicle is essential. According to the report by the US Department of Energy (2008), travel speed, the weight of the load as well as the transportation distance are the factors that affect the fuel consumption. Some studies about the fuel consumption model in terms of transportation exist in the literature, which provide relevant reference to the research on *G-VRP*.

The existing research on *VRP* with the aim of minimizing the fuel consumption seems rare. Kara et al. (2007) considered a more realistic cost of transportation that is affected by the load of the vehicle as well as the distance of the arc travelled. They define *Energy Minimizing Vehicle Routing Problem* (*EMVRP*) as the *CVRP* with a new objective of cost, in which the cost function is a product of the total load (including the weight of the empty vehicle) and the length of the arc. However, they used work to represent the energy so as to simplify the relationship between minimizing the consumed energy and the variables of the vehicle conditions. Details of the formulation of fuel consumption are not provided. A formulation of fuel consumption is provided in Xiao et al. (2012). They proposed a Fuel Consumption Rate (FCR) considered CVRP (*FCVRP*), which extends *CVRP* with the objective of minimizing fuel consumption. In their paper, both the distance traveled and the load are considered as the factors which determine the fuel costs. FCR is taken as a load dependent function, where FCR is linearly associated with the vehicle's load. Besides the transportation distance and the loading weight that are addressed in the above two papers, Kuo (2010) added the transportation speed to the fuel consumption calculation model in time-dependent *VRPs*. Other *VRP*-related studies that aim at minimizing total fuel consumption include Fagerholt (1999), Sambracos et al. (2004), Apaydin & Gonullu (2008), Maraš (2008), Nanthavanij et al. (2008), and Taveares et al. (2008).

Another problem of *G-VRP* deals with the recharging or refueling of the vehicles, particularly, the alternative-fuel powered vehicle (AFV). Government agencies, nonprofit organizations, municipalities and some private companies have started to convert their fleets of trucks to AFVs so as either to satisfy the energy policies or environmental regulations, or to voluntarily reduce the environmental impact (ErdoÄŸan and Miller-Hooks, 2012). The above papers concerning fuel consumption merely come up with the

formulation for computing the fuel consumption, assuming that the fuel is adequate for coving the whole tour. They do not consider the distance limitation that depends on fuel tank capacity. In this problem, recharging stations in the tour to overcome the capacity limitation of fuel tank are considered. To the best of our knowledge, there are only 2 research papers in the literature that address refueling or recharging problems. ErdoÄŸan and Miller-Hooks (2012) is the first to consider the possibility of recharging or refueling a vehicle on the route in *VRP*. They denoted this problem as *Green-VRP* (*G-VRP*), in which AFV are allowed to refuel on the tour to extend the distance it can travel. With the objective of minimizing the total distance, the model seeks to eliminate the risk of running out of fuel. They consider service time of each customer and the maximum duration restriction was posed on each route. Schneider et al. (2012) extended *G-VRP* with time windows.

6.1.3. *Future research directions in G-VRP*

As shown in Table 4, the existing *G-VRP* studies only cover vehicle capacity and time window constraints. There exist extensive *VRP* variants that can be combined with the *G-VRP* model and make it comprehensive and closer and more applicable to real-world problems. Heterogeneous vehicles are still not explored in the existing literature. As the fuel consumption model is closely related to the condition of the vehicle, the flexibility offered by using different types of vehicles may result in more reduction of fuel consumption. But it is still not yet known to what extent a mixed fleet might contribute to reducing the energy consumption. In the recharging problems, some restrictions in the real world have not yet been accommodated in the routing model. For example, the availability and the fuel capacity of the recharging stations will cause some change to the optimal routes. The stochastic service time of the recharging stations is also worth attention as it influences the time traveled and the arrival time at each point. Techniques like queuing models seem suitable for tackling the service time problem in this context.

Table 4

Recent studies of *G-VRP* during 2007-2012

VRP variants	Papers (Total: 5)
Basic VRP or TSP	ErdoÄŸan and Miller-Hooks, 2012
Capacitated VRP	Kara et al., 2007; Kuo, 2010; Xiao et al., 2012
VRP with Time Windows	Schneider et al., 2012

6.2. *The Pollution Routing Problem*

The road transport sector accounts for a large percentage of Greenhouse Gas (GHG) and in particular CO_2 emissions. The pollution from the emissions has direct or indirect hazardous effects on humans and on the whole ecosystem. The growing concerns about

such negative impacts of transportation on the environment require re-planning of the road transport network and flow by explicitly considering GHG emission (Bektaş and Laporte, 2011). Putting the *VRP*, at the center of transportation planning, opens opportunities for reducing emissions by including broader objectives that reflect environmental cost. The *Pollution Routing Problem* (*PRP*) aims at choosing a vehicle dispatching scheme with less pollution, in particular, reduction of carbon emissions. The review of *PRP* firstly investigates (i) the current studies on *PRP* during 2007-2012, and then gives (ii) the future research directions in *PRP*.

6.2.1. The current studies on PRP during 2007-2012

Reducing CO_2 emissions by extending the traditional *VRP* objectives of economic costs to consider relevant social and environmental impact is achievable (McKinnon, 2007; Palmer, 2007; Sbihi and Eglese, 2007a; Maden et al., 2010; Bektaş and Laporte, 2011). However, related studies on *VRP* from the perspective of minimizing emissions are seldom found. The traditional *VRP* objective of reducing the total distance will in itself contribute to a decrease of fuel consumption and environmental pollutant emissions. But this relationship needs to be directly measured using more accurate formulations. Pronello and André (2000) suggested that reliable models to measure the pollution generated by vehicle routes need to take into account more factors, such as the traveling time when the engine is cold. Only with these models can the environmental benefits in *VRP* be quantified. Sbihi and Eglese (2007a) considered a *TDVRP* in the context of traffic congestion. Since less pollution is produced when the vehicles are at best speeds, directing them away from congestion tends to be more environmental-friendly, even though it leads to longer traveling distance. Maden et al. (2010) also presented a *TDVRP* with congestion and reported about a 7% reduction of CO_2 emissions based on an emission measurement function was observed after planning routes according to the time-varying speeds. However, the objective of their *VRP* model remains the minimization of the total travel time rather than the reduction of emissions. Palmer (2007) developed an integrated routing and carbon dioxide emissions model and calculated the amount of CO_2 emitted on the journey as well as the travelling time and distance. The paper examined how the speed affects the reduction of CO_2 emissions in different congestion scenarios with time windows. The results showed that about 5% of reduction of CO_2 emissions could be achieved. Bauer et al. (2010) explicitly focus on minimizing greenhouse gas emissions in a model of intermodal freight transport, showing the potential of intermodal freight transport for reducing greenhouse emissions. Fagerholt et al. (2010) tried to reduce the fuel consumption and fuel emissions by optimizing speed in a shipping scenario. Given the fixed shipping routes and the time windows, the speed of each segment of a route is optimized in order to yield fuel savings.

Some studies sought to formulate a comprehensive objective function which measures economic costs and environmental costs so as to meet efficiency objectives and green criteria simultaneously. Ubeda et al. (2011) conducted a case study in which minimization of both the distances and pollutant emissions is the objective. The results

also revealed that backhauling seems more effective in controlling emissions. This suggests that backhauling could be initiated by companies to enhance energy consumption efficiency and reduce environmental impact. It appears that this paper is the first to incorporate minimizing GHG emissions in the model of *Vehicle Routing Problem with Backhauls*. Bektaş and Laporte (2011) proposed a *Pollution Routing Problem* with or without time windows and developed a comprehensive objective function that integrates the minimization of the cost of carbon emissions along with the operational costs of drivers and fuel consumption. However, their model assumed a free-flow speed of at least 40km/h, which was contrary to the real world situation where congestion occurs. Following up this research, Demir et al. (2012) proposed an extended Adaptive Large Neighborhood Search (ANLS) for *PRP* in order to enhance the computation efficiency for medium or large scale *PRP*. Faulin et al. (2011) presented a *CVRP* with environmental criteria and considered more complex environmental impact. Apart from the traditional economic costs measurement and the environmental costs that are caused by polluting emissions, the environmental costs derived from noise, congestion and wear and tear on infrastructure were also considered.

6.2.2. *Future research directions in PRP*

Bektaş and Laporte (2011) highlighted several very inspiring conclusions based on the observation of their computational experiment results. They also provided the possibility of considering heterogeneous vehicles and time-dependent conditions in future research. We believe that the speed of vehicles and the traffic conditions especially in the congested urban areas are not negligible and the real-time transportation information is able to lay a solid foundation for continual research into the *PRP* by providing dynamic real-world data. With the support of real-time information about traffic conditions, vehicles can be directed to other roads which are less congested. This implies a more environmental-friendly case because less emission is generated when vehicles are traveling at the best speeds. In this context, the problem concerns whether those routes with good traffic conditions are preferable at the expense of choosing a longer path. Thus interesting future study may come up with exploring the trade-off between greater traveling distance (economic costs) and environmental impact (environmental costs).

One remarkable observation from Bektaş and Laporte (2011) is that an appropriate time window restriction makes the effect of energy reduction more significant. Based on this relation, future research may involve exploring the trade-off between the economic cost (including penalties) and the environmental cost in routing problems with soft time window constraints. Another interesting observation is that higher variation of customer demand can contribute to more room for energy consumption reduction. Chances are that inventory models can be incorporated into the *PDP* model to determine an optimal set of customer demands that yields the most environmental cost effectiveness, especially in VMI policy where the customer demand is flexible and can be distributed in different

combinations. In that case, further study of *IRP* may extend its objectives with more environmental indicators, not merely the traditional economic cost like overall time or distance. The current studies on *PRP* are shown in Table 5.

Table 5

Recent studies of *PRP* during 2007-2012

VRP variants	Papers (Total: 6)
Basic VRP or TSP	Bauer et al., 2012;
Capacitated VRP	Faulin et al., 2011;
VRP with Time Windows	Palmer, 2007; Fagerholt et al., 2010; Bektaş and Laporte, 2011; Demir et al., 2012;
VRP with Clustered Backhauls	Ubeda et al., 2010;

6.3.   VRP in Reverse Logistics (VRPRL)

Reverse logistics has received close attention in recent years. Dekker et al. (2004) defined reverse logistics as "The process of planning, implementing and controlling backward flows of raw materials, in process inventory, packaging and finished goods, from a manufacturing, distribution or use point, to a point of recovery or point of proper disposal". An overview of reverse logistics was provided by Carter and Ellram (1998).

VRP in Reverse Logistics (*VRPRL*) focuses on the distribution aspects of reverse logistics. There is a large amount of research on reverse logistics. However, we found only a small number of studies on reverse logistics from the perspective of vehicle routing. Actually, on the medium level of a reverse logistics system, the operator and the relationship between the forward and backward (reverse) flows make a difference on the operational level. In this context, vehicle routing problems occur in different situations, which make *VRP* a direct and pertinent model for formulating the transportation issues in reverse logistics. Beullens et al. (2004) detected some gaps between vehicle routing models for reverse logistics and the availability of vehicle routing solution approaches in the literature. However, the coverage seems not exhaustive enough. Most *VRPRL* studies deal with recycling waste or end-of-life goods to one or more than one depot for further reprocessing. To facilitate the review of existing research of *VRPRL*, the problem is subdivided into four categories: Selective Pickups with Pricing, Waste Collection, End-of-life Goods Collection, and Simultaneous Distribution and Collection, which are summarized below. The future research directions in *VPRRL* are also suggested.

6.3.1.   Selective Pickups with Pricing

The selective-pickup vehicle routing problem with pricing in reverse logistics is characterized by only choosing profitable pickup points to visit and by making the collection operation as profitable as possible. This problem incorporates *VRP with Profits*

(Feillet et al., 2005) in the Pickup and Delivery Problem. A literature review of this problem was provided by Aras et al. (2011). Studies on this problem in the literature are limited. Privé et al. (2006) analyzed a vehicle-routing problem with the delivery of soft drinks to convenience stores and the pickup of empty bottles and aluminium cans. Each customer is visited exactly once. The deliveries were mandatory while the pickup process at each point was optional. Such collection was undertaken only when there was enough unused space and sufficient available loading capacity to load the collection at that moment. This problem was formulated as a *Vehicle Routing Problem with Pickups and Delivery*, with the setting of time window constraints, heterogeneous vehicles, and multiple types of products. The objective was the minimization of routing costs, minus the revenue yielded from the recycled bottles and cans. Gribkovskaia et al. (2008) examined a very similar problem but each customer was allowed to be visited twice. Aras et al. (2011) presented a selective multi-depot vehicle routing problem with pricing, in which the visit to each customer was selective, dependent on whether the visit was profitable and whether the remaining vehicle space could load all the recyclable products of that customer. Split collection was not allowed.

6.3.2. Waste Collection

Waste management, including waste avoidance, reuse and recycling, is a key process in protecting the environment and conserving resources. The transportation of waste materials is clearly part of the Green Logistics agenda (Sbihi and Eglese, 2007a). Vehicle routing models for waste collection issues date back to Beltrami and Bodin (1974). Recently they have been regarded as an important part of reverse logistics. Different variants of *VRP* are addressed in the literature to investigate the waste collection problem. Sculli et al. (1987) considered a *Site-dependent VRP* in refuse collection in Hong Kong. Mansini and Speranza (1998) developed a linear programming model for refuse collection services, which is a *Multi-compartment VRP*. *Multi-depot VRP* and *Location Routing Problem* for designing a waste recycling network were also discussed in Ramos and Oliveira (2011) and Mar-Ortiz et al. (2011), respectively.

6.3.3. End-of-life Goods Collection

The collection of some components of end-of-life products can benefit the original manufacturer because the recycled materials or components remain functional after further disposal or remanufacturing. Schultmann et al. (2006) investigated the reverse logistics of components of end-of-life vehicles in Germany. Tabu search is used to minimize the total distance of visiting up to 1,202 dismantlers scattered throughout Germany. Blanc et al. (2006) also presented a case study concerning recycling end-of-life vehicle components to optimize the logistics network for collecting containers that are used to deliver end-of-life materials from dismantlers in the Netherlands. They considered a vehicle routing model with settings of multiple depots and pickup and

delivery. Krikke et al. (2008) considered the *Inventory Routing Problem* in the collection of materials that are disassembled from end-of-life vehicles. Using online inventory information, the inventory levels were observed and then used to construct collection plans including two types of collection orders: MUST and CAN orders. Kim et al. (2009) studied the backward flow of logistics for recycling end-of-life consumer electronic goods in South Korea. The model assumed that each regional recycling center (depot) had a fixed but sufficient number of identical vehicles and maximum traveling distance for each vehicle was constrained. Even though there were four regional recycling centers in the case study, they formulated models for each depot separately rather than a multi-depot vehicle routing model. Kim et al. (2011) extended a similar problem to a *Multi-depot VRP*. As shown above, some of the studies in this category considered the scenarios of multiple depots. Other constraints, such as time window settings, pickup and delivery, split visits, site-dependent visits, and periodic visits, are not addressed in the literature that deals with this problem.

6.3.4. *Simultaneous Distribution and Collection*

Studies of this problem use a *VRP with Simultaneous Delivery and Pickup* model to formulate the distribution process of reverse logistics. Dell'Amico et al. (2006b) defined a 0-1 linear programming model and studied the application of the branch-and-price technique in solving this problem. Alshamrani et al. (2007) examined a real-world problem of blood distribution and collection of blood containers. Penalty cost was generated when the containers were not picked up. Additionally, stochastic demand and periodic visits were considered in the proposed model. Other studies include Dethloff (2001), Çatay (2010), and Tasan and Gen (2011).

6.3.5. *Future research directions in VRPRL*

In the light of the characteristics of the reverse logistics system and its operation, multi-depot setting and simultaneous pickup and delivery operations received relatively more attention in the studies of *VRPRL*, as shown in Table 6. However, time windows and periodic delivery imposed by the customer are seldom considered in the existing studies, even though such situations are frequently encountered in real-life waste collection issues. Additionally, most of papers we investigated above deal with the reverse flow from commercial locations, in which the issue was correspondingly modeled as a *Node Routing Problem*. Nevertheless, residential collection, which involves recycling household refuse door by door along a street, is a different problem and should be formulated as an *Arc Routing Problem*. To the best of our knowledge, research on the vehicle routing problem regarding the reverse logistics of residential collection (household refuse or end-of-life products) does not exist in the literature.

Reverse logistics in a multi-echelon distribution system also offer new research opportunities for *VRPRL*. Multi-echelon reverse logistics network design has drawn

researchers' interest in the literature (Fleischmann et al., 1997). Recently, Min et al. (2006) developed a nonlinear mixed integer programming model and genetic algorithm to provide a minimum-cost solution for designing a multi-echelon reverse logistics network. Srivastava (2008) also formulated a cost effective and efficient multi-echelon reverse logistics network with multiple products and maximum profit. However, both of them tackled the network design problem from the perspectives of location-allocation rather than vehicle routing. Since multi-echelon reverse logistics networks play a significant role in green logistics, using vehicle routing models to optimize this network will make a significant impact on Greenness.

Table 6

Recent studies of *VRPRL*

VRP variants	Papers (Total: 17)
__Selective Pickups with Pricing (Total: 3)__	
Capacitated VRP	Aras et al., 2011;
VRP with Time Windows	Privé et al., 2006;
VRP with Simultaneous Delivery and Pickup	Privé et al., 2006;
Multi-deopt VRP	Aras et al., 2011;
Mix Fleet VRP	Privé et al., 2006;
Generalized VRP	Gribkovskaia et al., 2008; Aras et al., 2011;
__Waste Collection (Total: 4)__	
Multi-deopt VRP	Ramos and Oliveira, 2011;
Mix Fleet VRP	Mar-Ortiz et al., 2011;
Location Routing Problem	Mar-Ortiz et al., 2011;
Site-dependent VRP	Sculli et al., 1987;
Multi-compartment VRP	Mansini And Speranza, 1998;
__End-of-life Goods Collection (Total: 5)__	
Capacitated VRP	Schultmann et al., 2006; Kim et al., 2009; Kim et al., 2011;
Multi-depot VRP	Blanc et al., 2006; Kim et al., 2011;
Inventory Routing Problem	Krikke et al., 2008;
__Simultaneous Distribution and Collection (Total: 5)__	
VRP with Simultaneous Delivery and Pickup	Dethloff, 2001; Dell'Amico et al., 2006; Alshamrani et al., 2007; Çatay, 2010; Tasan and Gen, 2011;

Overall, *GVRP* has grabbed researchers' attention during the last several years. Since its study is still at the beginning stage, there exist a variety of future research areas, as suggested in the next section.

7. Trends and future directions of Green Vehicle Routing Problems

Based on the review on the traditional *VRP* variants and *GVRP* presented above, we draw the following conclusions about the trends of *GVRP*, through the analysis of how the *GVRP* can interact with the traditional *VRP* variants.

1) *Interdisciplinary research and systematic approaches*

Although the number of the publication on *GVRP* is growing, the studies are still limited. The reason for this may be the fact that solving such problems calls for an interdisciplinary approach incorporating energy use and environmental impact, public policy, engineering, transportation system management, and even urban planning. The wide scope of the research content requires an interdisciplinary and systematic approach provided by researchers and engineers from different backgrounds. Besides, the experimental problem instances in existing research mainly come from previous research or are generated randomly. More realistic experimental data and real-world cases that support the research still need to be provided by government or other official organizations.

2) *VRP with uncertainty*

Stochastic service time, stochastic traveling time as well as stochastic customer demand are largely neglected in the literature, though these parameters are frequently used to describe the dynamic environment. Queuing models and inventory models might be involved in this problem to make the studies more convincing. The time windows and the customer demand in place will make more room for the reduction of energy consumption. In most cases, the time windows and customer demand are set by ambiguous linguistic statements and are closely related to the customer satisfaction level. Using the fuzzy theory, future studies may explore the trade-off between customer satisfaction, environmental cost and economic cost.

3) *More operational constraints in waste collection*

Most existing research assumed that the vehicles were identical. The studies incorporating heterogeneous vehicles are still limited. When dealing with using *Site-dependent VRP* to solve the waste collection problem, the different vehicle types are a key factor to determine the optimal routes. Other cases include considering multi-compartment vehicles and two-dimensional or three-dimensional loading constraints in recycling classified garbage. The problem of reverse logistics of residential collection, which is frequently encountered in real-life issues and should be formulated as *Arc Routing Problem*, is worthy of study.

4) *Multi-echelon distribution system*

All the problems presented focus on the traditional one-level distribution system rather than the multi-echelon distribution network. As the multi-echelon distribution system has drawn attention for academic research or for practical application, it is well worth exploring whether a multi-echelon vehicle dispatching system has a significant impact on reducing overall energy consumption and emissions. As part of green supply chain management, a multi-echelon reverse logistics network opens new possibilities for determining a more cost effective solution of dispatching vehicles for recycling refuse or end-of-life products.

8. Conclusion

Concern about Green Logistics has been constantly increasing both in industry and in academic research. In line with this "green" trend, *GVRP* has received scientific attention from researchers in the OR/MS field. To bring order into the research literature on *GVRP*, we reviewed the articles about *GVRP*, together with analyzing how the traditional *VRP* variants could be involved in or interact with *GVRP* and contribute to further study on *GVRP*. Notably, we suggest the trends and future directions for *GVRP* which offer insights and inspiration for interested researchers.

Even though the current literature of *GVRP* is still limited to idealized models and the gaps between the theoretical achievements and applicable agenda, we see a large number of potential, fruitful and practical research outcomes in this area. There is still a long way to go on the path to connect *VRP* with sustainable issues. We hope and trust that this literature survey will stimulate researchers' and logistics practitioners' interests in *GVRP* and lead to new research and application opportunities for a sustainable industry.

Acknowledgements

References

Alegre, J., Laguna, M., & Pacheco, J. (2007). Optimizing the periodic pick-up of raw materials for a manufacturer of auto parts. *European Journal of Operational Research*, 179(3), 736-746.

Alonso, F., Alvarez, M. J., & Beasley, J. E. (2008). A tabu search algorithm for the periodic vehicle routing problem with multiple vehicle trips and accessibility restrictions. *Journal of the Operational Research Society*, 59, 963-976.

Alshamrani, A., Mathur, K., & Ballou, R. H. (2007). Reverse logistics: simultaneous design of delivery routes and returns strategies. *Computers & Operations Research*, 34, 595-619.

Andersson, H., Hoff, A., Christiansen, M., Hasle, G., & Løkketangen, A. (2010). Industrial aspects and literature survey: combined inventory management and routing. *Computers & Operations Research*, 37(9), 1515–1536.

Angelelli, E., & Speranza, M. G. (2002). The application of a vehicle routing model to a waste-collection problem: Two case studies. *Journal of the Operational Research Society*, 53, 944–952.

Angelelli, E., Bianchessi, N., Mansini, R., & Speranza, M. G. (2010). Comparison of policies in dynamic routing problems. *Journal of the Operational Research Society*, 61, 686-695.

Apaydin, O., & Gonullu, M. T. (2008). Emission control with route optimization in solid waste collection process: A case study. *Sadhana*, 33, 71-82.

Aras, N., Aksen, D., & Tekin, M. T. (2011). Selective multi-depot vehicle routing problem with pricing. *Transportation Research Part C: Emerging Technologies*, 19, 866-884.

Archetti, C., Bertazzi, L., Laporte, G., & Speranza, M. G. (2007). A branch-and-cut algorithm for a vendor-managed inventory-routing problem. *Transportation Science*, 41(3), 382–391.

Archetti, C., Bouchard, M., & Desaulniers, G. (2011). Enhanced branch and price and cut for vehicle routing with split delivies and time windows. *Transportation Science*, 45, 285-298.

Archetti, C., Savelsbergh, M. W. P., & Speranza, M. G. (2006). Worst-case analysis for split delivery vehicle routing problems. *Transportation Science*, 40(2), 226-234.

Azi, N., Gendreau, M., Potvin, J.-Y. (2010). An exact algorithm for a vehicle routing problem with time windows and multiple use of vehicles. *European Journal of Operational Research*, 202, 756-763.

Balas, E. (1989). The prize collecting traveling salesman problem. *Networks*, 19, 621-636.

Baldacci, R., & Mingozzi, A. (2009). A unified exact method for solving different classes of vehicle routing problems. *Mathematical Programming*, 120, 347-380.

Baldacci, R., Bartolini, E., & Laporte, G. (2010a). Some application of the generalized vehicle routing problem. *Journal of the Operational Research Society*, 61, 1072-1077.

Baldacci, R., Toth, P., & Vigo, D. (2010b). Exact algorithms for routing problems under vehicle capacity constraints. *Annals of Operations Research*, 175, 213–245.

Baldacci, R., Battarra, M., & Vigo, D. (2008a). Routing a Heterogeneous Fleet of Vehicles. In: Golden, B. L., Raghavan, S., & Wasil, E. (Eds). *The Vehicle Routing Problem: Latest Advances and New Challenges*, Springer, New Work.

Baldacci, R., Christofides, N., & Mingozzi, A. (2008b). An exact algorithm for the vehicle routing problem based on the set partitioning formulation with additional cuts. *Mathematical Programming*, 115, 351-385.

Baldacci, R., Battarra, M., & Vigo, D. (2009). Valid inequalities for the fleet size and mix vehicle routing problem with fixed costs. *Networks*, 54, 178-189.

Baldacci, R., Mingozzi, A., & Calvo, R. W. (2011). An exact method for the capacitated location-routing problem. *Operations Research*, 59, 1284-1296.

Baldacci, R., Mingozzi, A., & Roberti, R. (2012). Recent exact algorithms for solving the vehicle routing problem under capacity and time window constraints. *European Journal of Operational Research*, 218, 1-6.

Baldacci, R., Mingozzi, A., Roberti, R., & Calvo, R. W. (2013). An exact algorithm for the two-echelon capacitated vehicle routing problem. *Operations Research*, 61, 298-314.

Baños, R., Ortega, J., Gil, C., Fernández, A., & de Toro, F. (2013). A simulated annealing-based parallel multi-objective approach to vehicle routing problems with time windows. *Expert Systems with Applications*, 40, 1696-1707;

Bauer, J., Bektaş, T., & Crainic, T. G. (2010). Minimizing greenhouse gas emissions in intermodal freight transport: an application to rail service design. *Journal of the Operational Research Society*, 61, 530-542.

Bektaş, T., & Laporte, G. (2011). The Pollution-Routing Problem. *Transportation Research Part B*, 45, 1232-1250.

Bélanger, N., Desaulniers, G., Soumis, F., & Desrosiers, J. (2006). Periodic airline fleet assignment with time windows, spacing constraints, and time dependent revenues. *European Journal of Operational Research*, 175 (3), 1754-1766.

Belenguer, J., Benavent, E., Prins, C. Prodhon, C., & Calvo R. W. (2011). A branch-and-cut method for the capacitated location-routing problem. *Computers & Operations Research*, 38, 931-941.

Bell, W. J., Dalberto, L. M., Fisher, M. L., Greenfield, A. J., Jaikumar, R., & Kedia, P. (1983). Improving the distribution of industrial gases with an on-line computerized routing and scheduling optimizer. *Interfaces*, 13(6), 4–23.

Beltrami, E. J., & Bodin, L. D. (1974). Networks and vehicle routing for municipal waste collection. *Networks*, 4, 65-94.

Berbotto, L., García, S., & Nogales, F. J. (2013). A randomized granular tabu search heuristic for the split delivery vehicle routing problem. *Annals of Operations Research*, in press.

Bertazzi, L., & Speranza, M. G. (2002). Continuous and discrete shipping strategies for the single link problem. *Transportation Science*, 36(3), 314–25.

Bertsimas, D. J. (1992). A vehicle routing problem with stochastic demand. *Operations Research*, 40, 574-585.

Bertsimas, D. J., & Simchi-Levi, D. (1996). A new generation of vehicle routing research: robust algorithms, addressing uncertainty. *Operations Research*, 44, 286-304.

Beullens, P., Wassenhove, L. V. & Oudheusden, D. V. (2004). *Collection and vehicle routing issues in reverse logistics*, in: Dekker, R., Fleischmann, M., Inderfurth K., & Wassenhove, L. van (Eds.), *Reverse Logistics. Quantitative Models for Closed-loop Supply Chains*, Springer-Verlag, Berlin, Heidelberg, New York, 95-134

Blakeley, F., Arguello, B., Cao, B., Hall, W., & Knolmajer, J. (2003). Optimizing periodic maintenance operations for Schindler Elevator Corporation. *Interfaces*, 33(1). 67-79.

Blanc, I. le, Krieken, M. van, Krikke, H., & Fleuren, H. (2006). Vehicle routing concepts in the closed-loop container network of ARN – a case study. *OR Spectrum*, 28, 53-71.

Bloemhof-Ruwaard, J. M., van Beek, P., Hordijk, L., & Van Wassenhove, L. N. (1995). Interactions between operational research and environmental management. *European Journal of Operational Research*, 85, 229-243.

Bodin, L., Golden, B., Assad, A., & Ball, M. (1983). Routing and scheduling of vehicles and crews: the state of the art. *Computers & Operations Research*, 10, 63–211.

Bortfeldt, A. (2011). A hybrid algorithm for the capacitated vehicle routing problem with three-dimensional loading constraints. *Computers & Operations Research*, in press.

Brandão, J. (2004). A tabu search algorithm for the open vehicle routing problem. *European Journal of Operational Research*, 157(3), 552-564

Brandão, J. (2011). A tabu search algorithm for the heterogeneous fixed fleet vehicle routing problem. *Computers & Operations Research*, 38, 140-151.

Bräysy, O, & Gendreau, M. (2005a). Vehicle routing problems with time windows, Part I: Route construction and local search algorithms. *Transportation Science*, 39, 104-118.

Bräysy, O, & Gendreau, M. (2005b). Vehicle routing problems with time windows, Part II: Metaheuristics. *Transportation Science*, 39, 119-139.

Bräysy, O., Dullaert W., Hasle, G., Mester, D. & Gendreau, M. (2008). An effective multi-restart deterministic annealing metaheuristic for the fleet size and mix vehicle routing problem with time windows. *Transportation Science*, 42(3), 371-386.

Bräysy, O., Porkka, P. P., Dullaert, W., Repoussis, P. P., & Tarantilis, C. D. (2009). A well-scalable metaheuristic for the fleet size and mix vehicle routing problem with time windows. *Expert System with Application*, 36, 8460-8475.

Bukchin, Y., & Sarin, S. C. (2006). Discrete and dynamic versus continuous and static loading policy for a multi-compartment vehicle. *European Journal of Operational Research*, 174, 1329-1337.

Campbell, A. M. & Savelsbergh, M. W. P. (2004). A Decomposition approach for the Inventory Routing Problem. *Transportation Science*, 38(4), 488-502.

Cappanera, P., Gouveia, L., & Scutellà, M. G. (2011). The skill vehicle routing problem. *Network Optimization, Lecture Notes in Computer Science*, 2011, vol. 6701/2011, 354-364.

Carrabs, F., Cordeau, J.-F., & Laporte, G. (2007). Variable Neighborhood Search for the Pickup and Delivery Traveling Salesman Problem with LIFO loading. *INFORMS Journal on Computing*, 19, 618-632.

Carter, C. R. & Ellram L. M. (1998). Reverse logistics: A review of the literature and framework for future investigation. *Journal of Business Logistics*, 19(1), 85-102.

Çatay, B. (2010). A new saving-based ant algorithm for the vehicle routing problem with simultaneous pickup and delivery. *Expert Systems with Application*, 37, 6809-6817.

Chajakis, E. D., & Guignard, M. (2003). Scheduling deliveries in vehicles with multiple compartments. *Journla of Global Optimization*, 26, 43-78.

Chao, I-M., & Liou, T.-S. (2005). A New Tabu Search Heuristic for the Site-Dependent Vehicle Routing Problem. *The Next Wave in Computing, Optimization, and Decision Technologies, Operations Research/Computer Science Interfaces Series*, 2005, vol. 29, III, 107-119.

Chao, I-M., Golden, B. L., & Wasil, E. A. (1996). The team orienteering problem. *European Journal of Operational Research*, 88, 464-474.

Chen, H.-K., Hsueh, C.-F., & Chang, M.-S. (2006). The real-time time-dependent vehicle routing problem. *Transportation Research Part E: Logistics and Transportation Review*, 42(5), 383-408.

Chen, Z.-L., & Xu, H. (2006). Dynamic column generation for dynamic vehicle routing with time windows. *Transportation Science*, 40, 74-88.

Cheng, R., Gen, M., & Tozawa, T. (1995). Vehicle routing problem with fuzzy due-time using genetic algorithms. *Japan Society for Fuzzy Theory and Systems*, 7, 1050-1061.

Cheung, B. K. S., Choy, K. L., Li, C.-L., Shi, W., Tang, J. (2008). Dynamic routing model and solution methods for fleet management with mobile technologies. *International Journal of Production Economics*, 113, 694-705.

Christensen, S. G., & Rousøe, D. M. (2010). Container loading with multi-drop constraints. *International Transactions in Operational Research*, 16, 727-743.

Christofides, N., Mingozzi, A., & Toth, P. (1979). The vehicle routing problem. In : Christofides, N., Mingozzi, A., Toth, P., & Sandi, C. (Eds), *Combinatorial optimization*, Wiley, Chichester.

Christophides, N. (1985). Vehicle routing. In: Lawler, E.L., Lenstra, J.K., Rinnooy Kan, A.H.G., Shmoys, D.B. (Eds), *The Traveling Salesman Problem: A Guided Tour of Combinatorial Optimization*, John Wiley and Sons Ltd.

Clarke, G., & Wright, J. W. (1964). Scheduling of vehicles from a central depot to a number of delivery points. *Operations Research*, 12, 568-581.

Coelho, L. C., Cordeau, J., & Laporte, G. (2012). The inventory-routing problem with transshipment. *Computers & Operations Research*, 39, 2537-2548.

Cook, T. M. & Russell, R. A. (1978). A simulation and statistical analysis of stochastic vehicle routing with time constraints. *Decision Sciences*, 9, 673-687.

Cooke, K. L. & Halsey, E. (1966). The shortest route through a network with time-dependent internodal transit times. *Journal of Mathematical Analysis and Applications*, 14(3), 493-498.

Cordeau, J.-F., & Maischberger, M. (2012). A parallel iterated tabu search heuristic for vehicle routing problems. *Computers & Operations Research*, 39, 2033-2050.

Cordeau, J.-F., Gendreau, G., Laporte, G., Potvin, J.-Y., & Semet, F. (2002). A guide to vehicle routing heuristics. *Journal of the Operational Research Society*, 53, 512-522.

Cordeau, J.-F., Laporte, G., & Mercier, A. (2001). A unified tabu search heuristic for vehicle routing problems with time windows. *Journal of the Operational Research Society*, 52, 928-936.

Cordeau, J.-F., Laporte, G., Savelsbergh, M. W. P., & Vigo, D. (2007). Vehicle routing. In: Barnhart, C and Laporte, G. (Eds), *Handbook in OR & MS, Vol. 14*, Elsevier, Amsterdam.

Crainic, T. G., Ricciardi, N., & Storchi, G. (2009). Models for evaluating and planning city logistics systems. *Transportation Science*, 43, 432–454.

Crevier, B. Cordeau, J.-F., & Laporte, G. (2007). The multi-depot vehicle routing problem with inter-depot routes. *European Journal of Operational Research*, 176, 756-773.

Daniel, S. E., Diakoulaki, D. C., & Pappis, C. P. (1997). Operations research and environmental planning. *European Journal of Operational Research*, 102, 248-263.

Dantzig, G. B., & Ramser, J. H. (1959). The truck dispatching problem. *Management Science*, 6, 80-91.

Dekker, R., Fleischmann, M., Inderfurth, K., & Van Wassenhove, L. N. (2004). *Reverse logistics: Quantitative models for closed-loop supply chains*. Springer, Berlin:.

Dell'Amico, M., Monaci, M., Pagani, C., & Vigo, D. (2006a). Heuristic approaches for the fleet size and mix vehicle routing problem with time windows. *Transportation Science*, 4, 516-526.

Dell'Amico, M., Righini, G., & Salani, M. (2006b). A branch-and-price approach to the vehicle routing problem with simultaneous distribution and collection. *Transportation Science*, 40, 235-247.

Demir, E., Bektaş, T., & Laporte, G. (2012). An adaptive large neighborhood search heuristic for the Pollution-Routing Problem. *European Journal of Operational Research*, 223, 346-359.

Derigs, U., Gottlieb, J., Kalkoff, J., Piesche, M., Rothlauf, F., & Vogel, U. (2011). Vehicle routing with compartments: applications, modeling and heuristics. *OR Spectrum*, 33, 885-914.

Dethloff, J. (2001). Vehicle routing and reverse logistics: the vehicle routing problem with simultaneous delivery and pick-up. *OR Spectrum*, 23, 79-96.

Doerner, K. F., Fuellerer, G., Gronalt, M., Hartl, R. F., & Iori, M. (2007). Metaheuristics for the vehicle routing problem with loading constraints. *Networks*, 49, 294-307.

Dondo, R. & Cerdá, J. (2007). A cluster-based optimization approach for the multi-depot heterogeneous fleet vehicle routing peoblem with time windows. *European Journal of Operational Research*, 176, 1478-1507.

Dondo, R., & Cerdá, J. (2013). A sweep-heuristic based formulation for the vehicle routing problem with cross-docking. *Computers & Chemical Engineering*, 48, 293-311.

Dror, M., & Ball, M. O. (1987). Inventory/routing: reduction from an annual to a short-period problem. *Naval Research Logistics*, 34, 891–905.

Dror, M., & Levy, L. (1986). A vehicle routing improvement algorithm-comparison of a "greedy" and a "matching" implementation for inventory routing. *Computers and Operations Research*, 23, 33-45.

Dror, M., & Trudeau, P. (1989). Savings by split delivery routing. *Transportation Science*, 23(2), 141–149.

Dror, M., Ball, M., & Golden, B. L. (1985). A computational comparison of algorithms for the inventory routing problem. *Annals of Operations Research*, 4, 3–23.

Dror, M., Laporte, G., & Louveaux, F. V. (1993). Vehicle routing with stochastic demands and restricted failures. *ZOR-Methods and Models of Operations Research*, 37, 273-283.

Duhamel, C., Lacomme, P., Quilliot, A., & Toussaint, H. (2011). A multi-start evolutionary local search for the two-dimensional loading capacitated vehicle routing problem. *Computers & Operations Research*, 38, 617-640.

El Fallahi, A., Prins, C., Wolfler Calvo, R., (2008) A memetic algorithm and a tabu search for the multi-compartment vehicle routing problem. *Computers & Operations Research*, 35(5), 1725–1741.

Erbao, C. & Mingyong, L. (2009). A hybrid differential evolution algorithm to vehicle routing problem with fuzzy demands. *Journal of Computational and Applied Mathematics*, 231, 302-310.

Erbao, C. & Mingyong, L. (2010). The open vehicle routing problem with fuzzy demands. *Expert System with Application*, 37, 2405-2411.

ErdoÄŸan, S., & Miller-Hooks, E. (2012). A green vehicle routing problem. *Transportation Research Part E: Logistics and Transportation Review*, 48(1), 100-114.

Fagerholt, K. (1999). Optimal fleet design in a ship routing problem. *International Transactions in Operational Research*, 6, 453-464.

Fagerholt, K., Laporte, G., & Norstad, I. (2010). Reducing fuel emissions by optimizing speed on shipping routes. *Journal of the Operational Research Society*, 61, 523-529.

Faulin, J., Juan, A., Lera, F., & Grasman, S. (2011). Solving the capacitated vehicle routing problem with environmental criteria based on real estimations in road transportation: A case study. *Procedia Social and Behavioral Sciences*, 20, 323-334.

Feillet, D., Dejax, P., & Gendreau, M. (2005). Traveling salesman problems with profits. *Transportation Science*, 39, 188-205.

Figliozzi, M. A. (2009). Planning approximations to the average length of vehicle routing problems with time window constraints. *Transportation Research Part B: Methodological*, 43(4), 438-447.

Figliozzi, M. A. (2010). An iterative route construction and improvement algorithm for the vehicle routing problem with soft time windows. *Transportation Research Part C: Emerging Technologies*, 18(5), 668-679.

Figliozzi, M. A. (2012). The time dependent vehicle routing problem with time windows: Benchmark problems, an efficient solution algorithm, and solution characteristics. *Transportation Research Part E: Logistics and Transportation Review*, 48(3), 616-636.

Fisher, M. L. (1994). Optimal solution of vehicle routing problems using minimum K-trees. *Operations Research*, 42, 626- 642.

Fisher, M. L., & Jaikumar, R. (1981). A generalized assignment heuristic for vehicle routing. *Networks*, 11, 109-124.

Fleischmann, M., Bloemhof-Ruwaard, J. M., Dekker, R., van der Laan, E., van Nunen, J. A.E.E., & Wassenhove, L. N. V. (1997). Quantitative models for reverse logistics: A review. *European Journal of Operational Research*, 103, 1-17.

Francis, P., & Smilowitz, K. (2006). Modeling techniques for periodic vehicle routing problems. *Transportation Research Part B*, 40, 872-884.

Francis, P., Smilowitz, K., & Tzur, M. (2006). The period vehicle routing problem with service choice. *Transportation Science*, 40(4), 439-454.

Frizzell, P. W., & Giffin, J. W. (1995). The split delivery vehicle scheduling problem with time windows and grid network distances. *Computers & Operational Research*, 22(6), 655–667.

Fuellerer, G., Doerner, K. F., Hartl, R. F., & Iori, M. (2009). Ant colony optimization for the two-dimensional loading vehicle routing problem. *Computers & Operations Research*, 36, 655-673.

Fuellerer, G., Doerner, K. F., Hartl, R. F., & Iori, M. (2010). Metaheuristics for vehicle routing problems with three-dimensional loading constraints. *European Journal of Operational Research*, 201, 751-759.

Gajpal, Y., & Abad, P. (2010). Saving-based algorithms for vehicle routing problem with simultaneous pickup and delivery. *Journal of the Operational Research Society*, 61, 1498-1509.

Gelinas, S., Desrochers, M. Desrosiers, J., & Solomon, M. M. (1995). A new branching strategy for time constrained routing problems with application to backhauling. *Annals of Operations Research*, 61, 91-109.

Gendreau, M., & Potvin, J.-Y. (1998). Dynamic vehicle routing and routing. In: Crainic, T. G., & Laporte, G. (Eds), *Fleet Management and Logistics*, Kluwer Academic Publishers.

Gendreau, M., Guertin, F., Potvin, J.-Y., & Séguin, R. (2006a). Neighborhood search heuristics for a dynamic vehicle routing problem with pick-ups and deliveries. *Transport Research Part C: Emerging Technologies*, 14, 157-174.

Gendreau, M., Iori, M., Laporte, G., & Martello, S. (2006b). A tabu search algorithm for a routing and container loading problem. *Transportation Science*, 40, 342-350.

Gendreau, M., Guertin, F., Potvin, J.-Y., & Taillard, É. (1999). Parallel tabu search for real-time vehicle routing and routing. *Transportation Science*, 33, 381-390.

Gendreau, M., Iori, M., Laporte, G., & Martello, S. (2008a). A tabu search heuristic for the vehicle routing problem with two-dimensional loading constraints. *Networks*, 51, 4-18.

Gendreau, M., Potvin, J.-Y., Bräysy, O., Hasle, G., & Løkketangen, A. (2008b). Metaheuristics for the vehicle routing problem and its extensions: A categorized bibliography. In: Golden, B., Raghavan, S., & Wasil, E. (Eds), *The vehicle routing problem: Latest advances and new challenges*, Springer.

Gendreau, M., Laporte, G., & Séguin, R. (1995). An exact algorithm for the vehicle routing problem with stochastic customers and demands. *Transportation Science*, 29, 143-155.

Gendreau, M., Laporte, G., & Séguin, R. (1996). Stochastic vehicle routing. *European Journal of Operational Research*, 88, 3-12.

Ghiani, G., & Improta, G. (2000). An efficient transformation of the generalized vehicle routing problem. *European Journal of Operational Research*, 122, 11-17.

Ghiani, G., Guerriero, F., Laporte, G., & Musmanno, R. (2003). Real-time vehicle routing: Solution concepts, algorithms and parallel computing strategies. *European Journal of Operational Research*, 151, 1-11.

Giosa, I., Tansini, I., & Viera, I. (2002). New assignment algorithms for the multi-depot vehicle routing problem. *Journal of the Operational Research Society*, 53, 977-984.

Golden, B. L. & Stewart Jr. W. (1978). Vehicle routing with probabilistic demands. In: D. Hogben, & D. Fife(Eds), *Computer Science and Statistics: Tenth Annual Symposium on the Interface*, NBS Special Publication 503, National Bureau of Standards, Washington, DC.

Golden, B. L., Assad, A., & Dahl, R. (1984). Analysis of a large scale vehicle routing problem with an inventory component. *Large Scale Systems*, 7, 181–190.

Golden, B. L., Raghavan, S., & Wasil, E. (2008). *The Vehicle Routing Problem: Latest Advances and New Challenges*, Springer, New Work.

Golden, B., Wasil, E., Kelly, J., & Chao, I.-M. (1998). The impact of metaheuristics on solving the vehicle routing problem: algorithms, problem sets, and computational results. In: Crainic, T. & Laporte, G. (Eds), *Fleet Management and Logistics*, Kluwer, Boston.

Gribkovskaia, I., Laporte, G., & Shyshou, A. (2008). The single vehicle routing problem with deliveries and selective pickups. *Computers & Operations Research*, 35, 2908-2924.

Hadjiconstantinou, E., & Baldacci, R., (1998). A multi-depot period vehicle routing problem arising in the utilities sector. *Journal of the Operational Research Society*, 49 (12), 1239-1248.

Hemmelmayr, V. C., Cordeau, J.-F., & Crainic, T. G. (2012). An adaptive large neighborhood search heuristic for two-echelon vehicle routing problems arising in city logistics. *Computers & Operations Research*, 39, 3215-3228.

Ho, S. C., & Haugland, D. (2004). A tabu search heuristic for the vehicle routing problem with time windows and split deliveries. *Computers & Operations Research*, 31, 1947-1964.

Hong, L. (2012). An improved LNS algorithm for real-time vehicle routing problem with time windows. *Computers & Operations Research*, 39, 151-163.

Ichoua, S., Gendreau, M., & Potvin, J.-Y. (2007). Planned route optimization for real-time vehicle routing. In: Zeimpekis, V., Tarantilis, C. D., Giaglis, G. M., & Minis, I. (Eds), *Dynamic Fleet Management – Concepts, Systems, Algorithms & Case Studies*, Operations Research/Computer Science Interfaces Series Vol. 38, Springer.

Ioannou, G., Kritikos, M., & Prastacos, G. (2001). A greedy look-ahead heuristic for the vehicle routing problem with time windows. *Journal of the Operational Research Society*, 52, 523-537.

Iori, M., Salazar-González, J. J., & Vigo, D. (2003). An exact approach for the symmetric capacitated vehicle routing problem with two dimensional loading constraints. Technical Report OR/03/04, DEIS, Università di Bologna, Bologna, Italy.

Iori, M., Salazar-González, J. J., & Vigo, D. (2007). An exact approach for the vehicle routing problem with two-dimensional loading constraints. *Transportation Science*, 41, 253-264.

Irnich, S. (2000). A multi-depot pickup and delivery problem with a single hub and heterogeneous vehicles. *European Journal of Operational Research*, 122, 310–28.

Jaillet, P. & Odoni, A. R. (1988). The probablistic vehicle routing problem. In: B. L. Golden and A. A. Assad (Eds), *Vehicle Routing: Methods and Studies*, North-Holland, Amsterdam.

Jaillet, P. (1987). Stochastic routing problem. In: G. Andreatta, F. Mason & P. Serafini (Eds), *Stochastics in Combinational Optimization*, World Scientific, New Jersey.

Jang, W., Lim, H. H., Crowe, T. J., Raskin, G., & Perkins, T. E. (2006). The Missouri Lottery optimizes its scheduling and routing to improve efficiency and balance. *Interfaces*, 36(4), 302-313.

Jézéquel, A. (1985). Probabilistic vehicle routing problem. M.Sc. Dissertation, Department of Civil Engineering, Massachusetts Institute of Technology, Cambridge, MA.

Jin, J., Crainic, T. G., & Løkketangen, A. (2012). A parallel multi-neighborhood cooperative tabu search for capacitated vehicle routing problems. *European Journal of Operational Research*, 222, 441-451.

Kallehauge, B. (2008). Formulations and exact algorithms for the vehicle routing problem with time windows. *Computers & Operations Research*, 35, 2307–2330.

Kallehauge, B., Larsen, J., Madsen, O. B. G., & Solomon, M. M. (2005). Vehicle routing problem with time windows. In: Desaulniers, G., Desrosiers, J., & Solomon, M. M. (Eds), *Column Generation*, GERAD 25th Anniversary Series, Springer, New York.

Kara, İ., Kara, B., & Yetis, M. (2007). Energy minimizing vehicle routing problem. *Lecture Notes in Computer Science*, 4616, 62-71.

Khebbache, S., Prins, C., Yalaoui, A., & Reghioui, M. (2009). Memetic Algorithm for two-dimensional loading capacitated vehicle routing problem with time windows. In: International Conference on Computers & Industrial Engineering, 2009. CIE 2009.

Kim, H., Yang, J., & Lee, K. (2009). Vehicle routing in reverse logistics for recycling end-of-life consumer electronic goods in South Korea. *Transportation Research Part E: Logistics and Transportation Review*, 14, 291-299.

Kok, A. L., Hans, E.W., & Schutten, J. M. J. (2012). Vehicle routing under time-dependent travel times: The impact of congestion avoidance. *Computers & Operations Research*, 39(5), 910-918.

Krikke, H., Blanc, I. le, Krieken, M. van, & Fleuren, H. (2008). Low-frequency collection of materials disassembled from end-of-life vehicles: On the value of on-line monitoring in optimizing route planning. *International Journal of Production Economics*, 111, 209-228.

Kritzinger, S., Doerner, K. F., Hartl, R. F., Kiechle, G., Stadler, H., & Manohar, S. S. (2012). Using Traffic Information for Time-Dependent Vehicle Routing. *Procedia - Social and Behavioral Sciences*, 39, 217-229.

Krumke, S. O., Saliba, S. Vredeveld, T., & Westphal, S. (2008). Approximation algorithms for a vehicle routing problem. *Mathematical Methods of Operations Research*, 68, 333-359.

Kuo, Y. (2010). Using simulated annealing to minimize fuel consumption for the time-dependent vehicle routing problem. *Computers & Industrial Engineering*, 59(1), 157-165.

Kuo, Y., & Wang, C.-C. (2012). A variable neighborhood search for the multi-depot vehicle routing problem with loading cost. *Expert Systems with Applications*, 39, 6949-6954.

Ladany, S., & Mehrez, A. (1984). Optimal routing of a single vehicle with loading constraints. *Transportation Planning and Technology*, 8, 301-306.

Lambert, V., Laporte, G., & Louveaux, F. V. (1993). Designing collection routes through bank branches. *Computers & Operations Research*, 20, 783-791.

Laporte, G. (1992). The vehicle routing problem: An overview of exact and approximate algorithms. *European Journal of Operational Research*, 59, 345-358.

Laporte, G. (2007). What you should know about the vehicle routing problem. *Naval Research Logistics*, 54, 811-819.

Laporte, G. (2009). Fifty years of vehicle routing. *Transportation Science*, 43, 408-416.

Laporte, G., & Martello, S. (1990). The selective traveling salesman problem. *Discrete Applied Mathematics*, 26, 193-207.

Laporte, G., Gendreau, M., Potvin, J.-Y., & Semet, F. (2000). Classical and modern heuristics for the vehicle routing problem. *International Transactions in Operational Research*, 7, 285-300.

Laporte, G., Louveaux, F. V., & Mercure, H. (1992). The vehicle routing problem with stochastic travel times. *Transportation Science*, 26, 161-170.

Lecluyse, C., Sörensen, K., & Peremans, H. (2013). A network-consistent time-dependent travel time layer for routing optimization problems. *European Journal of Operational Research*, 226(3), 395-413.

Lee, Y. H., Jung, J. W., & Lee, K. M. (2006). Vehicle routing scheduling for cross-docking in the supply chain. *Computers & Industrial Engineering*, 51, 247–256.

Leung, S. C. H., Zhou, X, Zhang, D., & Zheng, J. (2011). Extended guided tabu search and a new packing algorithm for the two-dimensional loading vehicle routing problem. *Computers & Operations Research*, 38, 205-215.

Li, F. (2005). Modeling and solving variants of the vehicle routing problem: Algorithms, test problems, and computation results. Ph.D. Dissertation, University of Maryland, College Park.

Li, F., Golden, B., & Wasil, E. (2007a). A record-to-record travel algorithm for solving the heterogeneous fleet vehicle routing problem. *Computers & Operations Research*, 34(9), 2734–2742.

Li, F., Golden, B., & Wasil, E. (2007b). The open vehicle routing problem: Algorithms, large-scale test problems, and computational results. *Computers & Operations Research*, 34, 2918-2930.

Li, H., & Lim, A. (2001). A metaheuristic for the pickup and delivery problem with time windows. 13th IEEE Internat. Conf. Tools with Artificial Intelligence, ICTAI-2001, Dallas, IEEE, 160-167.

Li, J.-Q., Mirchandani, P. B., & Borenstein, D. (2009a). Real-time vehicle routing problems with time windows. *European Journal of Operational Research*, 194, 711-727.

Li, X.-Y., Tian, P., & Leung, S. (2009b). An ant colony optimization metaheuristic hybridized with tabu search for open vehicle routing problems. *Journal of the Operational Research Society*, 60, 1012-1025.

Li, X., Leung, S. C. H., Tian, P. (2012). A multistart adaptive memory-based tabu search algorithm for the heterogeneous fixed fleet open vehicle routing problem. *Expert Systems with Application*, 39, 365-374.

Li, X., Tian, P. & Leung, C. H. (2010). Vehicle routing problems with time windows and stochastic travel and service times: Models and algorithm. *International Journal of Production Economics*, 125, 137-145.

Liao, Ch-J., Lin, Y., & Shih, S. C. (2010). Vehicle routing with cross-docking in the supply chain. *Expert Systems with Applications*, 37, 6868–6873.

Liu, F.-H., & Shen, S.-Y. (1999). The fleet size and mix vehicle routing problem with time windows. *Journal of the Operational Research Society*, 50(7), 721–732.

Liu, S., Huang, W., & Ma, H. (2009). An effective genetic algorithm for the fleet size and mix vehicle routing problems. *Transportation Research Part E: Logistics and Transportation Review*, 45, 434-445.

Maden, W., Eglese, R., & Black, D. (2010). Vehicle routing and scheduling with time-varying data: A case study. *Journal of the Operational Research Society*, 61, 515-522.

Madsen, O. B. G., Tosti, K., & Vælds, J. (1995). A heuristic method for dispatching repair men. *Annals of Operations Research*, 61, 213-226.

Malandraki, C., & Daskin, M. S. (1992). Time dependent vehicle routing problems: Formulations, properties and heuristic algorithms. *Transportation Science*, 26, 185-200.

Malapert, A., Guéret, C., Jussien, N., Langevin, A., & Rousseau, L.-M. (2008). Two-dimensional pickup and delivery routing problem with loading constraints. In: 1st Workshop on Bin Packing and Placement Constraints (BPPC'08), Paris.

Mansini, R., & Speranza, M. G. (1998). A linear programming model for the separate refuse collection service. *Computers & Operations Research*, 25, 659-673.

Maraš, V. (2008). Determining Optimal Transport Routes of Inland Waterway Container Ships. *Transportation Research Record*, 2026, 50-58.

Marinakis, Y. (2012). Multiple phase neighborhood search-GRASP for the capacitated vehicle routing problem. *Expert Systems with Applications*, 39, 6807-6815.

Marinakis, Y., & Migdalas, A. (2007). Annotated bibliography in vehicle routing. *Operational Research: An International Journal*, 7, 27-46.

Mar-Ortiz, J., Adenso-Diaz, B., & González-Velarde, J. (2011). Design of a recovery network for WEEE collection: the case of Galicia, Spain. *Journal of the Operational Research Society*, 62, 1471-1484.

McKinnon, A., (2007). CO_2 Emissions from freight transport in the UK. Technical Report. Prepared for the Climate Change Working Group of the Commission for Integrated Transport, London, UK. <http://resilientcities.gaiaspace.org/transport/files/-1/7/2007climatechange-freight.pdf> (accessed 05.02.12).

Mendoza, J. E., Castanier, B., Guéret, C., Medaglia, A. L., & Velasco, N. (2010). A memetic algorithm for the multi-compartment vehicle routing problem with stochastic demands. *Computers & Operations Research*, 37, 1886-1898.

Min, H., Current, J. & Schiling, D. (1992). The multiple depot vehicle routing problem with backhauling. *Journal of Business Logistics*, 13, 259-288.

Min, H., Jayaraman, V., & Srivastava, R. (1998). Combined location-routing problems: A synthesis and future research directions. *European Journal of Operational Research*, 108, 1-15.

Min, H., Ko, H. J., & Ko, C. S. (2006). A genetic algorithm approach to developing the multi-echelon reverse logistics network for product returns. *Omega*, 34, 56-69.

Mingozzi, A., Roberti, R., & Toth, P. (2012). An exact algorithm for the multitrip vehicle routing problem. *INFORMS Journal on Computing*, 25, 193-207.

Moccia, L., Cordeau, J.-F., & Laporte, G. (2012). An incremental tabu search heuristic for the generalized vehicle routing problem with time windows. *Journal of the Operational Research Society*, 63, 232-244.

Moura, A. (2008). A multi-objective genetic algorithm for the vehicle routing with time windows and loading. In: Bortfeldt A, Homberger J, Kopfer H, Pankratz G, Strangmeier R (Eds) *Intelligent Decision Support*. Gabler, Germany, 87–201.

Moura, A., & Oliveira, J. F. (2004). An integrated approach to the vehicle routing and container loading problems, Greece, EURO XX-20th Eur. Conf. on Oper. Res..

Mu, Q., & Eglese, R. W. (2011). Disrupted capacitated vehicle routing problem with order release delay. *Annals of Operations Research*, DOI 10.1007/s10479-011-0947-7.

Mu, Q., Fu, Z., Lysgaard, J., & Eglese, R. (2011). Disruption management of the vehicle routing problem with vehicle breakdown. *Journal of the Operational Research*, 62,742-749.

Muyldermans, L., & Pang, G. (2010). On the benefits of co-collection: experiments with a multi-compartment vehicle routing algorithm. *European Journal of Operational Research*, 206, 93-103.

Nag, B. (1986). Vehicle Routing in the Presence of Site/Vehicle Dependency Constraints. Ph.D. Dissertation, College of Business and Management, University of Maryland at College Park.

Nagy, G., & Salhi, S. (2005). Heuristic algorithm for single and multiple depot vehicle routing problems with pickups and deliveries. *European Journal of Operational Research*, 162, 126-141.

Nagy, G., & Salhi, S. (2007). Location-routing: Issues, models and methods. *European Journal of Operational Research*, 177, 649-672.

Nanthavanij, S., Boonprasurt, P., Jaruphongsa, W., Ammarapala, V. (2008). Vehicle routing problem with manual materials handling: Flexible delivery crew-vehicle assignments. In Proceeding of the 9th Asia Pacific industrial engineering and management system conference, Nusa Dua, Bali, Indonesia.

Nguyen, P. K., Crainic, T. G., & Toulouse, M. (2013). A tabu search for time-dependent multi-zone multi-trip vehicle routing problem with time windows. *European Journal of Operational Research*, 231, 43-56.

Oppen, J. & Løkketangen, A. (2008). A tabu search approach for the livestock collection problem. *Computers and Operations Research*, 35(10), 3213-3229.

Palmer, A. (2007). The development of an integrated routing and carbon dioxide emissions model for goods vehicles. Ph.D. Dissertation, School of Management, Cranfield University.

Pang, K.-W. (2011). An adaptive parallel route construction heuristic for the vehicle routing problem with time windows constraints. *Expert Systems with Applications*, 38, 11939-11946.

Paraskevopoulos, D. C., Repoussis, P. P., Tarantilis, C .D., Ioannou, G., & Prastacos, G. P. (2008). A reactive variable neighborhood tabu search for the heterogeneous fleet vehicle routing problem with time windows. *Journal of Heuristics*, 14, 425-455.

Parragh, S. N., Doerner, K. F., & Hartl, R. F. (2008a). A survey on pickup and delivery problems Part I: Transportation between customers and depot. *Journal für Betriebswirtschaft*, 58, 21-51.

Parragh, S. N., Doerner, K. F., & Hartl, R. F. (2008b). A survey on pickup and delivery problems Part II: Transportation between pickup and delivery locations. *Journal für Betriebswirtschaft*, 58, 81-117.

Perboli, G., Tadei, R., & Vigo, D. (2011). The two-echelon capacitated vehicle routing problem: Models and math-based heuristics. *Transportation Science*, 45, 364-380.

Pillac, V., Gendreau, M., Guéret, C., & Medaglia, A. L. (2012). A review of dynamic vehicle routing problems. *European Journal of Operational Research*, 225, 1-11.

Pirkwieser, S. & Gunther, R. (2009). Boosting a variable neighborhood search for the periodic vehicle routing problem with time windows by ILP techniques. Proceedings of the 8th Metaheuristic International Conference (MIC 2009), Hamburg, Germany.

Polacek, M., Hartl, R. F., Doerner, K., & Reimann, M. (2004). A variable neighborhood search for the multi depot vehicle routing problem with time windows. *Journal of Heuristics*, 10, 613-627.

Polimeni, A., & Vitetta, A. (2013). Optimising Waiting at Nodes in Time-Dependent Networks: Cost Functions and Applications. *Journal of Optimization Theory and Applications*, 156 (3), 805-818.

Polimeni, A., Russo, F., & Vitetta, A. (2010). Demand and routing models for urban goods movement simulation. *European Transport\Trasporti Europei*, 46, 3-23.

Potvin, J.-Y. (2009). Evolutionary algorithms for vehicle routing. *INFORMS Journal on Computing*, 21, 518-548.

Powell, W. B. (1988). A comparative review of alternative algorithms for the dynamic vehicle allocation problem. In: Golden, B. L., & Assad, A. A. (Eds), *Vehicle routing: methods and studies*, Amsterdam, Netherlands, North-Hollend.

Prescott-Gagnon, E., Desaulniers, G., & Rousseau, L.-M. (2009). A branch-and-price-based large neighborhood search algorithm for the vehicle routing problem with time windows. *Networks*, 54, 190-204.

Prins, C. (2009). A GRASP×evolutionary local search hybrid for the vehicle routing problem. In: Pereira, F. B., & Tavares, J. (Eds), *Bio-inspired Algorithms for the Vehicle Routing Problem*, Springer Berlin Heidelberg.

Privé, J., Renaud, J., Boctor, F., & Laporte, G. (2006). Solving a vehicle-routing problem arising in soft-drink distribution. *Journal of the Operational Research Society*, 57, 1045-1052.

Pronello, C., & André, M. (2000). Pollutant emissions estimation in road transport models (INRETS-LTE Report, vol. 2007).

Psaraftis, H. N. (1980). A dynamic programming solution to the single vehicle many-to-many immediate request dial-a-ride problem. *Transportation Science*, 14, 130-154.

Psaraftis, H. N. (1988). Dynamic vehicle routing problem. In: Golden, B. L., & Assad, A. A. (Eds), *Vehicle routing: methods and studies*, Amsterdam, Netherlands, North-Hollend.

Psaraftis, H. N. (1995). Dynamic vehicle routing: status and prospects. *Annals of Operations Research*, 61, 143-164.

Qureshi, A. G., Taniguchi, E., & Yamada, T. (2009). An exact solution approach for vehicle routing and scheduling problems with soft time windows. *Transportation Research Part E: Logistics and Transportation Review*, 45(6), 960-977.

Qureshi, A. G., Taniguchi, E., & Yamada, T. (2010). Exact solution for the vehicle routing problem with semi soft time windows and its application. *Procedia - Social and Behavioral Sciences*, 2(3), 5931-5943.

Qureshi, A. G., Taniguchi, E., & Yamada, T. (2012). A Microsimulation Based Analysis of Exact Solution of Dynamic Vehicle Routing with Soft Time Windows. *Procedia - Social and Behavioral Sciences*, 39, 205-216.

Ramos, T., & Oliveira, R. (2011). Delimitation of service areas in reverse logistics networks with multiple depots. *Journal of the Operational Research Society*, 62, 1198-1210.

Rei, W., Gendreau, M. & Soriano, P. (2010). A hybrid Monte Carlo local branching algorithm for the single vehicle routing problem with stochastic demands. *Transportation Science*, 44, 136-146.

Renaud, J., Laporte, G., & Boctor, F. F. (1996). A tabu search heuristic for the multi-depot vehicle routing problem. *Computers and Operations Research*, 23, 229-235.

Repoussis, P. P., & Tarantilis, C. D. (2010). Solving the fleet size and mix vehicle routing problem with time windows via adaptive memory programming. *Transportation Research Part C: Emerging Technologies*, 18, 695-712.

Repoussis, P. P., Tarantilis, C. D., & Ioannou, G. (2007). The open routing problem with time windows. *Journal of the Operational Research*, 58, 355-367.

Ribeiro, G. M., & Laporte, G. (2012). An adaptive large neighborhood search heuristic for the cumulative capacitated vehicle routing problem. *Computers & Operations Research*, 39, 728-735.

Rochat, Y., & Semet, F. (1994). A tabu search approach for delivering pet food and flour in Switzerland. *Journal of Operational Research Society*, 45, 1233-1246.

Ropke, S., Cordeau, J.-F., & Laporte, G. (2007). Models and branch-and-cut algorithms for pickup and delivery problems with time windows. *Networks*, 49, 455-472.

Russell, R. (1977). An effective heuristic for the M-Tour traveling salesman problem with some side conditions. *Operations Research*, 25, 517-524.

Russell, R. A. (1995). Hybrid heuristics for the vehicle routing problem with time windows. *Transportation Science*, 29, 156-166.

Salani, M. & Vacca, I. (2011). Branch and price for the vehicle routing problem with discrete split deliveries and time windows. *European Journal of Operational Research*, 213, 470-477.

Salhi, S., & Fraser, M. (1996). An integrated heuristic approach for the combined location vehicle fleet mix problem. Studies in *Locational Analysis*, 8, 3–21.

Salhi, S., & Nagy, G. (1999). A cluster insertion heuristic for single and multiple depot vehicle routing problems with backhauling. *Journal of the Operational Research Society*, 50, 1034-1042.

Salhi, S., & Sari, M. (1997). A multi-level composite heuristic for the multi-depot vehicle fleet mix problem. *European Journal of Operational Research*, 103, 95-112.

Salhi, S., Imran, A., & Wassan, N. A. (2013). The multi-depot vehicle routing problem with heterogeneous vehicle fleet: Formulation and a variable neighborhood search implementation. *Computers & Operations Research*, in press.

Salimifard, K., Shahbandarzaden, H. & Raeesi, R. (2012). Green transportation and the role of operation research. 2012 International Conference on Traffic and Transportation Engineering, Singapore.

Sambracos, E., Paravantis, J. A., Tarantilis, C. D., & Kiranoudis, C. T. (2004). Dispatching of small containers via coastal freight liners: The case of the Aegean Sea. *European Journal of Operational Research*, 152, 365–381.

Sariklis, D., & Powell, S. (2000). A heuristic method for the open vehicle routing problem. *Journal of the Operational Research Society*, 51, 564–573.

Sbihi, A., & Eglese, R. W. (2007a). Combinatorial optimization and green logistics. *4OR: A Quarterly Journal of Operations Research*, 5, 99-116.

Sbihi, A., & Eglese, R. W. (2007b). The relationship between vehicle routing and scheduling and green logistics – a literature survey. Working paper, Department of Management Science, Lancaster University Management School, LA14YX, UK.

Schneider, M., Stenger, A., & Goeke D. (2012). The Electric Vehicle Routing Problem with Time Windows and Recharging Stations. Technical Report, University of Kaiserslautern, Kaiserslautern, Germany.

Schrage, L. (1981). Formulation and structure of more complex/realistic routing and scheduling problems. *Networks*, 11, 229–32.

Schultmann, F., Zumkeller, M., & Rentz, O. (2006). Modeling reverse logistic tasks within closed-loop supply chains: An example from the automotive industry. *European Journal of Operational Research*, 171, 1033-1050.

Sculli, D., Mok, K. C., & Cheung, S. H. (1987). Scheduling vehicles for refuse collection. *Journal of the Operational Research Society*, 38, 233-239.

Semet, F., & Tailard, E. (1993). Solving real-life vehicle routing problems efficiently using tabu search. *Annals of Operations Research*, 41, 469-488.

Soler, D., Albiach, J., & Martínez, E. (2009). A way to optimally solve a time-dependent Vehicle Routing Problem with Time Windows. *Operations Research Letters*, 37(1), 37-42.

Solomon, M. M. (1987). Algorithms for the vehicle routing and scheduling problems with time window constraints. *Opeartions Research*, 35, 254-265.

Speidel, V. (1976). EDP-assisted fleet scheduling in tramp and coastal shipping. Proceedings of the 2nd International Ship Operation Automation Symposium, Washington, D.C., August 30-September 2.

Speranza, M. G. (1996). Ukovich W. An algorithm for optimal shipments with given frequencies. *Naval Research Logistics 1996*, 43(5), 655–71.

Srivastava, S. K. (2008). Network design for reverse logistics. *Omega*, 36, 535-548.

Stenger, A., Vigo, D., Enz, S., & Schwind, M. (2013). An adaptive variable neighborhood search algorithm for a vehicle routing problem arising in small package shipping. *Transportation Science*, 47, 64-80.

Taillard, É. D. (1993). Parallel Iterative Search Methods for Vehicle Routing Problems. *Networks*, 23, 661-676.

Tang, J., Pan, Z., Fung, R. Y. K., & Lau, H. (2009). Vehicle routing problem with fuzzy time windows. *Fuzzy Sets and Systems*, 160, 683-695.

Tarantilis, C. D., Zachariadis, E. E., & Kiranoudis, C. T. (2009). A hybrid metaheuristic algorithm for the integrated vehicle routing and three-dimensional container-loading problem. *IEEE Transaction on Intelligent Transportation Systems*, 10, 255-271.

Tasan, A. S., & Gen, M. (2011). A genetic algorithm based approach to vehicle routing problem with simultaneous pick-up and deliveries. *Computer & Industrial Engineering*, in press.

Taveares, G., Zaigraiova, Z., Semiao, V., & da Graca Carvalho, M. (2008). A case study of fuel savings through optimization of MSW transportation routes. *Management of Environmental Quality: An International Journal*, 19, 444–454.

Teodorović, D., & Pavković, G. (1996). The fuzzy set theory approach to the vehicle routing problem when demand at nodes is uncertain. *Fuzzy Sets and Systems*, 82, 307-317.

Tillman, F. A. (1969). The multiple terminal delivery problem with probablistic demands. *Transportation Science*, 3, 192-204.

Toth. P., & Vigo, D. (2002). *The Vehicle Routing Problem*, SIAM Monographs on Discrete mathematics and Applications, Philadelphia.

Tricoire, F., Doerner, K. F., Hartl, R. F., & Iori, M. (2011). Heuristic and exact algorithm for the multi-pile vehicle routing problem. *OR Spectrum*, 33, 931-959.

Tsiligirides, T. (1984). Heuristic methods applied to orienteering. *Journal of the Operational Research Society*, 35, 797–809.

Ubeta, S., Arcelus, F. J., & Faulin, J. (2011). Green logistics at Eroski: A case study. *International Journal of Production Economics*, 131, 44-51.

US Department of Energy (2008). Fuel economy guide. <http://www.fueleconomy.gov>.

Vidal T., Crainic, T. G., Gendreau, M., & Prins, C. (2013). A hybrid genetic algorithm with adaptive diversity management for a large class of vehicle routing problems with time-windows. *Computers & Operations Research*, 40, 475-489.

Vidal, T., Crainic, T. G., Gendreau, M., Lahrichi, N., & Rei, W. (2012). A hybrid genetic algorithm for multidepot and periodic vehicle routing problems. *Operations Research*, 60, 611-624.

Wang, C.-H., & Lu, J.-Z. (2009). A hybrid genetic algorithm that optimizes capacitated vehicle routing problems. *Expert Systems with Applications*, 36, 2921-2936.

Wasner, M., & Zäpfel, G. (2004). An integrated multi-depot hub-location vehicle routing model for network planning of parcel service. *Internaitonal Journal of Production Economics*, 90, 403-419.

Wassan, N. A., & Osman, I. H. (2002). Tabu search variants for the mix fleet vehicle routing problem. *Journal of the Operational Research Society*, 53, 768-782.

Watson-Gandy, C., & Dohm, P. (1973). Depot location with van salesmen - A practical approach. *Omega*, 1, 321-329.

Wen, M., Krapper, E., Larsen, J., & Stidsen, T. K. (2011). A multilevel variable neighborhood search heuristic for a practical vehicle routing and driver scheduling problem. *Networks*, 58, 311-322.

Wen, M., Larsen, J., Clausen, J., Cordeau, J. F., & Laporte, G. (2009). Vehicle routing with cross-docking. *Journal of the Operational Research Society*, 60, 1708–1718.

Wilson, H., & Weissberg, H. (1967). Advanced dial-a-ride algorithms research project: Final report. Technical Report. R76-20, Department of Civil Engineering, MIT, Cambridge, MA.

Wu, T., Low, C., & Bai, J. (2002). Heuristic solutions to multi-depot location-routing problems. *Computers & Operations Research*, 29, 1393.

Xiao, Y., Zhao, Q., Kaku, I., & Xu, Y. (2012). Development of a fuel consumption optimization model for the capacitated vehicle routing problem. *Computers & Operations Research*, 39(7), 1419-1431.

Xu, J., Yan, F., & Li, S. (2011). Vehicle routing optimization with soft time windows in a fuzzy random environment. *Transportation Research Part E*, 47, 1075-1091.

Yang, J., Jaillet, P., & Mahmassani, H. (2004). Real-time multivehicle truckload pickup and delivery problems. *Transportation Science*, 38, 135-148.

Yu, B., & Yang, Z. Z. (2011). An ant colony optimization model: The period vehicle routing problem with time windows. *Transportation Research Part E: Logistics and Transportation Review*, 47, 166-181.

Yu, B., Yang, Z.-Z., & Yao, B. (2009). An improved ant colony optimization for vehicle routing problem. *European Journal of Operational Research*, 196, 171-176.

Zachariadis, E. E., Tarantilis, C. D., & Kiranoudis, C. T. (2009). A guided tabu search for the vehicle routing problem with two-dimensional loading constraints. *European Journal of Operational Research*, 195, 720-743.

Zachariadis, E. E., Tarantilis, C. D., & Kiranoudis, C. T. (2011). The pallet-packing vehicle routing problem. *Transportation Science*, in press.

Zhang, X., & Tang, L. (2007). Disruption management for the vehicle routing problem with time windows. *Advanced Intelligent Computing Theories and Applications with Aspects of Contemporary Intelligent Computing Techniques, Communications in Computer and Information Science*, 2007, vol. 2, Part 5, 225-234.

Zhao, Q.-H., Chen, S., & Zang, C.-X. (2008). Model and algorithm for inventory/routing decision in a three-echelon logistics system. *European Journal of Operational Research*, 191, 623-635.

Zhao, Q.-H., Wang, S.-Y., & Lai, K. K. (2007). A partition approach to the inventory/routing problem. *European Journal of Operational Research*, 177, 786-802.

Zheng, Y. & Liu, B. (2006). Fuzzy vehicle routing model with credibility measure and its hybrid intelligent algorithm. *Applied Mathematics and Computation*, 176, 673-683.

Appendix: Mathematical models for CVRP and VRPTW

(1) The formulation of CVRP (Fisher and Jaikumar, 1981)

Constants

K	The number of vehicles.
n	The number of all customer nodes. All customers are indexed from 1 to n and the central depot is denoted as index 0.
b_k	The capacity of vehicle k .
a_i	The weight or volume of the shipment to customer i .
c_{ij}	The cost of direct travel from customer i to customer j .

Decision variables

y_{ik}	y_{ik} equals 1 if the order from customer i is delivered by vehicle k . Otherwise, y_{ik} equals 0.
x_{ijk}	x_{ijk} equals 1 if vehicle k travels directly from customer i to customer j . Otherwise, x_{ijk} equals 0.

The mathematical model

$$\min \sum_{ijk} c_{ij} x_{ijk} \tag{1}$$

s.t.

$$\sum_i a_i y_{ik} \leq b_k, \qquad k = 1,...,K \tag{2}$$

$$\sum_k y_{ik} = \begin{cases} K, & i = 0 \\ 1, & i = 1,...,n \end{cases} \tag{3}$$

$$y_{ik} \in \{0,1\}, \qquad i = 0,...,n; \quad k = 1,...,K \tag{4}$$

$$\sum_i x_{ijk} = y_{jk}, \qquad j = 0,...,n; \quad k = 1,...,K \tag{5}$$

$$\sum_j x_{ijk} = y_{ik}, \qquad i = 0,...,n; \quad k = 1,...,K \tag{6}$$

$$\sum_{ij \in S \times S} x_{ijk} \leq |S| - 1, \qquad S \subseteq \{1,...,n\}; \ 2 \leq |S| \leq n-1; \ k = 1,...,K \tag{7}$$

$$x_{ijk} \in \{0,1\}, \qquad i = 0,...,n; \ j = 0,...,n; \ k = 1,...,K \tag{8}$$

The objective function (1) aims at minimizing the total cost of transportation. Constraints (2) – (4) are the constraints of a generalized assignment problem, ensuring that the load assigned to a vehicle does not exceed the vehicle capacity, that each vehicle starts and ends at the depot, and that each customer is visited by some vehicle. Constraint (5) – (8) define a traveling salesman problem over the customers that have been assigned to a given vehicle k .

(2) The formulation of VRPTW (Ioannou et al., 2001)

Constants

V	The set of available identical vehicles.
C	The capacity of vehicle.
L	The set of customers including the depot. Index $i=1$ refers to the depot while indices i, j and u valued between 2 and n denote the customers.
q_i	The demand of customer i.
$[e_i, l_i]$	The time window requested by customer i, where e_i represents the earliest service starting time and l_i refers to the latest service starting time.
s_i	The service time of customer i.
t_{ij}	The travel time directly from customer i to customer j.
c_{ij}	The cost of direct travel from customer i to customer j.
w_k	The fixed cost of activating vehicle k.

Variables

a_i	The arrival time to customer i.
p_i	The departure time from customer i.

Decision variables

x_{ij}^k	x_{ij}^k equals 1 if customer i follows customer j in the sequence of customers visited by vehicle k. Otherwise, x_{ij}^k equals 0.
z_k	z_k equals 1 if vehicle k is activated. Otherwise, z_k equals 0.

The mathematical model

$$\min \sum_{k=1}^{|V|} \sum_{i=1}^{n} \sum_{j=1}^{n} c_{ij} x_{ij}^k + \sum_{k=1}^{|V|} w_k z_k \tag{9}$$

s.t.

$$\sum_{i=1}^{n} \sum_{k=1}^{|V|} x_{ij}^k = 1, \qquad \forall j = 2,3,...,n \tag{10}$$

$$\sum_{j=1}^{n} \sum_{k=1}^{|V|} x_{ij}^k = 1, \qquad \forall i = 2,3,...,n \tag{11}$$

$$x_{ij}^k \le z_k, \qquad \forall i,j = 1,2,...,n \tag{12}$$

$$\sum_{j=2}^{n} x_{1j}^k \le 1, \qquad \forall k = 1,2,...,|V| \tag{13}$$

$$\sum_{i=2}^{n} x_{i1}^k \le 1, \qquad \forall k = 1,2,...,|V| \tag{14}$$

$$\sum_{i=2}^{n} x_{iu}^{k} - \sum_{j=2}^{n} x_{uj}^{k} = 0, \qquad \forall k = 1,...,|V|; \ \ \forall u = 1,...,n \qquad (15)$$

$$\sum_{i \in F} \sum_{j \in F} x_{ij}^{k} \leq \sum_{i \in F} \sum_{j \in L} x_{ij}^{k} - 1, \qquad \forall F \subseteq L; \ 2 \leq |F| \leq \sum_{i \in L} \sum_{j \in L} x_{ij}^{k}, \forall k \in V \qquad (16)$$

$$\sum_{i=1}^{n} q_i (\sum_{j=1}^{n} x_{ij}^{k}) \leq C, \qquad \forall k = 1, 2,...,|V| \qquad (17)$$

$$a_j \geq (p_i + t_{ij}) - (1 - x_{ij}^{k})M, \ \ \forall i, j = 1, 2,...,n; \ \ \forall k = 1, 2,...,|V| \qquad (18)$$

$$a_j \leq (p_i + t_{ij}) + (1 - x_{ij}^{k})M, \ \ \forall i, j = 1, 2,...,n; \ \ \forall k = 1, 2,...,|V| \qquad (19)$$

$$a_i \leq p_i - s_i, \qquad \forall i = 1,...,n \qquad (20)$$

$$e_i \leq p_i \leq l_i, \qquad \forall i = 1,...,n \qquad (21)$$

$$a_1 = 0 \qquad (22)$$

$$x_{ij}^{k} \in \{0,1\}, \qquad \forall i, j = 1,...,n; \ \ \forall k = 1, 2,...,|V| \qquad (23)$$

$$z_k \in \{0,1\}, \qquad \forall k = 1, 2,...,|V| \qquad (24)$$

The objective function (9) formulates the trade-off between transportation and vehicle activation cost. Constraint (10) and (11) guarantee that every customer is serviced by exactly one vehicle. Constraint (12) ensures that no customers can be serviced by inactive vehicles. Constraint (13) and (14) bound the number of arcs, related to each vehicle directly leaving from and returning to the depot, to less than one, respectively. Constraint (15) accounts for the flow conservation equation that ensures the continuity of each vehicle route. Constraint (16) eliminates sub-tours. Constraint (17) limits the total load of each vehicle not larger than the vehicle capacity. Constraint (18) and (19) make sure that if customers j follows customer i in the route, the arrival time at customer j is equal to the departure time from customer i, plus the travel time between these two customers. Constraint (20) and (21) relate arrival time, departure time, and service time and guarantee that their relationships are compatible to the time window. Constraint (22) means the departure time from the depot is zero. Constraint (23) and (24) enforce x_{ij}^{k} and z_k as binary variables.

List of Tables

Table 1

The papers reviewed in this study

Year	Number of papers	The list of the papers	The studied VRP variants
1959	1	Dantzig and Ramser;	CVRP
1964	1	Clark and Wright;	CVRP
1966	1	Cooke and Halsey;	TDVRP
1967	1	Wilson and Weissberg;	PDP
1969	1	Tillman;	SVRP, MDVRP
1973	1	Watson-Gandy and Dohm;	LRP
1974	1	Beltrami and Bodin;	PVRP
1976	1	Speidel;	DVRP
1977	1	Russell;	VRPTW
1978	2	Cook and Russell; Golden and Stewart;	SVRP
1979	1	Christofides et al.;	
1980	1	Psaraftis;	DVRP
1981	2	Fisher and Jaikumar; Schrage;	VRPTW, CVRP
1983	2	Bell et al.; Bodin et al.;	IRP, TSP
1984	2	Golden et al.; Tsiligirides;	FSMVRP, Generalized VRP
1985	3	Christophides; Dror et al.; Jézéquel;	MCVRP, SVRP
1986	2	Dror and Levy; Nag;	IRP, Site-dependent VRP
1987	4	Dror and Ball; Jaillet; Sculli et al.; Solomon;	IRP, SVRP, VRPTW
1988	3	Jaillet and Odoni; Powell; Psaraftis;	SVRP, DVRP
1989	2	Balas; Dror and Trudeau;	Generalized VRP, SDVRP
1990	1	Laporte and Martello;	Generalized VRP
1992	5	Bertsimas; Laporte; Laporte et al.; Malandraki and Daskin; Min et al.;	SVRP, MDVRP, TDVRP
1993	4	Dror et al.; Lambert et al.; Semet and Tailard; Taillard;	SVRP, Site-dependent VRP
1994	2	Fisher; Rochat and Semet;	Site-dependent VRP
1995	8	Bloemhof-Ruwaard et al.; Cheng et al.; Frizzell and Giffin; Gelinas et al.; Gendreau et al.; Madsen et al.; Psaraftis; Russell;	FVRP, SDVRP, SVRP, PDP, DVRP, VRPTW
1996	7	Bertsimas and Simchi-Levi; Chao et al.; Gendreau et al.; Renaud et al.; Salhi and Fraser; Speranza; Teodorović and Pavković;	Generalized VRP, SVRP, MDVRP, FSMVRP, IRP, FVRP, DVRP
1997	3	Daniel et al.; Fleischmann et al.; Salhi and Sari;	MDVRP
1998	6	Cater and Ellram; Gendreau and Potvin; Golden et al.; Hadjiconstantinou and Baldacci; Mansini and Speranza; Min et al.;	PVRP, MCVRP, LRP, DVRP

1999	4	Fagerholt; Gendreau et al.; Liu and Shen; Salhi and Nagy;	FSMVRP, **G-VRP**, MDVRP, DVRP
2000	5	Ghiani and Improta; Irnich; Laporte et al.; Pronello and André; Sariklis and Powell;	Generalized VRP, FSMVRP, OVRP
2001	4	Cordeau et al; Dethloff; Ioannou et al.; Li and Lim;	**VRPRL**, VRPTW
2002	7	Angelelli and Speranza; Bertazzi and Speranza; Cordeau et al.; Giosa et al.; Toth and Vigo; Wassan and Osman; Wu et al.;	MDVRP, IRP, FSMVRP
2003	4	Blakeley et al.; Chajakis and Guignard; Ghiani et al.; Iori et al.;	PVRP, MCVRP, VRPLC, DVRP
2004	10	Beullens et al.; Brandão; Campbell and Savelsbergh; Dekker et al.; Ho and Haugland; Moura and Oliveira; Polacek et al.; Sambracos et al.; Wasner and Zäpfel; Yang et al.;	SDVRP, VRPLC, MDVRP, OVRP, IRP, **G-VRP**, DVRP
2005	7	Chao and Liou; Feillet et al.; Kallehauge et al.; Li; Nagy and Salhi; Bräysy and Gendreau (a); Bräysy and Gendreau (b)	Site-dependent VRP, Generalized VRP, MDVRP, VRPTW
2006	18	Archetti et al.; Bélanger et al.; Blanc et al.; Bukchin and Sarin; Chen et al.; Chen and Xu; Dell'Amico et al. (a); Dell'Amico et al. (b); Francis and Smilowitz; Francis et al.; Gendreau et al.(a); Gendreau et al.(b); Jang et al.; Lee et al.; Min et al.; Privé et al.; Schultmann et al.; Zheng and Liu;	**VRPRL**, SDVRP, PVRP, MCVRP, FSMVRP, VRPLC, MEVRP, FVRP, TDVRP, DVRP
2007	24	Alegre et al.; Alshamrani et al.; Archetti et al.; Cordeau et al.; Carrabs et al.; Crevier et al.; Doerner et al.; Dondo and Cerdá; Ichoua et al.; Iori et al.; Kara et al.; Laporte; Li et al. (a); Li et al. (b); Marinakis and Migdalas; McKinnon; Nagy and Salhi; Palmer; Repoussis et al.; Ropke et al.; Sbihi and Eglese (a); Sbihi and Eglese (b); Zhang and Tang; Zhao et al.;	**G-VRP**, **PRP**, **VRPRL**, Site-dependent VRP, IRP, MDVRP, VRPLC, FSMVRP, OVRP, LRP, DVRP, PDP, VRPTW
2008	25	Alonso et al.; Apaydin and Gonullu; Baldacci et al. (a); Baldacci et al. (b); Bräysy et al.; Cheung et al.; El Fallahi et al.; Gendreau et al. (a); Gendreau et al.(b); Golden et al.; Gribkovskaia et al.; Kallehauge; Krikke et al.; Krumke et al.; Malapert et al.; Maras̆; Moura; Nanthavanij et al.; Oppen and Løkketangen; Paraskevopoulos et al.; Parragh et al. (a); Parragh et al. (b); Srivastava; Taveares et al.; Zhao et al.;	**G-VRP**, **VRPRL**, Site-dependent VRP, FSMVRP, MCVRP, VRPLC, VRPTW, IRP, PDP, IRP, DVRP
2009	25	Baldacci and Mingozzi; Baldacci et al.; Bräysy et al.; Crainic et al.; Erbao and Mingyong; Figliozzi; Fuellerer et al.;	**VRPRL**, FSMVRP, MEVRP, FVRP, VRPLC, DVRP, PVRP, MEVRP,

		Khebbache et al.; Kim et al.; Laporte; Li et al.(a); Li et al.(b); Liu et al.; Pirkwieser and Gunther; Potvin; Prescott-Gagnon et al.; Prins; Qureshi et al.; Soler et al.; Tang et al.; Tarantilis et al; Wang and Lu; Wen et al.; Yu et al.; Zachariadis et al.;	VRPTW, OVRP, TDVRP
2010	23	Andersson et al.; Angelelli et al.; Azi et al.; Baldacci et al. (a); Baldacci et al. (b); Bauer et al.; Çatay; Christensen and Rousøe; Erbao and Mingyong; Fagerholt et al.; Figliozzi; Fuellerer et al.; Gajpal and Abad; Li et al.; Liao et al.; Maden et al.; Mendoza et al.; Muyldermans and Pang; Polimeni and Vitetta; Qureshi et al.; Rei et al.; Repoussis and Tarantilis; Kuo;	**G-VRP**, **VRPRL**, **PRP**, IRP, Generalized VRP, Site-dependent VRP, VRPLC, FVRP, SVRP, MEVRP, MCVRP, FSMVRP, DVRP, VRPTW, PDP
2011	26	Aras et al.; Archetti et al.; Baldacci et al.; Bektaş and Laporte; Belenguer et al.; Bortfeldt; Brandão; Cappanera et al.; Derigs et al.; Duhamel et al.; Faulin et al.; Leung et al.; Mar-Ortiz et al.; Mu and Eglese; Mu et al.; Pang; Perboli et al.; Ramos and Oliveira; Salani and Vacca; Tasan and Gen; Tricoire et al.; Ubeta et al.; Wen et al.; Xu et al.; Yu and Yang; Zachariadis et al.;	**VRPRL**, **PRP**, SDVRP, LRP, MDVRP, VRPLC, Site-dependent VRP, MCVRP, DVRP, MEVRP, FVRP, FSMVRP, VRPTW, PVRP
2012	23	Baldacci et al.; Coelho et al.; Cordeau and Maischbergr; Demir et al.; ErdoÄŸan and Miller-Hooks; Figliozzi; Hemmelmayr et al.; Hong; Jin et al.; Kok et al.; Kritzinger et al.; Kuo and Wang; Li et al.; Marinakis; Mingozzi et al.; Moccia et al.; Pillac et al.; Qureshi et al.; Ribeiro and Laporte; Salimifard et al.; Schneider et al.; Vidal et al.; Xiao et al.;	**G-VRP**, **PRP**, IRP, OVRP, MDVRP, TDVRP, MEVRP, DVRP, VRPTW, PVRP
2013	10	Baldacci et al.; Baños et al.; Berbotto et al.; Dondo and Cerdá; Lecluyse et al.; Nguyen et al.; Polimeni and Vitetta; Salhi et al.; Stenger et al.; Vidal et al.;	MEVRP, VRPTW, SDVRP, TDVRP, MDVRP

Note. CVRP, Capacitated VRP; TDVRP, Time-dependent VRP; PDP, Pickup and Delivery Problem; MDVRP, Multi-depot VRP; SVRP, Stochastic VRP; LRP, Location Routing Problem; PVRP, Periodic VRP; DVRP, Dynamic VRP; VRPTW, VRP with Time Windows; IRP, Inventory Routing Problem; FSMVRP, Fleet Size and Mix Vehicle Routing Problem; MCVRP, Multi-compartment VRP; SDVRP, Split-delivery VRP; FVRP, Fuzzy VRP; OVRP, Open VRP; VRPLC, VRP with Loading Constraints; MEVRP, Multi-echelon VRP; G-VRP, Green-VRP; PRP, Pollution Routing Problem; VRPRL, VRP in Reverse Logistics.

Table 2

The algorithms for *VRP* and recent related papers

Algorithms	Papers
Exact algorithms	Baldacci et al., 2008b; Baldacci and Mingozzi, 2009; Qureshi et al., 2009; Azi et al., 2010; Baldacci et al., 2012; Mingozzi et al., 2012; Baldacci et al., 2013
Classical heuristics	Li et al., 2007a; Gajpal and Abad, 2010; Figliozzi, 2010; Pang, 2011; Dondo and Cerdá, 2013
TS	Brandão, 2011; Cordeau and Maischberger, 2012; Jin et al., 2012; Moccia et al., 2012; Nguyen et al., 2013; Berbotto et al., 2013
SA	Kuo, 2010; Baños et al., 2013
GRASP	Prins, 2009; Marinakis, 2012
VNS	Paraskevopoulos et al., 2008; Wen et al., 2011; Kuo and Wang, 2012; Stenger et al., 2013; Salhi et al., 2013
LNS	Prescott-Gagnon et al., 2009; Hemmelmayr et al., 2012; Ribeiro and Laporte, 2012
GA	Liu et al., 2009; Wang and Lu, 2009; Vidal et al., 2012; Vidal et al., 2013
ACO	Yu et al., 2009; Fuellerer et al., 2009; Li et al., 2009b; Yu and Yang, 2011

Table 3

The main benchmark instances for *VRP*

VRP variants	Benchmark test instances
Capacitated VRP	Christofides et al., 1979
	Taillard, 1993
	Fisher, 1994
	Golden et al., 1998
VRP with Time Windows	Solomon, 1987
	Russell, 1995
Pickup and Delivery Problem with Time Windows	Li and Lim, 2001
	Ropke et al., 2007
Multi-depot VRP with Time Windows	Cordeau et al., 2001
Periodic VRP with Time Windows	Cordeau et al., 2001
VRP with Backhauls and Time Windows	Gelinas et al., 1995

Table 4

Recent studies of *G-VRP* during 2007-2012

VRP variants	Papers (Total: 5)
Basic VRP or TSP	ErdoÄŸan and Miller-Hooks, 2012
Capacitated VRP	Kara et al., 2007; Yiyo, 2010; Xiao et al., 2012
VRP with Time Windows	Schneider et al., 2012

Table 5

Recent studies of *PRP* during 2007-2012

VRP variants	Papers (Total: 6)
Basic VRP or TSP	Bauer et al., 2012;
Capacitated VRP	Faulin et al., 2011;
VRP with Time Windows	Palmer, 2007; Fagerholt et al., 2010; Bektaş and Laporte, 2011;
VRP with Clustered Backhauls	Ubeda et al., 2010;

Table 6

Recent studies of *VRPRL*

VRP variants	Papers (Total: 17)
Selective Pickups with Pricing (Total: 3)	
Capacitated VRP	Aras et al., 2011;
VRP with Time Windows	Privé et al., 2006;
VRP with Simultaneous Delivery and Pickup	Privé et al., 2006;
Multi-deopt VRP	Aras et al., 2011;
Mix Fleet VRP	Privé et al., 2006;
Generalized VRP	Gribkovskaia et al., 2008; Aras et al., 2011;
Waste Collection (Total: 4)	
Multi-deopt VRP	Ramos and Oliveira, 2011;
Mix Fleet VRP	Mar-Ortiz et al., 2011;
Location Routing Problem	Mar-Ortiz et al., 2011;
Site-dependent VRP	Sculli et al., 1987;
Multi-compartment VRP	Mansini And Speranza, 1998;
End-of-life Goods Collection (Total: 5)	
Capacitated VRP	Schultmann et al., 2006;

|	Kim et al., 2009; Kim et al., 2011;
Multi-depot VRP	Blanc et al., 2006; Kim et al., 2011;
Inventory Routing Problem	Krikke et al., 2008;
Simultaneous Distribution and Collection (Total: 5)	
VRP with Simultaneous Delivery and Pickup	Dethloff, 2001; Dell'Amico et al., 2006; Alshamrani et al., 2007; Çatay, 2010; Tasan and Gen, 2011;

List of Figures

**Fig. 1** The distribution of papers by year

Note. CVRP, Capacitated VRP; TDVRP, Time-dependent VRP; PDP, Pickup and Delivery Problem; MDVRP, Multi-depot VRP; SVRP, Stochastic VRP; LRP, Location Routing Problem; PVRP, Periodic VRP; DVRP, Dynamic VRP; VRPTW, VRP with Time Windows; IRP, Inventory Routing Problem;

FSMVRP, Fleet Size and Mix Vehicle Routing Problem; MCVRP, Multi-compartment VRP; SDVRP, Split-delivery VRP; FVRP, Fuzzy VRP; OVRP, Open VRP; VRPLC, VRP with Loading Constraints; MEVRP, Multi-echelon VRP; G-VRP, Green-VRP; PRP, Pollution Routing Problem; VRPRL, VRP in Reverse Logistics.

Fig. 2 The philosophy of the review work

Fig. 3 Classification of the Pickup and Delivery Problem

Fig. 4 The algorithms for *VRP* and their relation

Note. CVRP, Capacitated VRP; TDVRP, Time-dependent VRP; PDP, Pickup and Delivery Problem; MDVRP, Multi-depot VRP; SVRP, Stochastic VRP; LRP, Location Routing Problem; PVRP, Periodic VRP; DVRP, Dynamic VRP; VRPTW, VRP with Time Windows; IRP, Inventory Routing Problem; FSMVRP, Fleet Size and Mix Vehicle Routing Problem; MCVRP, Multi-compartment VRP; SDVRP, Split-delivery VRP; FVRP, Fuzzy VRP; OVRP, Open VRP; VRPLC, VRP with Loading Constraints; MEVRP, Multi-echelon VRP; G-VRP, Green-VRP; PRP, Pollution Routing Problem; VRPRL, VRP in Reverse Logistics.

Fig. 5 A landscape of the state-of-the-art of *VRP*

3

Survey of Green Vehicle Routing Problem: Past and future trends

Canhong Lin

Department of Industrial and Systems Engineering,

The Hong Kong Polytechnic University, Hunghom, Hong Kong

Email: 11901643r@connect.polyu.hk

K.L. Choy*

Department of Industrial and Systems Engineering,

The Hong Kong Polytechnic University, Hunghom, Hong Kong

Email: mfklchoy@inet.polyu.edu.hk

G.T.S. Ho

Department of Industrial and Systems Engineering,

The Hong Kong Polytechnic University, Hunghom, Hong Kong

Email: george.ho@polyu.edu.hk

S.H. Chung

Department of Industrial and Systems Engineering,

The Hong Kong Polytechnic University, Hunghom, Hong Kong

Email: mfnick@inet.polyu.edu.hk

H.Y. Lam

Department of Industrial and Systems Engineering,

The Hong Kong Polytechnic University, Hunghom, Hong Kong

Email: Cathy.Lam@connect.polyu.hk

*Correspondence Address:

Dr K.L. Choy

Department of Industrial and Systems Engineering

The Hong Kong Polytechnic University

Hung Hom, Kowloon

Hong Kong

Email: mfklchoy@inet.polyu.edu.hk

Tel: (852) 2766 6597

Fax: (852) 2362 5267

Research Highlights:

- To reflect the environmental sensitivity of Vehicle Routing Problem (VRP)

- To review the studies on VRP in energy consumption, emissions, reverse logistics

- To identify Green Vehicle Routing Problem (GVRP) and its classification

- To suggest the future research directions in GVRP