

GJØVIK UNIVERSITY COLLEGE

BACHELOR THESIS

Snowman

A complete, effective and secure rule management system for SNORT®

Authors:
Thomas NYHEIM
Eirik SKOGSTAD
Eigil OBRESTAD

Supervisor:
Slobodan PETROVIC

April 19, 2014

Preface

This is the preface.

Glossary

HDD Hard disk drive.

MD5 A cryptographic hash function producing a 128-bit hash value.

RAM Random access memory.

RPM Rounds per minute.

SSD Solid state drive.

URL Uniform resource locator.

Contents

Preface . . . . . **i**
Glossary . . . . . **ii**
Contents . . . . . **iii**
List of Figures . . . . . **v**
List of Tables . . . . . **vi**
1 INTRODUCTION **1**
1.1 Document Structure 1
1.2 Project Background 1
1.3 Previous Work 1
1.4 Target Audence 2
1.5 Project Objectives 2
1.6 Project Description 3
1.7 Academic Background 4
1.8 Framework 4
1.8.1 Software Development Methodology 4
1.8.2 Schedule 4
1.8.3 Project Organization 4
2 EXISTING SOLUTIONS **5**
3 REQUIREMENTS SPECIFICATION **6**
3.1 Functional Requirements 6
3.1.1 Program Workflow 6
3.1.2 Use Case Diagram 8
3.1.3 Domain Model 8
3.2 Supplemental Requirements 8
3.2.1 Functionality 8
3.2.2 Usability 8
3.2.3 Reliability 8
3.2.4 Performance 9
3.2.5 Security 9
3.2.6 Interoperability 9
3.3 Constraints 9
3.3.1 Platform 9
3.3.2 Data security 9
3.3.3 Graphical User Interface 10
4 DESIGN **11**
5 IMPLEMENTATION **12**
5.1 Frameworks 12
5.2 Concepts of Snort® 12
5.2.1 Rules 12
5.2.2 Rule sets 12

5.2.3 Generators . . . 12
5.2.4 Reference Types . . . 12
5.2.5 Event and detection filters . . . 12
5.3 Core module . . . 13
5.4 Update module . . . 13
5.4.1 Sources . . . 14
5.4.2 Files . . . 14
5.4.3 Running an update . . . 15
5.4.4 Rule parsing . . . 15
5.4.5 Classification, Generator and Reference Type parsing . . . 16
5.4.6 Logging . . . 16
5.5 Graphical User Interface . . . 16
5.5.1 Structure . . . 16
5.5.2 Design . . . 16
5.5.3 Features . . . 16
5.5.4 Rules/All rules page . . . 17
6 OPTIMIZATION . . . 18
6.1 Update . . . 18
7 SOFTWARE TESTING . . . 19
8 PERFORMANCE TESTING . . . 20
8.1 Definitions . . . 20
8.2 Environment . . . 20
8.3 Test suites . . . 21
8.3.1 Update processing . . . 21
9 RESULTS . . . 22
10 ANALYSIS OF RESULTS . . . 24
11 CONCLUSIONS . . . 25
Bibliography . . . 26

List of Figures

1 Program Workflow 6
2 Program Modules 7
3 Flow 13
4 GUI Structure 16
5 Rules/All rules page 17

List of Tables

1 Effects of different filter types. 13
2 Rule options used in this system. 14
3 Test systems. 20
4 Test cases in Test 1. 21
5 Test results for update processing. 23

1 INTRODUCTION

Følgende informasjon kan tas med her: - Organisering av rapporten og kort beskrivelse av sammenhengen mellom kapitlene. - Fullstendig definering av oppgaven med utdypning av hva oppgaven går ut på. Eksempelvis presiseres mål, problemområde, omfang og avgrensning. - Henvisning til eventuelle tidligere arbeider om samme emne. - Målgruppe for rapporten, jfr. mål- og mottakeranalysen. - Studentenes faglige bakgrunn. - Prosjektgruppens valgte arbeidsformer, f.eks. samtaler og intervjuer med kilder, reiser, bedriftsbesøk, litteraturstudier, laboratorieforsøk, modellbygging og testing. - Terminologibruk. Er eksempelvis faguttrykk brukt i en spesiell betydning? Innledningen skal ikke inneholde noe om det som er gjort i oppgaven og oppnådde resultater.

1.1 Document Structure

How have we organized this document

1.2 Terminology

Put explainations of difficult terms here.

1.3 Project Background

The Norwegian Armed Forces Cyber Defense (CYFOR) unit for Computer Network Defense (CND), Avdeling BKI, is responsible for detecting and stopping cyber-attacks against the critical infrastructure and command and control systems utilized by the Norwegian military. One of the tools used to carry out this task is the open source Intrusion Detection System (IDS) SNORT® (1).

SNORT® is a leading open source IDS that is used to detect potentially unwanted or malicious network traffic based on predefined patterns described in signatures. There are both free and commercial signatures available for SNORT® and as SNORT® has been highly adopted by the security community, these signatures are continually updated and maintained. Using SNORT® has been plagued for years by the fact that it does not have a good system for handling, updating or maintaining the signatures (henceforth called rules and rule sets) used for detection, thus making it cumbersome to utilize SNORT® for security analysts.

Avdeling BKI has therefore tasked a group of students from GUC to design and develop a more complete, effective and secure rule management system for SNORT® that can continue to live on beyond this project.

1.4 Previous Work

Research has shown that a good rule management system for SNORT® will improve the workflow and efficiency of the IDS significantly and a prototype for such a system was built in 2012 called Bring Home The Bacon (BHTB) (2). This prototype has been in use at Avdeling BKI since 2012, but is suffering from lacks in functionality and efficiency due to being a proof-of-concept prototype. The prototype did, however, prove that there is a significant gain from having an intuitive Graphical User Interface (GUI) by making the

operator workflow much more efficient, as you go from having to do complex operations in a Command Line Interface (CLI) to just push buttons to make the system do things automagically (2).

There was another similar project conducted at Gjøvik University College (GUC) in 2012 called Snortmanager (3) that also deals with managing SNORT® rules. However, that project is not properly released as open source software, the project files are available but there is no documentation or instructions publically available that describes usage and installation. The project has also not been maintained since its initial release, is designed for a specific company in mind and is heavily designed around the user interface. Enabling, disabling and configuring rules is also cumbersome in this system as this is based on plaintext arguments in "policies" that users must construct themselves. The rule distribution is also done manually 4from the files generated. This makes Snortmanager not very usable for Avdeling BKI and their routines.

1.5 Target Audence

Who wants to use the software and who wants to read this report.

1.6 Project Objectives

Result Objectives

Research, design and develop a system that as a minimum;

- Is programmatically more efficient than BHTB.
- Is developed as a standalone engine that responds to API calls from any arbitrary user interface.
- Is modular in design and allows future changes and additions to not affect existing functionality.
- Is scalable enough to handle both small and large sets of IDS sensors and rules in a production environment.
- Is able to download rules and rule sets from multiple customizable sources.
- Is able to distribute different rules to different IDS sensors.
- Can download and distribute automatically at set intervals.
- Is capable of exporting rules for sharing.
- Has the capability to activate, deactivate, threshold and suppress rules on a per sensor basis, in a way that is user friendly.
- Supports multi-user interaction.
- Can efficiently and safely work with different installations of SNORT® and various other third party tools, such as SNORBY.
- Is easy to install.
- Has an internal logging system for all activity.
- Is well documented and can be easily adopted by anyone as open source software.

In addition, the project will attempt to add the following functionality;

- A separate graphical user interface.
- Said user interface must be user friendly and intuitive, and require only limited knowledge of SNORT® rules from the user.
- The system can also distribute rules to Suricata, another SNORT®-like IDS, which can operate with the exact same rules as SNORT®.
- Implement security features that ensure confidentiality of rules.
- The project will investigate and potentially implement multi-threading technology to exploit modern hardware capacities.
- The system is capable of validating and checking rules for errors before they are distributed to production sensors.
- The system allows commenting of the rules.
- The system supports writing custom rules and editing existing rules.

Once the system has been developed, it will be released as an Open Source Software to the public in a well-documented format.

Effect Objectives

Forming baselines from the current prototype BHTB and from Snortmanager, the project has a goal to further increase the efficiency of rule management by investigating and implementing programming techniques such as multi-threading and a change-based system to reduce latency and delays in the system by as much as 50The project will therefore be measuring for this effect.

Furthermore, the project will research and implement safeguards against unintentional failures in SNORT® as a result of user error and malformed or misconfigured rules, thus reducing the potential downtime of the IDS sensors, as a SNORT® sensor will simply not restart if a single rule is malformed or misconfigured. Efficient ways of solving this problem will have to be researched.

1.7 Project Description

In broad strokes, this project is about designing a system that is a highly modular API-based engine, which is independent of any GUI. The project will be the spiritual successor to BHTB, but also take some inspiration from Snortmanager. Essentially taking good ideas from both projects, add a few of our own, and create a more adoptable open source rule management system for SNORT®.

We will utilize the latest stable version of Python as the main programming language for the project. C++ was also considered, but due to the limited time at our disposal, we feel we can create more functionality with Python, due to it requiring less memory management and general “programmer friendly” ways of doing things.

The system will require a database to function efficiently and the project will utilize MySQL, as this is the de facto standard for the Linux platform.

Furthermore, the project will also consist of creating a GUI that is user friendly and responsive. We will base this heavily on the GUI developed for BHTB in terms of displaying rules in lists and with buttons and checkboxes to manipulate them. We may also borrow some design ideas from Snorby (5), another SNORT® tool. The main technologies we will utilize for the GUI will consist of standard web-oriented languages such as HTML,

CSS, PHP and/or Javascript.

1.8 Academic Background

Talk about our pasts.

1.9 Framework

1.9.1 Software Development Methodology

As this project is time-restricted, the development should be as efficient as possible. We therefore need a model that utilizes the manpower we have present in the best possible way. The size of the group is also quite small, so big and complex development models would add too much bureaucracy to coordinate the project and is thus overkill.

As we want to have a lightweight development-model, some form of an agile development model with well-defined development-cycles is preferred. This way, each group-member can take an active part in the project and all members would feel a sense of ownership.

Developing iterative and incrementally, we are getting the best from both the unstructured world, and from the very well defined waterfall approach. We are able to get feedback during the project, and have a structured and reasonable way of actually doing changes in the plan while the project is running. At the same time we would be able to maintain the overall plan within cycles, so that it is possible to work individually, while still being well coordinated.

To be able to develop all the modules of the project within the timeframe, each development cycle will consist of multiple modules developed in parallel. This allows us to maximize our utilization of time and personnel.

The start of each cycle will consist of a meeting where we define the goals for that cycle, and identification of the individual tasks that we need to get done. This is similar to the start of a sprint in the development model Scrum.

In the development part of the cycle, we will individually work on the tasks that were defined in the planning-part. Regular meetings and cooperative programming within the group would ensure that we all pull the project in the same direction.

At the end of each cycle we should have a working set of software, which ideally should comply with all the goals set in the start of each cycle. We are planning to have a meeting with Avdeling BKI between each cycle to present the progress, and to let them influence the direction of the project.

After all development cycles have been complete, we will then make final assurances that everything works as intended and that all modules coexist in harmony. This part of the development will also consist of hands-on testing by the client and various performance testing.

1.9.2 Schedule

Refer to gantt diagram in project plan etc.

1.9.3 Project Organization

Talk about how we organized everything.

2 EXISTING SOLUTIONS

Her tenker jeg at vi tar med hva som fins av programvare fra før og peker påutfordringer i disse løesningene.

3 REQUIREMENTS SPECIFICATION

Many of the requirements for this system stems from functions that already reside in BHTB, which our client wants either reproduced or improved upon. That means the requirments for this project is closely tied to the way BHTB operates and its general workflow. In this coming section we will outline the specifications we've gathered from BHTB and from conversations with the client.

3.1 Functional Requirements

3.1.1 Program Workflow

To develop our requirements, we decided to chart the program workflow in order to better understand what the system is expected to do. Since this is to be a highly user-oriented system, we accomplished this by going over the old system, BHTB, step by step with the client and detailing the functions and various needs for improvement or additional functionality. From this, we developed a workflow chart that details the major system parts.




Figure 1: Program Workflow

To explain the workflow chart, the blue boxes are the major system functionalities, the green boxes are the major goals of the system and the arrows show the direction of flow the system should have.

As you can see, if you trace the arrows, all of the program flow ends up with rules being syncronized to the sensors. This makes sense, because that is the whole purpose of the system to begin with.

It's important to note that very early on, we decided that writing rules, automatically check them for errors and commenting them were nice-to-have features that we could implement if we had time to do so. Hence they are greyed out in the drawings.

From this workflow we could outline a rough modular design based on the naturally separate functions of updating rules, tuning them, distributing them and show them. We also added a database module, since most of our program was going to be centered around it.




Figure 2: Program Modules

Rule Downloading Module

This module will handle all functionality related to downloading rules, including comparing MD5 checksums.

Rule Pre-Storage Processing Module

This module will essentially take downloaded rules and parse and process them into objects that can be fed into the database.

DB Module

This module will handle all input and output to/from the database.

Rule Pre-Distribution Processing Module

This module will essentially take rules stored in the database and prepare them for distribution to sensors.

Rule Distribution Module

This module will be in charge of distributing rules out to the Snort sensors.

Tuning Module

This module will handle all functionality related to turning rules on or off, thresholding them or suppressing them.

Rule View Module

This module will contain all the functionality needed to display the system status and system functions to the user. It will be the primary way the user interacts with the system.

Daemon Module

This module will run continually on the system to ensure that the system is responsive and to carry out any interval based tasks, such as automatic updates or distributions.

Commenting Module

This module will allow users to attach comments to rules.

Rule Writing Module

This module will handle functionality for writing custom rules and editing existing rules.

Automatic Rule Checking Module

This module will be responsible for verifying rules to ensure that there are no malformed or misconfigured rules that may potentially break or cause a halt on a Snort sensor.

3.1.2 Use Case Diagram

Putt inn nytt use case diagram her!

3.1.3 Domain Model

Vi trenger en domene modell!!

3.2 Supplemental Requirements

In addition to the features discovered in the use cases, the system has some requirements that can be broken down into a RUP FURPS+ [some sort of link] fashion.

3.2.1 Functionality

- The system should be able to restart a Snort sensor in the event that one crashes.
- The system should be able to detect if a Snort sensor is not responsive over the network.
- The system must be portable to the majority of the popular linux distributions.

3.2.2 Usability

- The graphical user interface must be simple and clean, but still contain all the features any user might require to interact with the back-end system.
- The system interfaces, herein API and function calls, must be self-explanatory.

3.2.3 Reliability

- The system must not cause a SNORT sensor to crash.
- The system must be responsive to API calls at all times. In the event the system capacity limit is reached, new requests should be queued.

3.2.4 Performance

- The system should handle administration of at least 200 sensors.
- The database should be able to maintain at least 100 000 individual rules.
- Any operation in the system in normal operations (i.e. after the first big rule update) should take no longer than 1 second on average.
- The relationship between time and workload should be linear, meaning that if a single operation that takes 1ms, ten operations should take 10ms.

3.2.5 Security

- The link between the system server and the remote sensor must be secured in such a way that a man in the middle cannot read the transmission in plaintext.
- The remote sensor and the system server must verify that they are trusted parties in the system, through authentication.
- Certain important API calls must be protected against misuse from a non-trusted party.
- All processes and files related to them system must exert the principle of least privilege.

3.2.6 Interoperability

The system must be able to work with Snort in such a way that it can import new files to Snorts configuration files structure and must be able to reset Snort in such a way that the new configurations are loaded.

3.3 Constraints

3.3.1 Platform

As mentioned in the Project Plan, Snort is primarily used in conjunction with the Linux/UNIX operating systems. For that reason, the project was restricted to only develop for that platform. More specifically, we limited ourselves to the Ubuntu and Debian operating system, which is the primary platform the client uses as well. We have, however, stived to make the software portable.

3.3.2 Data security

While the system itself will not handle any data that may comprise of personal data, it may contain rules and rule sets that are considered classified or confidential. The system has therefore been built with this in mind and ensured confidentiality within the boundaries of the system. The system does not guarantee the confidentiality of the system outside these boundaries.

These boundaries include the program and its processes and threads, and the network link established between the system and remote sensors. The system assumes that the users have already established database security.

3.3.3 Graphical User Interface

The project has had its main focus on the systems functionality and efficiency from a programmatically standpoint and developing a graphical user interface (GUI) has been considered a secondary task and was prioritized as such. None the less, a GUI for demonstrational purposes has been included.

4 DESIGN

Utfyllende med grunngitt valg av metoder, rammeverk etc. Hovedtrekk fra design av system beskrives. Fullstendig designdokument bør være vedlegg til prosjektrapporten, mens dette punktet omhandler diskusjon av sentrale forhold. Ulike alternative design som studentene vurderte bør beskrives og valg av alternativ begrunnes.

5 IMPLEMENTATION

This chapter will focus on the technical implementation of the software.

5.1 Frameworks

To simplify (db, web, code) this project uses the Django framework.

5.2 Concepts of Snort®

This section will give a brief introduction to the basic concepts of Snort®, and discuss these in relation to features made in this project.

5.2.1 Rules

We used to be fans of *modifiers*, but now we praise the hierarchy!

A rule is basically a set of options that define ways of detecting, classifying and reporting a potential attack or threat on the network[1]. There are several types of options, but only the general rule options are relevant for this project. The general rule options provide information about the rule[1] (i.e. revision number, alert message). Other types of options, such as payload options which are actively used in detection, are not relevant for the management of rules and are thus not considered in this project.

A rule can either be enabled or disabled in the detection system, meaning that the rule will only have an effect on detection when it is enabled. Since this project is dealing with multiple sensors connected to one central database, this functionality has been expanded so that users can keep a rule enabled on one sensor and disabled on another. In addition, the user can also set an enabled/disabled flag on rulesets.

5.2.2 Rule sets

5.2.3 Generators

5.2.4 Reference Types

5.2.5 Event and detection filters

Various filters can be applied to rules in order to control the amount and frequency of alerts triggered by a single rule.

Inline thresholds are currently supported, but this functionality is deprecated

Threshold deprecated. Detection filters.

If a filter occurs inline, this filter is regarded as a default filter and will be active on every sensor where the rule operates. A user can choose to override the default filter on a sensor by defining a custom filter to be used on the respective sensor.

To stop Snort®from adding duplicate filters, all inline filters are removed from the rulestrings. Any filters extracted from the rulestring are written as plain text (i.e. as they appear in the original rulestring) in the *filters* field of the rule revision object. This is to ensure that all the original rule options are stored meaning that no data is lost or discarded.

[1] A rule actually consists of a header and options, rtfm.[1]




Figure 3: Flow

Filter type	Alerts
Event filter	
Limit	One for every event when *count* $\leq$ C in interval S
Threshold	One for every C events in interval S
Both	One per interval S when *count* $=$ C
Detection filter	One for every event when *count* $>$ C in interval S

Table 1: Effects of different filter types.

Filters are removed from the rulestring and transformed into event filter and detection filter objects.

5.3 Core module

Lorem, ipsum?

5.4 Update module

The purpose of the Update module is to fetch and read rules and configuration files from external sources, and populate the database with this information. Effectiveness in updates is a key issue, and a number of deliberate optimizations for performing updates, with the goal of saving time by omitting unnecessary operations, are explained in the following sections.

The term Update is used to refer to the actual module, including all its classes and functions. To avoid confusion with the module, the term *update-package* is specifically used to refer to update data coming from external sources.

This section will define an example rule to be used throughout subsequent sections and the remainder of the chapter, to illustrate the lifespan of a rule in the system.

Word: rulestring.

Data field	Description	Presence
sid	Unique identifier for a rule.	required
rev	Rule revision number.	required
msg	Notification text when rule triggers.	required
classtype	Connects the rule with a specific class of attacks.	required
gid	Generator ID to identify which subsystem generates the event where this rule fires.	optional
ruleset	The ruleset this rule belongs to.	optional
priority	Override default severity set by classtype.	optional
reference	Reference to external resource with information about this attack.	optional

Note: The *presence* column indicates whether a field is required or not by the parser in this system. Information is gathered from the Snort Users Manual [1](ch 3.4).

Table 2: Rule options used in this system.

5.4.1 Sources

A *source* is used by Update to determine where the update-package is located. Normally this is on a remote site, and the source contains the URL pointing to the location of the update-package. A source can be configured to update at regular intervals, or the user can run an update manually on a source. To make the update process more effective, Update makes use of an MD5 URL which points to a file containing the MD5 hash of the update-package. This hash is stored for every source (if available) and is compared to any pre-existing hash to verify if the system is up to date or not. Update will only download and process an update-package when it encounters a new hash.

5.4.2 Files

An update-package may contain various files depending on the source it comes from. This section will describe files supported by Snowman.

Rule files

A rule file is any file carrying the *.rules* file extension. These files contain raw rulestrings to be processed by Snort. A rulestring is basically a semicolon-separated list of rule options. Specific rule options used in this system are listed in table 2.

A badly formatted rulestring given to Snort will cause a crash, and Snort must be restarted.

Classification, Generator and Reference Configuration files

The classification files are identified by their name *classification.config* and contain rule classification strings that are used by Snort to categorize event data. A classification file will normally appear once per update-package, and rarely changes between updates[2].

[2]https://www.snort.org/vrt/snort-conf-configurations/

Sid message files

5.4.3 Running an update

As an example scenario, consider a rule (name, figure reference, source, ruleset etc.). An update is triggered on the source at the predefined time

The update is cancelled if the source is already up to date; the MD5-hashes of the latest update in the database, if any, and the latest update on the remote site are compared, and the process is terminated if these hashes are identical. Otherwise, the update is downloaded to a temporary directory and the update process continues. A file can be a tar-archive containing an arbitrary number of rulesets and configuration files, or it can be a plain text file containing Snort configuration (?).

The tar-archive is extracted, and the update module recursively parses each file in each folder. In most cases the update-package will contain only minor changes in relation to its predecessor, e.g. only one file is different in the latest package, and parsing all files that has not changed would therefore be a waste. To address this issue and save processing time, the name, path and MD5-hash of every file is stored in the database per source. Every time the update module parses a file, it first creates a hash of the file and compares this with the respective file's hash in the database. If the file is present in the database and the two hashes coincide, the file is considered *not new* and is skipped. The following sections will elaborate on the parsing of files based on file type.

parse files with regex.

5.4.4 Rule parsing

Some options can be defined both in the rulestring (inline) and in a separate file (standalone).

If any properties classified as *required* for a rule (table 2) are missing...

Non-existing rule sets, rule classes and generators are stored in the database

After the initial parsing of the rulestring, the parser checks if the rule already exists in the database, and if so whether the incoming revision number is higher than the latest revision of the pre-existing rule. The parsing will continue only in the event of a new rule or a newer revision of an existing rule.

rule moved to new ruleset.

Rule sets

A rule always belogs to a ruleset which can be specified in the raw rulestring. If the parser does not find this attribute in the rulestring, the filename is considered to be the ruleset name.

Threshold

A rule threshold defines a limit and/or threshold for the triggering of a specific rule, and can exist as an inline or standalone option. Rule thresholds are deprecated, and support for this functionality will cease in a future version of Snort®, where it is replaced by *detection filters* and *event filters* (see below) [1]. To maintain compatibility with current rules, Snowman supports reading inline and standalone threshold definitions.

Detection filters

Please explain..

Event filters

Please explain..

Suppression

Always standalone.

5.4.5 Classification, Generator and Reference Type parsing

These files contain a sequence of their respective entities (section 5.4.2), and are all parsed in the same manner. If a given entity is not already present in the database, it is created and stored. If the database already contains the entity, the existing entry in the database is overwritten.

Rule Message files

5.4.6 Logging

5.5 Graphical User Interface

The Graphical User Interface (GUI) is a template- and AJAX-based (desc/footnote?) Web application which uses Django's (desc) template system to implement the View part of the MVC-principle(ref). Each webpage is a template populated through Python-code before it is delivered to the Web server and ultimately the requesting Web browser.

Additional data that needs to be sent to a Web page, e.g. the user interacts with the GUI, is requested through JavaScript(desc) and AJAX-calls and then gets added to the already loaded DOM(desc) in the web browser.

5.5.1 Structure

The pages of the GUI is organized in the following structure:




Figure 4: GUI Structure

5.5.2 Design

The GUI is designed with simplicity in mind, which is achieved by using a front-end framework called Bootstrap(ref). This framework provides easy-to-use and ready-made design elements for HTML and CSS(desc), which has been crucial for saving time and energy in the project. Consider the example job of creating a <table> element and spending hours setting up and tweaking the CSS for the said table element, we could just add <table class='**table table-bordered**'> and get the table formatted nicely with colors and fonts that are typographically matching.

5.5.3 Features

Content Prefetching

One of the main features of our GUI design is our usage of prefetching to speed up loading. Instead of loading absolutely everything into the web browsers DOM, like our

predecessor BHTB did, we instead initially only load the first page or page elements. This significantly reduces loading times.

We then silently in the background load in any element the user might want to see next, through AJAX calls. When the user then interacts with the GUI, the next elements are shown to the user. The next-next elements are also loaded through AJAX calls so that they are ready.

This ensures that the user always has immidiate response from any interaction done with the GUI, while keeping loading times to a bare minimum.

5.5.4 Rules/All rules page




Figure 5: Rules/All rules page

This page serves as the complete list of all rules currently residing in the central database. Because the central database can literally contain hundreds of thousands of rules, this list is paginated. Pages are loaded using AJAX calls to prefetch them as needed.

Each row in the list can be clicked on, which expands an area containing additional information about the rule in question.

We anticipate that the main use of this page is to utilize the search function to find a specific rule or rules and then either retrieve information about them or tune them.

Rules can be tuned by checking the checkbox associated with the rule in question and then press the button that represent the desired function in the box to the left.

6 OPTIMIZATION

6.1 Update

7 SOFTWARE TESTING

Her beskrives hvordan opplegget rundt testing av applikasjonen har vært. Dette omfatter planlegging, valg av teststrategier, gjennomføring av tester og beskrivelser av sentrale feil funnet under testing, samt måten feil ble rettet opp på.

8 PERFORMANCE TESTING

Since Snowman is similar to BHTB and Snortmanager, it has been important to benchmark their performance in various formal test cases in order to highlight the strength and weaknesses in each software solution. The purpose of the tests is to reach final conclusions on key questions regarding the performance of Snowman, and to point out where the difference between the three software packages lies.

To get a picture of how the software performs on different systems, it was tested on three architectures (table 3). To minimize error, each test was run five times where the mean value of the runs is considered the valid test result. All tests can be reproduced with the test procedure documentation in appendix.

8.1 Definitions

The testing is split up into *test suites*, which contain a *problem* in the form of a question. The problem forms a clear description of what is to be tested, and how results should be evaluated. A test suite also contains one or more test cases which exist to address the problem. Test cases describe

each test suite consists of one or

results from test cases are referred to as the test results.

Each test case is composed of a series of

8.2 Environment

All tests are carried out on three systems, named *S1*, *S2* and *S3* (table 3). These systems differ in processing power, available memory and storage technology, and the results will indicate what impact these factors have for software performance. The performance testing in this report is also prone to error, as tests might get disturbed by other background processes etc. Testing on three systems gives results with a higher confidence, as results are checked aginst each other for inconsistencies. When an inconsistency in results is found, the test is run again to see if the inconsistency prevails.

System	Processor type	Memory	Storage
S1	Intel® Core™ 2 Solo, 1.4GHz	4GB RAM	5K RPM HDD
S2	Intel® Core™ i7, 6x3.2GHz	12GB RAM	10K RPM HDD
S3	Intel® Core™ i5, 4x3.2GHz	16GB RAM	SSD

Note: See appendix for full details.

Table 3: Test systems.

Deviation

8.3 Test suites

8.3.1 Update processing

The Update module is tested for speed and linearity, which is compared to

Test 1

Problem: How fast can the software process an update?

The purpose of this question is to determine the average processing time per rule. Results are ranked from short to long processing time, where shorter is better.

Test cases

To address this problem, five test cases were introduced. The tests contained an artificially generated update with 1, 10, 100, 1000 and 10000 rules, respectively. Rules were split into files with ten each (table 4).

Test case	Rules	Files
1-1-1	1	1
10-1-10	10	1
100-10-10	100	10
1000-100-10	1000	100
10000-1000-10	10000	1000

Table 4: Test cases in Test 1.

Test 2

Q2: How strong is the linear correlation between processing time and the size of an update?

This question rises from the requirements specification of Snowman (chapter 3), where it is stated that Snowman shall exhibit a linear increase in processing time in correlation to the number of rules in the update (where the number of rules depicts the update size). Results are ranked from strong correlation to no correlation, where stronger is better.

Q3: Does raising the ratio between files and rules increase processing time?

Updates can come with the rules either gathered in one file, or distributed over several files. This question is asked to examine the difference in processing time for these two scenarios. Results are ranked from no difference to big difference, where less difference is better.

Q4: Is the processing time shorter when the update contains no new rules?

Q5: Are the processing times for two updates identical when only one rule has changed between the updates?

This question seeks to determine how the software handles an update when there is only one change from the previous update. This is an important factor to consider, since an update usually contains only a small amount of changes from previous updates. Results are ranked from short processing time for second update to no difference in processing time, where shorter time is better.

An automatically generated update is used for Q1 through Q6

9 RESULTS

De faktiske observasjoner og data fra forsøk (f.eks. målinger) og undersøkelser (f.eks. utspørringer) presenteres på en oversiktlig måte ved tabeller og/eller diagrammer. Bruk skjønn for evt. plassering i vedlegg. Ved bruk av diagrammer skal det gis beskrivende tekst til grafer. Resultatene skal kort kommenteres, men ikke diskuteres. Viktige resultater gjengis kortfattet under ”Sammendrag”. En oversikt over tabeller og diagrammer med nummer og titler kan plasseres etter innholdsfortegnelsen.

Mean times calculated from five sequential test results. See appendix for a complete listing of results.

Software	Test	S1	S2	S3
Snowman v0.4	1-1-1	1058.179	151.946	622.640
	10-1-10	2289.518	327.655	1668.142
	100-10-10	17519.385	2356.610	12197.192
	1000-100-10	167645.267	22830.358	114617.561
	1000-1-1000	147170.285	20367.838	113901.478
	10000-1000-10	N/A	228038.066	1162468.835
BHTB	1-1-1	125.236	18.175	65.281
	10-1-10	148.323	19.711	72.025
	100-10-10	185.970	25.024	84.913
	1000-100-10	568.333	60.313	150.538
	1000-1-1000	445.476	49.908	175.805
	10000-1000-10	3606.043	440.334	910.172
Snortmanager	1-1-1	228.617	36.960	93.403
	10-1-10	265.275	37.569	107.554
	100-10-10	1251.275	159.113	139.005
	1000-100-1	9470.460	1360.276	491.512
	1000-1-1000	1836.396	228.044	509.243
	10000-1000-10	92428.555	13523.887	5105.158

All times in milliseconds. For complete results, see appendix.

Table 5: Test results for update processing.

10 ANALYSIS OF RESULTS

Diskusjon rund resultatene. Det skal gjøres en evaluering av hvorvidtvalgt løsning. Avvik drøftes. det er samsvar mellom kravspesifikasjonen satt opp og

11 CONCLUSIONS

De slutninger som kan trekkes fra resultatene og deres diskusjon skal være logisk og nøkternt oppbygd. Etterrettelighet er vesentlig. Konklusjoner skal fremkomme klart og uten tvetydigheter. Eventuell usikkerhet påpekes. Grunnlaget for slik tvil skal redegjøres under kapittel 6a/6b. De viktigste konklusjoner blir presentert i kortfattet versjon under ”Sammendrag”. Prosjektgruppen bør ta stilling til hva de faglige resultatene kan brukes til, hva gruppen faglig har lært av dette arbeidet, hva som evt. kunne vært gjort annerledes ved en gjentagelse av utviklingsarbeidet, og hvordan eventuelt videre arbeid rundt samme eller beslektet tema bør gjøres. Gruppen bør også kommentere den subjektive opplevelse av hovedprosjektet, og hvordan gruppeprosessen har vært. Kort sagt: Egenevaluering av gruppearbeidet.

Bibliography

[1] Roesch, M. 2012. *Snort Users Manual 2.9.3*. The Snort Project.