Axes adjustments API

plt.**subplots_adjust**(...)



Extent & origin API

ax.**imshow**(extent=..., origin=...)



Text alignments API

ax.**text**(..., ha=... , va=..., ...)



Text parameters API

ax.**text**(..., family=..., size=..., weight=...)
ax.**text**(..., fontproperties=...)

The quick brown fox — xx-large (1.73)
The quick brown fox — x-large (1.44)
The quick brown fox — large (1.20)
The quick brown fox — medium (1.00)
The quick brown fox — small (0.83)
The quick brown fox — x-small (0.69)
The quick brown fox — xx-small (0.58)

The quick brown fox jumps over the lazy dog — black (900)
The quick brown fox jumps over the lazy dog — bold (700)
The quick brown fox jumps over the lazy dog — semibold (600)
The quick brown fox jumps over the lazy dog — normal (400)
The quick brown fox jumps over the lazy dog — ultralight (100)

The quick brown fox jumps over the lazy dog — monospace
The quick brown fox jumps over the lazy dog — serif
The quick brown fox jumps over the lazy dog — sans
The quick brown fox jumps over the lazy dog — cursive

The quick brown fox jumps over the lazy dog — italic
The quick brown fox jumps over the lazy dog — normal

THE QUICK BROWN FOX JUMPS OVER THE LAZY DOG — small-caps
The quick brown fox jumps over the lazy dog — normal

Uniform colormaps



Sequential colormaps



Diverging colormaps



Qualitative colormaps



Miscellaneous colormaps



Color names API

Image interpolation API



Legend placement



ax.**legend**(loc="string", bbox_to_anchor=(x,y))

2: upper left	9: upper center	1: upper right
6: center left	10: center	7: center right
3: lower left	8: lower center	4: lower right

A: upper right / (-0.1,0.9)
B: center right / (-0.1,0.5)
C: lower right / (-0.1,0.1)
D: upper left / (0.1, -0.1)
E: upper center / (0.5, -0.1)
F: upper right / (0.9, -0.1)
G: lower left / (1.1, 0.1)
H: center left / (1.1,0.5)
I: upper left / (1.1, 0.9)
J: lower right / (0.9,1.1)
K: lower center / (0.5,1.1)
L: lower left / (0.1,1.1)

Annotation connection styles API



Annotation arrow styles API



How do I ...

... resize a figure?
→ fig.set_size_inches(w, h)
... save a figure?
→ fig.savefig("figure.pdf")
... save a transparent figure?
→ fig.savefig("figure.pdf", transparent=True)
... clear a figure/an axes?
→ fig.clear() → ax.clear()
... close all figures?
→ plt.close("all")
... remove ticks?
→ ax.set_[xy]ticks([])
... remove tick labels ?
→ ax.set_[xy]ticklabels([])
... rotate tick labels ?
→ ax.set_[xy]ticks(rotation=90)
... hide top spine?
→ ax.spines['top'].set_visible(False)
... hide legend border?
→ ax.legend(frameon=False)
... show error as shaded region?
→ ax.fill_between(X, Y+error, Y-error)
... draw a rectangle?
→ ax.add_patch(plt.Rectangle((0, 0), 1, 1)
... draw a vertical line?
→ ax.axvline(x=0.5)
... draw outside frame?
→ ax.plot(..., clip_on=False)
... use transparency?
→ ax.plot(..., alpha=0.25)
... convert an RGB image into a gray image?
→ gray = 0.2989*R + 0.5870*G + 0.1140*B
... set figure background color?
→ fig.patch.set_facecolor("grey")
... get a reversed colormap?
→ plt.get_cmap("viridis_r")
... get a discrete colormap?
→ plt.get_cmap("viridis", 10)
... show a figure for one second?
→ fig.show(block=False), time.sleep(1)

Performance tips

```
scatter(X, Y)                                  slow
plot(X, Y, marker="o", ls="")                  fast

for i in range(n): plot(X[i])                  slow
plot(sum([x+[None] for x in X],[]))            fast

cla(), imshow(…), canvas.draw()                slow
im.set_data(…), canvas.draw()                  fast
```

Beyond Matplotlib

Seaborn: Statistical Data Visualization
Cartopy: Geospatial Data Processing
yt: Volumetric data Visualization
mpld3: Bringing Matplotlib to the browser
Datashader: Large data processing pipeline
plotnine: A Grammar of Graphics for Python

NUMFOCUS
OPEN CODE = BETTER SCIENCE