

ASSIGNMENT – 11.2

Name: T.Snuhith Reddy

Roll Number : 2303A510H9

Batch - 03

Task 1:-

```
19 class Stack:
20     """
21     A Stack data structure that follows Last-In-First-Out (LIFO) principle.
22     This implementation uses a Python list as the underlying data structure.
23     Supports basic stack operations: push, pop, peek, and empty check.
24     Attributes:
25     | items (list): Internal list to store stack elements
26     """
27
28     def __init__(self):
29         """Initialize an empty stack."""
30         self.items = []
31
32     def push(self, item):
33         """
34         Add an item to the top of the stack.
35
36         Args:
37             item: The item to be added to the stack
38         """
39         self.items.append(item)
40
41     def pop(self):
42         """
43         Remove and return the top item from the stack.
44
45         Returns:
46             The top item from the stack
47
48         Raises:
49             IndexError: If the stack is empty
50         """
51         if self.is_empty():
52             raise IndexError("Pop from empty stack")
53         return self.items.pop()
54
55     def peek(self):
56         """
57         Return the top item from the stack without removing it.
58
59         Returns:
60             The top item from the stack
61
62         Raises:
63             IndexError: If the stack is empty
64         """
65         if self.is_empty():
66             raise IndexError("Peek from empty stack")
```

Output:-

```
Data Structures Implementation - Lab 11
=====

1. Stack Operations:
Stack after pushes: size = 3
Peek: 30
Pop: 30
Pop: 20
Is empty: False
```

Task 2:

```

class Queue:
    """
    A Queue data structure that follows First-In-First-Out (FIFO) principle.

    This implementation uses a Python list as the underlying data structure.
    Supports basic queue operations: enqueue, dequeue, front access, and size.

    Attributes:
    | items (list): Internal list to store queue elements
    """

    def __init__(self):
        """Initialize an empty queue."""
        self.items = []

    def enqueue(self, item):
        """
        Add an item to the rear of the queue.

        Args:
        | item: The item to be added to the queue
        """
        self.items.append(item)

    def dequeue(self):
        """
        Remove and return the front item from the queue.

        Returns:
        | The front item from the queue

        Raises:
        | IndexError: If the queue is empty
        """
        if self.is_empty():
            raise IndexError("Dequeue from empty queue")
        return self.items.pop(0)

```

```

def front(self):
    """
    Return the front item from the queue without removing it.

    Returns:
        The front item from the queue

    Raises:
        IndexError: If the queue is empty
    """
    if self.is_empty():
        raise IndexError("Front from empty queue")
    return self.items[0]

def is_empty(self):
    """
    Check if the queue is empty.

    Returns:
        bool: True if queue is empty, False otherwise
    """
    return len(self.items) == 0

def size(self):
    """
    Return the number of items in the queue.

    Returns:
        int: Number of items in the queue
    """
    return len(self.items)

```

Output:-

```

2. Queue Operations:
Queue after enqueues: size = 3
Front: 10
Dequeue: 10
Dequeue: 20
Is empty: False

```

Task 3:-

```
class Node:
    """
    A node in a singly linked list.

    Attributes:
        data: The data stored in the node
        next: Reference to the next node in the list
    """

    def __init__(self, data):
        """
        Initialize a node with given data.

        Args:
            data: The data to store in the node
        """
        self.data = data
        self.next = None

class SinglyLinkedList:
    """
    A singly linked list data structure.

    Supports insertion at the beginning and traversal/display operations.

    Attributes:
        head: Reference to the first node in the list
    """

    def __init__(self):
        """Initialize an empty singly linked list."""
        self.head = None

    def insert_at_beginning(self, data):
        """
        Insert a new node with given data at the beginning of the list.

        Args:
            data: The data to insert
        """
        new_node = Node(data)
        new_node.next = self.head
        self.head = new_node
```

```
def display(self):
    """
    Display all elements in the linked list.

    Prints the elements separated by ' -> ' and ends with 'None'
    """
    current = self.head
    while current:
        print(current.data, end=" -> ")
        current = current.next
    print("None")
```

Output:-

```
Is empty: False
```

```
3. Singly Linked List Operations:
Linked List after insertions:
10 -> 20 -> 30 -> None
```

Task 4:

```
class BSTNode:
    """
    Attributes:
        data: The data stored in the node
        left: Reference to the left child node
        right: Reference to the right child node
    """

    def __init__(self, data):
        """
        Initialize a BST node with given data.

        Args:
            data: The data to store in the node (must be comparable)
        """
        self.data = data
        self.left = None
        self.right = None

class BinarySearchTree:
    """
    A Binary Search Tree data structure.

    Supports insertion and in-order traversal operations.

    Attributes:
        root: Reference to the root node of the tree
    """

    def __init__(self):
        """Initialize an empty binary search tree."""
        self.root = None

    def insert(self, data):
        """
        Insert a new node with given data into the BST.

        Args:
            data: The data to insert (must be comparable)
        """
        if self.root is None:
```

```

if data < node.data:
    if node.left is None:
        node.left = BSTNode(data)
    else:
        self._insert_recursive(node.left, data)
else:
    if node.right is None:
        node.right = BSTNode(data)
    else:
        self._insert_recursive(node.right, data)

def in_order_traversal(self):
    """
    Perform in-order traversal of the BST and print the elements.

    In-order traversal visits left subtree, current node, right subtree.
    """
    self._in_order_recursive(self.root)
    print() # New line after traversal

def _in_order_recursive(self, node):
    """
    Helper method for recursive in-order traversal.

    Args:
        node: Current node in the recursion
    """
    if node:
        self._in_order_recursive(node.left)
        print(node.data, end=" ")
        self._in_order_recursive(node.right)

```

Output:

```

4. Binary Search Tree Operations:
BST after insertions - In-order traversal:
20 30 40 50 60 70 80

```

Task 5:-

```
class HashTable:
    """
    A Hash Table data structure with collision handling using chaining.

    Uses separate chaining (linked lists) to handle collisions.
    Supports insert, search, and delete operations.
```

```
    Attributes:
        size (int): The size of the hash table
        table (list): Internal list of buckets (each bucket is a list)
    """
```

```
    def __init__(self, size=10):
        """
        Initialize a hash table with given size.
        """
```

```
        Args:
            size (int): The number of buckets in the hash table
        """
        self.size = size
        self.table = [[] for _ in range(size)]
```

```
    def _hash(self, key):
        """
        Compute the hash value for a given key.
```

```
        Args:
            key: The key to hash
```

```
        Returns:
            int: The hash value (bucket index)
        """
```

```
        return hash(key) % self.size
```

```
    def insert(self, key, value):
        """
        Insert a key-value pair into the hash table.

        If the key already exists, updates the value.
```

```
        Args:
            key: The key to insert
```

```

# Check if key already exists
for i, (k, v) in enumerate(bucket):
    if k == key:
        bucket[i] = (key, value) # Update value
        return

# Key doesn't exist, add new entry
bucket.append((key, value))

def search(self, key):
    """
    Search for a value by its key in the hash table.

    Args:
        key: The key to search for

    Returns:
        The value associated with the key, or None if not found
    """
    bucket_index = self._hash(key)
    bucket = self.table[bucket_index]

    for k, v in bucket:
        if k == key:
            return v

    return None

def delete(self, key):
    """
    Delete a key-value pair from the hash table.

    Args:
        key: The key to delete

    Returns:
        bool: True if key was found and deleted, False otherwise
    """
    bucket_index = self._hash(key)
    bucket = self.table[bucket_index]

    for i, (k, v) in enumerate(bucket):

```

Output:-

5. Hash Table Operations:

Hash Table after insertions:

Bucket 0: [('cherry', 30)]

Bucket 1: []

Bucket 2: [('apple', 10), ('banana', 20)]

Bucket 3: []

Bucket 4: []

Bucket 5: []

Bucket 6: [('date', 40)]

Bucket 7: []

Bucket 8: []

Bucket 9: []

Search 'apple': 10

Search 'grape': None

Delete 'banana': True

Hash Table after deletion:

Bucket 0: [('cherry', 30)]

Bucket 1: []

Bucket 2: [('apple', 10)]

Bucket 3: []

Bucket 4: []

Bucket 5: []

Bucket 6: [('date', 40)]

Bucket 7: []

Bucket 8: []

Bucket 9: []

PS C:\Users\hp\OneDrive\Desktop\ai>

Extra question:

```
5
6 SIZE = 5
7 stack = []
8 top = -1
9
10 def push(value):
11     global top
12     if top == SIZE - 1:
13         print("Stack Overflow")
14     else:
15         stack.append(value)
16         top += 1
17         print(value, "inserted")
18
19 def pop():
20     global top
21     if top == -1:
22         print("Stack Underflow")
23     else:
24         removed = stack.pop()
25         print(removed, "removed")
26         top -= 1
27
28 # Testing the additional stack implementation
29 print("\n6. Additional Stack Implementation (Array-based):")
30
31 # Inserting elements
32 push('a')
33 push('b')
34 push('c')
35 push('d')
36 push('e')
37 push('f') # This should show Overflow
38
39 print()
40
41 # Removing elements
42 pop()
43 pop()
44 pop()
45 pop()
46 pop()
47 pop() # This should show Underflow
```

Output:

6. Additional Stack Implementation (Array-based):

a inserted

b inserted

c inserted

d inserted

e inserted

Stack Overflow

e removed

d removed

c removed

b removed

a removed

Stack Underflow