



# TEST REPORT

**Reference No.** ..... : WTA24F02028831E  
**Applicant** ..... : Handian Group Ningbo Washing Machine Co., Ltd.  
**Address** ..... : East Guanhaiwei Industrial Zone, Cixi City, Zhejiang Province, 315314, P. R. China  
**Manufacturer** ..... : The same as above  
**Address** ..... : The same as above  
**Product Name** ..... : Fully Automatic Washing Machine(電気洗濯機)  
**Model No.** ..... : FW30-2039, FW30-U508, FW30-U528, FW30-1508, FW35-2039, FW35-U508, FW35-U528, FW35-1508, FW35-1939, FW35-19399, FW35-HU528  
**Test specification** ..... : J55014-1(H27)  
**Date of Receipt sample** .... : 2024-02-29  
**Date of Test** ..... : 2024-03-01 to 2024-03-25  
**Date of Issue** ..... : 2024-04-29  
**Test Report Form No.** ..... : WEH-J55014A-01B  
**Test Result** ..... : **Pass**

**Remarks:**

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

**Prepared By:**

**Waltek Testing Group (Foshan) Co., Ltd.**


Address: 1/F., Building 19, Sunlink Machinery City, Xingye 4 Road,  
Guanglong Industrial Park, Chihua Neighborhood Committee, Chencun Town,  
Shunde District, Foshan, Guangdong, China

Tel:+86-757-23811398


Fax:+86-757-23811381

E-mail:info@waltek.com.cn

Tested by:

  
Kyrie Yun

Approved by:

  
Danny Zhou



## 1 Test Summary

EMISSION			
Test Item	Test Standard	Class / Severity	Result
Mains Terminal Disturbance Voltage, 148.5kHz to 30MHz	J55014-1(H27)	Table 1 of J55014-1	Pass
Disturbance Power, 30MHz to 300MHz	J55014-1(H27)	Table 2a, 2b of J55014-1	Pass
Discontinuous Disturbance (Click)	J55014-1(H27)	Clause 4.2.2 of J55014-1	Pass
Radiated Emission, 30MHz to 1000MHz	J55014-1(H27)	Table 3 of J55014-1	N/A

Remark:

Pass      Test item meets the requirement  
Fail        Test item does not meet the requirement  
N/A        Test case does not apply to the test object

# WALTEK





## 2 Contents

	Page
<b>COVER PAGE .....</b>	<b>1</b>
<b>1 TEST SUMMARY .....</b>	<b>2</b>
<b>2 CONTENTS .....</b>	<b>3</b>
<b>3 GENERAL INFORMATION .....</b>	<b>4</b>
3.1 GENERAL DESCRIPTION OF E.U.T .....	4
3.2 DETAILS OF E.U.T. ....	4
3.3 DESCRIPTION OF SUPPORT UNITS .....	4
3.4 STANDARDS APPLICABLE FOR TESTING.....	4
3.5 TEST FACILITY.....	5
3.6 SUBCONTRACTED.....	5
3.7 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
<b>4 EQUIPMENT USED DURING TEST.....</b>	<b>6</b>
4.1 SOFTWARE LIST .....	7
4.2 MEASUREMENT UNCERTAINTY .....	7
4.3 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT .....	7
4.4 DECISION RULE.....	7
<b>5 EMISSION TEST RESULTS.....</b>	<b>8</b>
5.1 MAINS TERMINALS DISTURBANCE VOLTAGE, 148.5kHz TO 30MHz.....	8
5.1.1 E.U.T. Operation .....	8
5.1.2 Block Diagram of Test Setup.....	8
5.1.3 Measurement Data .....	8
5.1.4 Corrected Amplitude & Margin Calculation.....	9
5.1.5 Mains Terminals Disturbance Voltage Test Data .....	9
5.2 DISTURBANCE POWER, 30MHz TO 300MHz .....	17
5.2.1 E.U.T. Operation .....	17
5.2.2 Block Diagram of Test Setup.....	17
5.2.3 Measurement Data .....	17
5.2.4 Disturbance Power Test Results on AC Line.....	18
5.3 DISCONTINUOUS DISTURBANCE (CLICK).....	22
5.3.1 E.U.T. Operation .....	22
5.3.2 Block Diagram of Setup.....	22
5.3.3 Measurement Data .....	22
5.3.4 Discontinuous Disturbance(Click) Test Results.....	23
<b>6 PHOTOGRAPHS – TEST SETUP .....</b>	<b>27</b>
6.1 PHOTOGRAPH – MAINS TERMINAL DISTURBANCE VOLTAGE TEST SETUP.....	27
6.2 PHOTOGRAPH – DISTURBANCE POWER TEST SETUP.....	27
6.3 PHOTOGRAPH – DISCONTINUOUS DISTURBANCE (CLICK) TEST SETUP.....	28
<b>7 PHOTOGRAPHS – CONSTRUCTIONAL DETAILS.....</b>	<b>29</b>
7.1 EUT – EXTERNAL VIEW.....	29



### 3 General Information

#### 3.1 General Description of E.U.T.

**Product Name** ..... : Fully Automatic Washing Machine(電気洗濯機)

**Model No.** ..... : FW30-2039, FW30-U508, FW30-U528, FW30-1508, FW35-2039, FW35-U508, FW35-U528, FW35-1508, FW35-1939, FW35-19399, FW35-HU528

**Remark**..... : There are 2 kinds different circuit diagram and PCB layout among all models:  
 (1) Models from Item 1 to 8 are identical only except for appearance.  
 (2) Models from Item 9 to 11 are identical only except for appearance.  
 Other details refer to section 3.2 model list.  
 Based on the above information, the applicable tests were performed on the two representative models: FW35-1508, FW35-19399.

#### 3.2 Details of E.U.T.

**Technical Data** ..... :

Item	Model	Rated Input	Wash Power	Spin Power
1.	FW30-2039	AC 100V, 50/60Hz	240W	200W
2.	FW30-U508	AC 100V, 50/60Hz	240W	200W
3.	FW30-U528	AC 100V, 50/60Hz	240W	200W
4.	FW30-1508	AC 100V, 50/60Hz	240W	200W
5.	FW35-2039	AC 100V, 50/60Hz	240W	200W
6.	FW35-U508	AC 100V, 50/60Hz	240W	200W
7.	FW35-U528	AC 100V, 50/60Hz	240W	200W
8.	<b>FW35-1508</b>	AC 100V, 50/60Hz	240W	200W
9.	FW35-1939	AC 100V, 50/60Hz	260W	220W
10.	<b>FW35-19399</b>	AC 100V, 50/60Hz	260W	220W
11.	FW35-HU528	AC 100V, 50/60Hz	260W	220W

#### 3.3 Description of Support Units

The EUT has been tested as an independent unit. FW35-1508, FW35-19399 are the test samples. All tests were performed in the condition of AC 100V/50Hz and AC 100V/60Hz input.

#### 3.4 Standards Applicable for Testing

The tests were performed according to following standards:

J55014-1(H27) 家庭用電気機器、電動工具及び類似品機器からの  
妨害波の許容値と測定法





### 3.5 Test Facility

The test facility has a test site registered with the following organizations:

- **ISED – Registration No.: 21895**

Waltek Testing Group (Foshan) Co., Ltd. has been registered and fully described in a report filed with the Innovation, Science and Economic Development Canada (ISED). The acceptance letter from the ISED is maintained in our files. Registration ISED number: 21895, March 12, 2019

- **FCC – Registration No.: 820106**

Waltek Testing Group (Foshan) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 820106, August 16, 2018

- **NVLAP – Lab Code: 600191-0**

Waltek Testing Group (Foshan) Co., Ltd. EMC Laboratory is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 600191-0.

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

### 3.6 Subcontracted

Whether parts of tests for the product have been subcontracted to other labs:

☐ Yes ☒ No

If Yes, list the related test items and lab information:

Test items: ---

Lab information: ---

### 3.7 Abnormalities from Standard Conditions

None.



#### 4 Equipment Used during Test

<input checked="" type="checkbox"/> Mains Terminal Disturbance Voltage (Conducted Emission) 1#					
Item	Equipment	Manufacturer	Model No.	Serial No.	Calibration Status
1.	EMI Test Receiver	R&S	ESR3	102423	Valid
2.	LISN	R&S	ENV216	101343	Valid
3.	Cable 7	HUBER+SUHNER	CBL2-NN-6M	223NN624	Valid
4.	Switch	CD	RSU-A4 18G	RSUA4008	Valid
<input type="checkbox"/> Mains Terminal Disturbance Voltage (Conducted Emission) 2#					
Item	Equipment	Manufacturer	Model No.	Serial No.	Calibration Status
1.	EMI Test Receiver	R&S	ESCI	101178	Valid
2.	LISN	R&S	ENV216	101215	Valid
3.	Cable 1	HUBER+SUHNER	CBL2-NN-6M	6102701	Valid
4.	Switch	ESE	RSU/M2	---	Valid
<input type="checkbox"/> Mains Terminal Disturbance Voltage (Conducted Emission) 3#					
Item	Equipment	Manufacturer	Model No.	Serial No.	Calibration Status
1.	EMI Test Receiver	R&S	ESR3	102842	Valid
2.	LISN	R&S	ENV216	101542	Valid
3.	Cable 12	YIHENG	LMR195UF-NMNM-2.5	---	Valid
4.	Manual RF Switch	YIHENG	SW-2	RSU0402	Valid
<input checked="" type="checkbox"/> Disturbance Power 1#					
Item	Equipment	Manufacturer	Model No.	Serial No.	Calibration Status
1.	EMI Test Receiver	R&S	ESR3	102423	Valid
2.	Absorbing Clamp	TESEQ	MDS21B	52398	Valid
3.	Cable 6	HUBER+SUHNER	CBL2-NN-3m	223NN322	Valid
4.	Switch	CD	RSU-A4 18G	RSUA4008	Valid
<input type="checkbox"/> Disturbance Power 2#					
Item	Equipment	Manufacturer	Model No.	Serial No.	Calibration Status
1.	EMI Test Receiver	R&S	ESCI	101178	Valid
2.	Absorbing Clamp	LUTHI	MDS21	4067	Valid
3.	Cable 5	HUBER+SUHNER	CBL2-NN-12m	223NN121	Valid
4.	Switch	ESE	RSU/M2	---	Valid
<input checked="" type="checkbox"/> Discontinuous Disturbance					
Item	Equipment	Manufacturer	Model No.	Serial No.	Calibration Status
1.	Discontinues Disturbance Analyzer	TESEQ	DIA1512D	28302	Valid
2.	LISN	SCHWARZBECK	NSLK 8128	8128-289	Valid

☐: Not Used

☒: Used





#### 4.1 Software List

Description	Manufacturer	Model	Version
EMI Test Software (Conducted Emission 1#)	FARATRONIC	EZ-EMC	EMEC-3A1
EMI Test Software (Conducted Emission 2#)	FARATRONIC	EZ-EMC	CON-03A1
EMI Test Software (Conducted Emission 3#)	FARATRONIC	EZ-EMC	COM 3A1.1
EMI Test Software (Disturbance Power 1#)	FARATRONIC	EZ-EMC	EMEC-3A1
EMI Test Software (Disturbance Power 2#)	FARATRONIC	EZ-EMC	CON-03A1
Click Test Software	SCHAFFNER	DIS9966	V2.5

#### 4.2 Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Conducted Emission	150kHz~30MHz	$\pm 2.6\text{dB}$	(1)
Disturbance Power	30MHz~300MHz	$\pm 3.2\text{dB}$	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

#### 4.3 Special Accessories and Auxiliary Equipment

Item	Equipment	Technical Data	Manufacturer	Model No.	Serial No.
1.	/	/	/	/	/

#### 4.4 Decision Rule

Compliance or non-compliance with a disturbance limit shall be determined in the following manner.

**If  $U_{\text{LAB}}$  is less than or equal to  $U_{\text{cispr}}$ , then**

- Compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- Non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

**If  $U_{\text{LAB}}$  is greater than  $U_{\text{cispr}}$ , then**

- Compliance is deemed to occur if no measured disturbance level, increased by  $(U_{\text{LAB}} - U_{\text{cispr}})$ , exceeds the disturbance limit;
- Non-compliance is deemed to occur if any measured disturbance level, increased by  $(U_{\text{LAB}} - U_{\text{cispr}})$ , exceeds the disturbance limit.



## 5 Emission Test Results

### 5.1 Mains Terminals Disturbance Voltage, 148.5kHz to 30MHz

Test Requirement..... : J55014-1  
Test Method..... : J55014-1  
Test Result..... : Pass  
Frequency Range..... : 148.5kHz to 30MHz  
Class/Severity..... : Table 1 of J55014-1

#### 5.1.1 E.U.T. Operation

##### Operating Environment:


Temperature..... : 24.8°C  
Humidity..... : 49.3%RH  
Atmospheric Pressure..... : 101.2kPa

##### EUT Operation:

Input Voltage..... : AC 100V/50Hz, AC 100V/60Hz  
Operating Mode..... : Wash mode

#### 5.1.2 Block Diagram of Test Setup

The Mains Terminals Disturbance Voltage tests were performed in accordance with the J55014-1.



#### 5.1.3 Measurement Data

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.





### 5.1.4 Corrected Amplitude & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Measurement} = \text{Reading Level} + \text{Correct Factor}$$

$$\text{Correct Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Measurement} - \text{Limit}$$

### 5.1.5 Mains Terminals Disturbance Voltage Test Data


**Model FW35-1508**

**AC 100V/50Hz input**

**Live Line**




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.3940	2.60	9.76	12.36	57.98	-45.62	QP	
2		0.3940	-1.40	9.76	8.36	49.94	-41.58	AVG	
3		0.5700	2.79	9.76	12.55	56.00	-43.45	QP	
4		0.5700	-5.53	9.76	4.23	46.00	-41.77	AVG	
5		0.8420	2.20	9.78	11.98	56.00	-44.02	QP	
6		0.8420	-3.67	9.78	6.11	46.00	-39.89	AVG	
7		1.0140	1.89	9.78	11.67	56.00	-44.33	QP	
8	*	1.0140	-2.65	9.78	7.13	46.00	-38.87	AVG	
9		1.2860	2.25	9.79	12.04	56.00	-43.96	QP	
10		1.2860	-3.07	9.79	6.72	46.00	-39.28	AVG	
11		1.7340	2.89	9.79	12.68	56.00	-43.32	QP	
12		1.7340	-3.85	9.79	5.94	46.00	-40.06	AVG	


**Model FW35-1508****AC 100V/50Hz input****Neutral Line**

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
		MHz	dBuV	Factor	ment	dBuV	dB	Detector	Comment
1		0.3220	3.76	9.69	13.45	59.66	-46.21	QP	
2		0.3220	1.59	9.69	11.28	52.61	-41.33	AVG	
3		0.4900	3.98	9.71	13.69	56.17	-42.48	QP	
4	*	0.4900	-1.45	9.71	8.26	46.37	-38.11	AVG	
5		0.7660	4.49	9.73	14.22	56.00	-41.78	QP	
6		0.7660	-2.63	9.73	7.10	46.00	-38.90	AVG	
7		0.9460	3.31	9.74	13.05	56.00	-42.95	QP	
8		0.9460	-2.48	9.74	7.26	46.00	-38.74	AVG	
9		1.2140	3.05	9.74	12.79	56.00	-43.21	QP	
10		1.2140	-2.82	9.74	6.92	46.00	-39.08	AVG	
11		2.5579	3.29	9.79	13.08	56.00	-42.92	QP	
12		2.5579	-3.58	9.79	6.21	46.00	-39.79	AVG	




**Model FW35-1508****AC 100V/60Hz input****Live Line**

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		5.2260	14.29	9.92	24.21	60.00	-35.79	QP	
2		5.2260	4.34	9.92	14.26	50.00	-35.74	AVG	
3		12.0140	16.23	10.15	26.38	60.00	-33.62	QP	
4		12.0140	5.09	10.15	15.24	50.00	-34.76	AVG	
5		14.2420	24.64	10.21	34.85	60.00	-25.15	QP	
6		14.2420	14.04	10.21	24.25	50.00	-25.75	AVG	
7		15.9980	24.44	10.25	34.69	60.00	-25.31	QP	
8	*	15.9980	14.99	10.25	25.24	50.00	-24.76	AVG	
9		21.9380	11.03	10.33	21.36	60.00	-38.64	QP	
10		21.9380	-1.08	10.33	9.25	50.00	-40.75	AVG	
11		25.5140	14.77	10.37	25.14	60.00	-34.86	QP	
12		25.5140	1.43	10.37	11.80	50.00	-38.20	AVG	


**Model FW35-1508****AC 100V/60Hz input****Neutral Line**

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector Comment
1		5.2380	14.31	9.90	24.21	60.00	-35.79	QP
2		5.2380	3.73	9.90	13.63	50.00	-36.37	AVG
3		12.2700	18.08	10.16	28.24	60.00	-31.76	QP
4		12.2700	8.08	10.16	18.24	50.00	-31.76	AVG
5	*	14.2940	28.07	10.24	38.31	60.00	-21.69	QP
6		14.2940	17.93	10.24	28.17	50.00	-21.83	AVG
7		16.3340	26.99	10.30	37.29	60.00	-22.71	QP
8		16.3340	15.33	10.30	25.63	50.00	-24.37	AVG
9		17.8180	18.89	10.32	29.21	60.00	-30.79	QP
10		17.8180	9.69	10.32	20.01	50.00	-29.99	AVG
11		23.9460	13.34	10.45	23.79	60.00	-36.21	QP
12		23.9460	2.30	10.45	12.75	50.00	-37.25	AVG




**Model FW35-19399****AC 100V/50Hz input****Live Line**

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
		MHz	Level	Factor	ment			Detector	Comment
			dBuV	dB	dBuV	dBuV	dB		
1		0.1590	15.59	9.71	25.30	65.52	-40.22	QP	
2		0.1590	-3.46	9.71	6.25	58.37	-52.12	AVG	
3		0.1940	11.48	9.72	21.20	63.86	-42.66	QP	
4		0.1940	-4.52	9.72	5.20	56.22	-51.02	AVG	
5		8.0020	11.23	10.03	21.26	60.00	-38.74	QP	
6		8.0020	11.15	10.03	21.18	50.00	-28.82	AVG	
7		14.2780	12.98	10.22	23.20	60.00	-36.80	QP	
8		14.2780	-0.82	10.22	9.40	50.00	-40.60	AVG	
9		16.0020	21.63	10.25	31.88	60.00	-28.12	QP	
10		16.0020	18.19	10.25	28.44	50.00	-21.56	AVG	
11		24.0020	22.25	10.35	32.60	60.00	-27.40	QP	
12	*	24.0020	22.30	10.35	32.65	50.00	-17.35	AVG	


**Model FW35-19399****AC 100V/50Hz input****Neutral Line**

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector Comment
1		0.1580	14.87	9.65	24.52	65.57	-41.05	QP
2		0.1580	-3.32	9.65	6.33	58.44	-52.11	AVG
3		7.9980	11.32	10.02	21.34	60.00	-38.66	QP
4		7.9980	11.29	10.02	21.31	50.00	-28.69	AVG
5		11.5100	23.05	10.15	33.20	60.00	-26.80	QP
6		11.5100	8.95	10.15	19.10	50.00	-30.90	AVG
7		13.3340	30.34	10.21	40.55	60.00	-19.45	QP
8	*	13.3340	21.31	10.21	31.52	50.00	-18.48	AVG
9		15.0020	31.04	10.26	41.30	60.00	-18.70	QP
10		15.0020	18.90	10.26	29.16	50.00	-20.84	AVG
11		21.8020	20.24	10.40	30.64	60.00	-29.36	QP
12		21.8020	9.03	10.40	19.43	50.00	-30.57	AVG



**Model FW35-19399****AC 100V/60Hz input****Live Line**

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		7.9980	11.27	10.03	21.30	60.00	-38.70	QP	
2		7.9980	11.26	10.03	21.29	50.00	-28.71	AVG	
3		11.4580	20.73	10.14	30.87	60.00	-29.13	QP	
4		11.4580	9.00	10.14	19.14	50.00	-30.86	AVG	
5		13.3340	28.78	10.20	38.98	60.00	-21.02	QP	
6		13.3340	18.64	10.20	28.84	50.00	-21.16	AVG	
7		14.8500	28.96	10.24	39.20	60.00	-20.80	QP	
8	*	14.8500	19.96	10.24	30.20	50.00	-19.80	AVG	
9		15.9980	21.95	10.25	32.20	60.00	-27.80	QP	
10		15.9980	13.54	10.25	23.79	50.00	-26.21	AVG	
11		21.9300	20.64	10.33	30.97	60.00	-29.03	QP	
12		21.9300	8.24	10.33	18.57	50.00	-31.43	AVG	

**Model FW35-19399****AC 100V/60Hz input****Neutral Line**

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		8.0020	11.33	10.02	21.35	60.00	-38.65	QP	
2		8.0020	11.29	10.02	21.31	50.00	-28.69	AVG	
3		11.4780	22.39	10.15	32.54	60.00	-27.46	QP	
4		11.4780	9.84	10.15	19.99	50.00	-30.01	AVG	
5		13.3340	29.99	10.21	40.20	60.00	-19.80	QP	
6		13.3340	18.89	10.21	29.10	50.00	-20.90	AVG	
7		14.7140	29.40	10.25	39.65	60.00	-20.35	QP	
8	*	14.7140	20.05	10.25	30.30	50.00	-19.70	AVG	
9		15.5260	22.93	10.28	33.21	60.00	-26.79	QP	
10		15.5260	12.29	10.28	22.57	50.00	-27.43	AVG	
11		21.9180	19.78	10.42	30.20	60.00	-29.80	QP	
12		21.9180	8.37	10.42	18.79	50.00	-31.21	AVG	





## 5.2 Disturbance Power, 30MHz to 300MHz

Test Requirement.....	: J55014-1
Test Method.....	: J55014-1
Test Result.....	: Pass
Frequency Range .....	: 30MHz to 300MHz
Class/Severity.....	: Table 2a, 2b of J55014-1

### 5.2.1 E.U.T. Operation

#### Operating Environment:


Temperature .....	: 26.0°C
Humidity.....	: 60.0%RH
Barometric Pressure.....	: 101.2kPa

#### EUT Operation:

Input Voltage .....	: AC 100V/50Hz, AC 100V/60Hz
Operating Mode.....	: Wash mode

### 5.2.2 Block Diagram of Test Setup

The Disturbance Power test was performed in accordance with the J55014-1.



### 5.2.3 Measurement Data


Extending the cable to 6 meters, performed quasi-peak & average measurements since peak emissions from the EUT were detected within 15dB of the limit line. Average measurements were only performed if the quasi-peak measurements were within 15dB of the average limit line.



## 5.2.4 Disturbance Power Test Results on AC Line

Model FW35-1508


AC 100V/50Hz input





## Model FW35-1508

## AC 100V/60Hz input








## Model FW35-19399


## AC 100V/50Hz input





## Model FW35-19399

## AC 100V/60Hz input





### 5.3 Discontinuous Disturbance (Click)

Test Requirement..... : J55014-1  
Test Method..... : J55014-1  
Test Result..... : Pass  
Frequency Range..... : 150kHz to 30MHz  
Class/Severity..... : Clause 4.2.2 of J55014-1

#### 5.3.1 E.U.T. Operation

##### Operating Environment:


Temperature..... : 22.6°C  
Humidity..... : 60%RH  
Atmospheric Pressure..... : 101.8kPa

##### EUT Operation :

Input Voltage..... : AC 100V/50Hz, AC 100V/60Hz  
Operating Mode..... : Wash mode

#### 5.3.2 Block Diagram of Setup

The discontinuous disturbance test was performed in accordance with J55014-1.



#### 5.3.3 Measurement Data

If none of the caused clicks has a duration longer than 20ms, 90% of the caused clicks have a duration less than 10ms, and the click rate is not more than 5, then the product is deemed to comply with the click requirements of J55014-1. See Clause 4.2.3.4 of J55014-1 for further details.





### 5.3.4 Discontinuous Disturbance(Click) Test Results

Test Model: FW35-1508

Input Voltage: AC 100V/50Hz input

Run A Observation time T1= 120 mins 0 secs

Frequency	150kHz	500kHz	1.4MHz	30MHz
Limit value (L)(dBuV)	56	46	46	50
Short clicks	0	0	0	0
Long clicks	0	0	0	0
Total (short + long) n	0	0	0	0
Click rate	0.00	0.00		
Continuous Interference (max)	0.00sec	0.00sec	0.00sec	0.00sec

Switching operations: s= ---

Click rate formula:  $N = n / T1$ 

Click rate used in calculating Run B limit : N1= --- N2= --- (used for 0.5MHz to 30MHz)

Run B Observation time T2= N/A

Frequency	150kHz	500kHz	1.4MHz	30MHz
Limit value (L)(dBuV) $L_q = L + 20 \log 30/N$ (max L + 44)	---	---	---	---
Short clicks	---	---	---	---
Long clicks	---	---	---	---
Total (short + long) n	---	---	---	---
Limit = RunA/4	---	---	---	---



Test Model: FW35-1508

Input Voltage: AC 100V/60Hz input

Run A Observation time T1= 120 mins 0 secs

Frequency	150kHz	500kHz	1.4MHz	30MHz
Limit value (L)(dBuV)	56	46	46	50
Short clicks	0	0	0	0
Long clicks	0	0	0	0
Total (short + long) n	0	0	0	0
Click rate	0.00	0.00		
Continuous Interference (max)	0.00sec	0.00sec	0.00sec	0.00sec

Switching operations: s= ---

Click rate formula:  $N = n / T1$ Click rate used in calculating Run B limit :  $N1 = \text{---}$   $N2 = \text{---}$  (used for 0.5MHz to 30MHz)

Run B Observation time T2= N/A

Frequency	150kHz	500kHz	1.4MHz	30MHz
Limit value (L)(dBuV) $L_q = L + 20 \log 30/N$ (max $L + 44$ )	---	---	---	---
Short clicks	---	---	---	---
Long clicks	---	---	---	---
Total (short + long) n	---	---	---	---
Limit = RunA/4	---	---	---	---



Test Model: FW35-19399

Input Voltage: AC 100V/50Hz input

Run A Observation time T1= 120 mins 0 secs

Frequency	150kHz	500kHz	1.4MHz	30MHz
Limit value (L)(dBuV)	56	46	46	50
Short clicks	0	0	0	0
Long clicks	0	0	0	0
Total (short + long) n	0	0	0	0
Click rate	0.00	0.00		
Continuous Interference (max)	0.00sec	0.00sec	0.00sec	0.00sec

Switching operations: s= ---

Click rate formula:  $N = n / T1$ 

Click rate used in calculating Run B limit : N1= --- N2= --- (used for 0.5MHz to 30MHz)

Run B Observation time T2= N/A

Frequency	150kHz	500kHz	1.4MHz	30MHz
Limit value (L)(dBuV) $L_q = L + 20 \log 30/N$ (max L + 44)	---	---	---	---
Short clicks	---	---	---	---
Long clicks	---	---	---	---
Total (short + long) n	---	---	---	---
Limit = RunA/4	---	---	---	---





Test Model: FW35-19399

Input Voltage: AC 100V/60Hz input

Run A Observation time T1= 120 mins 0 secs

Frequency	150kHz	500kHz	1.4MHz	30MHz
Limit value (L)(dBuV)	56	46	46	50
Short clicks	0	0	0	0
Long clicks	0	0	0	0
Total (short + long) n	0	0	0	0
Click rate	0.00	0.00		
Continuous Interference (max)	0.00sec	0.00sec	0.00sec	0.00sec

Switching operations: s= ---

Click rate formula:  $N = n / T1$ 

Click rate used in calculating Run B limit : N1= --- N2= --- (used for 0.5MHz to 30MHz)

Run B Observation time T2= N/A

Frequency	150kHz	500kHz	1.4MHz	30MHz
Limit value (L)(dBuV) $L_q = L + 20 \log 30/N$ (max L + 44)	---	---	---	---
Short clicks	---	---	---	---
Long clicks	---	---	---	---
Total (short + long) n	---	---	---	---
Limit = RunA/4	---	---	---	---

Remark:

- 1) The click rate N shall be determined at 150kHz for the frequency range 150kHz to 500kHz and at 500kHz for the frequency 500kHz to 30MHz ;
- 2) During RUN A, the click rate is not more than 5 and there is no long click. RUN B is unnecessary;



## 6 Photographs – Test Setup

### 6.1 Photograph – Mains Terminal Disturbance Voltage Test Setup



### 6.2 Photograph – Disturbance Power Test Setup







### 6.3 Photograph – Discontinuous Disturbance (Click) Test Setup



# WALTEK





## 7 Photographs – Constructional Details

### 7.1 EUT – External View

**Model FW35-1508**



**Model FW35-19399**



===== End of Report =====