Build firmware ESP3D for BigTreeTech E3 RRF

Download in source firmware : ESP3D 2.1.1

1 : Extract ESP3D-2.1.1.zip and copy the extract folder to the folder of your choice.

2 : Open Vscode and go to platformio extension. With platformio add folder ESP3D-2.1.1 extract previously.

3 : Now you need to configure the file platformio.ini for the wifi module ESP07S.

replace the parameters « dev » by :

[env:esp07s]
platform = espressif8266
board = esp07s
framework = arduino
monitor_speed = 115200
board_build.f_cpu = 80000000L
board_build.f_flash = 40000000L
board_build.flash_mode = qio

you need to get this:



4 : Once these parameters are added you can successfully compile the firmware for ESP3D.

5 : the firmware is located in the starting ESP3D folder D:\USER\Document\ESP3D-2.1.1\ESP3D-2.1.1\.pioenvs\esp8266

6 : Rename the firmware.bin file to ESP3D.bin

7 : Now all you have to do is copy this file into your SD card, insert it into your motherboard and turn on your printer. Wait a moment and your firmware is installed!

8 : Your printer is now available on your network, but there are still a few settings to activate so that your user interface works and your printer can connect to your network on its own.

9 : In your network manager connect you to ESP3D, open your browser and enter the base address 192.168.0.1 , the password is 12345678 .

10 : you are now connected to your printer, you will need to add the missing files in order to complete the configuration of your user interface.

11 : Go to your ESP3D folder and go to the folder D:\USER\Document\ESP3D-2.1.1\ESP3D-2.1.1\docs\Files

you must find this:

404
favicon
index.html

12 : copy the three files into your web interface and click upload

13 : Once the download is complete you can proceed to the web interface configuration step.







Click on the magnifying glass to select your network



add your network password



14 : After the configuration is complete, restart your printer and connect your computer to your regular network.

15 : Your printer must now display a new IP address

In the example below the IP address is 192.168.2.41

now you are connect !



Perform a test when entering the G28 commands

your printer communicates with your network and realizes are AUTOHOME



The installation is complete, you can configure your ESP3D and printer from the user interface.

Create by So’6 Rallye