Failsafe ECU through dynamic partial-reconfiguration in FPGAs

Constantin Schieber, 01228774 Rupert Schorn, XXXXXXX Andreas Hirtenlehner, XXXXXXXX Peter Schober, XXXXXXX

February 26, 2019

1 Introduction

Brief overview, problem statement and final outcome.

1.1 Required Tools and packages

- Vivado 2018.3
- \bullet Vivado 2018.2
- uVision 5 (Windows only)
- ARM Keil (Windows only)
- ARM Cortex M1 IP for Vivado




Figure 1: Block Diagram of the partial reconfiguration functionality

2 Cortex M1 / M3

Description of the setup of Cortex M1 and Cortex M3 Cores. [1] [2]

2.1 Usage of the Keil Toolchain

Link to tutorial enough? Maybe most basic steps (e.g. adaption of arty project for our needs). [3]

2.2 Usage of Cortex M1 in Vivado

Only global implementation / synthesis runs are permitted to obtain a working bitstream. If OOC (Out of Context) runs are used, everything except for the Cortex M1 will work fine. The Cortex M1 will enter a hard-fault state which does not allow recovery. This is indicated by a high bit on the Lockup port of the processor.

Also trivial, follow tutorial that is provided on ARM Website and adapt to own needs.

2.2.1 Code via Memory Initialization File

File is bound to synthesis process, how to change it...

2.3 How to mbed OS

How was the Cortex M1 Project adapted to support the Mbed OS? What is gained through the usage of mbed OS?

2.4 Implemented Functionality on the Cortex M1

How are the UART and IIC peripherals supported in the source code, which libraries are used, interrupt based or not, performance?

Show highlights of the code?

3 Bus and Peripherals

3.1 Used Peripherals

What Peripherals were used (Cortex M1/M3 Boards, which ones).

How to program / use them (only brief).

How are they connected to the Bus?

IIC and UART here or in next section.

3.2 Bus

How is it set up?

Made assumptions?

Document used / invented protocol.

4 Partial Reconfiguration

What is partially reconfigured - Cortex, uart, IIC.

Why not use AXI?

4.1 Integration Overview

[4], [5] Usage of ICAP.

How is the Zynq still used - Loading images and binary blobs from sd card into DDR.

4.2 Packaged IP

Why is the PR IP Packaged, how was it done? [?]

5 Organization

5.1 Assigned Sub-Tasks

5.1.1 Cortex M1

Evaluation of the provided Cortex-M1 from ARM and adaption of the provided toolchain to our needs.

Creation of a working stand-alone example, creation and integration of working IP-Packages for the Cortex-M1

5.1.2 Partial Reconfiguration

5.1.3 Bus Design

5.1.4 Hardware

5.2 Estimated Contribution

Contribution to the project was roughly the same for each group member.

Name	Cortex M1	Partial Reconfiguration	Bus Design	Hardware	mbed OS
Andreas Hirtenlehner	X			X	X
Constantin Schieber	X	\mathbf{X}			
Peter Schober	X	X			
Rupert Schorn			X	X	X

References

- "Arm® $DesignStart^{TM}$ [1] ARM, Cortex®-M1 FPGA-Xilinx edi-2018. Available: User Guide," [Online]. tion https: //static.docs.arm.com/100211/0001/arm cortex m1 designstart fpga_xilinx_edition_ug_100211_0001_00_en.pdf?_ga=2.121336076. 523725493.1550477241-1711067005.1549732081
- [2] —, "Cortex-M1 Technical Reference Manual." [Online]. Available: https://static.docs.arm.com/ddi0413/d/DDI0413D_cortexm1_r1p0_trm.pdf
- [3] "Getting Started." [Online]. Available: http://www2.keil.com/mdk5/install
- [4] Xilinx, "Vivado Design Suite User Guide: Partial Reconfiguration (UG909)," 2018. [Online]. Available: https://www.xilinx.com/support/documentation/sw_manuals/xilinx2018_3/ug909-vivado-partial-reconfiguration.pdf