

This document is free software; you can redistribute it and/or  
 Â Â Â modify it under the terms of the GNU General Public License,  
 version 2, as published by the Free Software Foundation.

You should have received a copy of the GNU General Public License  
 along with this program; if not, write to the Free Software  
 Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA  
 02110-1301 USA.

2009-02-14

[illegible]

## 1. Introduction

- ## 2. What's new in Debian GNU/Linux 5.0

- ### 2.3.1. Changes in kernel packaging

- ### 3. Installation System

- ### 3.1. What's new in the installation system?
- 3.1.1. Major changes
  - 3.1.2. Automated installation

## 4. Upgrades from previous releases

### 4.1. Preparing for the upgrade

- 4.1.1. Back up any data or configuration information
- 4.1.2. Inform users in advance
- 4.1.3. Prepare for recovery
- 4.1.4. Prepare a safe environment for the upgrade

### 4.2. Checking system status

- 4.2.1. Review actions pending in package manager
- 4.2.2. Disabling APT pinning
- 4.2.3. Checking packages status
- 4.2.4. The proposed-updates section
- 4.2.5. Unofficial sources and backports

### 4.3. Manually unmarking packages

### 4.4. Preparing sources for APT

- 4.4.1. Adding APT Internet sources
- 4.4.2. Adding APT sources for a local mirror
- 4.4.3. Adding APT source from CD-ROM or DVD

### 4.5. Upgrading packages

- 4.5.1. Recording the session
- 4.5.2. Updating the package list
- 4.5.3. Make sure you have sufficient space for the upgrade
- 4.5.4. Upgrade apt and/or aptitude first
- 4.5.5. Using aptitude's list of automatically-installed packages with apt
- 4.5.6. Minimal system upgrade
- 4.5.7. Upgrading the rest of the system
- 4.5.8. Possible issues during upgrade

### 4.6. Upgrading your kernel and related packages

- 4.6.1. Installing the kernel metapackage
- 4.6.2. Device enumeration reordering
- 4.6.3. Boot timing issues

### 4.7. Things to do before rebooting

- 4.7.1. Ease of use

### 4.8. System boot hangs on Waiting for root file system

- 4.8.1. How to avoid the problem before upgrading
- 4.8.2. How to recover from the problem after the upgrade

### 4.9. Preparing for the next release

### 4.10. Obsolete packages

- 4.10.1. Dummy packages

## 5. Issues to be aware of for lenny

### 5.1. Potential problems

- 5.1.1. Problems with devices related to udev
- 5.1.2. Some applications may no longer work with a 2.4 kernel
- 5.1.3. Certain network sites cannot be reached by TCP
- 5.1.4. Automatic poweroff stops working

- 5.1.5. Asynchronous network initialization may cause unpredictable behavior
- 5.1.6. Trouble when using WPA secured wireless networks
- 5.1.7. Problems with non-ASCII characters in filenames
- 5.1.8. Sound stops working
- 5.1.9. Potential Filesystem Corruption on upgrade

- 5.2. NFS mounts now handled by nfs-common
- 5.3. Change of Romanian (ro) keyboard layout
- 5.4. Upgrading apache2
- 5.5. NIS and Network Manager
- 5.6. Security status of Mozilla products
- 5.7. Security status of OCS Inventory and SQL-Ledger
- 5.8. KDE desktop
- 5.9. GNOME desktop changes and support
- 5.10. No default support for Unicode in emacs21\*
- 5.11. slurpd/replica will no longer work
- 5.12. Desktop not using full screen
- 5.13. DHCP failover issue
- 5.14. VServer Disk Limit

## 6. More information on Debian GNU/Linux

- 6.1. Further reading
- 6.2. Getting help
  - 6.2.1. Mailing lists
  - 6.2.2. Internet Relay Chat
- 6.3. Reporting bugs
- 6.4. Contributing to Debian

## A. Managing your etch system

- A.1. Upgrading your etch system
- A.2. Checking your sources list

## B. Contributors to the Release Notes

## C. Lenny dedicated to Thiemo Seufer

## Index

## Glossary

## Chapter 1. Introduction

This document informs users of the Debian GNU/Linux distribution about major changes in version 5.0 (codenamed "lenny").

The release notes provide information on how to upgrade safely from release 4.0 (codenamed etch) to the current release and inform users of known potential issues they could encounter in that process.

You can get the most recent version of this document from <http://www.debian.org/releases/lenny/releasenotes> (<http://www.debian.org/releases/lenny/releasenotes>) . If in doubt, check the date on the first page to make sure you are reading a current version.

### Caution

Note that it is impossible to list every known issue and that therefore a selection has been made based on a combination of the expected prevalence and impact of issues.

Please note that we only support and document upgrading from the previous release of Debian (in this case, the upgrade from 4.0).

If you need to upgrade from older releases, we suggest you read previous editions of the release notes and upgrade to 4.0 first.

### 1.1. Reporting bugs on this document

We have attempted to test all the different upgrade steps described in this document and to anticipate all the possible issues our users might encounter.

Nevertheless, if you think you have found a bug (incorrect information or information that is missing) in this documentation, please file a bug in the bug tracking system (<http://bugs.debian.org/>) against the release-notes package.

### 1.2. Contributing upgrade reports

We welcome any information from users related to upgrades from etch to lenny. If you are willing to share information please file a bug in the bug tracking system (<http://bugs.debian.org/>) against the upgrade-reports package with your results. We request that you compress any attachments that are included (using gzip).

Please include the following information when submitting your upgrade report:

- â– The status of your package database before and after the upgrade: dpkg's status database available at `/var/lib/dpkg/status` and aptitude's package state information, available at `/var/lib/aptitude/pkgstates`. You should have made a backup before the upgrade as described at Section 4.1.1, "Back up any data or configuration information", but you can also find backups of this information in `/var/backups`.

- â– Session logs created using script, as described in Section 4.5.1, "Recording the session".

- â– Your apt logs, available at `/var/log/apt/term.log` or your aptitude logs, available at `/var/log/aptitude`.

Note

You should take some time to review and remove any sensitive and/or confidential information from the logs before including them in a bug report as the information will be published in a public database.

### 1.3. Sources for this document

The source of this document is in DocBook XML format. The HTML version is generated using docbook-xsl and xsltproc. The PDF version is generated using dblatex or xmlroff. Sources for the Release Notes are available in the SVN repository of the Debian Documentation Project. You can use the web interface (<http://svn.debian.org/viewsvn/ddp/manuals/trunk/release-notes/>) to access its files individually through the web and see their changes. For more information on how to access the SVN please consult the Debian Documentation Project SVN information pages (<http://www.debian.org/doc/cvs>) .

## Chapter 2. What's new in Debian GNU/Linux 5.0

The Wiki (<http://wiki.debian.org/NewInLenny>) has more information about this topic.

This release adds official support for the ARM EABI (armel).

^ ^ ^ The following are the officially supported architectures for Debian GNU/Linux lenny:

â–□ Intel x86 ('i386')

â–□ Alpha ('alpha')

â–□ SPARC ('sparc')

â–□ PowerPC ('powerpc')

â– ARM ('power')

^ ^ ^ â–□ MIPS ('mips' (big-endian) and 'mipsel' (little-endian))

â–□ Intel Itanium ('ia64')

â– HP PA-RISC ('hppa')

â–□ S/390 ('s390')

â–□ AMD64 ('amd64')

â–□ ARM EABI ('armel')

You can read more about port status, and port-specific information for your architecture at the Debian port web pages (<http://www.debian.org/ports/>) .

## 2.1.^ What's new in the distribution?

This new release of Debian again comes with a lot more software than its predecessor etch; the distribution includes over 7700 new packages, for a total of over 23200 packages. Most of the software in the distribution has been updated: over 13400 software packages (this is 72% of all packages in etch). Also, a significant number of packages (over 3100, 17% of the packages in etch) have for various reasons been removed from the distribution. You will not see any updates for these packages and they will be marked as 'obsolete' in package management front-ends.

^ ^ ^ With this release, Debian GNU/Linux updates from X.Org 7.1 to X.Org 7.3.

Debian GNU/Linux again ships with several desktop applications and environments. Among others it now includes the desktop environments GNOME 2.22<sup>[1]</sup>, KDE 3.5.10, Xfce 4.4.2, and LXDE 0.3.2.1+svn20080509. Productivity applications have also been upgraded, including the office suites OpenOffice.org 2.4.1 and KOffice 1.6.3 as well as GNUMcash 2.2.6, GNUMeric 1.8.3 and Abiword 2.6.4.

Updates of other desktop applications include the upgrade to Evolution 2.22.3 and Pidgin 2.4.3 (formerly known as Gaim). The Mozilla suite has also been updated: iceweasel (version 3.0.6) is the unbranded Firefox web browser and icedove (version 2.0.0.19) is the unbranded Thunderbird mail client.

^ ^ ^ Among many others, this release also includes the following software updates:

â”€â”€â”€	Package	â”€”,Version in 4.0 â”€”, Version in 5.0 â”€”,
-----------	---------	--

[illegible]

[illegible]

The next time you run aptitude update, the system will become  
Â Â Â aware of the packages in the proposed-updates section and will  
consider them when looking for packages to upgrade.

Â Â Â This is not strictly a new feature of Debian, but one that has  
not been given much exposure before.

## 2.2.Â System improvements

There have been a number of changes in the distribution that will  
Â Â Â benefit new installations of lenny, but may not be automatically  
applied on upgrades from etch. This section gives an overview of  
the most relevant changes.

SELinux priority standard, but not enabled by default

The packages needed for SELinux (Security-Enhanced Linux)  
support have been promoted to priority standard. This means  
that they will be installed by default during new  
installations. For existing systems you can install SELinux  
using:

```
# aptitude install selinux-basics
```

Note that SELinux support is not enabled by default.  
Information on setting up and enabling SELinux can be found  
on the Debian Wiki (<http://wiki.debian.org/SELinux>) .

New default syslog daemon

The package rsyslog takes over as default system and kernel  
logging daemon for Debian 5.0, replacing syslogd and klogd.  
With stock logging rules, it can be used as a drop-in  
replacement; if you have custom rules, you should migrate  
Â Â Â them to the new configuration file, /etc/rsyslog.conf.

Users upgrading from etch need to install rsyslog and remove  
sysklogd manually. The default syslog daemon is not replaced  
automatically at the upgrade to lenny.

Better support for UTF-8

A number of additional applications will be set up to use  
UTF-8 by default or have better UTF-8 support than before.  
See at <http://wiki.debian.org/UTF8BrokenApps> (<http://wiki.debian.org/UTF8BrokenApps>) about applications that still  
have difficulties in handling UTF-8.

Identification of the release's revision

Starting from Lenny, /etc/debian\_version will indicate the  
revision number of the debian release (5.0, then 5.0.1, etc.)

This also means that you should not expect this file to be  
constant throught the release lifetime.

Â Â Â The Debian Wiki (<http://wiki.debian.org/Etch2LennyUpgrade>) has  
some additional information about changes between etch and lenny.

## 2.3.Â Major kernel-related changes

Â Â Â Debian GNU/Linux 5.0 ships with kernel version 2.6.26 for all  
architectures.

There have been major changes both in the kernel itself and in



the packaging of the kernel for Debian. Some of these changes complicate the upgrade procedure and can potentially result in problems while rebooting the system after the upgrade to lenny. This section gives an overview of the most important changes; information on how to work around potential issues is included in later chapters.

### 2.3.1. Changes in kernel packaging

Binary firmware for some drivers moved to non-free

Some drivers load binary firmware into the device they are supporting at run time. While this firmware was included in the stock kernel in previous releases, it has now be separately packaged in the non-free section. If you want to continue to use these devices after reboot, make sure the required firmware is present on the installed system. See section 6.4 of the Installation Manual (<http://www.debian.org/releases/stable/installmanual>) for details.

New OpenVZ kernel flavor

Debian GNU/Linux 5.0 provides pre-built kernel images for OpenVZ, a second virtualization solution to go alongside the Linux-VServer support included in etch. Advantages of OpenVZ include support for live migration, at the expense of a slightly higher overhead.

Kernel x86 packages unified

In previous releases there was a special -k7 kernel flavor for 32-bit AMD Athlon/Duron/Sempron processors. This variant has been dropped; the single single flavor -686 now handles all AMD/Intel/VIA 686 class processors.

Where possible, dummy transition packages that depend on the new packages have been provided for the dropped packages.

### 2.4. Emdebian 1.0 (based on Debian GNU/Linux lenny 5.0)

Lenny now contains the build tools for Emdebian which allow Debian source packages to be cross-built and shrunk to suit embedded ARM systems.

The Emdebian 1.0 distribution itself contains prebuilt ARM packages sufficient to create root filesystems that can be customised for specific machines and machine variants. Kernels and kernel modules need to be provided separately. Support for armel and i386 is under development. See the Emdebian webpage (<http://www.emdebian.org/>) for further information.

### 2.5. Netbook support

Netbooks, such as the Eee PC by Asus, are now supported by Debian. For the Eee PC, have a look at the `eeepc-acpi-scripts`. Also, Debian features a new Lightweight X11 Desktop Environment, `lxde`, which is beneficial for netbooks or other computers with relatively low performance.

### 2.6. Java now in Debian

The OpenJDK Java Runtime Environment `openjdk-6-jre` and Development Kit `openjdk-6-jdk`, needed for executing Java GUI and

Webstart programs or building such programs, are now in Debian. The packages are built using the IcedTea build support and patches from the IcedTea project.

^[1] With some modules from GNOME 2.20.

## Chapter 3. Installation System

The Debian Installer is the official installation system for Debian. It offers a variety of installation methods. Which methods are available to install your system depends on your architecture.

Images of the installer for lenny can be found together with the Installation Guide on the Debian website (<http://www.debian.org/releases/stable/debian-installer/>) .

The Installation Guide is also included on the first CD/DVD of the official Debian CD/DVD sets, at:

[/doc/install/manual/language/index.html](#)

You may also want to check the errata (<http://www.debian.org/releases/stable/debian-installer/index#errata>) for debian-installer for a list of known issues.

### 3.1. What's new in the installation system?

There has been a lot of development on the Debian Installer since its first official release with Debian GNU/Linux 3.1 (sarge) resulting in both improved hardware support and some exciting new features.

In these Release Notes we'll only list the major changes in the installer. If you are interested in an overview of the detailed changes since etch, please check the release announcements for the lenny beta and RC releases available from the Debian Installer's news history (<http://www.debian.org/devel/debian-installer/News/>) .

#### 3.1.1. Major changes

##### Support for loading firmware during installation

It is now possible to load firmware binary files from removable media when they're provided externally to Debian installation media.

##### Support for installation from Microsoft Windows

The installation media are now provided with an application that allows preparing the system to install Debian from Microsoft Windows environments.

##### SATA RAID support

##### Early upgrade of packages with security fixes

When used with functional network access, the installer will upgrade all packages that have been updated since the initial release of lenny. This upgrade happens during the installation step, before the installed system is booted.

As a consequence, the installed system is less likely to be vulnerable to security issues that were discovered and fixed between the release time of lenny and the installation time.

### Support for volatile

The installer can now optionally set up the installed system to use updated packages from [volatile.debian.org](http://volatile.debian.org). This archive hosts packages providing data that needs to be regularly updated over time, such as timezones definitions, anti-virus signature files, etc.

### New ports

The armel architecture is now supported. Images for i386 Xen guests are also provided.

### Support for hardware speech synthesis devices

Â Â Â

Several devices designed to provide hardware speech synthesis are now supported by the installer, therefore improving its accessibility for visually-impaired users.

### Support for relatime mount options

The installer can now set up partitions with the relatime mount option, so that access time on files and directories is updated only if the previous access time was earlier than the current modify or change time.

### NTP clock synchronization at installation time

The computer clock is now synchronized with NTP servers over the network during installation so that the installed system immediately has an accurate clock.

### New languages

Thanks to the huge efforts of translators, Debian can now be installed in 63 languages (50 using the text-based installation user interface and 13 supported only with the graphical user interface). This is five languages more than in etch. Languages added in this release include Amharic, Marathi, Irish, Northern Sami, and Serbian. Due to lack of translation updates, one language has been dropped in this release: Estonian. Another language that was disabled in etch has been reactivated: Welsh.

The languages that can only be selected using the graphical installer as their character sets cannot be presented in a non-graphical environment are: Amharic, Bengali, Dzongkha, Gujarati, Hindi, Georgian, Khmer, Malayalam, Marathi, Nepali, Punjabi, Tamil, and Thai.

### Simplified country choice

The country choice list is now grouped by continents, allowing an easier selection of country, when users don't want to pick the ones associated with the chosen language.

### 3.1.2.Â Automated installation

Some changes mentioned in the previous section also imply changes in the support in the installer for automated installation using

Ã Ã Ã preconfiguration files. This means that if you have existing preconfiguration files that worked with the etch installer, you cannot expect these to work with the new installer without modification.

The Installation Guide (<http://www.debian.org/releases/stable/>Ã Ã Ã installmanual) has an updated separate appendix with extensive documentation on using preconfiguration.

## ChapterÃ 4.Ã Upgrades from previous releases

### 4.1.Ã Preparing for the upgrade

We suggest that before upgrading you also read the information in Ã Ã Ã ChapterÃ 5, Issues to be aware of for lenny. That chapter covers potential issues not directly related to the upgrade process but which could still be important to know about before you begin.

#### 4.1.1.Ã Back up any data or configuration information

Before upgrading your system, it is strongly recommended that you make a full backup, or at least back up any data or configuration Ã Ã Ã information you can't afford to lose. The upgrade tools and process are quite reliable, but a hardware failure in the middle of an upgrade could result in a severely damaged system.

The main things you'll want to back up are the contents of /etc, Ã Ã Ã /var/lib/dpkg, /var/lib/aptitude/pkgstates and the output of dpkg --get-selections "\*" (the quotes are important).

The upgrade process itself does not modify anything in the /home directory. However, some applications (e.g. parts of the Mozilla suite, and the GNOME and KDE desktop environments) are known to overwrite existing user settings with new defaults when a new Ã Ã Ã version of the application is first started by a user. As a precaution, you may want to make a backup of the hidden files and directories (â€¢filesâ€¢) in users' home directories. This backup may help to restore or recreate the old settings. You may also want to inform users about this.

Any package installation operation must be run with superuser Ã Ã Ã privileges, so either log in as root or use su or sudo to gain the necessary access rights.

Ã Ã Ã The upgrade has a few preconditions; you should check them before actually executing the upgrade.

#### 4.1.1.1.Ã Make sure you are on a suitable kernel

lenny's version of glibc will not work with kernels older than 2.6.8 on any architecture and some architectures have higher Ã Ã Ã requirements. We strongly recommend that you upgrade to and test an etch 2.6.18 or 2.6.24 kernel or a custom kernel of at least version 2.6.18 before beginning the upgrade process.

#### 4.1.2.Ã Inform users in advance

It's wise to inform all users in advance of any upgrades you're Ã Ã Ã planning, although users accessing your system via an ssh connection should notice little during the upgrade, and should be able to continue working.

Ã Ã Ã If you wish to take extra precautions, back up or unmount the / home partition before upgrading.

You will probably have to do a kernel upgrade when upgrading to lenny, so a reboot will normally be necessary. Typically, this will be done after the upgrade is finished.

#### 4.1.3. Prepare for recovery

Because of the many changes in the kernel between etch and lenny regarding drivers, hardware discovery and the naming and ordering of device files, there is a real risk that you may experience problems rebooting your system after the upgrade. A lot of known potential issues are documented in this and the next chapters of these Release Notes.

For that reason it makes sense to ensure that you will be able to recover if your system should fail to reboot or, for remotely managed systems, fail to bring up networking.

If you are upgrading remotely via an ssh link it is highly recommended that you take the necessary precautions to be able to access the server through a remote serial terminal. There is a chance that, after upgrading the kernel and rebooting, some devices will be renamed (as described in Section 4.6.2, "Device enumeration reordering") and you will have to fix the system configuration through a local console. Also, if the system is rebooted accidentally in the middle of an upgrade there is a chance you will need to recover using a local console.

The most obvious thing to try first is to reboot with your old kernel. However, for various reasons documented elsewhere in this document, this is not guaranteed to work.

If that fails, you will need an alternative way to boot your system so you can access and repair it. One option is to use a special rescue image or a Linux live CD. After booting from that, you should be able to mount your root file system and chroot into it to investigate and fix the problem.

Another option we'd like to recommend is to use the rescue mode of the lenny Debian Installer. The advantage of using the installer is that you can choose between its many installation methods for one that best suits your situation. For more information, please consult the section "Recovering a Broken System" in chapter 8 of the Installation Guide (<http://www.debian.org/releases/stable/installmanual>) and the Debian Installer FAQ (<http://wiki.debian.org/DebianInstaller/FAQ>).

##### 4.1.3.1. Debug shell during boot using initrd

The initramfs-tools includes a debug shell<sup>[2]</sup> in the initrds it generates. If for example the initrd is unable to mount your root file system, you will be dropped into this debug shell which has basic commands available to help trace the problem and possibly fix it.

Basic things to check are: presence of correct device files in /dev; what modules are loaded (cat /proc/modules); output of dmesg for errors loading drivers. The output of dmesg will also show what device files have been assigned to which disks; you should check that against the output of echo \$ROOT to make sure that the root file system is on the expected device.

If you do manage to fix the problem, typing exit will quit the debug shell and continue the boot process at the point it failed. Of course you will also need to fix the underlying problem and regenerate the initrd so the next boot won't fail again.

#### 4.1.4.Â Prepare a safe environment for the upgrade

Â Â Â The distribution upgrade should be done either locally from a textmode virtual console (or a directly connected serial terminal), or remotely via an ssh link.

Â Â Â In order to gain extra safety margin when upgrading remotely, we suggest that you run upgrade processes in the virtual console provided by the screen program, which enables safe reconnection and ensures the upgrade process is not interrupted even if the remote connection process fails.

Important

Â Â Â You should not upgrade using telnet, rlogin, rsh, or from an X session managed by xdm, gdm or kdm etc on the machine you are upgrading. That is because each of those services may well be terminated during the upgrade, which can result in an inaccessible system that is only half-upgraded.

#### 4.2.Â Checking system status

Â Â Â The upgrade process described in this chapter has been designed for upgrades from *pure* etch systems without third-party packages. For the greatest reliability of the upgrade process, you may wish to remove third-party packages from your system before you begin upgrading.

Â Â Â This procedure also assumes your system has been updated to the latest point release of etch. If you have not done this or are unsure, follow the instructions in SectionÂ A.1, *Upgrading your etch system*.

##### 4.2.1.Â Review actions pending in package manager

Â Â Â In some cases, the use of apt-get for installing packages instead of aptitude might make aptitude consider a package as *unused* and schedule it for removal. In general, you should make sure the system is fully up-to-date and *clean* before proceeding with the upgrade.

Â Â Â Because of this you should review if there are any pending actions in the package manager aptitude. If a package is scheduled for removal or update in the package manager, it might negatively impact the upgrade procedure. Note that correcting this is only possible if your sources.list still points to etch and not to stable or lenny; see SectionÂ A.2, *Checking your sources list*.

Â Â Â To perform this review, launch aptitude in *visual mode* and press g (*Go*). If it shows any actions, you should review them and either fix them or implement the suggested actions. If no actions are suggested you will be presented with a message saying *No packages are scheduled to be installed, removed, or upgraded*.

##### 4.2.2.Â Disabling APT pinning

Â Â Â If you have configured APT to install certain packages from a distribution other than stable (e.g. from testing), you may have to change your APT pinning configuration (stored in /etc/apt/preferences) to allow the upgrade of packages to the versions in the new stable release. Further information on APT pinning can be found in apt\_preferences(5).

#### 4.2.3. Checking packages status

Regardless of the method used for upgrading, it is recommended that you check the status of all packages first, and verify that all packages are in an upgradable state. The following command will show any packages which have a status of Half-Installed or Failed-Config, and those with any error status.

```
# dpkg --audit
```

You could also inspect the state of all packages on your system using `dselect`, `aptitude`, or with commands such as

```
# dpkg -l | pager
```

```
or
```

```
# dpkg --get-selections "*" > ~/curr-pkgs.txt
```

It is desirable to remove any holds before upgrading. If any package that is essential for the upgrade is on hold, the upgrade will fail.

Note that `aptitude` uses a different method for registering packages that are on hold than `apt-get` and `dselect`. You can identify packages on hold for `aptitude` with

```
# aptitude search "~ahold" | grep "^h"
```

If you want to check which packages you had on hold for `apt-get`, you should use

```
# dpkg --get-selections | grep hold
```

If you changed and recompiled a package locally, and didn't rename it or put an epoch in the version, you must put it on hold to prevent it from being upgraded.

The `hold` package state for `aptitude` can be changed using:

```
# aptitude hold package_name
```

Replace `hold` with `unhold` to unset the `hold` state.

If there is anything you need to fix, it is best to make sure your `sources.list` still refers to `etch` as explained in Section A.2, "Checking your sources list".

#### 4.2.4. The proposed-updates section

If you have listed the `proposed-updates` section in your `/etc/apt/sources.list` file, you should remove it from that file before attempting to upgrade your system. This is a precaution to reduce the likelihood of conflicts.

#### 4.2.5. Unofficial sources and backports

If you have any non-Debian packages on your system, you should be aware that these may be removed during the upgrade because of conflicting dependencies. If these packages were installed by adding an extra package archive in your `/etc/apt/sources.list`, you should check if that archive also offers packages compiled for `lenny` and change the source line accordingly at the same time as your source lines for Debian packages.

Some users may have unofficial backported "newer" versions of packages that are in Debian installed on their etch system. Such packages are most likely to cause problems during an upgrade as they may result in file conflicts<sup>[3]</sup>. Section 4.5.8, "Possible issues during upgrade" has some information on how to deal with file conflicts if they should occur.

#### 4.2.5.1. Using backports.org packages

backports.org is a semi-official repository provided by Debian GNU/Linux developers, which provides newer packages for the stable release, based on a rebuild from the packages from the "testing" archive.

The backports.org repository mainly contains packages from "testing", with reduced version numbers so that the upgrade path from etch backports to lenny still works. However, there are a few backports which are made from unstable: security updates, plus the following exceptions: Firefox, the Linux kernel, OpenOffice.org, and X.Org.

If you do not use one of these exceptions, you can safely upgrade to lenny. If you use one of these exceptions, set the Pin-Priority (see `apt_preferences(5)`) temporarily to 1001 for all packages from lenny, and you should be able to do a safe `dist-upgrade` too.

#### 4.3. Manually unmarking packages

To prevent aptitude from removing some packages that were pulled in through dependencies, you need to manually unmark them as auto packages. This includes OpenOffice and Vim for desktop installs:

```
# aptitude unmarkauto openoffice.org vim
```

And 2.6 kernel images if you have installed them using a kernel metapackage:

```
# aptitude unmarkauto $(dpkg-query -W 'linux-image-2.6.*' | cut -f1)
```

Note

You can review which packages are marked as auto in aptitude by running:

```
# aptitude search '~i~M'
```

#### 4.4. Preparing sources for APT

Before starting the upgrade you must set up apt's configuration file for package lists, `/etc/apt/sources.list`.

apt will consider all packages that can be found via any "deb" line, and install the package with the highest version number, giving priority to the first line in the file (thus where you have multiple mirror locations, you'd typically first name a local hard disk, then CD-ROMs, and then HTTP/FTP mirrors).

Tip

You might need to add an GPG checking exception for DVDs and CD-ROMs. Add the following line to `/etc/apt/apt.conf`, if it's not already in `/etc/apt/apt.conf.d/00trustcdrom`:



```
APT::Authentication::TrustCDROM "true";
```

This does not work with DVD/CD-ROM image files, however.

A release can often be referred to both by its codename (e.g. etch, lenny) and by its status name (i.e. oldstable, stable, testing, unstable). Referring to a release by its codename has the advantage that you will never be surprised by a new release and for this reason is the approach taken here. It does of course mean that you will have to watch out for release announcements yourself. If you use the status name instead, you will just see loads of updates for packages available as soon as a release has happened.

#### 4.4.1. Adding APT Internet sources

The default configuration is set up for installation from main Debian Internet servers, but you may wish to modify `/etc/apt/sources.list` to use other mirrors, preferably a mirror that is network-wise closest to you.

Debian HTTP or FTP mirror addresses can be found at <http://www.debian.org/distrib/ftplist> (<http://www.debian.org/distrib/ftplist>) (look at the "list of Debian mirrors" section). HTTP mirrors are generally speedier than FTP mirrors.

For example, suppose your closest Debian mirror is <http://mirrors.kernel.org>. When inspecting that mirror with a web browser or FTP program, you will notice that the main directories are organized like this:

```
http://mirrors.kernel.org/debian/dists/lenny/main/binary-s390/...
http://mirrors.kernel.org/debian/dists/lenny/contrib/binary-s390/...
```

To use this mirror with apt, you add this line to your `sources.list` file:

```
deb http://mirrors.kernel.org/debian lenny main contrib
```

Note that the `'dists'` is added implicitly, and the arguments after the release name are used to expand the path into multiple directories.

After adding your new sources, disable the previously existing `deb` lines in `sources.list` by placing a hash sign (`#`) in front of them.

#### 4.4.2. Adding APT sources for a local mirror

Instead of using HTTP or FTP package mirrors, you may wish to modify `/etc/apt/sources.list` to use a mirror on a local disk (possibly mounted over NFS).

For example, your package mirror may be under `/var/ftp/debian/`, and have main directories like this:

```
/var/ftp/debian/dists/lenny/main/binary-s390/...
/var/ftp/debian/dists/lenny/contrib/binary-s390/...
```

To use this with apt, add this line to your `sources.list` file:

```
deb file:/var/ftp/debian lenny main contrib
```

Note that the `'dists'` is added implicitly, and the arguments after the release name are used to expand the path into multiple



program to record a transcript of the upgrade session. Then if a problem occurs, you will have a log of what happened, and if needed, can provide exact information in a bug report. To start the recording, type:

```
^ ^ ^ # script -t 2>~/upgrade-lenny.time -a ~/upgrade-lenny.script
```

or similar. Do not put the typescript file in a temporary directory such as /tmp or /var/tmp (files in those directories may be deleted during the upgrade or during any restart).

The typescript will also allow you to review information that has scrolled off-screen. Just switch to VT2 (using Alt+F2) and, after logging in, use less -R ~root/upgrade-lenny.script to view the file.

^ ^ ^ After you have completed the upgrade, you can stop script by typing exit at the prompt.

^ ^ ^ If you have used the -t switch for script you can use the scriptreplay program to replay the whole session:

```
^ ^ ^ # scriptreplay ~/upgrade-lenny.time ~/upgrade-lenny.script
```

#### 4.5.2. Updating the package list

^ ^ ^ First the list of available packages for the new release needs to be fetched. This is done by executing:

```
^ ^ ^ # aptitude update
```

Running this the first time new sources are updated will print out some warnings related to the availability of the sources. These warnings are harmless and will not appear if you rerun the command again.

#### 4.5.3. Make sure you have sufficient space for the upgrade

You have to make sure before upgrading your system that you have sufficient hard disk space when you start the full system upgrade described in Section 4.5.7, "Upgrading the rest of the system". First, any package needed for installation that is fetched from the network is stored in /var/cache/apt/archives (and the partial / subdirectory, during download), so you must make sure you have enough space on the file system partition that holds /var/ to temporarily download the packages that will be installed in your system. After the download, you will probably need more space in other file system partitions in order to both install upgraded packages (which might contain bigger binaries or more data) and new packages that will be pulled in for the upgrade. If your system does not have sufficient space you might end up with an incomplete upgrade that might be difficult to recover from.

Both aptitude and apt will show you detailed information of the disk space needed for the installation. Before executing the upgrade, you can see this estimate by running:

```
# aptitude -y -s -f --with-recommends dist-upgrade
[ ... ]
^ ^ ^ XXX upgraded, XXX newly installed, XXX to remove and XXX not upgraded.
Need to get xx.xMB/yyyMB of archives. After unpacking AAAMB will be used.
Would download/install/remove packages.
```

Note

Running this command at the beginning of the upgrade process may give an error, for the reasons described in the next sections. In that case you will need to wait until you've done the minimal system upgrade as in Section 4.5.6, "Minimal system upgrade" and upgraded your kernel before running this command to estimate the disk space.

Â Â Â If you do not have enough space for the upgrade, make sure you free up space beforehand. You can:

â– Remove packages that have been previously downloaded for installation (at /var/cache/apt/archives). Cleaning up the package cache by running apt-get clean or aptitude clean will remove all previously downloaded package files.

â– Remove forgotten packages. If you have popularity-contest installed, you can use popcon-largest-unused to list the packages you do not use that occupy the most space. You can also use deborphan or debfoster to find obsolete packages (see Section 4.10, "Obsolete packages" ). Alternatively you can start aptitude in "visual mode" and find obsolete packages under "Obsolete and Locally Created Packages".

â– Remove packages that take up too much space and are not currently needed (you can always reinstall them after the upgrade). You can list the packages that take up the most disk space with dpigs (available in the debian-goodies package) or with wajig (running wajig size).

You can list packages that take up most of the disk space with aptitude. Start aptitude into "visual mode", select Views "New Flat Package List" (this menu entry is available only after etch version), press l and enter ~i, press S and enter ~installsize, then it will give you nice list to work with. Doing this after upgrading aptitude should give you access to this new feature.

â– Remove translations and localization files from the system if they are not needed. You can install the localepurge package and configure it so that only a few selected locales are kept in the system. This will reduce the disk space consumed at /usr/share/local.

â– Temporarily move to another system, or permanently remove, system logs residing under /var/log/.

Â Â Â

â– Use a temporary /var/cache/apt/archives: You can use a temporary cache directory from another filesystem (USB storage device, temporary hard disk, filesystem already in use, ...)

â–â–

Note

â–, â–,

â–, Do not use an NFS mount as the network connection â–,

â–, could be interrupted during the upgrade. â–,

â–â–

For example, if you have a USB drive mounted on /media/usbkey:

1. remove the packages that have been previously downloaded for installation:

```
# apt-get clean
```

2. copy the directory /var/cache/apt/archives to the USB drive:

```
# cp -ax /var/cache/apt/archives /media/usbkey/
```

3. mount the temporary cache directory on the current one:

```
# mount --bind /media/usbkey/archives /var/cache/apt/archives
```

4. after the upgrade, restore the original /var/cache/apt/archives directory:

```
# umount /media/usbkey/archives
```

5. remove the remaining /media/usbkey/archives.

You can create the temporary cache directory on whatever filesystem is mounted on your system.

Note that in order to safely remove packages, it is advisable to switch your sources.list back to etch as described in Section A.2, "Checking your sources list".

#### 4.5.4. Upgrade apt and/or aptitude first

Several bug reports have shown that the versions of the aptitude and apt packages in etch are often unable to handle the upgrade to lenny. In lenny, apt is better at dealing with complex chains of packages requiring immediate configuration and aptitude is smarter at searching for solutions to satisfy the dependencies. These two features are heavily involved during the dist-upgrade to lenny, so it is necessary to upgrade these two packages before upgrading anything else.

The following command will upgrade both aptitude and apt:

```
# aptitude install aptitude apt dpkg
```

This step will also automatically upgrade libc6 and locales. At this point, some running services will be restarted, including xdm, gdm and kdm. As a consequence, local X11 sessions might be disconnected.

#### Upgrading with apt

Please note that using apt-get is not recommended for the upgrade from etch to lenny. If you do not have aptitude installed you are recommended to install it first.

If you want to perform the upgrade with apt or if the upgrade with aptitude failed and you want to try the upgrade with apt's dependency chain resolution algorithm, you should run:

```
# apt-get install apt
```

Note that you will have to adapt other aptitude commands to use apt-get instead.

#### 4.5.5. Using aptitude's list of automatically-installed packages with apt

aptitude maintains a list of packages that were installed automatically (for instance, as dependencies of another package). In lenny, apt now has this feature as well.

The first time the lenny version of aptitude is run, it will read in its list of automatically installed packages and convert it for use with the lenny version of apt. If you have aptitude

Ã Ã Ã installed, you should at least issue one aptitude command to do the conversion. One way to do this is by searching for a non-existent package:

```
# aptitude search "?false"
```

#### 4.5.6.Ã Minimal system upgrade

Because of certain necessary package conflicts between etch and lenny, running aptitude dist-upgrade directly will often remove  
Ã Ã Ã large numbers of packages that you will want to keep. We therefore recommend a two-part upgrade process, first a minimal upgrade to overcome these conflicts, then a full dist-upgrade.

Ã Ã Ã First, run:

```
Ã Ã Ã # aptitude safe-upgrade
```

This has the effect of upgrading those packages which can be  
Ã Ã Ã upgraded without requiring any other packages to be removed or installed.

The next step will vary depending on the set of packages that you have installed. These release notes give general advice about  
Ã Ã Ã which method should be used, but if in doubt, it is recommended that you examine the package removals proposed by each method before proceeding.

Some common packages that are expected to be removed include base-config, hotplug, xlibs, netkit-inetd, python2.3,  
Ã Ã Ã xfree86-common, and xserver-common. For more information about packages obsoleted in lenny, see SectionÃ 4.10, "Obsolete packages".

#### 4.5.7.Ã Upgrading the rest of the system

Ã Ã Ã You are now ready to continue with the main part of the upgrade. Execute:

```
Ã Ã Ã # aptitude dist-upgrade
```

This will perform a complete upgrade of the system, i.e. install the newest available versions of all packages, and resolve all  
Ã Ã Ã possible dependency changes between packages in different releases. If necessary, it will install some new packages (usually new library versions, or renamed packages), and remove any conflicting obsoleted packages.

When upgrading from a set of CD-ROMs (or DVDs), you will be asked  
Ã Ã Ã to insert specific CDs at several points during the upgrade. You might have to insert the same CD multiple times; this is due to inter-related packages that have been spread out over the CDs.

New versions of currently installed packages that cannot be upgraded without changing the install status of another package  
Ã Ã Ã will be left at their current version (displayed as "held back"). This can be resolved by either using aptitude to choose these packages for installation or by trying aptitude -f install package.

#### 4.5.8.Ã Possible issues during upgrade

Ã Ã Ã If an operation using aptitude, apt-get, or dpkg fails with the error

...

Ã Ã Ã E: Dynamic MMap ran out of room

the default cache space is insufficient. You can solve this by either removing or commenting lines you don't need in /etc/apt/sources.list or increasing the cache size. The cache size can be increased by setting APT::Cache-Limit in /etc/apt/apt.conf. The following command will set it to a value that should be sufficient for the upgrade:

Ã Ã Ã # echo 'APT::Cache-Limit "12500000";' >> /etc/apt/apt.conf

Ã Ã Ã This assumes that you do not yet have this variable set in that file.

Sometimes it's necessary to enable the APT::Force-LoopBreak option in APT to be able to temporarily remove an essential package due to a Conflicts/Pre-Depends loop. aptitude will alert you of this and abort the upgrade. You can work around this by specifying the option -o APT::Force-LoopBreak=1 on the aptitude command line.

It is possible that a system's dependency structure can be so corrupt as to require manual intervention. Usually this means using aptitude or

Ã Ã Ã # dpkg --remove package\_name

Ã Ã Ã to eliminate some of the offending packages, or

Ã Ã Ã # aptitude -f install  
# dpkg --configure --pending

Ã Ã Ã In extreme cases you might have to force re-installation with a command like

Ã Ã Ã # dpkg --install /path/to/package\_name.deb

File conflicts should not occur if you upgrade from a "pure" etch system, but can occur if you have unofficial backports installed. A file conflict will result in an error like:

Unpacking <package-foo> (from <package-foo-file>) ...  
dpkg: error processing <package-foo> (--install):  
trying to overwrite `<some-file-name>',  
Ã Ã Ã which is also in package <package-bar>  
dpkg-deb: subprocess paste killed by signal (Broken pipe)  
Errors were encountered while processing:  
<package-foo>

Ã Ã Ã You can try to solve a file conflict by forcibly removing the package mentioned on the last line of the error message:

Ã Ã Ã # dpkg -r --force-depends package\_name

Ã Ã Ã After fixing things up, you should be able to resume the upgrade by repeating the previously described aptitude commands.

During the upgrade, you will be asked questions regarding the configuration or re-configuration of several packages. When you are asked if any file in the /etc/init.d or /etc/terminfo directories, or the /etc/manpath.config file should be replaced by the package maintainer's version, it's usually necessary to answer 'yes' to ensure system consistency. You can always revert to the old versions, since they will be saved with a .dpkg-old extension.

If you're not sure what to do, write down the name of the package or file and sort things out at a later time. You can search in the typescript file to review the information that was on the screen during the upgrade.

#### 4.6. Upgrading your kernel and related packages

This section explains how to upgrade your kernel and identifies potential issues related to this upgrade. You can either install one of the linux-image-\* packages provided by Debian, or compile a customized kernel from source.

Note that a lot of information in this section is based on the assumption that you will be using one of the modular Debian kernels, together with initramfs-tools and udev. If you choose to use a custom kernel that does not require an initrd or if you use a different initrd generator, some of the information may not be relevant for you.

##### 4.6.1. Installing the kernel metapackage

When you dist-upgrade from etch to lenny, it is strongly recommended that you install a new linux-image-2.6-\* metapackage. This package may be installed automatically by the dist-upgrade process. You can verify this by running:

```
# dpkg -l "linux-image*" | grep ^ii
```

If you do not see any output, then you will need to install a new linux-image package by hand. To see a list of available linux-image-2.6 metapackages, run:

```
# apt-cache search linux-image-2.6- | grep -v transition
```

If you are unsure about which package to select, run uname -r and look for a package with a similar name. For example, if you see '2.6.18-6-686', it is recommended that you install linux-image-2.6-686. (Note that the k7 flavor no longer exists; if you are currently using the k7 kernel flavor, you should install the 686 flavor instead.) You may also use apt-cache to see a long description of each package in order to help choose the best one available. For example:

```
# apt-cache show linux-image-2.6-686
```

You should then use aptitude install to install it. Once this new kernel is installed you should reboot at the next available opportunity to get the benefits provided by the new kernel version.

For the more adventurous there is an easy way to compile your own custom kernel on Debian GNU/Linux. Install the kernel-package tool and read the documentation in /usr/share/doc/kernel-package.

If possible, it is to your advantage to upgrade the kernel package separately from the main dist-upgrade to reduce the chances of a temporarily non-bootable system. Note that this should only be done after the minimal upgrade process described in Section 4.5.6, "Minimal system upgrade".

##### 4.6.2. Device enumeration reordering

lenny features a more robust mechanism for hardware discovery than previous releases. However, this may cause changes in the



order devices are discovered on your system, affecting the order in which device names are assigned. For example, if you have two network adapters that are associated with two different drivers, the devices eth0 and eth1 refer to may be swapped. Please note that the new mechanism means that if you e.g. exchange ethernet adapters in a running lenny system, the new adapter will also get a new interface name.

For network devices, you can avoid this reordering by using udev rules, more specifically, through the definitions at /etc/udev/rules.d/70-persistent-net.rules<sup>[4]</sup>. Alternatively you can use the ifrename utility to bind physical devices to specific names at boot time. See ifrename(8) and iftab(5) for more information. The two alternatives (udev and ifrename) should not be used at the same time.

For storage devices, you can avoid this reordering by using initramfs-tools and configuring it to load storage device driver modules in the same order they are currently loaded. To do this, identify the order the storage modules on your system were loaded by looking at the output of lsmod. lsmod lists modules in the reverse order that they were loaded in, i.e., the first module in the list was the last one loaded. Note that this will only work for devices which the kernel enumerates in a stable order (like PCI devices).

However, removing and reloading modules after initial boot will affect this order. Also, your kernel may have some drivers linked statically, and these names will not appear in the output of lsmod. You may be able to decipher these driver names and load order from looking at /var/log/kern.log, or the output of dmesg.

Add these module names to /etc/initramfs-tools/modules in the order they should be loaded at boot time. Some module names may have changed between etch and lenny. For example, sym53c8xx\_2 has become sym53c8xx.

You will then need to regenerate your initramfs image(s) by executing update-initramfs -u -k all.

Once you are running a lenny kernel and udev, you may reconfigure your system to access disks by an alias that is not dependent upon driver load order. These aliases reside in the /dev/disk/ hierarchy.

#### 4.6.3. Boot timing issues

If an initrd created with initramfs-tools is used to boot the system, in some cases the creation of device files by udev can happen too late for the boot scripts to act on.

The usual symptoms are that the boot will fail because the root file system cannot be mounted and you are dropped into a debug shell. But if you check afterwards, all devices that are needed are present in /dev. This has been observed in cases where the root file system is on a USB disk or on RAID, especially if LILO is used.

A workaround for this issue is to use the boot parameter rootdelay=9. The value for the timeout (in seconds) may need to be adjusted.

#### 4.7. Things to do before rebooting

When aptitude dist-upgrade has finished, the “formal” upgrade is

Ã Ã Ã complete, but there are some other things that should be taken care of before the next reboot.

#### 4.7.1. Easy to use

Ã Ã Ã If you are using lilo as your bootloader (it is the default bootloader for some installations of etch) it is strongly recommended that you rerun lilo after the upgrade:

```
Ã Ã Ã # /sbin/lilo
```

Ã Ã Ã Notice this is needed even if you did not upgrade your system's kernel, as lilo's second stage will change due to the package upgrade.

Ã Ã Ã Also, review the contents of your /etc/kernel-img.conf and make sure that you have do\_bootloader = Yes in it. That way the bootloader will always be rerun after a kernel upgrade.

Ã Ã Ã If you encounter any issues when running lilo, review the symbolic links in / to vmlinuz and initrd and the contents of your /etc/lilo.conf for discrepancies.

Ã Ã Ã If you forgot to rerun lilo before the reboot or the system is accidentally rebooted before you could do this manually, your system might fail to boot. Instead of the lilo prompt, you will only see LI when booting the system<sup>[5]</sup>. See Section 4.1.3, "Prepare for recovery" for information on how to recover from this.

#### 4.8. System boot hangs on Waiting for root file system

Procedure to recover from /dev/hda that became /dev/sda

Ã Ã Ã

Ã Ã Ã Some users have reported that an upgrade could cause the kernel not to find the system root partition after a system reboot.

In such case, the system boot will hang on the following message:

Ã Ã Ã Waiting for root file system ...

and after a few seconds a bare busybox prompt will appear.

Ã Ã Ã This problem can occur when the upgrade of the kernel introduces the use of the new generation of IDE drivers. The IDE disk naming convention for the old drivers was hda, hdb, hdc, hdd. The new drivers will name the same disks respectively sda, sdb, sdc, sdd. The problem appears when the upgrade does not generate a new /boot/grub/menu.lst file to take the new naming convention into account. During the boot, Grub will pass a system root partition to the kernel that the kernel doesn't find.

Ã Ã Ã If you have encountered this problem after upgrading, jump to Section 4.8.2, "How to recover from the problem after the upgrade". To avoid the problem before upgrading, read ahead.

##### 4.8.1. How to avoid the problem before upgrading

Ã Ã Ã One can avoid this problem entirely by using an identifier for the root filesystem that does not change from one boot to the next. There are two possible methods for doing this - labeling the filesystem, or using the filesystem's universally unique identifier (UUID). These methods are supported in Debian since

the 'etch' release.

The two approaches have advantages and disadvantages. The labeling approach is more readable, but there may be problems if another filesystem on your machine has the same label. The UUID approach is uglier, but having two clashing UUIDs is highly unlikely.

For the examples below we assume the root filesystem is on /dev/hda6. We also assume your system has a working udev installation and ext2 or ext3 filesystems.

To implement the labeling approach:

1. Label the filesystem (the name must be < 16 characters) by running the command: `e2label /dev/hda6 rootfilesys`

2. Edit /boot/grub/menu.lst and change the line:

```
# kopt=root=/dev/hda6 ro
```

to

```
# kopt=root=LABEL=rootfilesys ro
```

â”€â”€â”€

Note

â”€”, â”€”,

â”€â”€â”€ â”€”, Do not remove the # at the start of the line, it â”€”,  
â”€”, needs to be there. â”€”,

â”€”â”€â”€

3. Update the kernel lines in menu.lst by running the command `update-grub`.

4. Edit /etc/fstab and change the line that mounts the / partition, e.g.:

```
/dev/hda6      /      ext3  defaults,errors=remount-ro 0 1
```

to

```
LABEL=rootfilesys      /      ext3  defaults,errors=remount-ro 0 1
```

The change that matters here is the first column, you don't need to modify the other columns of this line.

To implement the UUID approach:

1. Find out the universally unique identifier of your filesystem by issuing: `ls -l /dev/disk/by-uuid | grep hda6`. You can also use `vol_id --uuid /dev/hda6` (in etch) or `blkid /dev/hda6` (if already upgraded to lenny).

You should get a line similar to this one:

```
lrwxrwxrwx 1 root root 24 2008-09-25 08:16 d0dfcc8a-417a-41e3-ad2e-9736317f2d8a ->
../.. /hda6
```

The UUID is the name of the symbolic link pointing to /dev/hda6 i.e.: d0dfcc8a-417a-41e3-ad2e-9736317f2d8a.

â”€â”€â”€

Note

â”€”, â”€”,

â",Your filesystem UUID will be a different string. â",  
â""â"€

2. Edit /boot/grub/menu.lst and change the line:

```
# kopt=root=/dev/hda6 ro
```

Â Â Â to

```
# kopt=root=UUID=d0dfcc8a-417a-41e3-ad2e-9736317f2d8 ro
```

â"€â"€

Note

â", â",

â",Do not remove the # at the start of the line, it â",  
â",needs to be there. â",

â""â"€

3. Update the kernel lines in menu.lst by running the command  
update-grub.
4. Edit /etc/fstab and change the line that mounts the / partition,  
e.g.:

```
/dev/hda6 / ext3 defaults,errors=remount-ro 0 1
```

to

```
UUID=d0dfcc8a-417a-41e3-ad2e-9736317f2d8 / ext3 defaults,errors=remount-ro 0 1
```

The change that matters here is the first column, you don't need  
to modify the other columns of this line.

#### 4.8.2.Â How to recover from the problem after the upgrade

##### 4.8.2.1.Â Solution 1

This is applicable when Grub shows you the menu interface for  
selecting the entry you want to boot from. If such a menu does  
Â Â Â not appear, try pressing the Esc key before the kernel boots in  
order to make it appear. If you can't get into this menu, try  
SectionÂ 4.8.2.2, â€œSolution 2â€ or SectionÂ 4.8.2.3, â€œSolution 3â€.

1. In the Grub menu, highlight the entry you want to boot from.  
Press the e key to edit the options related to this entry.  
You will see something like:

```
root (hd0,0)
kernel /vmlinuz-2.6.26-1-686 root=/dev/hda6 ro
initrd /initrd.img-2.6.26-1-686
```

2. Highlight the line

```
kernel /vmlinuz-2.6.26-1-686 root=/dev/hda6 ro
```

Â Â Â press the e key and replace hdX with sdX (X being the letter  
a, b, c or d depending of your system). In my example the  
line becomes:

```
kernel /vmlinuz-2.6.26-1-686 root=/dev/sda6 ro
```

Then press Enter to save the modification. If other lines  
show hdX, change these line too. Don't modify the entry  
similar to root (hd0,0). Once all modifications are done,  
press the b key. And your system should now boot as usual.

3. Now that your system has booted, you need to fix this issue permanently. Jump to Section 4.8.1, "How to avoid the problem before upgrading" and apply one of the two proposed procedures.

#### 4.8.2.2. Solution 2

Boot from Debian GNU/Linux installation media (CD/DVD) and when prompted, pick rescue to launch rescue mode. Select your language, location, and keyboard mapping; then let it configure the network (no matter whether it succeeds or not). After a while, you should be asked to select the partition you want to use as root file system. The proposed choices will look something like:

```
/dev/ide/host0/bus0/target0/lun0/part1
/dev/ide/host0/bus0/target0/lun0/part2
/dev/ide/host0/bus0/target0/lun0/part5
/dev/ide/host0/bus0/target0/lun0/part6
```

If you know which partition is your root file system, choose the appropriate one. If you don't, just try with the first. If it complains about an invalid root file system partition, try the next one, and so on. Trying one after the other shouldn't harm your partitions and if you have only one operating system installed on your disks, you should easily find the right root file system partition. If you have many operating systems installed on your disks, it would be better to know exactly which is the right partition.

Once you have chosen a partition, you will be offered a range of options. Pick the option of executing a shell in the selected partition. If it complains that it cannot do that then try with another partition.

Now you should have shell access as user root on your root file system mounted on /target. You need access to the contents of the /boot, /sbin and /usr directories on your hard disk, which should now be available under /target/boot, /target/sbin and /target/usr. If these directories need to be mounted from other partitions, do so (see /etc/fstab if you have no idea of which partition to mount).

Jump to Section 4.8.1, "How to avoid the problem before upgrading" and apply one of the two proposed procedures to fix the problem permanently. Then type exit to leave the rescue shell and select reboot for rebooting the system as usual (don't forget to remove the bootable media).

#### 4.8.2.3. Solution 3

1. Boot from your favorite LiveCD distribution, such as Debian Live, Knoppix, or Ubuntu Live.
2. Mount the partition where your /boot directory is. If you don't know which one it is, use the output of the command dmesg to find whether your disk is known as hda, hdb, hdc, hdd or sda, sdb, sdc, sdd. Once you know which disk to work on, for example sdb, issue the following command to see the partition table of the disk and to find the right partition: fdisk -l /dev/sdb
3. Assuming that you have mounted the right partition under /mnt and that this partition contains the /boot directory and its content, edit the /mnt/boot/grub/menu.lst file.

Find the section similar to:

```
## ## End Default Options ##
```

```
title          Debian GNU/Linux, kernel 2.6.26-1-686
root           (hd0,0)
^ ^ ^ For kernel /vmlinuz-2.6.26-1-686 root=/dev/hda6
initrd         /initrd.img-2.6.26-1-686

title          Debian GNU/Linux, kernel 2.6.26-1-686 (single-user mode)
root           (hd0,0)
kernel         /vmlinuz-2.6.26-1-686 root=/dev/hda6 ro single
initrd         /initrd.img-2.6.26-1-686
```

```
### END DEBIAN AUTOMAGIC KERNELS LIST
```

and replace every hda, hdb, hdc, hdd with sda, sdb, sdc, sdd, as appropriate. Don't modify the line similar to:

```
root           (hd0,0)
```

4. Reboot the system, remove the LiveCD and your system should boot correctly.
5. When it has booted, apply one of the two proposed procedures under Section 4.8.1, "How to avoid the problem before upgrading" to fix the problem permanently.

#### 4.9. Preparing for the next release

After the upgrade there are several things you can do to prepare for the next release.

If the new kernel image metapackage was pulled in as a dependency of the old one, it will be marked as automatically installed, which should be corrected:

```
^ ^ ^      # aptitude unmarkauto $(dpkg-query -W 'linux-image-2.6-*' | cut -f1)
```

Remove obsolete and unused packages as described in Section 4.10, "Obsolete packages". You should review which configuration files they use and consider purging the packages to remove their configuration files.

#### 4.10. Obsolete packages

Introducing several thousand new packages, lenny also retires and omits more than two thousand old packages that were in etch. It provides no upgrade path for these obsolete packages. While nothing prevents you from continuing to use an obsolete package where desired, the Debian project will usually discontinue security support for it a year after lenny's release [6], and will not normally provide other support in the meantime. Replacing them with available alternatives, if any, is recommended.

There are many reasons why packages might have been removed from the distribution: they are no longer maintained upstream; there is no longer a Debian Developer interested in maintaining the packages; the functionality they provide has been superseded by different software (or a new version); or they are no longer considered suitable for lenny due to bugs in them. In the latter case, packages might still be present in the "unstable" distribution.

Detecting which packages in an updated system are "obsolete" is easy since the package management front-ends will mark them as such. If you are using aptitude, you will see a listing of these packages in the "Obsolete and Locally Created Packages" entry. dselect provides a similar section but the listing it presents might differ.

Also, if you have used aptitude to manually install packages in etch it will have kept track of those packages you manually installed and will be able to mark as obsolete those packages pulled in by dependencies alone which are no longer needed if a package has been removed. Also, aptitude, unlike deborphan will not mark as obsolete packages that you manually installed, as opposed to those that were automatically installed through dependencies.

There are additional tools you can use to find obsolete packages such as deborphan, debfoster or cruft. deborphan is highly recommended, although it will (in default mode) only report obsolete libraries: packages in the "libs" or "oldlibs" sections that are not used by any other packages. Do not blindly remove the packages these tools present, especially if you are using aggressive non-default options that are prone to produce false positives. It is highly recommended that you manually review the packages suggested for removal (i.e. their contents, size and description) before you remove them.

The Debian Bug Tracking System (<http://bugs.debian.org/>) often provides additional information on why the package was removed. You should review both the archived bug reports for the package itself and the archived bug reports for the [ftp.debian.org pseudo-package](http://ftp.debian.org/pseudo-package) (<http://bugs.debian.org/cgi-bin/pkgreport.cgi?pkg=ftp.debian.org&archive=yes>) .

The list of obsolete packages includes:

â apache (1.x), successor is apache2

â bind (8), successor is bind9

â php4, successor is php5

â postgresql-7.4, successor is postgresql-8.1

â exim (3), successor is exim4

#### 4.10.1. Dummy packages

Some packages from etch have been split into several packages in lenny, often to improve system maintainability. To ease the upgrade path in such cases, lenny often provides "dummy" packages: empty packages that have the same name as the old package in etch with dependencies that cause the new packages to be installed. These "dummy" packages are considered obsolete packages after the upgrade and can be safely removed.

Most (but not all) dummy packages' descriptions indicate their purpose. Package descriptions for dummy packages are not uniform, however, so you might also find deborphan with the --guess options useful to detect them in your system. Note that some dummy packages are not intended to be removed after an upgrade but are, instead, used to keep track of the current available version of a program over time.

There are usually two workarounds to these problems: either revert the maximum allowed TCP window sizes to a smaller value



Ä Ä Ä (preferable) or turn off TCP window scaling altogether (deprecated). See the example commands in the debian-installer errata page (<http://www.debian.org/devel/debian-installer/errata>) .

#### 5.1.4.Ä Automatic poweroff stops working

On some older systems, shutdown -h may not power off the system anymore (but just stop it). This happens because APM needs to be Ä Ä Ä used there. Adding acpi=off apm=power\_off to the kernel's command line, e.g. in grub or lilo configuration files should fix this issue. Please see bug #390547 (<http://bugs.debian.org/390547>) for additional information.

#### 5.1.5.Ä Asynchronous network initialization may cause unpredictable behavior

On systems which use udev to load drivers for network interfaces, it is possible due to the asynchronous nature of udev that the network driver will not be loaded before /etc/init.d/networking runs on system boot. Although including allow-hotplug to /etc/Ä Ä Ä network/interfaces (in addition to auto) will ensure that the network interface is enabled once it becomes available, there is no guarantee that this will finish before the boot sequence begins to start network services, some of which may not behave correctly in the absence of the network interface.

#### 5.1.6.Ä Trouble when using WPA secured wireless networks

Ä Ä Ä

In etch, the wpa\_supplicant package was set up as a system Ä Ä Ä service, configured via /etc/default/wpa\_supplicant and a user-provided /etc/wpa\_supplicant.conf.

In lenny, /etc/init.d/wpa\_supplicant has been dropped and the Ä Ä Ä Debian package now integrates with /etc/network/interfaces, similar to other packages such as wireless-tools. This means wpa\_supplicant no longer provides a system service directly.

For information on configuring wpa\_supplicant please refer to /usr/share/doc/wpa\_supplicant/README.modes.gz, which gives examples Ä Ä Ä for /etc/network/interfaces files. Updated information about the usage of the wpa\_supplicant package in Debian can be found in the Debian Wiki (<http://wiki.debian.org/WPA>) .

#### 5.1.7.Ä Problems with non-ASCII characters in filenames

Mounting vfat, ntfs or iso9660 file systems with files that include non-ASCII characters in their filenames will give failures when one tries to use the filenames unless mounting is Ä Ä Ä done with the utf8 option. An indication might be the following failure: â€œInvalid or incomplete multibyte or wide characterâ€œ. A possible solution is to use defaults,utf8 as mount options for vfat, ntfs and iso9660 file systems when they contain filenames with non-ASCII characters.

Ä Ä Ä Note that the Linux kernel does not support case-insensitive filename handling for vfat when the utf8 option is used.

#### 5.1.8.Ä Sound stops working

In rare cases, sound might stop working after the upgrade. If this happens, go through the ALSA checklist:

â–¶ run alsacnf as root user,

â–¶ add your user to the audio group,

â–¶ make sure the sound channel levels are up and unmuted (using alsamixer),

â–¶ make sure arts and esound are not running,

Â Â Â â–¶ make sure no OSS modules are loaded,

â–¶ make sure the speakers are actually switched on, and

â–¶ check whether the command

cat /dev/urandom > /dev/audio

or the command

speaker-test

works for root.

#### 5.1.9.Â Potential Filesystem Corruption on upgrade

Starting with Kernel 2.6.25, Linux on the s390 architecture  
Â Â Â running under z/VM hypervisor uses a new CCW for DASD access that triggers an error in z/VM leading to I/O errors and finally file system inconsistency.

This error could be confirmed running z/VM 5.3 with RSU  
Â Â Â (Recommended Service Update) 5304 and was fixed by IBM in RSU 5305 (service level 802).

In the IBM problem report (<http://www-01.ibm.com/support/docview.wss?uid=isg1VM64417>) a z/OS guest is mentioned, nevertheless this problem also affects linux guests.

#### 5.2.Â NFS mounts now handled by nfs-common

Since util-linux 2.13 NFS mounts are no longer handled by util-linux itself, but by nfs-common. Since not all systems mount NFS shares and to avoid a standard portmapper installation util-linux only suggests nfs-common. If you need to mount NFS  
Â Â Â shares, make sure nfs-common is installed on your system. The preinstallation script of the mount package checks whether NFS mounts exist and aborts if /usr/sbin/mount.nfs from nfs-common is not present or if nfs-common is out-of-date. Either upgrade nfs-common or unmount any NFS mounts prior to upgrading mount.

#### 5.3.Â Change of Romanian (ro) keyboard layout

Because of the upgrade to xkb-data version 1.3 in lenny the default variant for Romanian (ro) layout is now producing the correct ȚȚ characters (comma below) instead of ȚȚ (cedilla below). Also some of the variants have been renamed. The old  
Â Â Â variant names still work, but users are encouraged to update their /etc/X11/xorg.conf. More info as well as possible side effects due to this change are available in the wiki (Romanian language only) (<http://wiki.debian.org/L10N/Romanian/Lenny/Notes>)

#### 5.4.Â Upgrading apache2

The apache2 default configuration has changed in some ways that

Â Â Â may require manual changes to your configuration. The most important changes are:

Â Â Â NameVirtualHost \* has been changed to NameVirtualHost \*:80. If you have added more name based virtual hosts, you need to change <VirtualHost \*> to <VirtualHost \*:80> for each of them.

Â Â Â The Apache User and Group and the PidFile path are now configured in /etc/apache2/envvars. If you have changed these settings from their default values, you need to change that file. This also means that starting apache2 with apache2 -k start is no longer possible, you have to use /etc/init.d/apache2 or apache2ctl.

Â Â Â The suexec helper program needed for mod\_suexec is now shipped in a separate package, apache2-suexec, which is not installed by default.

Â Â Â More module specific configuration has been moved from /etc/apache2/apache2.conf to /etc/apache2/mods-available/\*.conf.

Â Â Â For more detailed information, see /usr/share/doc/apache2.2-common/NEWS.Debian.gz and /usr/share/doc/apache2.2-common/README.Debian.gz.

## 5.5.Â NIS and Network Manager

Â Â Â

Â Â Â

Â Â Â The version of ypbind included with nis for lenny contains support for Network Manager. This support causes ypbind to disable NIS client functionality when Network Manager reports that the computer is disconnected from the network. Since Network Manager will usually report that the computer is disconnected when it is not in use, NIS users with NIS client systems should ensure that Network Manager support is disabled on those systems.

Â Â Â This can be done by either uninstalling the network-manager package, or editing /etc/default/nis to add -no-dbus to YPBINDARGS.

Â Â Â The use of -no-dbus is the default for new installs of Debian, but was not the default in previous releases.

## 5.6.Â Security status of Mozilla products

Â Â Â The Mozilla programs firefox, thunderbird, and sunbird (rebranded in Debian to iceweasel, icedove, and iceowl, respectively), are important tools for many users. Unfortunately the upstream security policy is to urge users to update to new upstream versions, which conflicts with Debian's policy of not shipping large functional changes in security updates. We cannot predict it today, but during the lifetime of lenny the Debian Security Team may come to a point where supporting Mozilla products is no longer feasible and announce the end of security support for Mozilla products. You should take this into account when deploying Mozilla and consider alternatives available in Debian if the absence of security support would pose a problem for you.

Â Â Â iceape, the unbranded version of the seamonkey internet suite has been removed from lenny (with the exception of a few internal library packages).

## 5.7.Â Security status of OCS Inventory and SQL-Ledger

The webservice packages ocsinventory-server and sql-ledger are included in the lenny release but have special security requirements that users should be aware of before deploying them. These two webservices are designed for deployment only behind an authenticated HTTP zone and should never be made available to untrusted users; and therefore they receive only limited security support from the Debian security team. Users should therefore take particular care when evaluating who to grant access to these services.

## 5.8. KDE desktop

There are no huge changes in the KDE Desktop Environment from the version shipped in etch. Lenny ships an updated translation and service release of KDE 3.5 that is a mixture of 3.5.9 and 3.5.10. Some modules are labeled as version 3.5.9, but have been updated and include most of the same changes found in 3.5.10. Overall, lenny ships 3.5.10 without the kicker improvements shipped in kdebases and some bug fixes in kdepim.

Lenny will be the last stable release including a KDE 3 series environment.

## 5.9. GNOME desktop changes and support

There have been many changes in the GNOME desktop environment from the version shipped in etch to the version in lenny, you can find more information in the GNOME 2.22 Release Notes (<http://library.gnome.org/misc/release-notes/2.22/>) .

## 5.10. No default support for Unicode in emacs21\*

Emacs21 and emacs21-nox are not configured to use Unicode by default. For more information and a workaround please see bug #419490 (<http://bugs.debian.org/419490>) . Consider switching to emacs22, emacs22-gtk, or emacs22-nox.

## 5.11. slurpd/replica will no longer work

OpenLDAP has dropped support for LDAP replication via the slurpd service in release 2.4.7. Existing configurations need to be reconfigured for the LDAP Sync Replication engine (syncrepl). More verbose documentation can be found at <http://www.openldap.org/doc/admin24/replication.html> (<http://www.openldap.org/doc/admin24/replication.html>) .

## 5.12. Desktop not using full screen

The driver for Intel Mobile GM965 may wrongly detect a VGA output and set the size of the screen to a lower value to accommodate it. The symptom of this bug is that the desktop manager will only use a fraction of the screen. Correct behaviour can be forced by adding the following lines to the /etc/X11/xorg.conf configuration file.

```
Section "Monitor"
    Identifier "VGA"
    Option "Ignore" "true"
EndSection
```

Please refer to the bug #496169 (<http://bugs.debian.org/496169>) for more informations.

### 5.13. DHCP failover issue

When running a failover pair of DHCP servers, the peer names need to be consistent, otherwise DHCP will crash.

Please see bug #513506 (<http://bugs.debian.org/513506>) and <https://lists.isc.org/pipermail/dhcp-users/2007-September/004538.html> (<https://lists.isc.org/pipermail/dhcp-users/2007-September/004538.html>) for more information.

### 5.14. VServer Disk Limit

To use the disk limit feature of vservers in lenny, you should use the mount option tag (instead of tagid in etch).

You should manually update /etc/fstab and/or any script which uses tagid. Otherwise, the partition will not be mounted and thus the vservers will not start.

## Chapter 6. More information on Debian GNU/Linux

### 6.1. Further reading

Beyond these release notes and the installation guide, further documentation on Debian GNU/Linux is available from the Debian Documentation Project (DDP), whose goal is to create high-quality documentation for Debian users and developers. Documentation, including the Debian Reference, Debian New Maintainers Guide, and Debian FAQ are available, and many more. For full details of the existing resources see the DDP website (<http://www.debian.org/doc/ddp>) .

Documentation for individual packages is installed into /usr/share/doc/package. This may include copyright information, Debian specific details and any upstream documentation.

### 6.2. Getting help

There are many sources of help, advice and support for Debian users, but these should only be considered if research into documentation of the issue has exhausted all sources. This section provides a short introduction into these which may be helpful for new Debian users.

#### 6.2.1. Mailing lists

The mailing lists of most interest to Debian users are the debian-user list (English) and other debian-user-language lists (for other languages). For information on these lists and details of how to subscribe see <http://lists.debian.org/> (<http://lists.debian.org/>) . Please check the archives for answers to your question prior to posting and also adhere to standard list etiquette.

#### 6.2.2. Internet Relay Chat

Debian has an IRC channel dedicated to the support and aid of Debian users located on the OFTC IRC network. To access the channel, point your favorite IRC client at [irc.debian.org](http://irc.debian.org) and join #debian.

Please follow the channel guidelines, respecting other users fully. The guidelines are available at the Debian Wiki (<http://wiki.debian.org/DebianIRC>) .

Â Â Â For more information on OFTC please visit the website (<http://www.oftc.net/>) .

### 6.3.Â Reporting bugs

We strive to make Debian GNU/Linux a high quality operating system, however that does not mean that the packages we provide are totally free of bugs. Consistent with Debian's "open development" philosophy and as a service to our users, we provide all the information on reported bugs at our own Bug Tracking System (BTS). The BTS is browseable at <http://bugs.debian.org/> (<http://bugs.debian.org/>) .

If you find a bug in the distribution or in packaged software that is part of it, please report it so that it can be properly fixed for future releases. Reporting bugs requires a valid email address. We ask for this so that we can trace bugs and developers can get in contact with submitters should additional information be needed.

You can submit a bug report using the program `reportbug` or manually using email. You can read more about the Bug Tracking System and how to use it by reading the reference documentation (available at `/usr/share/doc/debian` if you have `doc-debian` installed) or online at the Bug Tracking System (<http://bugs.debian.org/>) .

### 6.4.Â Contributing to Debian

You do not need to be an expert to contribute to Debian. By assisting users with problems on the various user support lists (<http://lists.debian.org/>) you are contributing to the community. Identifying (and also solving) problems related to the development of the distribution by participating on the development lists (<http://lists.debian.org/>) is also extremely helpful. To maintain Debian's high quality distribution, submit bugs (<http://bugs.debian.org/>) and help developers track them down and fix them. If you have a way with words then you may want to contribute more actively by helping to write documentation (<http://www.debian.org/doc/ddp>) or translate (<http://www.debian.org/international/>) existing documentation into your own language.

If you can dedicate more time, you could manage a piece of the Free Software collection within Debian. Especially helpful is if people adopt or maintain items that people have requested for inclusion within Debian. The Work Needing and Prospective Packages database (<http://www.debian.org/devel/wnpp/>) details this information. If you have an interest in specific groups then you may find enjoyment in contributing to some of Debian's subprojects which include ports to particular architectures, Debian Jr. (<http://www.debian.org/devel/debian-jr/>) and Debian With (<http://www.debian.org/devel/debian-med/>) .

In any case, if you are working in the free software community in any way, as a user, programmer, writer or translator you are already helping the free software effort. Contributing is rewarding and fun, and as well as allowing you to meet new people it gives you that warm fuzzy feeling inside.

## AppendixÂ A.Â Managing your etch system

This appendix contains information on how to make sure you can install or upgrade etch packages before you upgrade to lenny.

This should only be necessary in specific situations.

#### A.1. Upgrading your etch system

Basically this is no different than any other upgrade of etch you've been doing. The only difference is that you first need to make sure your package list still contains references to etch as explained in Section A.2, "Checking your sources list".

If you upgrade your system using a Debian mirror, it will automatically be upgraded to the latest etch point release.

#### A.2. Checking your sources list

If any of the lines in your /etc/apt/sources.list refer to 'stable', you are effectively already using lenny. If you have already run apt-get update, you can still get back without problems following the procedure below.

If you have also already installed packages from lenny, there probably is not much point in installing packages from etch anymore. In that case you will have to decide for yourself whether you want to continue or not. It is possible to downgrade packages, but that is not covered here.

Open the file /etc/apt/sources.list with your favorite editor (as root) and check all lines beginning with deb http: or deb ftp: for a reference to "stable". If you find any, change stable to etch.

If you have any lines starting with deb file:, you will have to check for yourself if the location they refer to contains an etch or a lenny archive.

#### Important

Do not change any lines that begin with deb cdrom:. Doing so would invalidate the line and you would have to run apt-cdrom again. Do not be alarmed if a 'cdrom' source line refers to "unstable". Although confusing, this is normal.

If you've made any changes, save the file and execute

```
# apt-get update
```

to refresh the package list.

#### Appendix B. Contributors to the Release Notes

Many people helped with the release notes, including, but not limited to

Adam Di Carlo, Andreas Barth, Andrei Popescu, Anne Bezemer, Bob Hilliard, Charles Plessy, Christian Perrier, Daniel Baumann, Eddy Petrićor, Emmanuel Kasper, Esko Arajärvi, Frans Pop, Giovanni Rapagnani, Gordon Farquharson, Javier Fernández-Sanguino Peña, Jens Seidel, Jonas Meurer, Joseph Rodin, Justin B Rye, LaMont Jones, Luk Claes, Martin Michlmayr, Michael Biebl, Moritz Mühlenhoff, Noah Meyerhans, Noritada Kobayashi, Osamu Aoki, Peter Green, Rob Bradford, Samuel Thibault, Simon Bienlein, Simon Paillard, Stefan Fritsch, Steve Langasek, Tobias Scherer, Vincent McIntyre, and W. Martin Borgert.

This document has been translated into many languages. Many thanks to the translators!

## Appendix C. Lenny dedicated to Thiemo Seufer

The Debian Project has lost an active member of its community.  
Thiemo Seufer died on December 26th, 2008 in a tragic car accident.

Thiemo was involved in Debian in many ways. He maintained several packages and was the main supporter of the Debian ports to the MIPS architecture. He was also a member of our kernel team, as well as a member of the Debian Installer team. His contributions reached far beyond the Debian project: he also worked on the MIPS port of the Linux kernel, the MIPS emulation of qemu, and far too many smaller projects to be named here.

Thiemo's work, dedication, broad technical knowledge and ability to share this with others will be missed. His contributions will not be forgotten. The high standards of Thiemo's work make it hard to pick up.

To honour his contributions to Debian, the project dedicates the release of Debian GNU/Linux 5.0 "Lenny" to Thiemo.

### Index

#### A

Abiword, What's new in the distribution?  
Apache, What's new in the distribution?

#### B

BIND, What's new in the distribution?  
Blu-ray, What's new in the distribution?

#### C

CD, What's new in the distribution?  
Cherokee, What's new in the distribution?  
Courier, What's new in the distribution?

#### D

Dia, What's new in the distribution?  
DocBook XML, Sources for this document  
DVD, What's new in the distribution?

#### AND

Ekiga, What's new in the distribution?  
Emdebian, Emdebian 1.0 (based on Debian GNU/Linux lenny 5.0)  
Evolution, What's new in the distribution?  
Exim, What's new in the distribution?

#### F

Firefox, What's new in the distribution?

#### G

Gaim, What's new in the distribution?  
GCC, What's new in the distribution?  
GIMP, What's new in the distribution?  
GNOME, What's new in the distribution?  
GNUCash, What's new in the distribution?



GNUmeric, What's new in the distribution?

I

IcedTea, Java now in Debian

J

Java, Java now in Debian

K

KDE, What's new in the distribution?

KOffice, What's new in the distribution?

L

LILO, Boot timing issues

Linux Standards Base, What's new in the distribution?

LXDE, What's new in the distribution?

M

Microsoft Windows, Major changes

Mozilla, What's new in the distribution?, Security status of Mozilla products

MySQL, What's new in the distribution?

N

Network Manager, NIS and Network Manager

NIS, NIS and Network Manager

THE

OCS Inventory, Security status of OCS Inventory and SQL-Ledger

OpenJDK, Java now in Debian

OpenOffice.org, What's new in the distribution?

OpenSSH, What's new in the distribution?

OpenVZ, Changes in kernel packaging

P

packages

apache, Obsolete packages

apache2, Obsolete packages

apache2-suexec, Upgrading apache2

apt, Contributing upgrade reports, Preparing sources for APT,  
Adding APT Internet sources, Adding APT sources for a local  
mirror, Make sure you have sufficient space for the upgrade,  
Upgrade apt and/or aptitude first, Using aptitude's list of  
automatically-installed packages with apt

aptitude, Package management, Make sure you have sufficient space  
for the upgrade, Upgrade apt and/or aptitude first, Using  
aptitude's list of automatically-installed packages with apt

base-config, Minimal system upgrade

bind, Obsolete packages

bind9, Obsolete packages

dblatex, Sources for this document

debian-goodies, Make sure you have sufficient space for the  
upgrade

doc-debian, Reporting bugs

docbook-xsl, Sources for this document

eeepc-acpi-scripts, Netbook support

emacs22, No default support for Unicode in emacs21\*  
emacs22-gtk, No default support for Unicode in emacs21\*  
emacs22-nox, No default support for Unicode in emacs21\*  
exim, Obsolete packages  
exim4, Obsolete packages  
firefox, Security status of Mozilla products  
glibc, Make sure you are on a suitable kernel  
grub, Automatic poweroff stops working  
hotplug, Minimal system upgrade  
iceape, Security status of Mozilla products  
icedove, What's new in the distribution?, Security status of  
    Mozilla products  
iceowl, Security status of Mozilla products  
iceweasel, What's new in the distribution?, Security status of  
    Mozilla products  
initramfs-tools, Debug shell during boot using initrd, Upgrading  
    your kernel and related packages, Device enumeration  
    reordering, Boot timing issues  
kernel-package, Installing the kernel metapackage  
libc6, Upgrade apt and/or aptitude first  
lilo, Rerun lilo, Automatic poweroff stops working  
linux-image-\*, Upgrading your kernel and related packages  
linux-image-2.6-686, Installing the kernel metapackage  
localepurge, Make sure you have sufficient space for the upgrade  
locales, Upgrade apt and/or aptitude first  
lxde, Netbook support  
mount, NFS mounts now handled by nfs-common  
netkit-inetd, Minimal system upgrade  
network-manager, NIS and Network Manager  
nfs-common, NFS mounts now handled by nfs-common  
nis, NIS and Network Manager  
ocsinventory-server, Security status of OCS Inventory and  
    SQL-Ledger  
php4, Obsolete packages  
php5, Obsolete packages  
popularity-contest, Make sure you have sufficient space for the  
    upgrade  
postgresql-7.4, Obsolete packages  
postgresql-8.1, Obsolete packages  
python2.3, Minimal system upgrade  
release-notes, Reporting bugs on this document  
rsyslog, System improvements  
seamonkey, Security status of Mozilla products  
sql-ledger, Security status of OCS Inventory and SQL-Ledger  
squid, Some applications may no longer work with a 2.4 kernel  
sunbird, Security status of Mozilla products  
sysklogd, System improvements  
thunderbird, Security status of Mozilla products  
udev, Upgrading your kernel and related packages, Device  
    enumeration reordering, Boot timing issues, Problems with  
    devices related to udev, Asynchronous network initialization  
    may cause unpredictable behavior  
upgrade-reports, Contributing upgrade reports  
util-linux, NFS mounts now handled by nfs-common  
wireless-tools, Trouble when using WPA secured wireless networks  
wpasupplicant, Trouble when using WPA secured wireless networks  
xfree86-common, Minimal system upgrade  
xkb-data, Change of Romanian (ro) keyboard layout  
xlibs, Minimal system upgrade  
xmlroff, Sources for this document  
xserver-common, Minimal system upgrade  
xsltproc, Sources for this document

PHP, What's new in the distribution?

Pidgin, What's new in the distribution?

Postfix, What's new in the distribution?  
PostgreSQL, What's new in the distribution?

S

SELinux, System improvements  
SQL-Ledger, Security status of OCS Inventory and SQL-Ledger

T

Thunderbird, What's new in the distribution?  
Tomcat, What's new in the distribution?

IN

Unicode, No default support for Unicode in emacs21\*

In

virtualization, Changes in kernel packaging  
visually-impaired users, Major changes  
VServer, Changes in kernel packaging

IN

WPA, Trouble when using WPA secured wireless networks

X

Xfce, What's new in the distribution?

Glossary

ACPI

Advanced Configuration and Power Interface

ALSA

Advanced Linux Sound Architecture

APM

Advanced Power Management

CD

Compact Disc

CD-ROM

Compact Disc Read Only Memory

DHCP

Dynamic Host Configuration Protocol

DNS

Domain Name System

DVD

Digital Versatile Disc

GIMP

GNU Image Manipulation Program

GNU

GNU's Not Unix

GPG

GNU Privacy Guard

GO

Integrated Drive Electronics

LDAP

Lightweight Directory Access Protocol

USE

Linux LOader

LSB

Linux Standards Base

LVM

Logical Volume Manager

MTA

Mail Transport Agent

NFS

Network File System

NOTHING

Network Interface Card

NIS

Network Information Service

US

Open Sound System

RAID

Redundant Array of Independent Disks

RPC

Remote Procedure Call

HOURS

Serial Advanced Technology Attachment

USB

Universal Serial Bus

UUID

Universally Unique Identifier

VGA

Video Graphics Array

WPA

Wi-Fi Protected Access