

Questão 1

- 1- How many instance variables does Surgeon have?
 - 1 variables, **workAtHospital**
- 2- How many instance variables does FamilyDoctor have?
 - 2 variables, **workAtHospital and makeHouseCalls**
- 3- How many methods does Doctor have?
 - 1 methods, **treatPatient()**
- 4- How many methods does Surgeon have?
 - 2 methods, **treatPatient() and makeIncision()**
- 5- How many methods does FamilyDoctor have?
 - 2 methods, **treatPatient() and giveAdvice()**
- 6- Can a FamilyDoctor do treatPatient()?
 - Yes, because it inherits this method from Doctor
- 7- Can a FamilyDoctor do makeIncision()?
 - No, because that method belongs only to the Surgeon subclass

Questão 2

- Candidato 1: Resposta letra B
Candidato 2: Resposta letra D
Candidato 3: Resposta letra G
Candidato 4: Resposta letra D

Questão 3

Nesse caso o melhor e único par que gera a saída esperada é o par 1:

A:

```
boolean frighten(int d){  
    System.out.println("arrgh");  
    return true;  
}
```

B:

```
boolean frighten(int x){  
    System.out.println("a bite?");  
    return false;  
}
```

Questão 4

```
public class Rowboat extends Boat {  
    public void rowTheBoat() {  
        System.out.print("stroke natasha ");  
    }  
}  
  
public class Boat {  
    private int length;  
    public void setLength(int len) {  
        length = len;  
    }  
    public int getLength() {  
        return length;  
    }  
}
```

```
        public void move() {  
            System.out.print("drift ");  
        }  
    }  
    public class TestBoats {  
        public static void main(String[] args) {  
            Boat b1 = new Boat();  
            Sailboat b2 = new Sailboat();  
            Rowboat b3 = new Rowboat();  
            b1.move();  
            b3.move();  
            b2.move();  
        }  
    }  
    public class Sailboat extends Boat {  
        public void move() {  
            System.out.print("hoist sail ");  
        }  
    }  
}
```