

Rajalakshmi Engineering College

Name: Soameshwaran D
Email: 240701520@rajalakshmi.edu.in
Roll no: 240701520
Phone: 7358671540
Branch: REC
Department: I CSE FE
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 5_CY

Attempt : 1
Total Mark : 40
Marks Obtained : 39

Section 1 : Coding

1. Problem Statement

Alex is working with grayscale pixel intensities from an old photo that has been scanned in a single row. To detect edges in the image, Alex needs to calculate the differences between each pair of consecutive pixel intensities.

Your task is to write a program that performs this calculation and returns the result as a tuple of differences.

Input Format

The first line of input contains an integer n , representing the number of pixel intensities.

The second line contains n space-separated integers representing the pixel intensities.

Output Format

The output displays a tuple containing the absolute differences between consecutive pixel intensities.

Refer to the sample output for format specifications.

Sample Test Case

Input: 5

200 100 20 80 10

Output: (100, 80, 60, 70)

Answer

```
# You are using Python
n = int(input())
```

```
pixels = list(map(int, input().split()))
```

```
differences = tuple(abs(pixels[i] - pixels[i+1]) for i in range(n - 1))
```

```
print(differences)
```

Status : Correct

Marks : 10/10

2. Problem Statement

Emily is a librarian who keeps track of books borrowed and returned by her patrons. She maintains four sets of book IDs: the first set represents books borrowed, the second set represents books returned, the third set represents books added to the collection, and the fourth set represents books that are now missing. Emily wants to determine which books are still borrowed but not returned, as well as those that were added but are now missing. Finally, she needs to find all unique book IDs from both results.

Help Emily by writing a program that performs the following operations on four sets of integers:

Compute the difference between the borrowed books (first set) and the returned books (second set). Compute the difference between the added books (third set) and the missing books (fourth set). Find the union of the results from the previous two steps, and sort the final result in descending order.

Input Format

The first line of input consists of a list of integers representing borrowed books.

The second line of input consists of a list of integers representing returned books.

The third line of input consists of a list of integers representing added books.

The fourth line of input consists of a list of integers representing missing books.

Output Format

The first line of output displays the difference between sets P and Q, sorted in descending order.

The second line of output displays the difference between sets R and S, sorted in descending order.

The third line of output displays the union of the differences from the previous two steps, sorted in descending order.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 1 2 3

2 3 4

5 6 7

6 7 8

Output: [1]

[5]

[5, 1]

Answer

You are using Python

```
borrowed = set(map(int, input().split()))  
returned = set(map(int, input().split()))  
added = set(map(int, input().split()))  
missing = set(map(int, input().split()))
```

```
borrowed_not_returned = sorted(borrowed - returned, reverse=True)  
print(borrowed_not_returned)
```

```
added_not_missing = sorted(added - missing, reverse=True)  
print(added_not_missing)
```

```
final_result = sorted(set(borrowed_not_returned) | set(added_not_missing),  
reverse=True)  
print(final_result)
```

Status : Correct

Marks : 10/10

3. Problem Statement

Samantha is working on a text analysis tool that compares two words to find common and unique letters. She wants a program that reads two words, w1, and w2, and performs the following operations:

Print the letters common to both words, in alphabetical order. Print the letters that are unique to each word, in alphabetical order. Determine if the set of letters in the first word is a superset of the letters in the second word. Check if there are no common letters between the two words and print the result as a Boolean value.

Ensure the program ignores case differences and leading/trailing spaces in the input words.

Your task is to help Samantha in implementing the same.

Input Format

The first line of input consists of a string representing the first word, w1.

The second line consists of a string representing the second word, w2.

Output Format

The first line of output should display the sorted letters common to both words, printed as a list.

The second line should display the sorted letters that are unique to each word, printed as a list.

The third line should display a Boolean value indicating if the set of letters in w1 is a superset of the set of letters in w2.

The fourth line should display a Boolean value indicating if there are no common letters between w1 and w2.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: program

Peace

Output: ['a', 'p']

['c', 'e', 'g', 'm', 'o', 'r']

False

False

Answer

```
# You are using Python
```

```
w1 = input().strip().lower()
```

```
w2 = input().strip().lower()
```

```
set1 = set(w1)
```

```
set2 = set(w2)
```

```
common = sorted(set1 & set2)
```

```
print(common)
```

```
unique = sorted((set1 ^ set2))
```

```
print(unique)
```

```
print(set1.issuperset(set2))
```

```
print(set1.isdisjoint(set2))
```

Status : Correct

Marks : 10/10

4. Problem Statement

Alex is tasked with managing the membership lists of several exclusive clubs. Each club has its own list of members, and Alex needs to determine the unique members who are part of exactly one club when considering all clubs together.

Your goal is to help Alex by writing a program that calculates the symmetric difference of membership lists from multiple clubs and then finds the total number of unique members.

Input Format

The first line of input consists of an integer k , representing the number of clubs.

The next k lines each contain a space-separated list of integers, where each integer represents a member's ID.

Output Format

The first line of output displays the symmetric difference of the membership lists as a set.

The second line displays the sum of the elements in this symmetric difference.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 3

1 2 3

2 3 4

5 6 7

Output: {1, 4, 5, 6, 7}

23

Answer

```
# You are using Python
# Read the number of clubs
k = int(input())

# Initialize the symmetric difference set as an empty set
symmetric_diff = set()

# Process each club's membership list
for _ in range(k):
    members = set(map(int, input().split()))
    symmetric_diff = symmetric_diff.symmetric_difference(members)

# Print the symmetric difference set
print(symmetric_diff)

# Print the sum of the elements in the symmetric difference set
print(sum(symmetric_diff))
```

Status : Partially correct

Marks : 9/10