

From Policy Gradient to Actor-Critic methods


Soft Actor Critic

Olivier Sigaud
with the help of Thomas Pierrot

Sorbonne Université
<http://people.isir.upmc.fr/sigaud>



Soft Actor Critic: The best of two worlds



- ▶ TRPO and PPO: π_θ stochastic, on-policy, **low sample efficiency**, **stable**
- ▶ DDPG and TD3: π_θ deterministic, replay buffer, **better sample efficiency**, **unstable**
- ▶ SAC: “Soft” means “entropy regularized”, π_θ stochastic, replay buffer
- ▶ Adds entropy regularization to favor exploration (follow-up of several papers)
- ▶ **Attempt to be stable and sample efficient**
- ▶ **Three successive versions**



Haarnoja, T., Zhou, A., Hartikainen, K., Tucker, G., Ha, S., Tan, J., Kumar, V., Zhu, H., Gupta, A. Abbeel, P. et al. (2018) Soft actor-critic algorithms and applications. *arXiv preprint arXiv:1812.05905*



Haarnoja, T., Zhou, A., Abbeel, P., & Levine, S. (2018) Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. *arXiv preprint arXiv:1801.01290*



Haarnoja, T. Tang, H., Abbeel, P. and Levine, S. (2017) Reinforcement learning with deep energy-based policies. *arXiv preprint arXiv:1702.08165*



Soft Actor-Critic

SAC learns a **stochastic** policy π^* maximizing both rewards and entropy:

$$\pi^* = \arg \max_{\pi_{\theta}} \sum_t \mathbb{E}_{(\mathbf{s}_t, \mathbf{a}_t) \sim \rho_{\pi_{\theta}}} [r(\mathbf{s}_t, \mathbf{a}_t) + \alpha \mathcal{H}(\pi_{\theta}(\cdot | \mathbf{s}_t))]$$

- ▶ The entropy is defined as: $\mathcal{H}(\pi_{\theta}(\cdot | \mathbf{s}_t)) = \mathbb{E}_{\mathbf{a}_t \sim \pi_{\theta}(\cdot | \mathbf{s}_t)} [-\log \pi_{\theta}(\mathbf{a}_t | \mathbf{s}_t)]$
- ▶ SAC changes the traditional MDP objective
- ▶ Thus, it converges toward different solutions
- ▶ Consequently, it introduces a new value function, the soft value function
- ▶ As usual, we consider a policy π_{θ} and a soft action-value function $\hat{Q}_{\phi}^{\pi_{\theta}}$



Volodymyr Mnih, Adria Puigdomenech Badia, Mehdi Mirza, Alex Graves, Timothy P. Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. (2016) Asynchronous methods for deep reinforcement learning. *arXiv preprint arXiv:1602.01783*

Soft policy evaluation

- Usually, we define $\hat{V}_\phi^{\pi_\theta}(\mathbf{s}_t) = \mathbb{E}_{\mathbf{a}_t \sim \pi_\theta(\cdot|\mathbf{s}_t)} [\hat{Q}_\phi^{\pi_\theta}(\mathbf{s}_t, \mathbf{a}_t)]$
- In soft updates, we rather use:

$$\begin{aligned}
 \hat{V}_\phi^{\pi_\theta}(\mathbf{s}_t) &= \mathbb{E}_{\mathbf{a}_t \sim \pi_\theta(\cdot|\mathbf{s}_t)} \left[\hat{Q}_\phi^{\pi_\theta}(\mathbf{s}_t, \mathbf{a}_t) \right] + \alpha \mathcal{H}(\pi_\theta(\cdot|\mathbf{s}_t)) \\
 &= \mathbb{E}_{\mathbf{a}_t \sim \pi_\theta(\cdot|\mathbf{s}_t)} \left[\hat{Q}_\phi^{\pi_\theta}(\mathbf{s}_t, \mathbf{a}_t) \right] + \alpha \mathbb{E}_{\mathbf{a}_t \sim \pi_\theta(\cdot|\mathbf{s}_t)} [-\log \pi_\theta(\mathbf{a}_t|\mathbf{s}_t)] \\
 &= \mathbb{E}_{\mathbf{a}_t \sim \pi_\theta(\cdot|\mathbf{s}_t)} \left[\hat{Q}_\phi^{\pi_\theta}(\mathbf{s}_t, \mathbf{a}_t) - \alpha \log \pi_\theta(\mathbf{a}_t|\mathbf{s}_t) \right]
 \end{aligned}$$

Critic updates

- We define a standard Bellman operator:

$$\begin{aligned}\mathcal{T}^{\pi} \hat{Q}_{\phi}^{\pi_{\theta}}(s_t, \mathbf{a}_t) &= r(s_t, \mathbf{a}_t) + \gamma V_{\phi}^{\pi_{\theta}}(s_{t+1}) \\ &= r(s_t, \mathbf{a}_t) + \gamma \mathbb{E}_{\mathbf{a}_t \sim \pi_{\theta}(\cdot | s_{t+1})} \left[\hat{Q}_{\phi}^{\pi_{\theta}}(s_{t+1}, \mathbf{a}_t) - \alpha \log \pi_{\theta}(\mathbf{a}_t | s_{t+1}) \right]\end{aligned}$$

Critic parameters can be learned by minimizing the loss associated to $J_Q(vth)$:

$$loss_Q(\theta) = \mathbb{E}_{(s_t, \mathbf{a}_t, s_{t+1}) \sim \mathcal{D}} \left[\left(r(s_t, \mathbf{a}_t) + \gamma \hat{V}_{\phi}^{\pi_{\theta}}(s_{t+1}) - \hat{Q}_{\phi}^{\pi_{\theta}}(s_t, \mathbf{a}_t) \right)^2 \right]$$

$$\text{where } V_{\phi}^{\pi_{\theta}}(s_{t+1}) = \mathbb{E}_{\mathbf{a} \sim \pi_{\theta}(\cdot | s_{t+1})} \left[\hat{Q}_{\phi}^{\pi_{\theta}}(s_{t+1}, \mathbf{a}) - \alpha \log \pi_{\theta}(\mathbf{a} | s_{t+1}) \right]$$

- Similar to DDPG update, but with entropy

Actor updates

- Update policy such as to become greedy w.r.t to the soft Q-value
- Choice: update the policy towards the exponential of the soft Q-value

$$J_{\pi}(\theta) = \mathbb{E}_{\mathbf{s}_t \sim \mathcal{D}} [KL(\pi_{\theta}(\cdot | \mathbf{s}_t)) || \frac{\exp(\frac{1}{\alpha} \hat{Q}_{\phi}^{\pi_{\theta}}(\mathbf{s}_t, \cdot))}{Z_{\theta}(\mathbf{s}_t)}].$$


- $Z_{\theta}(\mathbf{s}_t)$ is just a normalizing term to have a distribution
- SAC does not minimize directly this expression but a surrogate one that has the same gradient w.r.t θ

The policy parameters can be learned by minimizing:

$$J_{\pi}(\theta) = \mathbb{E}_{\mathbf{s}_t \sim \mathcal{D}} \left[\mathbb{E}_{\mathbf{a}_t \sim \pi_{\theta}(\cdot | \mathbf{s}_t)} \left[\alpha \log \pi_{\theta}(\mathbf{a}_t | \mathbf{s}_t) - \hat{Q}_{\phi}^{\pi_{\theta}}(\mathbf{s}_t, \mathbf{a}_t) \right] \right]$$

- Similar to DDPG update, but with entropy

Continuous vs discrete actions setting



- ▶ SAC works in both the discrete action and the continuous action setting
- ▶ Discrete action setting:
 - ▶ The critic takes a state and returns a Q-value per action
 - ▶ The actor takes a state and returns probabilities over actions
- ▶ Continuous action setting:
 - ▶ The critic takes a state and an action vector and returns a scalar Q-value
 - ▶ Need to choose a distribution function for the actor
 - ▶ SAC uses a squashed Gaussian: $\mathbf{a} = \tanh(n)$ where $n \sim \mathcal{N}(\mu_\phi, \sigma_\phi)$

Computing the actor loss

- ▶ To compute

$$J_{\pi}(\theta) = \mathbb{E}_{\mathbf{s}_t \sim \mathcal{D}} \left[\mathbb{E}_{\mathbf{a}_t \sim \pi_{\theta}(\cdot | \mathbf{s}_t)} \left[\alpha \log \pi_{\theta}(\mathbf{a}_t | \mathbf{s}_t) - \hat{Q}_{\phi}^{\pi_{\theta}}(\mathbf{s}_t, \mathbf{a}_t) \right] \right]$$

- ▶ SAC needs to estimate an expectation over actions sampled from the actor,
- ▶ That is $\mathbb{E}_{\mathbf{a}_t \sim \pi_{\theta}(\cdot | \mathbf{s}_t)} [F(\mathbf{s}_t, \mathbf{a}_t)]$ where F is a scalar function of the action.
- ▶ In the discrete action setting, $\pi_{\theta}(\cdot | \mathbf{s}_t)$ is a vector of probabilities
 - ▶ $\mathbb{E}_{\mathbf{a}_t \sim \pi_{\theta}(\cdot | \mathbf{s}_t)} [F(\mathbf{s}_t, \mathbf{a}_t)] = \pi_{\theta}(\cdot | \mathbf{s}_t)^T F(\mathbf{s}_t, \cdot)$
 - ▶ No specific difficulty
- ▶ In the continuous action setting:
 - ▶ The actor returns μ_{θ} and σ_{θ}
 - ▶ Re-parameterization trick: $\mathbf{a}_t = \tanh(\mu_{\theta} + \epsilon \cdot \sigma_{\theta})$ where $\epsilon \sim \mathcal{N}(0, 1)$
 - ▶ Thus, $\mathbb{E}_{\mathbf{a}_t \sim \pi_{\theta}(\cdot | \mathbf{s}_t)} [F(\mathbf{s}_t, \mathbf{a}_t)] = \mathbb{E}_{\epsilon \sim \mathcal{N}(0, 1)} [F(\mathbf{s}_t, \tanh(\mu_{\theta} + \epsilon \sigma_{\theta}))]$
 - ▶ This trick reduces the variance of the expectation estimate (not always!)
 - ▶ Can still backprop from samples w.r.t θ



Mohamed, S., Rosca, M., Figurnov, M., and Mnih, A. (2020) Monte carlo gradient estimation in machine learning. *J. Mach. Learn. Res.*, 21(132):1–62



Critic update improvements (from TD3)

- ▶ As in TD3, SAC uses two critics $\hat{Q}_{\phi_1}^{\pi_\theta}$ and $\hat{Q}_{\phi_2}^{\pi_\theta}$
- ▶ The TD-target becomes:

$$y_t = r + \gamma \mathbb{E}_{\mathbf{a}_{t+1} \sim \pi_\theta(\cdot | \mathbf{s}_{t+1})} \left[\min_{i=1,2} \hat{Q}_{\phi_i}^{\pi_\theta}(\mathbf{s}_{t+1}, \mathbf{a}_{t+1}) - \alpha \log \pi_\theta(\mathbf{a}_{t+1} | \mathbf{s}_{t+1}) \right]$$

And the losses:

$$\begin{cases} J(\theta) = \mathbb{E}_{(\mathbf{s}_t, \mathbf{a}_t, \mathbf{s}_{t+1}) \sim \mathcal{D}} \left[\left(\hat{Q}_{\phi_1}^{\pi_\theta}(\mathbf{s}_t, \mathbf{a}_t) - y_t \right)^2 + \left(\hat{Q}_{\phi_2}^{\pi_\theta}(\mathbf{s}_t, \mathbf{a}_t) - y_t \right)^2 \right] \\ J(\theta) = \mathbb{E}_{s \sim \mathcal{D}} \left[\mathbb{E}_{\mathbf{a}_t \sim \pi_\theta(\cdot | \mathbf{s}_t)} \left[\alpha \log \pi_\theta(\mathbf{a}_t | \mathbf{s}_t) - \min_{i=1,2} \hat{Q}_{\phi_i}^{\pi_\theta}(\mathbf{s}_t, \mathbf{a}_t) \right] \right] \end{cases}$$

- ▶ Since the actor and critic updates are those of DDPG but with entropy, if we set $\alpha = 0$ and take a deterministic policy, we exactly get TD3



Fujimoto, S., van Hoof, H., & Meger, D. (2018) Addressing function approximation error in actor-critic methods. *arXiv preprint arXiv:1802.09477*



Automatic Entropy Adjustment

- ▶ The temperature α needs to be tuned for each task
- ▶ Finding a good α is non trivial
- ▶ Instead of tuning α , tune a lower bound \mathcal{H}_0 for the policy entropy
- ▶ And change the optimization problem into a constrained one

$$\begin{cases} \pi^* = \underset{\pi}{\operatorname{argmax}} \sum_t \mathbb{E}_{(\mathbf{s}_t, \mathbf{a}_t) \sim \rho_{\pi_{\theta}}} [r(\mathbf{s}_t, \mathbf{a}_t)] \\ \text{s.t. } \forall t \mathbb{E}_{(\mathbf{s}_t, \mathbf{a}_t) \sim \rho_{\pi_{\theta}}} [-\log \pi_{\theta}(\mathbf{a}_t | \mathbf{s}_t)] \geq \mathcal{H}_0, \end{cases}$$

- ▶ Use heuristic to compute \mathcal{H}_0 from the action space size


α can be learned to satisfy this constraint by minimizing:

$$J(\alpha) = \mathbb{E}_{\mathbf{s}_t \sim \mathcal{D}} [\mathbb{E}_{\mathbf{a}_t \sim \pi_{\theta}(\cdot | \mathbf{s}_t)} [-\alpha \log \pi_{\theta}(\mathbf{a}_t | \mathbf{s}_t) - \alpha \mathcal{H}_0]]$$

Practical algorithm

- ▶ Initialize neural networks π_θ and $\hat{Q}_\phi^{\pi_\theta}$ weights
- ▶ Play k steps in the environment by sampling actions with π_θ
- ▶ Store the collected transitions in a replay buffer
- ▶ Sample k batches of transitions in the replay buffer
- ▶ Update the temperature α , the actor and the critic using SGD
- ▶ Repeat this cycle until convergence

Distributional estimation



- ▶ Using a distribution of estimates is more stable than a single estimate
- ▶ C51, D4PG, ...
- ▶ TQC uses N critic heads to estimate a distribution of Q-values
- ▶ Taking the Q-value as a random variable rather than a maximum likelihood estimate



Bellemare, M. G., Dabney, W., and Munos, R. (2017) A distributional perspective on reinforcement learning. *arXiv preprint arXiv:1707.06887*

Truncated Quantile Critics





Figure 2. Step-by-step construction of the temporal difference target distribution $Y(s, a)$. First, we compute approximations of the return distribution conditioned on s' and a' by evaluating N separate target critics. Second, we make a mixture out of the N distributions from the previous step. Third, we truncate the right tail of this mixture to obtain atoms $z_{(i)}(s', a')$ from equation 11. Fourthly, we add entropy term, discount and add reward as in soft Bellman equation.

- Each atom is a Q-value estimate
- To fight overestimation bias, TD3 and SAC take the min over two critics
- TQC truncates the higher quantiles




Arsenii Kuznetsov, Pavel Shvechikov, Alexander Grishin, and Dmitry Vetrov. Controlling overestimation bias with truncated mixture of continuous distributional quantile critics. In *International Conference on Machine Learning*, pp. 5556–5566. PMLR, 2020

Rationale: bias-variance diagram




- x-axis = bias, y-axis = variance
- Taking the min or the average over N networks is not flexible
- Truncating the higher quantiles results in getting closer to the optimal policy

Performance



- Top figure: Humanoid-v2
- From 5 to a single critic
- Outperforms SAC, easier to use

Impact of truncation



- ▶ red = performance
- ▶ blue = distribution of error
- ▶ The optimal number of truncated quantiles is not always the same

Any question?



Send mail to: Olivier.Sigaud@upmc.fr



Bellemare, M. G., Dabney, W., and Munos, R. (2017).

A distributional perspective on reinforcement learning.

In Precup, D. and Teh, Y. W., editors, *Proceedings of the 34th International Conference on Machine Learning, ICML 2017, Sydney, NSW, Australia, 6-11 August 2017*, volume 70 of *Proceedings of Machine Learning Research*, pages 449–458. PMLR.



Fujimoto, S., van Hoof, H., and Meger, D. (2018).

Addressing function approximation error in actor-critic methods.

In Dy, J. G. and Krause, A., editors, *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pages 1582–1591. PMLR.



Haarnoja, T., Zhou, A., Abbeel, P., and Levine, S. (2018a).

Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor.

In Dy, J. G. and Krause, A., editors, *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pages 1856–1865. PMLR.



Haarnoja, T., Zhou, A., Hartikainen, K., Tucker, G., Ha, S., Tan, J., Kumar, V., Zhu, H., Gupta, A., Abbeel, P., et al. (2018b).

Soft actor-critic algorithms and applications.

arXiv preprint arXiv:1812.05905.



Kuznetsov, A., Shvechikov, P., Grishin, A., and Vetrov, D. P. (2020).

Controlling overestimation bias with truncated mixture of continuous distributional quantile critics.

In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pages 5556–5566. PMLR.



Mnih, V., Badia, A. P., Mirza, M., Graves, A., Lillicrap, T. P., Harley, T., Silver, D., and Kavukcuoglu, K. (2016).

Asynchronous methods for deep reinforcement learning.

In Balcan, M. and Weinberger, K. Q., editors, *Proceedings of the 33rd International Conference on Machine Learning, ICML 2016, New York City, NY, USA, June 19-24, 2016*, volume 48 of *JMLR Workshop and Conference Proceedings*, pages 1928–1937. JMLR.org.



Mohamed, S., Rosca, M., Figurnov, M., and Mnih, A. (2020).

Monte carlo gradient estimation in machine learning.

J. Mach. Learn. Res., 21(132):1–62.