

Energy Efficiency in Railway Scheduling

Paul Tennigkeit, Georgi Abshilava

Universität Potsdam

21.09.2026

Outline

Motivation: Energy Efficiency Problem

Baseline ASP Model

Acceleration Mechanics

Energy Mechanics

Results

Conclusion

Motivation: Energy Efficiency Problem

- ▶ Model the real-world better (Trains' engine types and masses)
- ▶ Add energy efficiency as a secondary objective to pathfinding (How do the energy constraints affect pathfinding?)

Baseline ASP Model

- ▶ Establishes rules to handle essential train behavior
 - ▶ Directions
 - ▶ Movements
 - ▶ Transitions
 - ▶ Collision and Reachability Constraints
 - ▶ Schedule Optimization

Directions and Movements

```
% Directions
```

```
dir(s).
```

```
dir(n).
```

```
dir(w).
```

```
dir(e).
```

```
% Movement Operation
```

```
moving(move_forward).
```

```
moving(move_left).
```

```
moving(move_right).
```

```
% Movement on Grid
```

```
delta(A,s,1,0) :- moving(A).
```

```
delta(A,n,-1,0) :- moving(A).
```

```
delta(A,e,0,1) :- moving(A).
```

```
delta(A,w,0,-1) :- moving(A).
```

Transitions

```
% Transition facts: To represent different track types
% ID : track ID
% Dir1: pointing direction of agent
% Act : associated action with movement towards exit
% Dir2: exit direction
transition(ID, Dir1, Act, Dir2).
```

Reachability Constraints

```
% define states (cell, time, direction),  
% which are reachable by a train  
reachable(ID,T,A,X2,Y2,T2,Dir2) :-  
    A != wait,  
    position(ID,(X,Y),T,Dir1),  
    cell((X,Y),Cell),  
    transition(Cell,Dir1,A,Dir2),  
    delta(A,Dir2,DX,DY),  
    X2 = X + DX,  
    Y2 = Y + DY,  
    speed(ID,S),  
    T2 = T + S,  
    time(T2).  
  
reachable(ID,T,wait,X,Y,T+1,Dir) :-  
    position(ID,(X,Y),T,Dir),  
    time(T+1).
```

Reachability Constraints

```
% Choose exactly one valid transition at each time step
1 { position(ID,(X2,Y2),T2,Dir2)
    : reachable(ID,T,A,X2,Y2,T2,Dir2)
} 1 :- position(ID,(_,_),T,_),
    not reached(ID,T).

% Track the time interval a train spends inside a cell.
% This is to make enforcing collision constraints easier.
chosen(ID,T,A,X,Y,X2,Y2,T2) :-
    position(ID,(X,Y),T,_),
    position(ID,(X2,Y2),T2,_),
    reachable(ID,T,A,X2,Y2,T2,_).

stay(ID,X,Y,T1) :- chosen(ID,T,_,X,Y,_,_,T2),
    time(T1),
    T <= T1,
    T1 < T2.
```

Reachability Constraints

```
% a train reached its target if their position matches  
reached(ID,T) :- position(ID,(X,Y),T,_),  
                   end(ID,(X,Y),_).
```

Collision Constraints

```
% Trains can not occupy the same cell at the same time  
:- stay(ID1,X,Y,T),  
   stay(ID2,X,Y,T),  
   ID1 < ID2.
```

```
% Trains can not swap their position  
:- stay(ID1,X1,Y1,T),  
   stay(ID2,X2,Y2,T),  
   stay(ID1,X2,Y2,T+1),  
   stay(ID2,X1,Y1,T+1),  
   ID1 < ID2.
```

Schedule Optimization

```
% stop searching if train is not
% in time to reach its target anymore
:- position(ID,(X,Y),T,_),
   end(ID,(EX,EY),Arr),
   speed(ID,InvSpd),
   T + (|X-EX| + |Y-EY|)*InvSpd > Arr.

% the arrival times should be minimized
reached_earlier(ID,T) :- reached(ID,T),
                           reached(ID,T0), T0 < T.
arrival(ID,T) :- reached(ID,T),
                  not reached_earlier(ID,T).

% minimize summed arrival times
#minimize { T@2,ID : arrival(ID,T) }.
```

Acceleration Mechanics

- ▶ Speed Changes in General
- ▶ Turning, Waiting, and Arrival Physics
- ▶ Solver Heuristics

Speed Changes in General

```
% Interpret given train speeds as maximum speeds  
max_speed(ID,S) :- speed(ID,S).
```

```
% Trains start with a speed of 1/4  
temp_speed(ID, Dep+1, 4) :- start(ID,(_,_),Dep,_).
```

Speed Changes in General

```
% Allow gradual speed changed, while
% respecting the physical limits of the train.
% The train can change its speed up to one
% step at a time
1{
    temp_speed(ID,T2,S-1);
    temp_speed(ID,T2,S);
    temp_speed(ID,T2,S+1)
}1
:- chosen(ID,T,A,_,_,_,_,T2),
   A != wait,
   temp_speed(ID,T,S),
   max_speed(ID,MS),
   S-1 >= MS,
   S+1 <= 4.
```

Speed Changes in General

```
% Lower Bound
1{
  temp_speed(ID,T2,S-1);
  temp_speed(ID,T2,S)
}1
:- chosen(ID,T,A,_,_,_,_,T2),
   A != wait,
   temp_speed(ID,T,S),
   max_speed(ID,MS),
   S-1 >= MS,
   S+1 > 4.
```

Speed Changes in General

```
% Upper Bound
1{
    temp_speed(ID,T2,S);
    temp_speed(ID,T2,S+1)
}1
:- chosen(ID,T,A,_,_,_,_,T2),
   A != wait,
   temp_speed(ID,T,S),
   max_speed(ID,MS),
   S-1 < MS,
   S+1 <= 4.
```

Speed Changes in General

```
% In between (maintain speed)
temp_speed(ID,T2,S) :- chosen(ID,T,A,_,_,_,_,T2),
                        A != wait,
                        temp_speed(ID,T,S),
                        max_speed(ID,MS),
                        S-1 < MS,
                        S+1 > 4.
```

Turning, Waiting, and Arrival Physics

```
% You have to take a turn with inverse speed >= 3
:- position(ID,_,T,Dir1),
   temp_speed(ID,T,S),
   T2 = T + S,
   position(ID,_,T2,Dir2),
   Dir1 != Dir2,
   S < 3.
```

Turning, Waiting, and Arrival Physics

```
% to be able to wait, you need to have speed 1/4
reachable(ID,T,wait,X,Y,T+1,Dir) :-
    position(ID,(X,Y),T,Dir),
    time(T+1),
    temp_speed(ID,T,4).

% after waiting, you have to start with speed 1/4
temp_speed(ID,T2,4) :- chosen(ID,T,wait,_,_,_,T2).
```

Turning, Waiting, and Arrival Physics

```
% you can only arrive at your goal if your  
% inverse speed was 4 before  
:- reached(ID,T2),  
    temp_speed(ID,T1,S),  
    T2 = T1 + S,  
    S < 4.
```

Solver Heuristics

```
% prefer to not wait
wait_position(ID,X2,Y2,T2,Dir2) :-
    reachable(ID,T,wait,X2,Y2,T2,Dir2).

#heuristic position(ID,(X2,Y2),T2,Dir2)
    : wait_position(ID,X2,Y2,T2,Dir2).
    [-50,1]

% schedule trains one by one
#heuristic position(ID,(X,Y),T,Dir) : start(ID,_,Dep,_).
    [-Dep,1]

% prefer getting faster
#heuristic temp_speed(ID,T,S) : position(ID,_,T,_).
    [-S,1]
```

Energy Mechanics

- ▶ Energy Cost Factors and Power Types
- ▶ Energy Consumption for Different Types of Actions (Moving Straight, Turning, Braking)
- ▶ Encoding Optimization

Cost Factors and Power Types

```
% Energy cost factor of trains
% based on power type + weight
pow_cost_fac(ID,1) :- pow_type(ID, electro).
pow_cost_fac(ID,2) :- pow_type(ID, hybrid).
pow_cost_fac(ID,3) :- pow_type(ID, diesel).
pow_cost_fac(ID,4) :- pow_type(ID, hydrogen).

% A train's weight is defined in
% the environment's logic program
cost_fac(ID,CF) :- pow_cost_fac(ID,PCF),
                    weight(ID,W),
                    CF = PCF * W.
```

Cost of Moving Straight

```
% (Kinetic) Energy consumed is proportional  
% to square of speed  
energy(ID,T2,E) :- action(train(ID),A,T),  
                      A != wait,  
                      position(ID,_,T,Dir),  
                      temp_speed(ID,T,S),  
                      T2 = T + S,  
                      position(ID,_,T2,Dir),  
                      cost_fac(ID,CF),  
                      E = 100 * CF * 1/S * 1/S.
```

Cost of Turning

```
% Energy loss due to curve resistance
% 10% penalty applied to straight-moving energy formula
energy(ID,T2,E) :- position(ID,_,T,Dir1),
                    temp_speed(ID,T,S),
                    T2 = T + S,
                    position(ID,_,T2,Dir2),
                    Dir1 != Dir2,
                    cost_fac(ID,CF),
                    E = 100 * CF * 1/S * 1/S * 11/10.
```

Cost of Braking

```
% 40% return of energy due to regenerative braking
prev_wait(ID,T) :- action(train(ID),_,T),
                    time(T-1),
                    action(train(ID),wait,T-1).
energy(ID,T+1,E) :- action(train(ID),wait,T),
                    not prev_wait(ID,T),
                    cost_fac(ID,CF),
                    E = -1 * 100 * 4/10 * CF * 1/4 * 1/4.
```

Results




Figure: Environment used to test the encodings. The global simulation time is set to 63 time steps

Results

```
train(0).  
start(0,(6,19),0,w).  
end(0,(10,5),63).  
speed(0,1).  
pow_type(0, electro).  
weight(0,2).
```

```
train(1).  
start(1,(9,5),0,e).  
end(1,(7,19),63).  
speed(1,1).  
pow_type(1, diesel).  
weight(1,1).
```

Results

Table: Train 0 (1)

Time Step	Position	Direction	Status	Given Command
1	(6, 19)	w	waiting	move_forward
2	(6, 18)	w	ready to depart	wait
3	(6, 18)	w	ready to depart	wait
4	(6, 18)	w	ready to depart	wait
5	(6, 18)	w	ready to depart	wait
6	(6, 18)	w	ready to depart	wait
7	(6, 18)	w	ready to depart	wait
8	(6, 18)	w	ready to depart	wait
9	(6, 18)	w	ready to depart	wait
10	(6, 18)	w	ready to depart	wait
11	(6, 18)	w	ready to depart	wait
12	(6, 18)	w	ready to depart	wait
13	(6, 18)	w	ready to depart	move_forward
14	(6, 17)	w	moving	wait
15	(6, 17)	w	stopped	move_forward

Results

Table: Train 0 (2)

Time Step	Position	Direction	Status	Given Command
16	(6, 16)	w	moving	move_forward
17	(6, 15)	w	moving	move_forward
18	(6, 14)	w	moving	move_forward
19	(6, 13)	w	moving	move_forward
20	(6, 12)	w	moving	move_forward
21	(6, 11)	w	moving	move_forward
22	(6, 10)	w	moving	move_forward
23	(7, 10)	s	moving	move_forward
24	(8, 10)	s	moving	move_forward
25	(9, 10)	s	moving	move_right
26	(9, 9)	w	moving	move_forward
27	(9, 8)	w	moving	move_left
28	(10, 8)	s	moving	move_forward
29	(10, 7)	w	moving	move_forward
30	(10, 6)	w	moving	move_forward
31	(10, 5)	w	moving	none

Results

Table: Train 1

Time Step	Position	Direction	Status	Given Command
1	(9, 5)	e	waiting	move_forward
2	(9, 6)	e	ready to depart	move_forward
3	(9, 7)	e		move_forward
4	(9, 8)	e	moving	move_forward
5	(9, 9)	e	moving	move_forward
6	(9, 10)	e	moving	move_left
7	(8, 10)	n	moving	move_forward
8	(7, 10)	n	moving	move_forward
9	(6, 10)	n	moving	move_forward
10	(6, 11)	e	moving	move_forward
11	(6, 12)	e	moving	move_forward
12	(6, 13)	e	moving	move_forward
13	(6, 14)	e	moving	move_forward
14	(6, 15)	e	moving	move_forward
15	(6, 16)	e	moving	move_right
16	(7, 16)	s	moving	move_forward
17	(7, 17)	e	moving	move_forward
18	(7, 18)	e	moving	move_forward
19	(7, 19)	e	moving	none

Results

Table: Train 0 (1)

Time Step	Position	Direction	Status	Given Command	Temp Speed	Consumed Energy
1	(6, 19)	w	waiting	move_forward	4	none
5	(6, 18)	w	ready to depart	move_forward	3	12
8	(6, 17)	w		move_forward	2	22
10	(6, 16)	w		move_forward	1	50
11	(6, 15)	w	moving	move_forward	2	200
13	(6, 14)	w	moving	move_right	3	50
16	(5, 14)	n	moving	move_forward	2	24
18	(4, 14)	n	moving	move_forward	3	50
21	(4, 13)	w	moving	move_forward	2	24
23	(4, 12)	w	moving	move_forward	1	50
24	(4, 11)	w	moving	move_forward	1	200
25	(4, 10)	w	moving	move_forward	1	200
26	(4, 9)	w	moving	move_forward	1	200
27	(4, 8)	w	moving	move_forward	1	200
28	(4, 7)	w	moving	move_forward	1	200
29	(4, 6)	w	moving	move_forward	1	200

Results

Table: Train 0 (2)

Time Step	Position	Direction	Status	Given Command	Temp Speed	Consumed Energy
30	(4, 5)	w	moving	move_forward	1	200
31	(4, 4)	w	moving	move_forward	1	200
32	(4, 3)	w	moving	move_forward	1	200
33	(4, 2)	w	moving	move_forward	1	200
34	(4, 1)	w	moving	move_forward	2	200
36	(4, 0)	w	moving	move_forward	3	50
39	(5, 0)	s	moving	move_forward	2	24
41	(6, 0)	s	moving	move_forward	1	50
42	(7, 0)	s	moving	move_forward	1	200
43	(8, 0)	s	moving	move_forward	2	200
45	(9, 0)	s	moving	move_forward	3	50
48	(9, 1)	e	moving	move_forward	2	24
50	(9, 2)	e	moving	move_right	3	50
53	(10, 2)	s	moving	move_forward	3	24
56	(10, 3)	e	moving	move_forward	3	24
59	(10, 4)	e	moving	move_forward	4	22
63	(10, 5)	e	moving	none	4	12

Results

Table: Train 1 (1)

Time Step	Position	Direction	Status	Given Command	Temp Speed	Consumed Energy
1	(9, 5)	e	waiting	wait	4	none
2	(9, 5)	e	ready to depart	move_forward	4	-7
6	(9, 6)	e	moving	move_forward	3	18
9	(9, 7)	e	moving	move_forward	4	33
13	(9, 8)	e	moving	move_forward	3	18
16	(9, 9)	e	moving	wait	4	33
17	(9, 9)	e	stopped	wait	4	-7
18	(9, 9)	e	stopped	move_forward	4	none
22	(9, 10)	e	moving	move_left	4	18
26	(8, 10)	n	moving	wait	4	19
27	(8, 10)	n	stopped	move_forward	4	-7
31	(7, 10)	n	moving	move_forward	3	18
34	(6, 10)	n	moving	move_forward	4	33
38	(6, 11)	e	moving	move_forward	3	19
41	(6, 12)	e	moving	move_forward	2	33
43	(6, 13)	e	moving	move_forward	2	75

Results

Table: Train 1 (2)

Time Step	Position	Direction	Status	Given Command	Temp Speed	Consumed Energy
45	(6, 14)	e	moving	move_forward	2	75
47	(6, 15)	e	moving	move_forward	3	75
50	(6, 16)	e	moving	move_right	3	33
53	(7, 16)	s	moving	move_forward	3	36
56	(7, 17)	e	moving	move_forward	3	36
59	(7, 18)	e	moving	move_forward	4	33
63	(7, 19)	e	moving	none	4	18

Conclusion

- ▶ Our encoding can capture energy consumption behavior of trains accurately
- ▶ Work needs to be done regarding computation time: Clingo took 12 minutes to find a solution for this small environment (baseline encoding: 16 seconds)
- ▶ Our encoding does not take slopes into account