

Energy Efficiency in Railway Scheduling

Paul Tennigkeit, Georgi Abshilava

Universität Potsdam

21.09.2026

Outline

Motivation: Energy Efficiency Problem

Baseline ASP Model

- ▶ Establishes rules to handle essential train behavior
 - ▶ Directions
 - ▶ Movements
 - ▶ Transitions
 - ▶ Collision and Reachability Constraints
 - ▶ Schedule Optimization

Directions and Movements

```
% Directions
```

```
dir(s).
```

```
dir(n).
```

```
dir(w).
```

```
dir(e).
```

```
% Movement Operation
```

```
moving(move_forward).
```

```
moving(move_left).
```

```
moving(move_right).
```

```
% Movement on Grid
```

```
delta(A,s,1,0) :- moving(A).
```

```
delta(A,n,-1,0) :- moving(A).
```

```
delta(A,e,0,1) :- moving(A).
```

```
delta(A,w,0,-1) :- moving(A).
```

Transitions

```
% Transition facts: To represent different track types
% ID : track ID
% Dir1: pointing direction of agent
% Act : associated action with movement towards exit
% Dir2: exit direction
transition(ID, Dir1, Act, Dir2).
```

Collision Constraints

```
% Trains can not occupy the same cell at the same time
:- stay(ID1,X,Y,T),
   stay(ID2,X,Y,T),
   ID1 < ID2.
```

```
% Trains can not swap their position
:- stay(ID1,X1,Y1,T),
   stay(ID2,X2,Y2,T),
   stay(ID1,X2,Y2,T+1),
   stay(ID2,X1,Y1,T+1),
   ID1 < ID2.
```

Reachability Constraints

```
% define states (cell, time, direction),  
% which are reachable by a train  
reachable(ID,T,A,X2,Y2,T2,Dir2) :-  
    A != wait,  
    position(ID,(X,Y),T,Dir1),  
    cell((X,Y),Cell),  
    transition(Cell,Dir1,A,Dir2),  
    delta(A,Dir2,DX,DY),  
    X2 = X + DX,  
    Y2 = Y + DY,  
    speed(ID,S),  
    T2 = T + S,  
    time(T2).  
  
reachable(ID,T,wait,X,Y,T+1,Dir) :-  
    position(ID,(X,Y),T,Dir),  
    time(T+1).
```

Reachability Constraints

```
% Choose exactly one valid transition at each time step
1 { position(ID,(X2,Y2),T2,Dir2)
    : reachable(ID,T,A,X2,Y2,T2,Dir2)
} 1 :- position(ID,(_,_),T,_),
    not reached(ID,T).

% Track the time interval a train spends inside a cell.
% This is to make enforcing collision constraints easier.
chosen(ID,T,A,X,Y,X2,Y2,T2) :-
    position(ID,(X,Y),T,_),
    position(ID,(X2,Y2),T2,_),
    reachable(ID,T,A,X2,Y2,T2,_).

% a train reached its target if their position matches
reached(ID,T) :- position(ID,(X,Y),T,_),
    end(ID,(X,Y),_).
```

Schedule Optimization

```
% stop searching if train is not
% in time to reach its target anymore
:- position(ID,(X,Y),T,_),
    end(ID,(EX,EY),Arr),
    speed(ID,InvSpd),
    T + (|X-EX| + |Y-EY|)*InvSpd > Arr.

% the arrival times should be minimized
reached_earlier(ID,T) :- reached(ID,T),
                        reached(ID,T0), T0 < T.
arrival(ID,T) :- reached(ID,T),
                 not reached_earlier(ID,T).

% minimize summed arrival times
#minimize { T@2,ID : arrival(ID,T) }.
```




Figure: Baseline Encoding in Action (at timestep 37)

Table: Train 0

Time step	Position	direction	status	Given Command
34	(11, 1)	s	moving	move_forward
35	(12, 1)	s	moving	move_forward
36	(13, 1)	s	moving	move_forward
37	(13, 2)	e	moving	move_forward
38	(13, 3)	e	moving	move_forward
39	(13, 4)	e	moving	move_forward
40	(13, 5)	e	moving	move_forward

Table: Train 1

Time step	Position	direction	status	Given Command
34	(7, 20)	w	moving	move_forward
35	(7, 19)	w	moving	move_forward
36	(7, 18)	w	moving	move_forward
37	(7, 17)	w	moving	move_forward
38	(7, 16)	w	moving	move_forward
39	(7, 15)	w	moving	move_forward
40	(7, 14)	w	moving	move_forward

Table: Train 2

Time step	Position	direction	status	Given Command
28	(12, 11)	w	moving	move_forward
32	(11, 11)	n	moving	move_forward
36	(10, 11)	n	moving	wait
37	(10, 11)	n	stopped	move_forward
41	(9, 11)	n	moving	move_forward
45	(8, 11)	n	moving	move_left
49	(8, 10)	w	moving	move_forward

Table: Train 3

Time step	Position	direction	status	Given Command
34	(13, 5)	e	moving	move_forward
35	(13, 6)	e	moving	move_forward
36	(13, 7)	e	moving	move_forward
37	(13, 8)	e	moving	move_forward
38	(13, 9)	e	moving	move_forward
39	(13, 10)	e	moving	move_forward
40	(13, 11)	e	moving	move_forward

Energy Encoding Mechanics

Energy Costs of Actions

Search Optimization and Heuristics

Results and Comparison with Baseline Model

Conclusion