Product identity and scope

Model A30-6206 - single-row deep-groove bearing

DOCUMENT ID
DS-CAND-A

REVISION
3

EFFECTIVE DATE
2026-10-22

OWNER
Supplier Alpha Engineering

CLASSIFICATION
Synthetic hackathon fixture

Identification

- Candidate ID: CAND-A
- Supplier part: A30-6206-R3
- Bearing family: 6205 equivalent
- Nominal bore class: 30 mm

Document scope

- Supplier catalog characteristics for the stated part and revision.
- Values are product-level specifications unless an application is named.
- Plant-A qualification and production release are outside this datasheet.

Synthetic supplier fixture. Availability does not imply production release.

Dimensions

Controlled dimensions for Candidate A

DOCUMENT ID
DS-CAND-A

REVISION
3

EFFECTIVE DATE
2026-10-22

OWNER
Supplier Alpha Engineering

CLASSIFICATION
Synthetic hackathon fixture

Dimensions table

- Bore diameter | 30 mm | tolerance 0 / -0.010 mm
- Outside diameter | 52 mm | tolerance 0 / -0.013 mm
- Width | 15 mm | tolerance 0 / -0.120 mm
- Corner radius | 1.0 mm maximum

Application reference

- Seat family: BEARING-SEAT-25MM
- Measurement condition: 20 C
- Drawing compatibility still requires application review.

Load ratings

Catalog ratings under supplier reference conditions

DOCUMENT ID
DS-CAND-A

REVISION
3

EFFECTIVE DATE
2026-10-22

OWNER
Supplier Alpha Engineering

CLASSIFICATION
Synthetic hackathon fixture

Load ratings table

- Basic dynamic load rating | 16 kN
- Basic static load rating | 7.8 kN
- Reference speed | 12,000 rpm
- Limiting speed | 15,000 rpm

Rating basis

- Ratings follow the supplier's catalog calculation basis.
- Application factors and duty-cycle suitability require Engineering review.

Lubrication and evidence limitations

General product information - not application qualification

DOCUMENT ID
DS-CAND-A

REVISION
3

EFFECTIVE DATE
2026-10-22

OWNER
Supplier Alpha Engineering

CLASSIFICATION
Synthetic hackathon fixture

Supplied condition

- Factory grease: Supplier Alpha G-42
- Shield configuration: dual shield
- Storage range: -20 C to 50 C

Explicit evidence limitation

- No application-specific lubricant temperature qualification is provided for HIGH-TEMP-LUBRICATION.
- No test result demonstrates suitability at the Assembly A operating temperature.
- REQ-LUBE-TEMP-001 therefore requires evidence or qualification testing.

Missing application evidence must remain UNKNOWN. Do not infer compatibility from storage range.