

# Machine Learning

Justin Grimmer

Professor  
Department of Political Science  
Stanford University

April 16th, 2019

# Discovery

Search for new ways to organize text

- Complement, Not Replace, Organizations of Text
- There is No Ground Truth Conceptualization
- Once you have a conceptualization it is yours

Clustering: partition of documents

- Discover categories
- Assign documents to categories

## Fully Automated Clustering

- 1) Notion of distance
- 2) Definition of “good” clustering
- 3) Optimization method

# K-Means $\rightsquigarrow$ Objective Function

$N$  documents  $\mathbf{x}_i = (x_{i1}, x_{i2}, \dots, x_{iJ})$  (normalized)

# K-Means $\rightsquigarrow$ Objective Function

$N$  documents  $\mathbf{x}_i = (x_{i1}, x_{i2}, \dots, x_{iJ})$  (normalized)

Goal  $\rightsquigarrow$  Partition documents into  $K$  clusters.

# K-Means $\rightsquigarrow$ Objective Function

$N$  documents  $\mathbf{x}_i = (x_{i1}, x_{i2}, \dots, x_{iJ})$  (normalized)

Goal  $\rightsquigarrow$  Partition documents into  $K$  clusters.

Two parameters to estimate

# K-Means $\rightsquigarrow$ Objective Function

$N$  documents  $\mathbf{x}_i = (x_{i1}, x_{i2}, \dots, x_{iJ})$  (normalized)

Goal  $\rightsquigarrow$  Partition documents into  $K$  clusters.

Two parameters to estimate

- 1)  $K \times J$  matrix of cluster centers  $\Theta$ .

# K-Means $\rightsquigarrow$ Objective Function

$N$  documents  $\mathbf{x}_i = (x_{i1}, x_{i2}, \dots, x_{iJ})$  (normalized)

Goal  $\rightsquigarrow$  Partition documents into  $K$  clusters.

Two parameters to estimate

- 1)  $K \times J$  matrix of cluster centers  $\Theta$ .

Cluster  $k$  has center



# K-Means $\rightsquigarrow$ Objective Function

$N$  documents  $\mathbf{x}_i = (x_{i1}, x_{i2}, \dots, x_{iJ})$  (normalized)

Goal  $\rightsquigarrow$  Partition documents into  $K$  clusters.

Two parameters to estimate

- 1)  $K \times J$  matrix of cluster centers  $\Theta$ .

Cluster  $k$  has center

$$\boldsymbol{\theta}_k = (\theta_{1k}, \theta_{2k}, \dots, \theta_{Jk})$$

# K-Means $\rightsquigarrow$ Objective Function

$N$  documents  $\mathbf{x}_i = (x_{i1}, x_{i2}, \dots, x_{iJ})$  (normalized)

Goal  $\rightsquigarrow$  Partition documents into  $K$  clusters.

Two parameters to estimate

- 1)  $K \times J$  matrix of cluster centers  $\Theta$ .

Cluster  $k$  has center

$$\boldsymbol{\theta}_k = (\theta_{1k}, \theta_{2k}, \dots, \theta_{Jk})$$

$\boldsymbol{\theta}_k = \text{exemplar}$  for cluster  $k$

# K-Means $\rightsquigarrow$ Objective Function

$N$  documents  $\mathbf{x}_i = (x_{i1}, x_{i2}, \dots, x_{iJ})$  (normalized)

Goal  $\rightsquigarrow$  Partition documents into  $K$  clusters.

Two parameters to estimate

- 1)  $K \times J$  matrix of cluster centers  $\Theta$ .

Cluster  $k$  has center

$$\boldsymbol{\theta}_k = (\theta_{1k}, \theta_{2k}, \dots, \theta_{Jk})$$

$\boldsymbol{\theta}_k = \text{exemplar}$  for cluster  $k$

- 2)  $\mathbf{T}$  is an  $N \times K$  matrix. Each row is an indicator vector.

# K-Means $\rightsquigarrow$ Objective Function

$N$  documents  $\mathbf{x}_i = (x_{i1}, x_{i2}, \dots, x_{iJ})$  (normalized)

Goal  $\rightsquigarrow$  Partition documents into  $K$  clusters.

Two parameters to estimate

- 1)  $K \times J$  matrix of cluster centers  $\Theta$ .

Cluster  $k$  has center

$$\boldsymbol{\theta}_k = (\theta_{1k}, \theta_{2k}, \dots, \theta_{Jk})$$

$\boldsymbol{\theta}_k = \text{exemplar}$  for cluster  $k$

- 2)  $\mathbf{T}$  is an  $N \times K$  matrix. Each row is an indicator vector.

If observation  $i$  is from cluster  $k$ , then

# K-Means $\rightsquigarrow$ Objective Function

$N$  documents  $\mathbf{x}_i = (x_{i1}, x_{i2}, \dots, x_{iJ})$  (normalized)

Goal  $\rightsquigarrow$  Partition documents into  $K$  clusters.

Two parameters to estimate

- 1)  $K \times J$  matrix of cluster centers  $\Theta$ .

Cluster  $k$  has center

$$\boldsymbol{\theta}_k = (\theta_{1k}, \theta_{2k}, \dots, \theta_{Jk})$$

$\boldsymbol{\theta}_k = \text{exemplar}$  for cluster  $k$

- 2)  $\mathbf{T}$  is an  $N \times K$  matrix. Each row is an indicator vector.

If observation  $i$  is from cluster  $k$ , then

$$\boldsymbol{\tau}_i = (0, 0, \dots, 0, \underbrace{1}_{k^{th}}, 0, \dots, 0)$$

# K-Means $\rightsquigarrow$ Objective Function

$N$  documents  $\mathbf{x}_i = (x_{i1}, x_{i2}, \dots, x_{iJ})$  (normalized)

Goal  $\rightsquigarrow$  Partition documents into  $K$  clusters.

Two parameters to estimate

- 1)  $K \times J$  matrix of cluster centers  $\Theta$ .

Cluster  $k$  has center

$$\boldsymbol{\theta}_k = (\theta_{1k}, \theta_{2k}, \dots, \theta_{Jk})$$

$\boldsymbol{\theta}_k = \text{exemplar}$  for cluster  $k$

- 2)  $\mathbf{T}$  is an  $N \times K$  matrix. Each row is an indicator vector.

If observation  $i$  is from cluster  $k$ , then

$$\boldsymbol{\tau}_i = (0, 0, \dots, 0, \underbrace{1}_{k^{th}}, 0, \dots, 0)$$

Hard Assignment

# K-Means $\rightsquigarrow$ Objective Function

Assume squared euclidean distance

# K-Means $\rightsquigarrow$ Objective Function

Assume squared euclidean distance

$$f(\mathbf{X}, \mathbf{T}, \mathbf{\Theta}) = \sum_{i=1}^N \sum_{k=1}^K \underbrace{\tau_{ik}}_{\text{cluster indicator}} \underbrace{\left( \sum_{j=1}^J (x_{ij} - \theta_{kj})^2 \right)}_{\text{Squared Euclidean Distance}}$$



# K-Means $\rightsquigarrow$ Objective Function

Assume squared euclidean distance

$$f(\mathbf{X}, \mathbf{T}, \boldsymbol{\Theta}) = \sum_{i=1}^N \sum_{k=1}^K \underbrace{\tau_{ik}}_{\text{cluster indicator}} \underbrace{\left( \sum_{j=1}^J (x_{ij} - \theta_{kj})^2 \right)}_{\text{Squared Euclidean Distance}}$$

- Calculate squared euclidean distance from center

# K-Means $\rightsquigarrow$ Objective Function

Assume squared euclidean distance

$$f(\mathbf{X}, \mathbf{T}, \mathbf{\Theta}) = \sum_{i=1}^N \sum_{k=1}^K \underbrace{\tau_{ik}}_{\text{cluster indicator}} \underbrace{\left( \sum_{j=1}^J (x_{ij} - \theta_{kj})^2 \right)}_{\text{Squared Euclidean Distance}}$$

- Calculate squared euclidean distance from center
- **Only** for the assigned cluster

# K-Means $\rightsquigarrow$ Objective Function

Assume squared euclidean distance

$$f(\mathbf{X}, \mathbf{T}, \mathbf{\Theta}) = \sum_{i=1}^N \sum_{k=1}^K \underbrace{\tau_{ik}}_{\text{cluster indicator}} \underbrace{\left( \sum_{j=1}^J (x_{ij} - \theta_{kj})^2 \right)}_{\text{Squared Euclidean Distance}}$$

- Calculate squared euclidean distance from center
- **Only** for the assigned cluster
- Two trivial solutions

# K-Means $\rightsquigarrow$ Objective Function

Assume squared euclidean distance

$$f(\mathbf{X}, \mathbf{T}, \mathbf{\Theta}) = \sum_{i=1}^N \sum_{k=1}^K \underbrace{\tau_{ik}}_{\text{cluster indicator}} \underbrace{\left( \sum_{j=1}^J (x_{ij} - \theta_{kj})^2 \right)}_{\text{Squared Euclidean Distance}}$$

- Calculate squared euclidean distance from center
- **Only** for the assigned cluster
- Two trivial solutions
  - If  $K = N$  then  $f(\mathbf{X}, \mathbf{T}, \mathbf{\Theta}) = 0$  (Minimum)

# K-Means $\rightsquigarrow$ Objective Function

Assume squared euclidean distance

$$f(\mathbf{X}, \mathbf{T}, \mathbf{\Theta}) = \sum_{i=1}^N \sum_{k=1}^K \underbrace{\tau_{ik}}_{\text{cluster indicator}} \underbrace{\left( \sum_{j=1}^J (x_{ij} - \theta_{kj})^2 \right)}_{\text{Squared Euclidean Distance}}$$

- Calculate squared euclidean distance from center
- **Only** for the assigned cluster
- Two trivial solutions
  - If  $K = N$  then  $f(\mathbf{X}, \mathbf{T}, \mathbf{\Theta}) = 0$  (Minimum)
  - Each observation in its own cluster

# K-Means $\rightsquigarrow$ Objective Function

Assume squared euclidean distance

$$f(\mathbf{X}, \mathbf{T}, \mathbf{\Theta}) = \sum_{i=1}^N \sum_{k=1}^K \underbrace{\tau_{ik}}_{\text{cluster indicator}} \underbrace{\left( \sum_{j=1}^J (x_{ij} - \theta_{kj})^2 \right)}_{\text{Squared Euclidean Distance}}$$

- Calculate squared euclidean distance from center
- **Only** for the assigned cluster
- Two trivial solutions
  - If  $K = N$  then  $f(\mathbf{X}, \mathbf{T}, \mathbf{\Theta}) = 0$  (Minimum)
    - Each observation in its own cluster
    - $\theta_i = \mathbf{x}_i$

# K-Means $\rightsquigarrow$ Objective Function

Assume squared euclidean distance

$$f(\mathbf{X}, \mathbf{T}, \mathbf{\Theta}) = \sum_{i=1}^N \sum_{k=1}^K \underbrace{\tau_{ik}}_{\text{cluster indicator}} \underbrace{\left( \sum_{j=1}^J (x_{ij} - \theta_{kj})^2 \right)}_{\text{Squared Euclidean Distance}}$$

- Calculate squared euclidean distance from center
- **Only** for the assigned cluster
- Two trivial solutions
  - If  $K = N$  then  $f(\mathbf{X}, \mathbf{T}, \mathbf{\Theta}) = 0$  (Minimum)
    - Each observation in its own cluster
    - $\theta_i = \mathbf{x}_i$
  - If  $K = 1$ ,  $f(\mathbf{X}, \mathbf{T}, \mathbf{\Theta}) = N \times \sum_{j=1}^J \sigma_j^2 w$

# K-Means $\rightsquigarrow$ Objective Function

Assume squared euclidean distance

$$f(\mathbf{X}, \mathbf{T}, \mathbf{\Theta}) = \sum_{i=1}^N \sum_{k=1}^K \underbrace{\tau_{ik}}_{\text{cluster indicator}} \underbrace{\left( \sum_{j=1}^J (x_{ij} - \theta_{kj})^2 \right)}_{\text{Squared Euclidean Distance}}$$

- Calculate squared euclidean distance from center
- **Only** for the assigned cluster
- Two trivial solutions
  - If  $K = N$  then  $f(\mathbf{X}, \mathbf{T}, \mathbf{\Theta}) = 0$  (Minimum)
    - Each observation in its own cluster
    - $\theta_i = x_i$
  - If  $K = 1$ ,  $f(\mathbf{X}, \mathbf{T}, \mathbf{\Theta}) = N \times \sum_{j=1}^J \sigma_j^2 w$ 
    - Each observation in same cluster



# K-Means $\rightsquigarrow$ Objective Function

Assume squared euclidean distance

$$f(\mathbf{X}, \mathbf{T}, \mathbf{\Theta}) = \sum_{i=1}^N \sum_{k=1}^K \underbrace{\tau_{ik}}_{\text{cluster indicator}} \underbrace{\left( \sum_{j=1}^J (x_{ij} - \theta_{kj})^2 \right)}_{\text{Squared Euclidean Distance}}$$

- Calculate squared euclidean distance from center
- **Only** for the assigned cluster
- Two trivial solutions
  - If  $K = N$  then  $f(\mathbf{X}, \mathbf{T}, \mathbf{\Theta}) = 0$  (Minimum)
    - Each observation in its own cluster
    - $\theta_i = x_i$
  - If  $K = 1$ ,  $f(\mathbf{X}, \mathbf{T}, \mathbf{\Theta}) = N \times \sum_{j=1}^J \sigma_j^2 w$ 
    - Each observation in same cluster
    - $\theta_1 = \text{Average across documents}$

# K-Means $\rightsquigarrow$ Optimization

Coordinate descent

# K-Means $\rightsquigarrow$ Optimization

Coordinate descent  $\rightsquigarrow$  iterate between labels and centers.

# K-Means $\rightsquigarrow$ Optimization

**Coordinate descent**  $\rightsquigarrow$  iterate between labels and centers.

Iterative algorithm: each iteration  $t$

# K-Means $\rightsquigarrow$ Optimization

**Coordinate descent**  $\rightsquigarrow$  iterate between labels and centers.

Iterative algorithm: each iteration  $t$

- Conditional on  $\Theta^{t-1}$  (from previous iteration), choose  $\mathbf{T}^t$

# K-Means $\rightsquigarrow$ Optimization

**Coordinate descent**  $\rightsquigarrow$  iterate between labels and centers.

Iterative algorithm: each iteration  $t$

- Conditional on  $\Theta^{t-1}$  (from previous iteration), choose  $\mathcal{T}^t$
- Conditional on  $\mathcal{T}^t$ , choose  $\Theta^t$

# K-Means $\rightsquigarrow$ Optimization

**Coordinate descent**  $\rightsquigarrow$  iterate between labels and centers.

Iterative algorithm: each iteration  $t$

- Conditional on  $\Theta^{t-1}$  (from previous iteration), choose  $\mathcal{T}^t$
- Conditional on  $\mathcal{T}^t$ , choose  $\Theta^t$

Repeat until convergence  $\rightsquigarrow$  as measured as change in  $f$  dropping below threshold  $\epsilon$

# K-Means $\rightsquigarrow$ Optimization

**Coordinate descent**  $\rightsquigarrow$  iterate between labels and centers.

Iterative algorithm: each iteration  $t$

- Conditional on  $\Theta^{t-1}$  (from previous iteration), choose  $\mathbf{T}^t$
- Conditional on  $\mathbf{T}^t$ , choose  $\Theta^t$

Repeat until convergence  $\rightsquigarrow$  as measured as change in  $f$  dropping below threshold  $\epsilon$

$$\text{Change} = f(\mathbf{X}, \mathbf{T}^t, \Theta^t) - f(\mathbf{X}, \mathbf{T}^{t-1}, \Theta^{t-1})$$



# K-Means $\rightsquigarrow$ Optimization

# K-Means $\rightsquigarrow$ Optimization

1) initialize  $K$  cluster centers  $\theta_1^t, \theta_2^t, \dots, \theta_K^t$ .

# K-Means $\rightsquigarrow$ Optimization

- 1) initialize  $K$  cluster centers  $\theta_1^t, \theta_2^t, \dots, \theta_K^t$ .
- 2) Choose  $T^t$

# K-Means $\rightsquigarrow$ Optimization

- 1) initialize  $K$  cluster centers  $\theta_1^t, \theta_2^t, \dots, \theta_K^t$ .
- 2) Choose  $\mathbf{T}^t$

$$\tau_{im}^t = \begin{cases} 1 & \text{if } m = \arg \min_k \sum_{j=1}^J (x_{ij} - \theta_{kj}^t)^2 \\ 0 & \text{otherwise,} \end{cases}.$$

# K-Means $\rightsquigarrow$ Optimization

- 1) initialize  $K$  cluster centers  $\theta_1^t, \theta_2^t, \dots, \theta_K^t$ .
- 2) Choose  $\mathbf{T}^t$

$$\tau_{im}^t = \begin{cases} 1 & \text{if } m = \arg \min_k \sum_{j=1}^J (x_{ij} - \theta_{kj}^t)^2 \\ 0 & \text{otherwise,} \end{cases}.$$

In words: Assign each document  $\mathbf{x}_i$  to the closest center  $\theta_m^t$

# K-Means $\rightsquigarrow$ Optimization

# K-Means $\rightsquigarrow$ Optimization

3) Choose  $\Theta^t \rightsquigarrow$  Focus on the center for cluster  $k$

# K-Means $\rightsquigarrow$ Optimization

3) Choose  $\Theta^t \rightsquigarrow$  Focus on the center for cluster  $k$

$$f(\mathbf{X}, \mathbf{T}^t, \mathbf{\Theta})_k = \sum_{i=1}^N \tau_{ik}^t \left( \sum_{j=1}^J (x_{ij} - \theta_{jk})^2 \right)$$



# K-Means $\rightsquigarrow$ Optimization

3) Choose  $\Theta^t \rightsquigarrow$  Focus on the center for cluster  $k$

$$f(\mathbf{X}, \mathbf{T}^t, \mathbf{\Theta})_k = \sum_{i=1}^N \tau_{ik}^t \left( \sum_{j=1}^J (x_{ij} - \theta_{jk})^2 \right)$$

$$\frac{\partial f(\mathbf{X}, \mathbf{T}^t, \mathbf{\Theta})_k}{\partial \theta_{kj}} = -2 \sum_{i=1}^N \tau_{ij}^t (x_{ij} - \theta_{jk})$$

# K-Means $\rightsquigarrow$ Optimization

3) Choose  $\Theta^t \rightsquigarrow$  Focus on the center for cluster  $k$

$$f(\mathbf{X}, \mathbf{T}^t, \Theta)_k = \sum_{i=1}^N \tau_{ik}^t \left( \sum_{j=1}^J (x_{ij} - \theta_{jk})^2 \right)$$

$$\frac{\partial f(\mathbf{X}, \mathbf{T}^t, \Theta)_k}{\partial \theta_{kj}} = -2 \sum_{i=1}^N \tau_{ij}^t (x_{ij} - \theta_{jk})$$

$$0 = -2 \sum_{i=1}^N \tau_{ij}^t (x_{ij} - \theta_{jk}^*)$$

# K-Means $\rightsquigarrow$ Optimization

3) Choose  $\Theta^t \rightsquigarrow$  Focus on the center for cluster  $k$

$$f(\mathbf{X}, \mathbf{T}^t, \Theta)_k = \sum_{i=1}^N \tau_{ik}^t \left( \sum_{j=1}^J (x_{ij} - \theta_{jk})^2 \right)$$

$$\frac{\partial f(\mathbf{X}, \mathbf{T}^t, \Theta)_k}{\partial \theta_{kj}} = -2 \sum_{i=1}^N \tau_{ij}^t (x_{ij} - \theta_{jk})$$

$$0 = -2 \sum_{i=1}^N \tau_{ij}^t (x_{ij} - \theta_{jk}^*)$$

$$= \sum_{i=1}^N \tau_{ij}^t x_{ij} - \theta_{jk}^* \sum_{i=1}^N \tau_{ij}^t$$

# K-Means $\rightsquigarrow$ Optimization

3) Choose  $\Theta^t \rightsquigarrow$  Focus on the center for cluster  $k$

$$f(\mathbf{X}, \mathbf{T}^t, \Theta)_k = \sum_{i=1}^N \tau_{ik}^t \left( \sum_{j=1}^J (x_{ij} - \theta_{jk})^2 \right)$$

$$\frac{\partial f(\mathbf{X}, \mathbf{T}^t, \Theta)_k}{\partial \theta_{kj}} = -2 \sum_{i=1}^N \tau_{ij}^t (x_{ij} - \theta_{jk})$$

$$0 = -2 \sum_{i=1}^N \tau_{ij}^t (x_{ij} - \theta_{jk}^*)$$

$$= \sum_{i=1}^N \tau_{ij}^t x_{ij} - \theta_{jk}^* \sum_{i=1}^N \tau_{ij}^t$$

$$\frac{\sum_{i=1}^N \tau_{ik}^t x_{ij}}{\sum_{i=1}^N \tau_{ik}^t} = \theta_{jk}^*$$

# K-Means $\rightsquigarrow$ Optimization

$$\boldsymbol{\theta}^{t+1} = \frac{\sum_{i=1}^N \tau_{ik} \mathbf{x}_i}{\sum_{i=1}^N \tau_{ik}}$$

# K-Means $\rightsquigarrow$ Optimization

$$\boldsymbol{\theta}^{t+1} = \frac{\sum_{i=1}^N \tau_{ik} \mathbf{x}_i}{\sum_{i=1}^N \tau_{ik}} \propto \sum_{i=1}^N \tau_{ik} \mathbf{x}_i$$

# K-Means $\rightsquigarrow$ Optimization

$$\boldsymbol{\theta}^{t+1} = \frac{\sum_{i=1}^N \tau_{ik} \mathbf{x}_i}{\sum_{i=1}^N \tau_{ik}} \propto \sum_{i=1}^N \tau_{ik} \mathbf{x}_i$$

In words:  $\boldsymbol{\theta}^{t+1}$  is the average of the documents assigned to  $k$ .

# K-Means $\rightsquigarrow$ Optimization

$$\boldsymbol{\theta}^{t+1} = \frac{\sum_{i=1}^N \tau_{ik} \mathbf{x}_i}{\sum_{i=1}^N \tau_{ik}} \propto \sum_{i=1}^N \tau_{ik} \mathbf{x}_i$$

In words:  $\boldsymbol{\theta}^{t+1}$  is the average of the documents assigned to  $k$ .  
Optimization algorithm:



# K-Means $\rightsquigarrow$ Optimization

$$\boldsymbol{\theta}^{t+1} = \frac{\sum_{i=1}^N \tau_{ik} \mathbf{x}_i}{\sum_{i=1}^N \tau_{ik}} \propto \sum_{i=1}^N \tau_{ik} \mathbf{x}_i$$

In words:  $\boldsymbol{\theta}^{t+1}$  is the average of the documents assigned to  $k$ .

Optimization algorithm:

- Initialize centers

# K-Means $\rightsquigarrow$ Optimization

$$\boldsymbol{\theta}^{t+1} = \frac{\sum_{i=1}^N \tau_{ik} \mathbf{x}_i}{\sum_{i=1}^N \tau_{ik}} \propto \sum_{i=1}^N \tau_{ik} \mathbf{x}_i$$

In words:  $\boldsymbol{\theta}^{t+1}$  is the average of the documents assigned to  $k$ .

Optimization algorithm:

- Initialize centers
- Do until converged:

# K-Means $\rightsquigarrow$ Optimization

$$\boldsymbol{\theta}^{t+1} = \frac{\sum_{i=1}^N \tau_{ik} \mathbf{x}_i}{\sum_{i=1}^N \tau_{ik}} \propto \sum_{i=1}^N \tau_{ik} \mathbf{x}_i$$

In words:  $\boldsymbol{\theta}^{t+1}$  is the average of the documents assigned to  $k$ .

Optimization algorithm:

- Initialize centers
- Do until converged:
  - For each document, find closest center  $\rightsquigarrow \tau_i^t$

# K-Means $\rightsquigarrow$ Optimization

$$\boldsymbol{\theta}^{t+1} = \frac{\sum_{i=1}^N \tau_{ik} \mathbf{x}_i}{\sum_{i=1}^N \tau_{ik}} \propto \sum_{i=1}^N \tau_{ik} \mathbf{x}_i$$

In words:  $\boldsymbol{\theta}^{t+1}$  is the average of the documents assigned to  $k$ .  
Optimization algorithm:

- Initialize centers
- Do until converged:
  - For each document, find closest center  $\rightsquigarrow \tau_i^t$
  - For each center, take average of assigned documents  $\rightsquigarrow \boldsymbol{\theta}_k^t$

# K-Means $\rightsquigarrow$ Optimization

$$\boldsymbol{\theta}^{t+1} = \frac{\sum_{i=1}^N \tau_{ik} \mathbf{x}_i}{\sum_{i=1}^N \tau_{ik}} \propto \sum_{i=1}^N \tau_{ik} \mathbf{x}_i$$


In words:  $\boldsymbol{\theta}^{t+1}$  is the average of the documents assigned to  $k$ .  
Optimization algorithm:

- Initialize centers
- Do until converged:
  - For each document, find closest center  $\rightsquigarrow \tau_i^t$
  - For each center, take average of assigned documents  $\rightsquigarrow \boldsymbol{\theta}_k^t$
  - Update change  $f(\mathbf{X}, \mathbf{T}^t, \boldsymbol{\Theta}^t) - f(\mathbf{X}, \mathbf{T}^{t-1}, \boldsymbol{\Theta}^{t-1})$


# Visual Example



# Visual Example




# Visual Example







# Visual Example




# Visual Example




# Visual Example




# Visual Example




# Visual Example




# Visual Example



# Visual Example




# Visual Example






# Visual Example



# Visual Example



# An Example: Jeff Flake

To the R Code!

# Interpreting Cluster Components

## Unsupervised methods

# Interpreting Cluster Components

Unsupervised methods  $\rightsquigarrow$  low startup costs, high post-model costs

# Interpreting Cluster Components

Unsupervised methods  $\rightsquigarrow$  low startup costs, high post-model costs

- Apply clustering methods, we have groups of documents

# Interpreting Cluster Components

Unsupervised methods  $\rightsquigarrow$  low startup costs, high post-model costs

- Apply clustering methods, we have groups of documents
- How to interpret the groups?

# Interpreting Cluster Components

Unsupervised methods  $\rightsquigarrow$  low startup costs, high post-model costs

- Apply clustering methods, we have groups of documents
- How to interpret the groups?
- Two (broad) methods:



# Interpreting Cluster Components

Unsupervised methods  $\rightsquigarrow$  low startup costs, high post-model costs

- Apply clustering methods, we have groups of documents
- How to interpret the groups?
- Two (broad) methods:
  - Manual identification (Quinn et al 2010)

# Interpreting Cluster Components

Unsupervised methods  $\rightsquigarrow$  low startup costs, high post-model costs

- Apply clustering methods, we have groups of documents
- How to interpret the groups?
- Two (broad) methods:
  - Manual identification (Quinn et al 2010)
    - Sample set of documents from same cluster

# Interpreting Cluster Components

Unsupervised methods  $\rightsquigarrow$  low startup costs, high post-model costs

- Apply clustering methods, we have groups of documents
- How to interpret the groups?
- Two (broad) methods:
  - Manual identification (Quinn et al 2010)
    - Sample set of documents from same cluster
    - Read documents

# Interpreting Cluster Components

Unsupervised methods  $\rightsquigarrow$  low startup costs, high post-model costs

- Apply clustering methods, we have groups of documents
- How to interpret the groups?
- Two (broad) methods:
  - Manual identification (Quinn et al 2010)
    - Sample set of documents from same cluster
    - Read documents
    - Assign cluster label

# Interpreting Cluster Components

Unsupervised methods  $\rightsquigarrow$  low startup costs, high post-model costs

- Apply clustering methods, we have groups of documents
- How to interpret the groups?
- Two (broad) methods:
  - Manual identification (Quinn et al 2010)
    - Sample set of documents from same cluster
    - Read documents
    - Assign cluster label
  - Automatic identification

# Interpreting Cluster Components

Unsupervised methods  $\rightsquigarrow$  low startup costs, high post-model costs

- Apply clustering methods, we have groups of documents
- How to interpret the groups?
- Two (broad) methods:
  - Manual identification (Quinn et al 2010)
    - Sample set of documents from same cluster
    - Read documents
    - Assign cluster label
  - Automatic identification
    - Know label classes

# Interpreting Cluster Components

Unsupervised methods  $\rightsquigarrow$  low startup costs, high post-model costs

- Apply clustering methods, we have groups of documents
- How to interpret the groups?
- Two (broad) methods:
  - Manual identification (Quinn et al 2010)
    - Sample set of documents from same cluster
    - Read documents
    - Assign cluster label
  - Automatic identification
    - Know label classes
    - Use methods to identify separating words

# Interpreting Cluster Components

Unsupervised methods  $\rightsquigarrow$  low startup costs, high post-model costs

- Apply clustering methods, we have groups of documents
- How to interpret the groups?
- Two (broad) methods:
  - Manual identification (Quinn et al 2010)
    - Sample set of documents from same cluster
    - Read documents
    - Assign cluster label
  - Automatic identification
    - Know label classes
    - Use methods to identify separating words
    - Use these to help infer differences across clusters



# Interpreting Cluster Components

Unsupervised methods  $\rightsquigarrow$  low startup costs, high post-model costs

- Apply clustering methods, we have groups of documents
- How to interpret the groups?
- Two (broad) methods:
  - Manual identification (Quinn et al 2010)
    - Sample set of documents from same cluster
    - Read documents
    - Assign cluster label
  - Automatic identification
    - Know label classes
    - Use methods to identify separating words
    - Use these to help infer differences across clusters
- Transparency

# Interpreting Cluster Components

Unsupervised methods  $\rightsquigarrow$  low startup costs, high post-model costs

- Apply clustering methods, we have groups of documents
- How to interpret the groups?
- Two (broad) methods:
  - Manual identification (Quinn et al 2010)
    - Sample set of documents from same cluster
    - Read documents
    - Assign cluster label
  - Automatic identification
    - Know label classes
    - Use methods to identify separating words
    - Use these to help infer differences across clusters
- **Transparency**
  - Debate what clusters are

# Interpreting Cluster Components

Unsupervised methods  $\rightsquigarrow$  low startup costs, high post-model costs

- Apply clustering methods, we have groups of documents
- How to interpret the groups?
- Two (broad) methods:
  - Manual identification (Quinn et al 2010)
    - Sample set of documents from same cluster
    - Read documents
    - Assign cluster label
  - Automatic identification
    - Know label classes
    - Use methods to identify separating words
    - Use these to help infer differences across clusters
- Transparency
  - Debate what clusters are
  - Debate what they mean

# Interpreting Cluster Components

Unsupervised methods  $\rightsquigarrow$  low startup costs, high post-model costs

- Apply clustering methods, we have groups of documents
- How to interpret the groups?
- Two (broad) methods:
  - Manual identification (Quinn et al 2010)
    - Sample set of documents from same cluster
    - Read documents
    - Assign cluster label
  - Automatic identification
    - Know label classes
    - Use methods to identify separating words
    - Use these to help infer differences across clusters
- **Transparency**
  - Debate what clusters are
  - Debate what they mean
  - Provide documents + organizations

# Interpreting Cluster Components

Unsupervised methods  $\rightsquigarrow$  low startup costs, high post-model costs

- Apply clustering methods, we have groups of documents
- How to interpret the groups?
- Two (broad) methods:
  - Manual identification (Quinn et al 2010)
    - Sample set of documents from same cluster
    - Read documents
    - Assign cluster label
  - Automatic identification
    - Know label classes
    - Use methods to identify separating words
    - Use these to help infer differences across clusters
- **Transparency**
  - Debate what clusters are
  - Debate what they mean
  - Provide documents + organizations

back to the R code!

# How Do We Choose $K$ ?

# How Do We Choose $K$ ?

- Previous Analysis Assumed We Know Number of Clusters

# How Do We Choose $K$ ?

- Previous Analysis Assumed We Know Number of Clusters
- How Do We Choose Cluster Number?



# How Do We Choose $K$ ?

- Previous Analysis Assumed We Know Number of Clusters
- How Do We Choose Cluster Number?
- Cannot Compare  $f$  across clusters

# How Do We Choose $K$ ?

- Previous Analysis Assumed We Know Number of Clusters
- How Do We Choose Cluster Number?
- Cannot Compare  $f$  across clusters
  - Sum squared errors decreases as  $K$  increases

# How Do We Choose $K$ ?

- Previous Analysis Assumed We Know Number of Clusters
- How Do We Choose Cluster Number?
- Cannot Compare  $f$  across clusters
  - Sum squared errors decreases as  $K$  increases
  - Trivial answer: each document in own cluster (useless)

# How Do We Choose $K$ ?

- Previous Analysis Assumed We Know Number of Clusters
- How Do We Choose Cluster Number?
- Cannot Compare  $f$  across clusters
  - Sum squared errors decreases as  $K$  increases
  - Trivial answer: each document in own cluster (useless)
  - Modeling problem: Fit often increases with features

# How Do We Choose $K$ ?

- Previous Analysis Assumed We Know Number of Clusters
- How Do We Choose Cluster Number?
- Cannot Compare  $f$  across clusters
  - Sum squared errors decreases as  $K$  increases
  - Trivial answer: each document in own cluster (useless)
  - Modeling problem: Fit often increases with features
- How do we choose number of clusters?

# How Do We Choose $K$ ?

- Previous Analysis Assumed We Know Number of Clusters
- How Do We Choose Cluster Number?
- Cannot Compare  $f$  across clusters
  - Sum squared errors decreases as  $K$  increases
  - Trivial answer: each document in own cluster (useless)
  - Modeling problem: Fit often increases with features
- How do we choose number of clusters?

Think!

# How Do We Choose $K$ ?

- Previous Analysis Assumed We Know Number of Clusters
- How Do We Choose Cluster Number?
- Cannot Compare  $f$  across clusters
  - Sum squared errors decreases as  $K$  increases
  - Trivial answer: each document in own cluster (useless)
  - Modeling problem: Fit often increases with features
- How do we choose number of clusters?

Think!

- No one statistic captures how you want to use your data

# How Do We Choose $K$ ?

- Previous Analysis Assumed We Know Number of Clusters
- How Do We Choose Cluster Number?
- Cannot Compare  $f$  across clusters
  - Sum squared errors decreases as  $K$  increases
  - Trivial answer: each document in own cluster (useless)
  - Modeling problem: Fit often increases with features
- How do we choose number of clusters?

## Think!

- No one statistic captures how you want to use your data
- But, can help guide your selection



# How Do We Choose $K$ ?

- Previous Analysis Assumed We Know Number of Clusters
- How Do We Choose Cluster Number?
- Cannot Compare  $f$  across clusters
  - Sum squared errors decreases as  $K$  increases
  - Trivial answer: each document in own cluster (useless)
  - Modeling problem: Fit often increases with features
- How do we choose number of clusters?

## Think!

- No one statistic captures how you want to use your data
- But, can help guide your selection
- Combination statistic + manual search

# How Do We Choose $K$ ?

- Previous Analysis Assumed We Know Number of Clusters
- How Do We Choose Cluster Number?
- Cannot Compare  $f$  across clusters
  - Sum squared errors decreases as  $K$  increases
  - Trivial answer: each document in own cluster (useless)
  - Modeling problem: Fit often increases with features
- How do we choose number of clusters?

## Think!

- No one statistic captures how you want to use your data
- But, can help guide your selection
- Combination statistic + manual search  $\leadsto$  discuss statistical methods/experimental methods on Thursday
- Humans should be the final judge

# How Do We Choose $K$ ?

- Previous Analysis Assumed We Know Number of Clusters
- How Do We Choose Cluster Number?
- Cannot Compare  $f$  across clusters
  - Sum squared errors decreases as  $K$  increases
  - Trivial answer: each document in own cluster (useless)
  - Modeling problem: Fit often increases with features
- How do we choose number of clusters?

## Think!

- No one statistic captures how you want to use your data
- But, can help guide your selection
- Combination statistic + manual search  $\leadsto$  discuss statistical methods/experimental methods on Thursday
- Humans should be the final judge
  - Compare insights across clusterings

# Mixture of Unigram Models (Mixture of Multinomials)

Mixture models  $\rightsquigarrow$  wide range of applications

# Mixture of Unigram Models (Mixture of Multinomials)

Mixture models  $\rightsquigarrow$  wide range of applications

Single distribution data generating process:

# Mixture of Unigram Models (Mixture of Multinomials)

Mixture models  $\rightsquigarrow$  wide range of applications

Single distribution data generating process:

$$\mathbf{x}_i \sim \text{Distribution}(\text{parameters})$$

# Mixture of Unigram Models (Mixture of Multinomials)

Mixture models  $\rightsquigarrow$  wide range of applications

Single distribution data generating process:

$$\mathbf{x}_i \sim \text{Distribution}(\text{parameters})$$

Mixture of distribution data generating process:

# Mixture of Unigram Models (Mixture of Multinomials)

Mixture models  $\rightsquigarrow$  wide range of applications

Single distribution data generating process:

$$\mathbf{x}_i \sim \text{Distribution}(\text{parameters})$$

Mixture of distribution data generating process:

$$\tau_i | \boldsymbol{\pi} \sim \text{Multinomial}(1, \boldsymbol{\pi})$$



# Mixture of Unigram Models (Mixture of Multinomials)

Mixture models  $\rightsquigarrow$  wide range of applications

Single distribution data generating process:

$$\mathbf{x}_i \sim \text{Distribution}(\text{parameters})$$

Mixture of distribution data generating process:

$$\tau_i | \boldsymbol{\pi} \sim \text{Multinomial}(1, \boldsymbol{\pi})$$

$$\mathbf{x}_i | \tau_{ik} = 1 \sim \text{Distribution}(\text{parameters}_k)$$

# Mixture of Unigram Models (Mixture of Multinomials)

Mixture models  $\rightsquigarrow$  wide range of applications

Single distribution data generating process:

$$\mathbf{x}_i \sim \text{Distribution}(\text{parameters})$$

Mixture of distribution data generating process:

$$\tau_i | \boldsymbol{\pi} \sim \text{Multinomial}(1, \boldsymbol{\pi})$$

$$\mathbf{x}_i | \tau_{ik} = 1 \sim \text{Distribution}(\text{parameters}_k)$$

In words:

# Mixture of Unigram Models (Mixture of Multinomials)

Mixture models  $\rightsquigarrow$  wide range of applications

Single distribution data generating process:

$$\mathbf{x}_i \sim \text{Distribution}(\text{parameters})$$

Mixture of distribution data generating process:

$$\tau_i | \boldsymbol{\pi} \sim \text{Multinomial}(1, \boldsymbol{\pi})$$

$$\mathbf{x}_i | \tau_{ik} = 1 \sim \text{Distribution}(\text{parameters}_k)$$

In words:

- Draw a cluster label

# Mixture of Unigram Models (Mixture of Multinomials)

Mixture models  $\rightsquigarrow$  wide range of applications

Single distribution data generating process:

$$\mathbf{x}_i \sim \text{Distribution}(\text{parameters})$$

Mixture of distribution data generating process:

$$\tau_i | \boldsymbol{\pi} \sim \text{Multinomial}(1, \boldsymbol{\pi})$$

$$\mathbf{x}_i | \tau_{ik} = 1 \sim \text{Distribution}(\text{parameters}_k)$$

In words:

- Draw a cluster label
- Given distribution, draw realization

# Mixture of Unigram Models (Mixture of Multinomials)

A mixture of unigram-language models

$$\boldsymbol{\pi} \sim \text{Dirichlet}(\mathbf{1})$$

$$\boldsymbol{\theta} \sim \text{Dirichlet}(\mathbf{1})$$

$$\tau_i | \boldsymbol{\pi} \sim \text{Multinomial}(1, \boldsymbol{\pi})$$

$$\mathbf{x}_i | \tau_{ik} = 1, \boldsymbol{\theta}_k \sim \text{Multinomial}(N_i, \boldsymbol{\theta}_k)$$

# Mixture of Unigram Models (Mixture of Multinomials)

This implies the following posterior distribution:

$$p(\mathbf{T}, \mathbf{\Theta}, \boldsymbol{\pi} | \mathbf{X})$$

# Mixture of Unigram Models (Mixture of Multinomials)

This implies the following posterior distribution:

$$p(\mathbf{T}, \mathbf{\Theta}, \pi | \mathbf{X}) \propto \overbrace{p(\pi)p(\boldsymbol{\theta})}^1 \underbrace{p(\mathbf{X}, \mathbf{T} | \pi, \boldsymbol{\theta})}_{\text{Complete data likelihood}}$$

# Mixture of Unigram Models (Mixture of Multinomials)

This implies the following posterior distribution:

$$\begin{aligned} p(\mathbf{T}, \boldsymbol{\Theta}, \boldsymbol{\pi} | \mathbf{X}) &\propto \overbrace{p(\boldsymbol{\pi})p(\boldsymbol{\theta})}^1 \underbrace{p(\mathbf{X}, \mathbf{T} | \boldsymbol{\pi}, \boldsymbol{\theta})}_{\text{Complete data likelihood}} \\ &\propto \underbrace{\prod_{i=1}^N p(\boldsymbol{\tau}_i, \mathbf{x}_i | \boldsymbol{\theta}, \boldsymbol{\pi})}_{\text{Complete data likelihood}} \end{aligned}$$



# Mixture of Unigram Models (Mixture of Multinomials)

This implies the following posterior distribution:

$$\begin{aligned} p(\mathbf{T}, \boldsymbol{\Theta}, \boldsymbol{\pi} | \mathbf{X}) &\propto \overbrace{p(\boldsymbol{\pi})p(\boldsymbol{\theta})}^1 \underbrace{p(\mathbf{X}, \mathbf{T} | \boldsymbol{\pi}, \boldsymbol{\theta})}_{\text{Complete data likelihood}} \\ &\propto \underbrace{\prod_{i=1}^N p(\boldsymbol{\tau}_i, \mathbf{x}_i | \boldsymbol{\theta}, \boldsymbol{\pi})}_{\text{Complete data likelihood}} \\ &\propto \prod_{i=1}^N p(\boldsymbol{\tau}_i | \boldsymbol{\pi}) p(\mathbf{x}_i | \boldsymbol{\theta}, \boldsymbol{\tau}_i) \end{aligned}$$

# Mixture of Unigram Models (Mixture of Multinomials)

This implies the following posterior distribution:

$$p(\mathbf{T}, \mathbf{\Theta}, \pi | \mathbf{X}) \propto \overbrace{p(\pi)p(\boldsymbol{\theta})}^1 \underbrace{p(\mathbf{X}, \mathbf{T} | \pi, \boldsymbol{\theta})}_{\text{Complete data likelihood}}$$

$$\propto \underbrace{\prod_{i=1}^N p(\tau_i, \mathbf{x}_i | \boldsymbol{\theta}, \pi)}_{\text{Complete data likelihood}}$$

$$\propto \prod_{i=1}^N p(\tau_i | \pi) p(\mathbf{x}_i | \boldsymbol{\theta}, \tau_i)$$

$$\propto \prod_{i=1}^N \prod_{k=1}^K \left[ \pi_k \prod_{j=1}^J \theta_{jk}^{x_{ik}} \right]^{\tau_{ik}}$$

# Mixture of Unigram Models (Mixture of Multinomials)

Obtain MAP estimates  $\rightsquigarrow$  EM Algorithm

# Mixture of Unigram Models (Mixture of Multinomials)

Obtain MAP estimates  $\rightsquigarrow$  EM Algorithm

1) Initialize parameters  $\Theta^t, \pi^t$

# Mixture of Unigram Models (Mixture of Multinomials)

Obtain MAP estimates  $\rightsquigarrow$  EM Algorithm

- 1) Initialize parameters  $\Theta^t, \pi^t$
- 2) **Expectation step**: compute  $p(\tau_i | \Theta^t, \pi^t, \mathbf{X}) \rightsquigarrow \mathbf{r}_i^t$

# Mixture of Unigram Models (Mixture of Multinomials)

Obtain MAP estimates  $\rightsquigarrow$  EM Algorithm

- 1) Initialize parameters  $\Theta^t, \pi^t$
- 2) **Expectation step**: compute  $p(\tau_i | \Theta^t, \pi^t, \mathbf{X}) \rightsquigarrow \mathbf{r}_i^t$
- 3) **Maximization step**: maximize with respect to  $\Theta$  and  $\pi$ :

# Mixture of Unigram Models (Mixture of Multinomials)

Obtain MAP estimates  $\rightsquigarrow$  EM Algorithm

- 1) Initialize parameters  $\Theta^t, \pi^t$
- 2) **Expectation step**: compute  $p(\tau_i | \Theta^t, \pi^t, \mathbf{X}) \rightsquigarrow \mathbf{r}_i^t$
- 3) **Maximization step**: maximize with respect to  $\Theta$  and  $\pi$ :

$$E[\log \text{Complete data} | \theta_k, \pi] = \sum_{i=1}^N \sum_{k=1}^K \log p(\mathbf{x}_i, \tau_{ik}^t | \theta_k, \pi_k) p(\tau_{ik}^t | \Theta, \pi_k)$$

# Mixture of Unigram Models (Mixture of Multinomials)

Obtain MAP estimates  $\rightsquigarrow$  EM Algorithm

- 1) Initialize parameters  $\Theta^t, \pi^t$
- 2) **Expectation step**: compute  $p(\tau_i | \Theta^t, \pi^t, \mathbf{X}) \rightsquigarrow \mathbf{r}_i^t$
- 3) **Maximization step**: maximize with respect to  $\Theta$  and  $\pi$ :

$$E[\log \text{Complete data} | \theta_k, \pi] = \sum_{i=1}^N \sum_{k=1}^K \log p(\mathbf{x}_i, \tau_{ik}^t | \theta_k, \pi_k) p(\tau_{ik}^t | \Theta, \pi_k)$$

Obtain  $\Theta^{t+1}, \pi^{t+1}$



# Mixture of Unigram Models (Mixture of Multinomials)

Obtain MAP estimates  $\rightsquigarrow$  EM Algorithm

- 1) Initialize parameters  $\Theta^t, \pi^t$
- 2) **Expectation step**: compute  $p(\tau_i | \Theta^t, \pi^t, \mathbf{X}) \rightsquigarrow \mathbf{r}_i^t$
- 3) **Maximization step**: maximize with respect to  $\Theta$  and  $\pi$ :

$$E[\log \text{Complete data} | \theta_k, \pi] = \sum_{i=1}^N \sum_{k=1}^K \log p(\mathbf{x}_i, \tau_{ik}^t | \theta_k, \pi_k) p(\tau_{ik}^t | \Theta, \pi_k)$$

Obtain  $\Theta^{t+1}, \pi^{t+1}$

- 4) Assess change

# Mixture of Unigram Models (Mixture of Multinomials)

Obtain MAP estimates  $\rightsquigarrow$  EM Algorithm

- 1) Initialize parameters  $\Theta^t, \pi^t$
- 2) **Expectation step**: compute  $p(\tau_i | \Theta^t, \pi^t, \mathbf{X}) \rightsquigarrow \mathbf{r}_i^t$
- 3) **Maximization step**: maximize with respect to  $\Theta$  and  $\pi$ :

$$E[\log \text{Complete data} | \theta_k, \pi] = \sum_{i=1}^N \sum_{k=1}^K \log p(\mathbf{x}_i, \tau_{ik}^t | \theta_k, \pi_k) p(\tau_{ik}^t | \Theta, \pi_k)$$

Obtain  $\Theta^{t+1}, \pi^{t+1}$

- 4) Assess change

$$\begin{aligned} \text{Change} &= E[\log \text{Complete data} | \Theta^{t+1}, \pi^{t+1}] \\ &\quad - E[\log \text{Complete data} | \Theta^t, \pi^t] \end{aligned}$$

# Mixture of Unigram Models (Mixture of Multinomials)

Obtain MAP estimates  $\rightsquigarrow$  EM Algorithm

- 1) Initialize parameters  $\Theta^t, \pi^t$
- 2) **Expectation step**: compute  $p(\tau_i | \Theta^t, \pi^t, \mathbf{X}) \rightsquigarrow \mathbf{r}_i^t$
- 3) **Maximization step**: maximize with respect to  $\Theta$  and  $\pi$ :

$$E[\log \text{Complete data} | \theta_k, \pi] = \sum_{i=1}^N \sum_{k=1}^K \log p(\mathbf{x}_i, \tau_{ik}^t | \theta_k, \pi_k) p(\tau_{ik}^t | \Theta, \pi_k)$$

Obtain  $\Theta^{t+1}, \pi^{t+1}$

- 4) Assess change

$$\begin{aligned} \text{Change} &= E[\log \text{Complete data} | \Theta^{t+1}, \pi^{t+1}] \\ &\quad - E[\log \text{Complete data} | \Theta^t, \pi^t] \end{aligned}$$

Our update steps will be strikingly similar to the K-Means algorithm

# Mixture of Unigram Models (Mixture of Multinomials)

Obtain MAP estimates  $\rightsquigarrow$  EM Algorithm

- 1) Initialize parameters  $\Theta^t, \pi^t$
- 2) **Expectation step**: compute  $p(\tau_i | \Theta^t, \pi^t, \mathbf{X}) \rightsquigarrow \mathbf{r}_i^t$
- 3) **Maximization step**: maximize with respect to  $\Theta$  and  $\pi$ :

$$E[\log \text{Complete data} | \theta_k, \pi] = \sum_{i=1}^N \sum_{k=1}^K \log p(\mathbf{x}_i, \tau_{ik}^t | \theta_k, \pi_k) p(\tau_{ik}^t | \Theta, \pi_k)$$

Obtain  $\Theta^{t+1}, \pi^{t+1}$

- 4) Assess change

$$\begin{aligned} \text{Change} &= E[\log \text{Complete data} | \Theta^{t+1}, \pi^{t+1}] \\ &\quad - E[\log \text{Complete data} | \Theta^t, \pi^t] \end{aligned}$$

Our update steps will be strikingly similar to the K-Means algorithm

# Mixture of Unigram Models (Mixture of Multinomials)

1) Initialize parameters  $\Theta^t$  and  $\pi^t$

# Mixture of Unigram Models (Mixture of Multinomials)

- 1) Initialize parameters  $\Theta^t$  and  $\pi^t$
- 2) E-Step

# Mixture of Unigram Models (Mixture of Multinomials)

- 1) Initialize parameters  $\Theta^t$  and  $\pi^t$
- 2) **E-Step**

$$p(\tau_{ik} | \Theta^t, \pi^t, \mathbf{X})$$

# Mixture of Unigram Models (Mixture of Multinomials)

- 1) Initialize parameters  $\Theta^t$  and  $\pi^t$
- 2) E-Step

$$p(\tau_{ik} | \Theta^t, \pi^t, \mathbf{X}) = \frac{\overbrace{p(\tau_{ik} | \pi^t) p(\mathbf{x}_i | \theta_k^t)}^{\text{general form}}}{\sum_{m=1}^K (p(\tau_{im} | \pi^t) p(\mathbf{x}_i | \theta_m^t))}$$



# Mixture of Unigram Models (Mixture of Multinomials)

- 1) Initialize parameters  $\Theta^t$  and  $\pi^t$
- 2) **E-Step**

$$\begin{aligned} p(\tau_{ik} | \Theta^t, \pi^t, \mathbf{X}) &= \frac{\overbrace{p(\tau_{ik} | \pi^t) p(\mathbf{x}_i | \theta_k^t)}^{\text{general form}}}{\sum_{m=1}^K (p(\tau_{im} | \pi^t) p(\mathbf{x}_i | \theta_m^t))} \\ &= \frac{\pi_k^t \prod_{j=1}^J (\theta_{jk}^t)^{x_{ij}}}{\sum_{m=1}^K (\pi_m^t \prod_{j=1}^J (\theta_{jm}^t)^{x_{ij}})} \end{aligned}$$

# Mixture of Unigram Models (Mixture of Multinomials)

- 1) Initialize parameters  $\Theta^t$  and  $\pi^t$
- 2) **E-Step**

$$\begin{aligned} p(\tau_{ik} | \Theta^t, \pi^t, \mathbf{X}) &= \overbrace{\frac{p(\tau_{ik} | \pi^t) p(\mathbf{x}_i | \theta_k^t)}{\sum_{m=1}^K (p(\tau_{im} | \pi^t) p(\mathbf{x}_i | \theta_m^t))}}^{\text{general form}} \\ &= \frac{\pi_k^t \prod_{j=1}^J (\theta_{jk}^t)^{x_{ij}}}{\sum_{m=1}^K (\pi_m^t \prod_{j=1}^J (\theta_{jm}^t)^{x_{ij}})} \end{aligned}$$

Define:

# Mixture of Unigram Models (Mixture of Multinomials)

- 1) Initialize parameters  $\Theta^t$  and  $\pi^t$
- 2) **E-Step**

$$\begin{aligned} p(\tau_{ik} | \Theta^t, \pi^t, \mathbf{X}) &= \frac{\overbrace{p(\tau_{ik} | \pi^t) p(\mathbf{x}_i | \theta_k^t)}^{\text{general form}}}{\sum_{m=1}^K (p(\tau_{im} | \pi^t) p(\mathbf{x}_i | \theta_m^t))} \\ &= \frac{\pi_k^t \prod_{j=1}^J (\theta_{jk}^t)^{x_{ij}}}{\sum_{m=1}^K (\pi_m^t \prod_{j=1}^J (\theta_{jm}^t)^{x_{ij}})} \end{aligned}$$

Define:

$$r_{ik}^t \equiv \frac{\pi_k^t \prod_{j=1}^J (\theta_{jk}^t)^{x_{ij}}}{\sum_{m=1}^K (\pi_m^t \prod_{j=1}^J (\theta_{jm}^t)^{x_{ij}})}$$

# Mixture of Unigram Models (Mixture of Multinomials)

- 1) Initialize parameters  $\Theta^t$  and  $\pi^t$
- 2) **E-Step**

$$\begin{aligned} p(\tau_{ik} | \Theta^t, \pi^t, \mathbf{X}) &= \overbrace{\frac{p(\tau_{ik} | \pi^t) p(\mathbf{x}_i | \theta_k^t)}{\sum_{m=1}^K (p(\tau_{im} | \pi^t) p(\mathbf{x}_i | \theta_m^t))}}^{\text{general form}} \\ &= \frac{\pi_k^t \prod_{j=1}^J (\theta_{jk}^t)^{x_{ij}}}{\sum_{m=1}^K (\pi_m^t \prod_{j=1}^J (\theta_{jm}^t)^{x_{ij}})} \end{aligned}$$

Define: Avoid underflow

$$r_{ik}^t = \left[ 1 + \sum_{k' \neq k} \frac{\pi_{k'} \prod_{j=1}^J (\theta_{jk'}^t)^{x_{ij}}}{\pi_k \prod_{j=1}^J (\theta_{jk}^t)^{x_{ij}}} \right]^{-1}$$

# Mixture of Unigram Models (Mixture of Multinomials)

3) **M-Step:**

# Mixture of Unigram Models (Mixture of Multinomials)

## 3) M-Step:

$$E[\log \text{Complete data} | \boldsymbol{\theta}, \boldsymbol{\pi}] = \sum_{i=1}^N \sum_{k=1}^K E[\tau_{ik}] \log \left( \pi_k \prod_{j=1}^J \theta_{jk}^{x_{ik}} \right)$$

# Mixture of Unigram Models (Mixture of Multinomials)

## 3) M-Step:

$$\begin{aligned} E[\log \text{Complete data} | \boldsymbol{\theta}, \boldsymbol{\pi}] &= \sum_{i=1}^N \sum_{k=1}^K E[\tau_{ik}] \log \left( \pi_k \prod_{j=1}^J \theta_{jk}^{x_{ik}} \right) \\ &= \sum_{i=1}^N \sum_{k=1}^K r_{ik}^t \log \pi_k + \sum_{i=1}^N \sum_{k=1}^K \sum_{j=1}^J r_{ik}^t x_{ij} \log \theta_{jk} \end{aligned}$$

# Mixture of Unigram Models (Mixture of Multinomials)

## 3) M-Step:

$$\begin{aligned} E[\log \text{Complete data} | \boldsymbol{\theta}, \boldsymbol{\pi}] &= \sum_{i=1}^N \sum_{k=1}^K E[\tau_{ik}] \log \left( \pi_k \prod_{j=1}^J \theta_{jk}^{x_{ij}} \right) \\ &= \sum_{i=1}^N \sum_{k=1}^K r_{ik}^t \log \pi_k + \sum_{i=1}^N \sum_{k=1}^K \sum_{j=1}^J r_{ik}^t x_{ij} \log \theta_{jk} \end{aligned}$$

Introducing constraints, differentiating, setting equal to zero and algebra yields:



# Mixture of Unigram Models (Mixture of Multinomials)

## 3) M-Step:

$$\begin{aligned} E[\log \text{Complete data} | \boldsymbol{\theta}, \boldsymbol{\pi}] &= \sum_{i=1}^N \sum_{k=1}^K E[\tau_{ik}] \log \left( \pi_k \prod_{j=1}^J \theta_{jk}^{x_{ik}} \right) \\ &= \sum_{i=1}^N \sum_{k=1}^K r_{ik}^t \log \pi_k + \sum_{i=1}^N \sum_{k=1}^K \sum_{j=1}^J r_{ik}^t x_{ij} \log \theta_{jk} \end{aligned}$$

Introducing constraints, differentiating, setting equal to zero and algebra yields:

$$\pi_k^{t+1} = \frac{\sum_{i=1}^N r_{ik}^t}{N}$$

# Mixture of Unigram Models (Mixture of Multinomials)

## 3) M-Step:

$$\begin{aligned} E[\log \text{Complete data} | \theta, \pi] &= \sum_{i=1}^N \sum_{k=1}^K E[\tau_{ik}] \log \left( \pi_k \prod_{j=1}^J \theta_{jk}^{x_{ij}} \right) \\ &= \sum_{i=1}^N \sum_{k=1}^K r_{ik}^t \log \pi_k + \sum_{i=1}^N \sum_{k=1}^K \sum_{j=1}^J r_{ik}^t x_{ij} \log \theta_{jk} \end{aligned}$$

Introducing constraints, differentiating, setting equal to zero and algebra yields:

$$\begin{aligned} \pi_k^{t+1} &= \frac{\sum_{i=1}^N r_{ik}^t}{N} \\ \theta_{jk}^{t+1} &= \frac{\sum_{i=1}^N r_{ik}^t x_{ij}}{\sum_{m=1}^J \sum_{i=1}^N r_{ik}^t x_{im}} \end{aligned}$$

# Mixture of Unigram Models (Mixture of Multinomials)

## 3) M-Step:

$$\begin{aligned} E[\log \text{Complete data} | \boldsymbol{\theta}, \boldsymbol{\pi}] &= \sum_{i=1}^N \sum_{k=1}^K E[\tau_{ik}] \log \left( \pi_k \prod_{j=1}^J \theta_{jk}^{x_{ij}} \right) \\ &= \sum_{i=1}^N \sum_{k=1}^K r_{ik}^t \log \pi_k + \sum_{i=1}^N \sum_{k=1}^K \sum_{j=1}^J r_{ik}^t x_{ij} \log \theta_{jk} \end{aligned}$$

Introducing constraints, differentiating, setting equal to zero and algebra yields:

$$\begin{aligned} \pi_k^{t+1} &= \frac{\sum_{i=1}^N r_{ik}^t}{N} \\ \theta_{jk}^{t+1} &= \frac{\sum_{i=1}^N r_{ik}^t x_{ij}}{\sum_{m=1}^J \sum_{i=1}^N r_{ik}^t x_{im}} \propto \sum_{i=1}^N r_{ik}^t \mathbf{x}_i \end{aligned}$$

# Example: Jeff Flake Again!

To the R Code!

# Fully Automated Clustering

# Fully Automated Clustering

- Notion of similarity and “good” partition  $\rightsquigarrow$  clustering

# Fully Automated Clustering

- Notion of similarity and “good” partition  $\rightsquigarrow$  clustering
- Many clustering methods:

# Fully Automated Clustering

- Notion of similarity and “good” partition  $\rightsquigarrow$  clustering
- Many clustering methods:
  - Spectral clustering



# Fully Automated Clustering

- Notion of similarity and “good” partition  $\rightsquigarrow$  clustering
- Many clustering methods:
  - Spectral clustering
  - Affinity Propagation

# Fully Automated Clustering

- Notion of similarity and “good” partition  $\rightsquigarrow$  clustering
- Many clustering methods:
  - Spectral clustering
  - Affinity Propagation
  - Non-parametric statistical models

# Fully Automated Clustering

- Notion of similarity and “good” partition  $\rightsquigarrow$  clustering
- Many clustering methods:
  - Spectral clustering
  - Affinity Propagation
  - Non-parametric statistical models
  - Hierarchical clustering

# Fully Automated Clustering

- Notion of similarity and “good” partition  $\rightsquigarrow$  clustering
- Many clustering methods:
  - Spectral clustering
  - Affinity Propagation
  - Non-parametric statistical models
  - Hierarchical clustering
  - Biclustering

# Fully Automated Clustering

- Notion of similarity and “good” partition  $\rightsquigarrow$  clustering
- Many clustering methods:
  - Spectral clustering
  - Affinity Propagation
  - Non-parametric statistical models
  - Hierarchical clustering
  - Biclustering
  - ...

# Fully Automated Clustering

- Notion of similarity and “good” partition  $\rightsquigarrow$  clustering
- Many clustering methods:
  - Spectral clustering
  - Affinity Propagation
  - Non-parametric statistical models
  - Hierarchical clustering
  - Biclustering
  - ...
- How do we know we have something useful?

# Fully Automated Clustering

- Notion of similarity and “good” partition  $\rightsquigarrow$  clustering
- Many clustering methods:
  - Spectral clustering
  - Affinity Propagation
  - Non-parametric statistical models
  - Hierarchical clustering
  - Biclustering
  - ...
- How do we know we have something useful?
  - Validation: read the documents

# Fully Automated Clustering

- Notion of similarity and “good” partition  $\rightsquigarrow$  clustering
- Many clustering methods:
  - Spectral clustering
  - Affinity Propagation
  - Non-parametric statistical models
  - Hierarchical clustering
  - Biclustering
  - ...
- How do we know we have something useful?
  - Validation: read the documents
  - Validation: experiments to assess cluster quality  $\rightsquigarrow$  Thursday



# Fully Automated Clustering

- Notion of similarity and “good” partition  $\rightsquigarrow$  clustering
- Many clustering methods:
  - Spectral clustering
  - Affinity Propagation
  - Non-parametric statistical models
  - Hierarchical clustering
  - Biclustering
  - ...
- How do we know we have something useful?
  - Validation: read the documents
  - Validation: experiments to assess cluster quality  $\rightsquigarrow$  Thursday
  - Validation: model based fit statistics

# Fully Automated Clustering

- Notion of similarity and “good” partition  $\rightsquigarrow$  clustering
- Many clustering methods:
  - Spectral clustering
  - Affinity Propagation
  - Non-parametric statistical models
  - Hierarchical clustering
  - Biclustering
  - ...
- How do we know we have something useful?
  - Validation: read the documents
  - Validation: experiments to assess cluster quality  $\rightsquigarrow$  Thursday
  - Validation: model based fit statistics
- How do we know we have the “right” model?

# Fully Automated Clustering

- Notion of similarity and “good” partition  $\rightsquigarrow$  clustering
- Many clustering methods:
  - Spectral clustering
  - Affinity Propagation
  - Non-parametric statistical models
  - Hierarchical clustering
  - Biclustering
  - ...
- How do we know we have something useful?
  - Validation: read the documents
  - Validation: experiments to assess cluster quality  $\rightsquigarrow$  Thursday
  - Validation: model based fit statistics
- How do we know we have the “right” model?

YOU DON'T!

# Fully Automated Clustering

- Notion of similarity and “good” partition  $\rightsquigarrow$  clustering
- Many clustering methods:
  - Spectral clustering
  - Affinity Propagation
  - Non-parametric statistical models
  - Hierarchical clustering
  - Biclustering
  - ...
- How do we know we have something useful?
  - Validation: read the documents
  - Validation: experiments to assess cluster quality  $\rightsquigarrow$  Thursday
  - Validation: model based fit statistics
- How do we know we have the “right” model?

**YOU DON'T!**  $\rightsquigarrow$  And never will

# Fully Automated Clustering

- Notion of similarity and “good” partition  $\rightsquigarrow$  clustering
- Many clustering methods:
  - Spectral clustering
  - Affinity Propagation
  - Non-parametric statistical models
  - Hierarchical clustering
  - Biclustering
  - ...
- How do we know we have something useful?
  - Validation: read the documents
  - Validation: experiments to assess cluster quality  $\rightsquigarrow$  Thursday
  - Validation: model based fit statistics
- How do we know we have the “right” model?

**YOU DON'T!**  $\rightsquigarrow$  And never will  $\rightsquigarrow$  but  
still useful(!!!!)

# Fully Automated Clustering

- Notion of similarity and “good” partition  $\rightsquigarrow$  clustering
- Many clustering methods:
  - Spectral clustering
  - Affinity Propagation
  - Non-parametric statistical models
  - Hierarchical clustering
  - Biclustering
  - ...
- How do we know we have something useful?
  - Validation: read the documents
  - Validation: experiments to assess cluster quality  $\rightsquigarrow$  Thursday
  - Validation: model based fit statistics
- How do we know we have the “right” model?

**YOU DON'T!**  $\rightsquigarrow$  And never will  $\rightsquigarrow$  but  
still useful(!!!!)

# Appendix: Why EM Works

Goal:

$$\operatorname{argmax}_{\theta} p(\mathbf{X}|\theta) = \sum_{\mathbf{T}} p(\mathbf{X}, \mathbf{T}|\theta)$$

Define:

$$\begin{aligned}\mathcal{L}(q, \theta) &= \sum_{\mathbf{T}} q(\mathbf{T}) \log \left[ \frac{p(\mathbf{X}, \mathbf{T}|\theta)}{q(\mathbf{T})} \right] \\ K(q||p) &= - \sum_{\mathbf{T}} q(\mathbf{T}) \log \left[ \frac{p(\mathbf{T}|\mathbf{X}, \theta)}{q(\mathbf{T})} \right]\end{aligned}$$

Then:

$$\log p(\mathbf{X}|\theta) = \mathcal{L}(q, \theta) + K(q||p)$$

## Appendix: Why EM Works

$$\begin{aligned}\mathcal{L}(q, \theta) + K(q||p) &= \sum_{\mathbf{T}} q(\mathbf{T}) \log \left[ \frac{p(\mathbf{X}, \mathbf{T}|\theta)}{q(\mathbf{T})} \right] - \sum_{\mathbf{T}} q(\mathbf{T}) \log \left[ \frac{p(\mathbf{T}|\mathbf{X}, \theta)}{q(\mathbf{T})} \right] \\ &= \sum_{\mathbf{T}} q(\mathbf{T}) \log(p(\mathbf{X}|\theta)) + \sum_{\mathbf{T}} q(\mathbf{T}) \log(p(\mathbf{T}|\mathbf{X}, \theta)) \\ &\quad - \sum_{\mathbf{T}} q(\mathbf{T}) \log q(\mathbf{T}) - \sum_{\mathbf{T}} q(\mathbf{T}) \log p(\mathbf{T}|\mathbf{X}, \theta) + \sum_{\mathbf{T}} q(\mathbf{T}) \log q(\mathbf{T}) \\ &= \log p(\mathbf{X}|\theta)\end{aligned}$$

Collect terms that cancel and recognize  $\sum_{\mathbf{T}} q(\mathbf{T}) = 1$  and we see equivalence



## Appendix: Why EM Works

$K(q||p) \geq 0$  with  $K(q||p) = 0$  only if  $q = p$ . So,  $\mathcal{L}(q, \theta)$  is a lower-bound on the log-likelihood.

E-step

$$\log p(\mathbf{X}|\theta) - K(q||p) = \mathcal{L}(q, \theta)$$

$\mathcal{L}(q, \theta) \rightsquigarrow$  biggest when  $K(q||p) = 0$ , so set

$$q(\mathbf{T}) = p(\mathbf{T}|\mathbf{X}, \theta)$$

M-step:

Given the new value of  $q$ , maximize parameters (expectation of the log complete data likelihood)

Change in log-likelihood will be greater  $\rightsquigarrow$  because new maximum induces non-zero KL-divergence. Changes in log-likelihood are greater than changes in lower bound.