

# A Tutorial on Physics-Informed Neural Networks (PINNs)

From 1D ODEs to 2D PDEs, and the Black–Scholes Equation

Simon Scheidegger

Department of Economics, University of Lausanne; Grantham Research Institute, LSE

Wednesday, August 26th, 2025

# Table of Contents

- 1 Introduction to PINNs
- 2 1D ODE: Zero Boundary Conditions
- 3 1D ODE: Non-Zero Boundary Conditions
- 4 2D PDE: NZB
- 5 The Black–Scholes PDE
- 6 Conclusion

# What Are Physics-Informed Neural Networks (PINNs)?

- PINNs incorporate physical laws (ODEs, PDEs, etc.) into the training of neural networks.
- Instead of (or in addition to) fitting standard labeled data, we penalize the network if it violates the governing equations.
- Use automatic differentiation (AD) to compute derivatives for the PDE or ODE residual.
- Boundary/initial conditions are enforced as part of the loss function.
- We effectively transform solving differential equations into a data-driven, neural-network–based learning problem.

# General PINN Strategy

- 1 Define a neural network  $u_\theta(x)$  (or  $u_\theta(x, y)$ , etc. for PDEs).
- 2 Use automatic differentiation to compute partial derivatives needed for the PDE/ODE.
- 3 Define the **residual** for the equation, e.g.  $F(u_\theta, x)$ .
- 4 Incorporate boundary or initial conditions by adding penalty terms to the loss.
- 5 Train (optimize) to minimize:

$$\mathcal{L}(\theta) = \underbrace{\text{MSE}(F(u_\theta, x))}_{\text{Equation Residual}} + \underbrace{\text{MSE}(u_\theta(\text{boundary}) - \text{BC})}_{\text{Boundary Loss}} + \dots$$

- 6 After training,  $u_\theta$  approximates the solution.

# 1D ODE with Zero Boundary Conditions

**Example ODE:**

$$\frac{d^2 y}{dx^2} = -1, \quad x \in (0, 1),$$

with **boundary conditions**

$$y(0) = 0, \quad y(1) = 0.$$

**Analytical solution:**

$$y(x) = -\frac{x^2}{2} + \frac{x}{2}.$$

**PINN Setup:**

- Define  $y_\theta(x)$  as a neural net.
- PDE residual:  $r(x) = y_\theta''(x) + 1$ .
- Enforce boundary conditions  $y_\theta(0) = 0$  and  $y_\theta(1) = 0$ .

## Code Reference:

- `day2/Scheidegger/code/01_ODE_ZBC.ipynb` demonstrates the full PyTorch implementation.
- It constructs a small network, sets up the ODE residual, and enforces boundary conditions within the loss.
- Training is run via Adam, and a final plot compares the learned solution to the analytical solution.

# 1D ODE with Non-Zero Boundary Conditions

**Example ODE** (same interior PDE, different BCs):

$$y''(x) = -1, \quad x \in (0, 1),$$

$$y(0) = 1, \quad y(1) = 2.$$

**Analytical solution:**

$$y(x) = -\frac{x^2}{2} + \frac{x}{2} + 1.$$

## Main Difference:

- The boundary conditions now are  $y(0) = 1$  and  $y(1) = 2$ .
- Only the boundary part of the loss changes.

## Code Reference:

- `day2/Scheidegger/code/02_ODE_NZB.ipynb` shows the minor modifications in the boundary loss terms.
- `day2/Scheidegger/code/02_ODE_NZB_HARD.ipynb` shows the modification of the Ansatz function.



# Hard vs. Soft Enforcement of Boundary/Initial Conditions

## Hard (exact) enforcement

- BCs satisfied *by construction* via ansatz:

$$u_{\theta}^{\text{hard}}(x) = g(x) + B(x)N_{\theta}(x), \quad B|_{\partial\Omega} = 0, \quad g|_{\partial\Omega} = u_{\text{BC}}.$$

Example (1D,  $y(0) = a$ ,  $y(1) = b$ ):

$$y_{\theta}^{\text{hard}}(x) = a(1-x) + bx + x(1-x)N_{\theta}(x).$$

- Pros: zero BC error; often better conditioning near  $\partial\Omega$ .
- Cons: need  $B, g$  design; awkward for complex/Neumann BCs; may limit expressivity.

## Soft (penalty) enforcement

- Add BC penalties to loss:

$$\mathcal{L} = \text{MSE}(F(u_{\theta})) + \lambda_{\text{BC}} \text{MSE}(u_{\theta}|_{\partial\Omega} - u_{\text{BC}}) + \lambda_{\text{IC}} \text{MSE}(\cdot).$$

- Pros: simple; works for varied BCs and irregular domains.
- Cons: only approximate; depends on  $\lambda$  and boundary sampling.

**Tips:** Oversample boundaries, normalize/weight losses, use augmented Lagrangian or  $\lambda$ -annealing for better BC accuracy.

# 2D Poisson: PDE, Boundary Conditions, Analytic Solution

**Domain:**  $\Omega = (0, 1)^2$ , with boundary  $\partial\Omega$ .

$$\begin{aligned} -\Delta u(x, y) &= f(x, y), & (x, y) \in \Omega, \\ u(x, y) &= g(x, y), & (x, y) \in \partial\Omega. \end{aligned}$$

**Analytic solution (used for  $f$  and  $g$ ):**

$$u^*(x, y) = x^2 + y + \sin(\pi x) \sin(\pi y), \quad f(x, y) = 2 - 2\pi^2 \sin(\pi x) \sin(\pi y).$$

**Dirichlet boundary values (non-zero on all sides):**

$$\begin{aligned} g(0, y) &= y, & g(1, y) &= 1 + y, \\ g(x, 0) &= x^2, & g(x, 1) &= x^2 + 1. \end{aligned}$$

- [day2/Scheidegger/code/02\\_PDE\\_NZB.ipynb](#).

# Black–Scholes Recap

$$\frac{\partial V}{\partial t} + \frac{1}{2}\sigma^2 S^2 \frac{\partial^2 V}{\partial S^2} + rS \frac{\partial V}{\partial S} - rV = 0.$$

$$\text{Terminal: } V(S, T) = \max(S - K, 0).$$

$$\text{Boundaries: } V(0, t) = 0, \quad V(S_{\max}, t) \approx S_{\max} - Ke^{-r(T-t)}.$$

## Key Steps in the PINN Setup:

- PDE residual:

$$V_t + 0.5 \sigma^2 S^2 V_{SS} + rS V_S - r V.$$

- Boundary conditions at  $S = 0$  and  $S = S_{\max}$ .
- Terminal condition at  $t = T$ .

## Code Reference:

- `day2/Scheidegger/code/03_Black_Scholes_PINNs.ipynb` contains the full implementation.

# Exercise: 1D ODE with Non-Zero Boundary Conditions

**Problem (domain  $x \in (0, 1)$ ):**

$$y''(x) + y(x) = x,$$

$$y(0) = 1, \quad y(1) = 0.3$$

This is a second-order, linear, non-homogeneous ODE with *non-zero* Dirichlet boundary conditions.

**Tasks:**

- 1 Implement a PINN with *soft* boundary enforcement (penalty): minimize  $\text{MSE}(y''_{\theta} + y_{\theta} - x)$  on  $(0, 1) + \lambda \text{MSE}(\{y_{\theta}(0) - 1, y_{\theta}(1) - 0.3\})$ .
- 2 Implement a PINN with *hard* boundary enforcement (lifting): use  $y_{\theta}(x) = A(x) + B(x)N_{\theta}(x)$  where  $A(0) = 1$ ,  $A(1) = 0.3$  and  $B(0) = B(1) = 0$ , train only on  $\text{MSE}(y''_{\theta} + y_{\theta} - x)$ .
- 3 Compare solutions vs.  $y^*(x)$  on a dense grid: report relative  $L^2$  errors, boundary errors, and show plots.

**Hints (optional):**

- A simple choice:  $A(x) = (1 - 0.3)(1 - x) + 0.3x = 1 - 0.7x$ ,  $B(x) = x(1 - x)$ .
- Solution: 04\_Solution.ipynb.

# Summary & Next Steps

- We introduced PINNs: enforcing PDE/ODE constraints by building them into the loss function.
- Showed ODEs, PDEs, boundary conditions, and terminal conditions.
- Demonstrated examples: 1D boundary value problems, 2D Black–Scholes.
- In practice, you can adapt these templates to more complex PDEs, domains, or multi-dimensional states.

# Some References

- M. Raissi, P. Perdikaris, and G. E. Karniadakis, Physics-Informed Neural Networks: A Deep Learning Framework (2019).
- J. Berg and K. Nystroem, A Unified Deep Artificial Neural Network Approach to PDEs in Complex Geometries (2017).
- For HJB PDE references in reinforcement-learning contexts, see: D. Jiang, F. Meng, Q. Sun, X. Xue, and Y. Zou. DeepRitz Method (2019).

Thank You!

Questions?