



**POLITECNICO
MILANO 1863**



Design Document

Professor

Nome Professore

University Course

Nome del corso

Author

Nome 1

Nome 2

Nome 3

Personal Code

Matricola 1

Matricola 2

Matricola 3

Settembre, 2025

Contents

1	Introduction	1
1.1	Purpose	1
1.2	Scope	1
1.3	Definitions, Acronyms, Abbreviations	1
1.4	References	2
1.4.1	Main References	2
1.4.2	Other References	2
2	Architectural Design	3
2.1	Overview	3
2.1.1	High-level components	3
2.1.2	High level components interaction	4
2.2	Component view	5
2.2.1	High level component view	5
2.2.2	Mobile Smartphone App component view	7
2.2.3	Smartphone Application External Libraries	8
2.2.4	Mobile Smartwatch App component view	8
2.3	Deployment view	8
2.4	Runtime view	10
2.4.1	Selected Use Cases	10
2.4.2	Add Diary Page use case sequence diagram	10
2.4.3	Watch–Phone Pairing Mechanism	11
2.4.4	Logout	11
2.4.5	Security Properties	12
2.5	Component interfaces	12
2.6	Selected architectural styles and patterns	12
2.6.1	Architectural Patterns: Model–View–Controller with Mediator and Observer	12
2.7	Other Design Decisions	13
2.7.1	Flutter as Application Framework	13
2.7.2	Firebase as Backend-as-a-Service	13
2.7.3	Phone Smartwatch Pairing	14
2.7.4	Network Connectivity Requirements and smartwatch Platform	14
3	Functional Requirements	15
3.0.1	Account and Profile Management	15
3.0.2	Home, Routes and Route Details	15
3.0.3	Diary Management	16
3.0.4	Search and Challenges	16
3.0.5	Profile and Social Features	17
3.0.6	Navigation and Sensor Information	17

1. Introduction

1.1 Purpose

Triplo is a cross-platform mobile application for smartphones and smartwatches, conceived as a digital logbook for trekking activities.

The application aims to enhance the experience of hiking in mountain environments by combining route information, environmental data, and recording of personal activity.

Users can explore predefined trekking routes and access useful information about the paths, including navigation support and contextual data such as weather conditions.

At the same time, the application allows hikers to document their experiences by creating logbook entries enriched with photos and personal diary notes.

The platform also enables users to discover and follow other hikers, and to browse selected entries from their trekking diaries, enhancing the sharing of experiences and inspiration for future hikes.

During a hike, users can optionally complete challenges, such as time-based goals designed to enrich the trekking experience.

The following sections describe the system architecture, the main functionalities of the application, and the technological choices adopted in its development.

1.2 Scope

Triplo supports users during trekking activities by providing guidance, contextual information, and tools to document their experiences in mountain environments.

The application focuses on the Madonna di Campiglio area and offers a set of predefined trekking routes with different levels of difficulty.

During a hike, users can access information related to the selected route, including navigation support and environmental conditions that may influence the trekking experience.

The application also encourages engagement through optional challenges that users may complete along the route. Each trekking activity can be recorded in a personal digital logbook, where users can document their experience by adding photos and diary notes. Users can also browse selected entries from the logbooks of other hikers they follow, allowing them to discover new routes and gain inspiration from shared experiences.

The application aims to support outdoor exploration while enabling users to record, revisit, and share meaningful moments from their trekking activities.

1.3 Definitions, Acronyms, Abbreviations

- GPS Generic term used in this document to indicate satellite-based positioning systems available on the device (such as GPS, Galileo, and others)
- LTE (Long Term Evolution) is a mobile communication standard. LTE is also referred to as “4G”, the fourth generation of mobile communication technology. LTE consists of a number of enhancements to the “Universal Mobile Telecommunications System” (UMTS) – the third generation of mobile communications.

1.4 References

1.4.1 Main References

- Design and Implementation of Mobile Applications Lectures and Slides
 - Introduction <https://webeep.polimi.it/mod/resource/view.php?id=399280>
 - Flutter <https://webeep.polimi.it/mod/resource/view.php?id=399287>
 - Android <https://webeep.polimi.it/mod/resource/view.php?id=411641>
 - iOS <https://webeep.polimi.it/mod/resource/view.php?id=417791>
 - Lectures <https://webeep.polimi.it/mod/url/view.php?id=376880>

1.4.2 Other References

- Flutter Documentation <https://docs.flutter.dev/>
- Firebase Documentation <https://firebase.google.com/docs/>
- OpenWeather API Documentation
https://openweathermap.org/api/one-call-3?collection=one_call_api_3.0
- Severe Weather Alerts API
<https://www.weatherbit.io/api/alerts>
- Oracle Documentation: What Is Model-View-Controller (MVC)?
<https://www.oracle.com/technical-resources/articles/javase/application-design-with-mvc.html>
- Deutsche Telekom Documentation: What is LTE?
<https://www.telekom.com/en/company/details/the-nine-most-important-facts-about-lte-606>

2. Architectural Design

2.1 Overview

2.1.1 High-level components

The Triplo system is designed according to a modular architecture in which the main application logic is implemented on the client side, while backend functionalities are delegated to managed services and external APIs, as illustrated in Figures 2.1 and 2.2.




Figure 2.1: Overview Diagram: Blue lines denote the smartphone application’s connectivity with Firebase and external services, providing full access to all Firebase modules and external APIs. Dashed green lines denote the smartwatch application’s connectivity, which is limited to selected Firebase services, Firestore and Storage and specific external services, for example OpenTopoMap. The smartphone and smartwatch applications access the network independently, reflecting their ability to operate as standalone clients, while still relying on a shared set of backend services for data and functionality.

2.1.2 High level components interaction




Figure 2.2: Detailed Overview Diagram

The system separates concerns between presentation, application logic, and data management by adopting a Model–View–Controller (MVC) architectural pattern. Both the presentation layer and the core application logic are implemented within the Flutter-based applications, while remaining logically decoupled through the use of Controllers that mediate between Views and Models.

In particular, the mobile application represents the main client, while the smartwatch application provides a lightweight extension offering a subset of functionalities adapted to the constraints and interaction model of wearable devices, relying on the same backend services and data sources.

User interactions are handled by the View layer, while business logic and coordination between components are delegated to Controllers, which act as the central mediation layer between the user interface and the underlying data models.

Data management and authentication are handled through Firebase services, specifically Firebase Authentication, Cloud Firestore, and Firebase Storage. The system leverages Firebase as a Backend-as-a-Service (BaaS) platform, providing managed services for authentication, data storage and user management, relying on platform-specific SDKs for access to these resources. The adoption of Backend-as-a-Service (BaaS) solutions enables the system to replace a traditional custom server-side layer with a more lightweight and scalable architecture. By delegating data management, authentication, and storage to managed services, architectural complexity is reduced by eliminating the need for maintaining a dedicated custom backend infrastructure. In addition to Firebase, the system integrates external third-party services (e.g., weather, map, and satellite APIs), which are accessed via RESTful APIs over

HTTPS.

This architectural approach emphasizes a client-driven design, reduces backend complexity, and enables scalability by leveraging managed cloud services.

This approach removes the need for a dedicated backend gateway or custom server-side components, allowing the application to directly orchestrate interactions with backend services and external resources.

2.2 Component view

2.2.1 High level component view




Figure 2.3: High level component view

The high-level component diagram provides an overview of the main architectural elements of the system and their interactions. The system is composed of two client applications, namely the smartphone application and the smartwatch application, both relying on a shared set of backend services and external resources.

The graphical user interfaces (GUIs) are represented following the convention adopted in both the *Software Engineering* and *UML Distilled* books quoted in the references. In this context, each GUI represents a group of related pages or a major functional area of the application, rather than a single page.

The diagram highlights the presence of two versions of the application. The smartphone application represents the main client and provides the full set of functionalities. It is implemented using Flutter, which enables cross-platform development and allows the application to run on both Android and iOS devices, as explained in section 2.7.

The smartwatch application represents a lightweight extension of the system and is deployed on Wear OS, as discussed in section 2.7. It provides a subset of functionalities adapted to the constraints of wearable devices.

Both applications interact with a common set of backend services and selected external resources. In particular, both the smartphone and smartwatch applications access Firestore for data storage and Firebase Storage for media management, as well as shared external services such as OpenTopoMap for map visualization. However, the smartwatch application is intentionally restricted to a subset of services, reflecting its role as a lightweight client and the constraints of wearable devices.

An architectural difference regards authentication. While the smartphone application directly relies on Firebase Authentication, the smartwatch application does not perform authentication independently. Instead, it adopts a pairing mechanism based on QR code scanning. Through this process, the smartphone securely associates an authenticated user with the smartwatch by storing the corresponding

identifier in Firestore.

This design choice provides several advantages, detailed in section 2.7.3

Access to backend resources such as Firestore, Firebase Storage, and selected external services is otherwise shared between the smartphone and smartwatch applications. The diagram explicitly shows which services are accessible from each client, clarifying the distribution of responsibilities.

The system also integrates multiple external services, for example map providers such as OpenTopoMap and Google Satellite View, as well as external authentication providers. Weather alert functionalities rely on both Weatherbit and a Demo Meteo Server. The latter is used exclusively for demonstration purposes, allowing the simulation of weather alerts without depending on real external conditions.

The operating system interfaces are modeled as platform components, Smartphone OS and Watch OS. These platforms are not accessed directly by the application; instead, access is mediated through Flutter packages that provide abstractions over native operating system services. The specific packages used to interact with such services are detailed in the diagrams of the smartphone application components, section 2.2.2 and of the smartwatch application components, section 2.2.4.

The interfaces associated with Firebase services, Firebase Authentication, Firestore, and Firebase Storage are based on the SDKs provided by the Backend-as-a-Service platform. These SDKs abstract the underlying communication mechanisms and offer a structured way to access backend functionalities, as documented in the Firebase official documentation.

In contrast, the remaining external interfaces, such as Weather API, Weather Alert API, Satellite API, are accessed through RESTful communication. In these cases, the application uses HTTP-based requests via Flutter libraries, handling data exchange in JSON format and performing client-side decoding.

The token verification API is not directly managed within the application logic but is represented the complete authentication flow. In particular, when authentication is performed through an external provider, Google, the application obtains an authentication token which is then passed to Firebase Authentication. Firebase subsequently validates this token with the external provider as part of the OAuth2-based authentication process. This additional interaction is abstracted by the SDK but is included in the diagram to provide a more accurate representation of the overall system behavior.

Figure 2.4: Smartphone Application component view




Figure 2.4: Smartphone Application component view

Domain controllers, such as `UserController`, `DiaryController`, `TrekkingController`, and `ChallengeCon` are responsible for coordinating the application logic related to their respective functional domains. These controllers manage interactions between the View layer and the Model layer, and they also mediate access to backend resources such as Firebase services.

Therefore, in the proposed architecture:

- domain controllers manage the application use cases and the interaction with Firebase-related resources;
- The `ServiceController` acts as a unified facade aggregating multiple underlying services, including external APIs (weather, maps) and device-level services (location, permissions, navigation)
- Firebase is modeled as a set of backend services used by the application, rather than as a custom backend.

2.2.3 Smartphone Application External Libraries

2.2.4 Mobile Smartwatch App component view

2.3 Deployment view




Figure 2.5: Deploy Diagram

The deployment diagram is consistent with the UML deployment notation described in chapter 8 of the UML Distilled book and on page 52 of the Software Engineering book listed in the references. Physical hardware units are modeled through the `<device>` stereotype, while software platforms and runtime contexts are represented through the `<executionEnvironment>` stereotype.

The deployed software elements are shown as `<artifact>`. Communication paths are represented by links annotated with the corresponding protocol or interaction type, such as HTTPS, REST/HTTPS, and OAuth/HTTPS.

In particular, the diagram distinguishes the mobile deployment on Android and iOS devices, while the smartwatch deployment is limited to Wear OS. The cloud side is modeled as a device containing different execution environments, namely Firebase and the set of external providers, which host the artifacts used by the applications.

The deployment diagram represents the distribution of the application artifacts across different execution environments. In particular, the smartphone application is deployed as an artifact on both

Package	Purpose
flutter	Core UI toolkit for building cross-platform applications
provider	State management and implementation of the Observer pattern
firebase_core	Initialization of Firebase services
firebase_auth	User authentication management
cloud_firestore	Firebase cloud database for application data
firebase_storage	Cloud storage for images and media files
google_sign_in	Google authentication integration
flutter_map	Map rendering using OpenStreetMap tiles
latlong2	Geographic coordinate utilities
geolocator	Device location services
geocoding	Address and location conversion
flutter_compass	Compass and orientation data
image_picker	Image selection from device gallery or camera
mobile_scanner	QR code scanning functionality
shared_preferences	Local persistent key-value storage
flutter_local_notifications	Local notification management
workmanager	Background tasks
permission_handler	Runtime permission handling
flutter_dotenv	Environment variable management
uuid	Unique identifiers
intl	Internationalization and localization utilities
share_plus	Content sharing across apps
flutter_cache_manager	Image and file caching
cupertino_icons	iOS-style icon set

Table 2.1: Main dependencies used in the smartphone application

iOS and Android execution environments, while the smartwatch application is deployed separately on a Wear OS execution environment.

Although the smartphone application is shown as deployed on two distinct platforms, it is important to note that it is based on a single shared codebase. The application is developed using Flutter, a cross-platform framework that allows the same source code to be compiled and executed on both iOS and Android devices. As a result, the two deployments correspond to different execution environments of the same application, rather than distinct implementations.

In contrast, the smartwatch application is implemented as a separate artifact. While it shares the same backend services and part of the architectural structure, it is specifically designed for the Wear OS environment and provides a reduced set of functionalities for wearable devices. Therefore, it is represented as a distinct deployment unit in the diagram.

2.4 Runtime view

2.4.1 Selected Use Cases

The identified use cases provide an abstract representation of the interactions between the user and the system. They have been selected to capture the essential functionalities of the application and to model its observable behavior from the user's perspective.

This set of use cases is representative of the main system capabilities and supports a clear understanding of the services offered to the user.

- Add Diary Page
- Explore trekkings on Map
- View trekking information
- View weather information
- Search Users
- Search trekking
- View compass and altitude information
- Participate in Route Challenge
- Login
- Register
- Pair Smartwatch
- Update User Profile

2.4.2 Add Diary Page use case sequence diagram

The most important part of the *Add Diary Page* sequence diagram is the save phase, where the data entered by the user is stored in the system.

When the user presses the save button, the `DiaryPage` starts the process by showing a loading page and then it formats the date, computing the duration from hours and minutes. If the user has selected photos, the page calls the `DiaryController` to upload them to `FirestoreStorage`. The controller uploads each image and returns a list of paths, which will be stored in the diary instance.

After this step, the `DiaryPage` calls the `addDiary(...)` method of the `DiaryController`, passing all the collected data. The controller retrieves the current user identifier from `FirebaseAuth`, generates a new unique identifier for the diary, and creates a `DiaryModel` object.

Before saving the diary in `Firestore`, the object is converted into a `Map<String, dynamic>`. This is necessary because Firestore stores data in a JSON-like format, which is based on key-value pairs. The map represents the diary as a set of fields (such as date, duration, notes, etc.), where each field is associated with a value. The type `dynamic` is used because these values can have different types, such as strings, numbers, booleans, or lists.

Once converted, the map is stored in the `diary` collection in Firestore. At the same time, the controller updates the user document, adding the diary identifier to either the public or private diary list, depending on the selected visibility.

Finally, the control returns to the `DiaryPage`, which updates the user level through the `UserController` and navigates to the `UserPage`, completing the operation.

2.4.3 Watch–Phone Pairing Mechanism

Overview

The pairing mechanism associates a Wear OS device with an authenticated mobile user through a backend-mediated approval process. The watch does not authenticate directly with Firebase Auth; instead, device identity and user identity are linked via Firestore.

Device Identity

Each watch generates (or restores) a persistent `watchId`, stored securely on-device. A corresponding document exists in:

```
watch/{watchId}
```

The `watchId` uniquely identifies the physical device and is never deleted during logout.

Pairing Flow

1. Initialization (Watch) The watch generates a random UUID (`qrToken`) and writes:

```
watch_pair/{watchId}
```

with:

- `status = "waiting"`
- `uid = null`
- `qrToken`
- `createdAt, expiresAt`

A QR code encoding `watchId` and `qrToken` is displayed.

2. Approval (Phone) After scanning the QR, the authenticated mobile app:

- Verifies token validity and expiration.
- Updates the document with:
 - `status = "approved"`
 - `uid = request.auth.uid`

3. Completion (Watch) The watch listens to the document in real time. When `status == "approved"` and `uid` is set, pairing is considered complete and the watch loads user data using that `uid`.

Session Restoration

On startup, the watch checks:

```
watch_pair/{watchId}
```

If the document is already approved, the session is restored automatically.

2.4.4 Logout

Logout does not delete the device identity. Instead, the watch resets:

- `status = "waiting"`
- `uid = null`

This preserves device identity while removing user association.

2.4.5 Security Properties

- Only the watch may create/reset pairing in `waiting` state.
- Only authenticated users may approve pairing.
- QR tokens are random and time-limited.

This design cleanly separates device identity from user authentication while minimizing credential exposure on the wearable device.

2.5 Component interfaces

2.6 Selected architectural styles and patterns

2.6.1 Architectural Patterns: Model–View–Controller with Mediator and Observer




Figure 2.6: Model view controller pattern, adapted from Apple and Oracle documentation

The system adopts the Model–View–Controller (MVC) architectural pattern to separate presentation, application logic, and data management. Within this structure, each role is assigned a specific responsibility in order to improve modularity, maintainability, and clarity of interactions.

The **Model** represents the knowledge and expertise related to the application domain. It includes the core data structures of the system, such as **Diary**, **Trekking**, and **User**. The Model is independent from the user interface and does not handle user interactions directly.

The **View** is responsible for rendering the user interface and collecting user input. Its role is limited to presentation and interaction handling, without directly applying business logic or modifying domain data.

The **Controller** manages the application logic and coordinates the interaction between View and Model. In the adopted variant of MVC, consistent with the interpretation described in both Apple and Oracle documentation, the Controller also plays the role of a *Mediator*. More precisely, the View does not directly manipulate the Model; instead, user actions are forwarded to the Controller, which interprets them, executes the required logic, and updates the corresponding Model data. In this way, the Controller acts as the central coordination point of the interaction, reducing direct dependencies between presentation and domain data.

In addition, the architecture relies on the **Observer pattern** to keep the user interface consistent with state changes. When the state managed by a Controller is updated, the interested Views are notified through the listener mechanism provided by the Flutter framework, based on `ChangeNotifier`, integrated via `Provider`, so that they can refresh their representation accordingly. This notification-based interaction avoids tight coupling and supports consistency across multiple dependent Views.

Therefore, the adopted solution combines the structural organization of MVC with the use of the Mediator pattern in the Controller and the Observer pattern. This combination is particularly suitable for the Flutter-based implementation of the system, where the presentation layer, the application logic, and the domain data remain clearly separated while still cooperating through a well-defined interaction model.

2.7 Other Design Decisions

2.7.1 Flutter as Application Framework

Flutter was selected for the implementation of the client applications because it provides an effective balance between cross-platform development, interface consistency, and maintainability. A primary requirement of the project was the possibility of deploying the smartphone application on both Android and iOS while preserving the same visual structure and interaction style across platforms. In this respect, Flutter offers a significant advantage, since it enables the development of a single shared codebase while also providing a uniform UI across platforms.

Compared with native alternatives such as Kotlin and Swift, Flutter avoids the need to maintain two separate implementations for Android and iOS, thus reducing duplication of development effort and simplifying maintenance. Compared with other cross-platform solutions, the choice of Flutter was particularly suitable for this project because it supports the construction of a coherent and controlled UI layer, which was important for preserving the same application identity and user experience on both mobile platforms.

2.7.2 Firebase as Backend-as-a-Service

The adoption of a Backend-as-a-Service solution represents a strategic architectural decision aimed at improving maintainability, scalability, and integration.

Firebase was adopted as the backend solution to support a scalable and robust system architecture while maintaining a clear separation between client-side logic and backend responsibilities. Rather than introducing a custom server-side layer, the system relies on a Backend-as-a-Service approach, where core functionalities are delegated to managed cloud services.

This choice allows the architecture to focus on the coordination of application logic on the client side, while relying on well-established and production-ready services for critical backend responsibilities such as authentication, data persistence, and media storage, integrating with the client applications through platform-specific SDKs.

From an architectural perspective, this approach improves modularity and reduces system complexity by eliminating the need to design and maintain a dedicated backend infrastructure. This approach presents notable advantages, including scalability, reliability, and security, through managed services that are designed to handle distributed workloads and concurrent access patterns.

Furthermore, the use of Firebase aligns well with the multi-platform nature of the system, as both smartphone and smartwatch applications can interact with the same backend services in a consistent and unified manner. This contributes to maintaining a coherent data model across different devices.

2.7.3 Phone Smartwatch Pairing

While the smartphone application directly relies on Firebase Authentication, the smartwatch application does not perform authentication independently. Instead, it adopts a pairing mechanism based on QR code scanning. Through this process, the smartphone securely associates an authenticated user with the smartwatch by storing the corresponding identifier in Firestore.

This design choice provides several advantages:

- avoids handling user credentials on the smartwatch, reducing the exposure of sensitive data on a constrained and potentially less secure device
- simplifies the user interaction model, eliminating the need for credential input on devices where text entry is inherently limited and less user-friendly
- avoids the need to enforce specific authentication methods, such as Google Sign-In, on the smartwatch, allowing the authentication process to remain centralized on the smartphone.

For these reasons, the interaction is intentionally defined as a pairing process rather than a traditional login, reflecting both its security properties and its role within the overall system architecture.

2.7.4 Network Connectivity Requirements and smartwatch Platform

The smartwatch application requires reliable access to internet connectivity in order to provide a complete and consistent user experience. In particular, network access is necessary for several core functionalities of the system.

The application relies on external services to retrieve real-time data, such as maps, which are essential for trekking activities.

Internet access enables communication with backend services and APIs, allowing the application to fetch dynamic content and maintain updated information.

Given these requirements, the choice of Wear OS as the target platform is appropriate and justified. Wear OS supports multiple network communication modes, including:

- **Bluetooth connectivity:** allows the smartwatch to access the internet indirectly through a paired smartphone.
- **Wi-Fi connectivity:** enables the device to connect directly to wireless networks, allowing standalone operation in specific scenarios.
- **Cellular connectivity (LTE with eSIM):** available on selected devices, providing full independence from the smartphone and ensuring continuous connectivity during outdoor activities.

This flexibility ensures that the application can operate under different conditions, ranging from smartphone-assisted usage to fully autonomous scenarios. In particular, the availability of LTE-enabled devices makes Wear OS especially suitable for outdoor and trekking contexts, where the user may not always have access to their smartphone.

3. Functional Requirements

3.0.1 Account and Profile Management

- FR1** The system shall allow users to register by providing email and password
- FR2** The system shall allow users to register using an external authentication provider
- FR3** The system shall allow users to log in using email and password
- FR4** The system shall allow users to log in using an external authentication provider
- FR5** The system shall allow users to reset their password
- FR6** When registration is successful, the system shall create a user profile
- FR7** When registration is successful, the system shall assign a default username based on the user's email
- FR8** The system shall allow users to update their username
- FR9** The system shall allow users to update their profile image
- FR10** The system shall allow users to update their name
- FR11** The system shall allow users to update their surname
- FR12** The system shall allow users to update their birth date
- FR13** When users are registered with email and password, the system shall allow them to update their email address
- FR14** When users are authenticated through an external provider, the system shall allow them to restore their profile image from the provider
- FR15** The system shall allow users to change the application language
- FR16** The system shall allow users to pair a smartwatch with their account
- FR17** The system shall allow users to enable weather notifications for selected routes

3.0.2 Home, Routes and Route Details

- FR18** The system shall display routes on a map
- FR19** The system shall classify routes according to their difficulty level
- FR20** The system shall display routes using different colors based on their difficulty level
- FR21** When a user selects a route, the system shall display detailed information about the selected route

- FR22** The system shall display route information including starting point, ending point, difficulty level, length, estimated time, and elevation gain
- FR23** The system shall indicate the suitability of a route for families
- FR24** The system shall display a textual description of the route
- FR25** The system shall display refreshment points associated with the route
- FR26** The system shall display challenges associated with the route
- FR27** The system shall display summary weather information for the selected route
- FR28** The system shall allow users to save a route to their profile
- FR29** The system shall allow users to remove a saved route from their profile
- FR30** The system shall allow users to start a navigation session for a selected route
- FR31** When a navigation session ends, the system shall suggest creating a diary entry for the route

3.0.3 Diary Management

- FR32** The system shall allow users to create a diary entry associated with a selected route
- FR33** The system shall allow users to specify the date of the activity in a diary entry
- FR34** The system shall allow users to specify the duration of the activity in a diary entry
- FR35** The system shall allow users to select followed users who participated in the activity
- FR36** The system shall allow users to add textual notes to a diary entry
- FR37** The system shall allow users to indicate the presence of refreshment stops during the activity
- FR38** The system shall allow users to select completed challenges in a diary entry
- FR39** The system shall allow users to select a mood associated with the activity
- FR40** The system shall allow users to upload images to a diary entry
- FR41** The system shall allow users to mark a diary entry as public or private
- FR42** The system shall allow users to save a diary entry
- FR43** The system shall allow users to discard a diary entry before saving it

3.0.4 Search and Challenges

- FR44** The system shall allow users to search for other users
- FR45** The system shall allow users to search for routes
- FR46** The system shall display search results according to the selected search type
- FR47** The system shall display public profile information of searched users
- FR48** The system shall display route information for searched routes
- FR49** The system shall display diary entries from followed users
- FR50** The system shall display the available challenges
- FR51** The system shall display the requirements for completing each challenge

3.0.5 Profile and Social Features

- FR52** The system shall display the user's profile picture, username, and level
- FR53** The system shall display the number of diary entries created by the user
- FR54** The system shall display the number of followers of the user
- FR55** The system shall display the number of followed users
- FR56** The system shall allow users to access the public profile of a follower
- FR57** The system shall allow users to access the public profile of a followed user
- FR58** The system shall allow users to share a public link to their profile

3.0.6 Navigation and Sensor Information

- FR59** The system shall display compass information
- FR60** The system shall display the current heading in degrees
- FR61** The system shall display the user's current altitude
- FR62** The system shall display the user's current geographic coordinates