OliveTrace
Team handover

Read this first while Sofiene is offline. This is the shared handover for all five members. Date: 22 October 2026.

Team: Sofiene Zayati, Mariem Ammari, Oussema Benjemia, Hana Fkiri and Aymen Jenhani.

1. Current state and immediate priorities

All five modules and the verified DevOps pipeline are merged into main. Docker works locally. Hosted Railway deployment is blocked by a platform outage; use the full local application for the module demonstration.

Status	What it means
DONE	All five modules integrated in main; shared authentication/roles; current producer/farm features; consumer recovery and catalog improvements.
TESTED	240 tests / 1,740 assertions passed on local SQLite and a separate MySQL test schema. Docker image built and HTTP paths checked.
CI	PASSED: tests and code quality, Docker build, migrations and HTTP smoke checks.
SONAR	Quality Gate passed on main. New-code coverage 100%; overall project coverage 68.0%; new duplication 0%.
RAILWAY	BLOCKED: Railway refuses new deployments during its platform incident. No hosted services or live URL created.
NEVER IN GIT	.env, API keys, SMTP app passwords, local database passwords, database exports and private uploads.

Next action for each member: pull main, update dependencies/schema/assets, then test your own role and module locally. Do not overwrite your .env or delete your database.

Repository / main
CI evidence
SonarQube dashboard
DevOps integration PR #8

Hosted demo: no working URL has been confirmed in this edition. Use the native local application for the full functional demonstration.

Source revision used for the reported checks: 027336e. The latest main commit can additionally contain these PDFs.

2. First setup on a new PC

Use Windows PowerShell for these commands. Required: Git, compatible PHP (minimum 8.3; 8.4 tested in CI/Docker), Composer 2, Node 24 (or supported Node 22.12+) with npm 10+, and a running MySQL server. Enable MySQL/mbstring/XML/curl/intl/fileinfo/GD/ZIP extensions. An old XAMPP PHP can take priority in PATH.

```
git clone https://github.com/SofieneZayati/OliveTrace.git
cd OliveTrace
composer install
npm.cmd ci
Copy-Item .env.example .env
php artisan key:generate
```

The copy/key commands above are for a NEW installation only. Open .env with **notepad .env**. Use your own local database login; the repository does not contain a live database.

```
DB_CONNECTION=mysql
DB_HOST=127.0.0.1
DB_PORT=3306
DB_DATABASE=olivetrace
DB_USERNAME=root
DB_PASSWORD=
```

Create the database in phpMyAdmin/MySQL. Example SQL:

```
CREATE DATABASE IF NOT EXISTS olivetrace
CHARACTER SET utf8mb4 COLLATE utf8mb4_unicode_ci;
```

```
php artisan config:clear
php artisan migrate --seed
php artisan storage:link
php artisan olivetrace:check-database
npm.cmd run build
php artisan serve
```

Open **http://127.0.0.1:8000**. Keep the server terminal open. Ctrl+C stops it. Seeding is for a new/local demo database; do not reseed over edits without checking what the seeders update.

3. Updating an existing checkout

First stop the development server with Ctrl+C and run **git status**. Save/commit your work or stash it intentionally before switching branches. The commands below keep an existing .env and database.

```
git fetch origin
git switch main
git pull --ff-only origin main
composer install
npm.cmd ci
php artisan optimize:clear
php artisan migrate
npm.cmd run build
php artisan olivetrace:check-database
php artisan serve
```

If Git says your branch diverged or local changes would be overwritten, stop and ask the team. Do not use reset --hard, clean -fd, migrate:fresh or delete .env to solve an update problem.

If you need the portable PHP on Sofiene's PCs

```
$phpDirectory = Join-Path $env:LOCALAPPDATA 'OliveTraceTools\php84'
$env:PATH = "$phpDirectory;$env:PATH"
$env:PHPRC = $phpDirectory
php -v
```

These lines select an already installed PHP; they do not install it. The repository helpers Use-OliveTrace.ps1 and Start-LocalMySql.ps1 depend on that PC's portable tools. On a teammate's PC, use their own PHP/MySQL (for example start MySQL in XAMPP) instead.

Continue on your own branch

```
git switch -c feature/YOUR-NAME-final origin/main
```

Choose an unused name. If you already have an active feature branch, switch to it and merge origin/main after saving your work. Push your feature branch and open a PR; do not overwrite another person's branch or force-push main.

4. Accounts, modules and test scenario

Development accounts only: all accounts below use **OliveTrace123!** after the development seeders run. These are local dummy accounts, not hosted administrator credentials.

Email	Role / purpose
admin@test.com	Admin: users, roles and back-office moderation.
producer@test.com	Producer: Sofiene's farms/profile/care, Mariem's harvest/mill requests.
miller@test.com	Miller: milling requests and operations.
lab@test.com	Laboratory: analyses and certification.
distributor@test.com	Distributor: products and shipments.
consumer@test.com	Consumer: reviews, complaints and personal dashboard.

Owner	Local smoke test before validation
Sofiene Zayati	Edit producer profile; create/edit farm; check private coordinate map; log farm care; ask AI; save advice and turn a recommendation into a tracked task.
Mariem Ammari	Harvest > mill request > milling confirmations/operation > oil lot. Check validation and owner/miller permissions.
Oussema Benjemia	Certification request > laboratory results > certificate/PDF. Check pending/valid/expired behaviour and laboratory AI.
Hana Fkiri	Public/hidden product > shipment > delivery status and CO2 estimate. Check catalog and product origin story.
Aymen Jenhani	Consumer review/complaint > admin moderation and Groq draft/summary/reply. Check private purchase proof, approval and notifications.

All members: test one invalid form on the server, one forbidden action with a different role, and one successful workflow. Public region maps are approximate; exact farm GPS stays with the owner/admin. Producer declarations and transport estimates are not laboratory certification.

5. AI, mail and common problems

Private .env settings

```
GEMINI_API_KEY=YOUR_PRIVATE_KEY
FARM_AI_PROVIDER=gemini
FARM_AI_MODEL=gemini-3.1-flash-lite
LAB_AI_MODEL=gemini-3.1-flash-lite
GROQ_API_KEY=YOUR_PRIVATE_KEY
CONSUMER_AI_MODEL=openai/gpt-oss-120b
MAIL_MAILER=log
```

Fill keys privately, then run **php artisan config:clear**. Gemini and Groq are separate providers. The repository and these PDFs do not distribute private keys. Groq is used for complaint drafts, review summaries and tone-based review replies. Farm/lab AI needs the Gemini configuration. Advice is reviewed; it never automatically changes a farm or sends a customer response.

For Hana's optional live AI: set **OLIVETRACE_IMPACT_AI_ENABLED=true** for impact advice; product drafts use the separate **PRODUCT_DESCRIPTION_API_KEY** and model variables in .env.example. Their local fallback is not a live AI response. Mariem's model uses HARVEST_AI_MODEL.

Live Groq requests and TLS authentication to Gmail passed on this desktop. No email was sent during that check. CI uses mocked AI/mail, so each presenting laptop must test its own real provider. Leave MAIL_MAILER=log without an approved private SMTP configuration; reset links are then in storage/logs/laravel.log.

Problem	Check / action
Connection refused (2002)	Start the MySQL server; check host/port. php artisan serve does not start MySQL.
Access denied (1045)	Your .env DB username/password must match your own database. Then config:clear.
Missing users or tables	migrate updates the schema. A NEW demo database also needs db:seed.
Wrong PHP / missing extension	Check php -v and php --ini; select PHP 8.4 and run composer check-platform-reqs.
Missing/stale CSS or JavaScript	npm.cmd ci then npm.cmd run build; reload the browser.
AI unavailable	Check private provider key/model, internet, quota and rate limits. Manual work must remain available.

Use **php artisan test** for the default isolated test suite. **php scripts/test-mysql.php** requires a separate olivetrace_testing schema; it must never point at your real project database.

6. DevOps handover and remaining actions

Implemented: production Dockerfile; separate local Docker/MySQL stack; persistent upload/database volumes; runtime caches; database-aware /up; reverse-proxy HTTPS support; GitHub tests/coverage/SonarQube/Docker checks; Railway configuration; recovery guide; this PDF and the professor's PDF.

Still pending or restricted: Finish Railway only after the platform resumes (steps on page 8). Every member must prepare their presenting PC, private API keys and local module scenario. Send the professor PDF before validation. No additional business feature is assigned by this handover.

Railway currently refuses new deployments during a platform incident. No project/service or hosted URL has been created. Official incident status. Sonar CI token expires on 21 November 2026; the repository owner must renew the SONAR_TOKEN secret before then.

Useful Docker commands - optional

Docker Desktop must be running. Native Windows setup remains supported and is the quickest way to demonstrate all module features.

```
Copy-Item docker/variables.example .env.docker
notepad .env.docker
docker compose --env-file .env.docker up -d --build mysql
docker compose --env-file .env.docker run --rm --build app `
  php artisan migrate --force
docker compose --env-file .env.docker up -d app
docker compose --env-file .env.docker logs --tail=50 app
docker compose --env-file .env.docker stop
```

Fill APP_KEY and both database passwords in .env.docker; generate a new key with php artisan key:generate --show. This is a separate database and initially has no demo data. See docs/devops.md for the tested one-off local seed command. Never use down -v unless you intend to delete the container environment's volumes.

Before the 14:00 validation

1. Pull main and run the update commands.
2. Confirm your local login and module workflow.
3. Test AI from the actual presenting laptop.
4. Open CI, SonarQube and the hosted URL; keep the complete local app running.
5. Send OliveTraceDevops.pdf to the teacher before the session. This handover is for the team.

If something needs Sofiene: leave the command, exact error and your branch/commit in the group. Do not post .env contents, API keys, SMTP passwords or database exports. No additional module feature has been assigned as part of the DevOps work.

Detailed deployment/recovery guide | Professor document | Latest main revision

7. Make another PC fully ready

Nothing depends on this desktop's absolute project path. Clone the repository into any folder, then run the setup/update commands from that folder. Do not copy vendor/ or node_modules/ from another PC; recreate them from the lock files.

Check installed software first

```
git --version
php -v
php --ini
composer --version
node -v
npm.cmd -v
composer check-platform-reqs
```

Run the last check after composer install. Install only what is missing or incompatible. Official downloads: Git, PHP for Windows, Composer, Node.js and MySQL. Docker Desktop is optional for ordinary local development.

Create the additional farm-care demo data

On a LOCAL demo database, after the main seeders have run:

```
php artisan db:seed --class=FarmCareDemoSeeder
php artisan db:seed --class=FarmJournalDemoSeeder
```

These add fictional farm map points and journal/tasks without fabricating AI reports. Sign in as producer@test.com. Generate genuine AI reports through the configured provider; reports from this desktop are not automatically copied by Git.

What Git does not transfer

Your database rows, .env, API keys, mail passwords and storage/app uploads are local/private. Migrations plus seeders create the shared DEMO data; they do not copy Sofiene's exact current records. To move existing records, export/import MySQL privately and copy the necessary uploads through a trusted private channel. Back up the target before importing and preserve the original APP_KEY if moving encrypted data.

CI, SonarQube and Railway on a laptop

The hosted dashboards work in a browser; no Sonar CLI, Railway CLI or local Sonar server is needed to pull/run the app or show CI evidence. Docker Desktop is required only to run compose locally. GitHub write access requires an accepted collaborator invitation and the correct GitHub account; a 403 push error is a permission/account issue.

Keep MySQL running and the terminal with php artisan serve open. CRUD works locally after assets are built; live AI, map tiles and hosted dashboards require internet. Verify the presenting laptop before leaving for university.

8. Finish Railway when the platform resumes

Current situation: the Limited Trial account is available, but New returns "Deploys have been paused temporarily". No application or MySQL service was created. A local Docker deployment is verified at localhost:8080 on this desktop; other PCs must start their own environment.

Order	Action for the repository / Railway owner
1. Check availability	Read the official incident status. If the account still blocks new deployments, keep the local demo ready and try later. Do not activate a paid plan.
2. Create services	Create a project with MySQL and the application sourced from SofieneZayati/OliveTrace, branch main. Use only these two services, one application replica.
3. Set private variables	Use docker/railway-variables.example. Set a NEW stable APP_KEY; keep APP_ENV=production, APP_DEBUG=false and MAIL_MAILER=log. MySQL variable references assume the service name MySQL.
4. Preserve uploads	Attach an app volume at /var/www/html/storage/app. Verify MySQL has its persistent database volume too.
5. Gate the release	Enable Wait for CI for main. railway.json selects Dockerfile, migrate --force before deployment, and /up as the health check. Do not reset or automatically seed a hosted database.
6. Expose HTTPS	Generate the Railway domain, set APP_URL to that HTTPS URL, then deploy. Keep secure session cookies and TRUSTED_PROXIES configured as in the example.
7. Verify and record	Check /up, /, /login and /catalog; inspect logs and usage. Record the public URL and deployed commit for the professor. Confirm Wait for CI is enabled.

Generate the hosted application key locally without changing your current .env:

```
php artisan key:generate --show
```

Copy that output privately into Railway APP_KEY. Keep it stable across redeploys. Fill optional AI/SMTP keys only if those integrations will be tested on the host; a hosted deployment demonstration can use no AI keys and no customer email delivery.

If connecting GitHub or creating services asks for account-owner verification/authorization, Sofiene must complete that step when awake. Teammates do not need Railway admin access to run the app locally. This document does not claim that hosted CD has already succeeded.

Incident status | Variable template | Detailed deployment guide