OliveTrace
Team handover

Read this first while Sofiene is offline. This is the shared handover for all five members. Date: 22 October 2026.

1. Current state and immediate priorities

All five modules are integrated. Docker and the local test suites are verified. The upgraded GitHub pipeline is running; Railway deployment is the next step.

Status	What it means
DONE	All five modules integrated in main; shared authentication/roles; current producer/farm features; consumer recovery and catalog improvements.
TESTED	240 tests / 1,740 assertions passed on local SQLite and a separate MySQL test schema. Docker image built and HTTP paths checked.
CI	In progress: new coverage, SonarQube quality gate and Docker job.
SONAR	CI analysis is being verified; automatic analysis was replaced by GitHub Actions.
RAILWAY	Pending: Limited Trial account, 0 hosted services created so far.
NEVER IN GIT	.env, API keys, SMTP app passwords, local database passwords, database exports and private uploads.

Next action for each member: pull main, update dependencies/schema/assets, then test your own role and module locally. Do not overwrite your .env or delete your database.

Repository / main
CI evidence
SonarQube dashboard
DevOps integration PR #8

Hosted demo: no working URL has been confirmed in this edition. Use the native local application for the full functional demonstration.

Source revision used for the reported checks: 282811a. The latest main commit can additionally contain these PDFs.

2. First setup on a new PC

Required: Git, PHP 8.4 with MySQL/mbstring/XML/curl/intl/fileinfo/GD/ZIP extensions, Composer 2, Node 24 (or supported Node 22.12+) with npm 10+, and a running MySQL server. The PHP used by your terminal must be compatible; an old XAMPP PHP can take priority in PATH.

```
git clone https://github.com/SofieneZayati/OliveTrace.git
cd OliveTrace
composer install
npm.cmd ci
Copy-Item .env.example .env
php artisan key:generate
```

The copy/key commands above are for a NEW installation only. Open .env with **notepad .env**. Use your own local database login; the repository does not contain a live database.

```
DB_CONNECTION=mysql
DB_HOST=127.0.0.1
DB_PORT=3306
DB_DATABASE=olivetrace
DB_USERNAME=root
DB_PASSWORD=
```

Create the database in phpMyAdmin/MySQL. Example SQL:

```
CREATE DATABASE IF NOT EXISTS olivetrace
CHARACTER SET utf8mb4 COLLATE utf8mb4_unicode_ci;
```

```
php artisan config:clear
php artisan migrate --seed
php artisan olivetrace:check-database
npm.cmd run build
php artisan serve
```

Open **http://127.0.0.1:8000**. Keep the server terminal open. Ctrl+C stops it. Seeding is for a new/local demo database; do not reseed over edits without checking what the seeders update.

3. Updating an existing checkout

First stop the development server with Ctrl+C and run **git status**. Save/commit your work or stash it intentionally before switching branches. The commands below keep an existing .env and database.

```
git fetch origin
git switch main
git pull --ff-only origin main
composer install
npm.cmd ci
php artisan optimize:clear
php artisan migrate
npm.cmd run build
php artisan olivetrace:check-database
php artisan serve
```

If Git says your branch diverged or local changes would be overwritten, stop and ask the team. Do not use reset --hard, clean -fd, migrate:fresh or delete .env to solve an update problem.

If you need the portable PHP on Sofiene's PCs

```
$phpDirectory = Join-Path $env:LOCALAPPDATA 'OliveTraceTools\php84'
$env:PATH = "$phpDirectory;$env:PATH"
$env:PHPRC = $phpDirectory
php -v
```

These lines select an already installed PHP; they do not install it. The repository helpers Use-OliveTrace.ps1 and Start-LocalMySql.ps1 depend on that PC's portable tools. On a teammate's PC, use their own PHP/MySQL (for example start MySQL in XAMPP) instead.

Continue on your own branch

```
git switch -c feature/YOUR-NAME-final origin/main
```

Choose an unused name. If you already have an active feature branch, switch to it and merge origin/main after saving your work. Push your feature branch and open a PR; do not overwrite another person's branch or force-push main.

4. Accounts, modules and test scenario

Development accounts only: all accounts below use **OliveTrace123!** after the development seeders run. These are local dummy accounts, not hosted administrator credentials.

Email	Role / purpose
admin@test.com	Admin: users, roles and back-office moderation.
producer@test.com	Producer: Sofiene's farms/profile/care, Mariem's harvest/mill requests.
miller@test.com	Miller: milling requests and operations.
lab@test.com	Laboratory: analyses and certification.
distributor@test.com	Distributor: products and shipments.
consumer@test.com	Consumer: reviews, complaints and personal dashboard.

Owner	Local smoke test before validation
Sofiene	Edit producer profile; create/edit farm; check private coordinate map; log farm care; ask AI; save advice and turn a recommendation into a tracked task.
Mariem	Harvest > mill request > milling confirmations/operation > oil lot. Check validation and owner/miller permissions.
Oussema	Certification request > laboratory results > certificate/PDF. Check pending/valid/expired behaviour and laboratory AI.
Hana	Public/hidden product > shipment > delivery status and CO2 estimate. Check catalog and product origin story.
Aymen	Consumer review/complaint > admin moderation and Groq draft/summary/reply. Check private purchase proof, approval and notifications.

All members: test one invalid form on the server, one forbidden action with a different role, and one successful workflow. Public region maps are approximate; exact farm GPS stays with the owner/admin. Producer declarations and transport estimates are not laboratory certification.

5. AI, mail and common problems

Private .env settings

```
GEMINI_API_KEY=YOUR_PRIVATE_KEY
FARM_AI_PROVIDER=gemini
FARM_AI_MODEL=gemini-3.1-flash-lite
LAB_AI_MODEL=gemini-3.1-flash-lite
GROQ_API_KEY=YOUR_PRIVATE_KEY
CONSUMER_AI_MODEL=openai/gpt-oss-120b
MAIL_MAILER=log
```

Fill keys privately, then run **php artisan config:clear**. Gemini and Groq are separate providers. The repository and these PDFs do not distribute private keys. Groq is used for complaint drafts, review summaries and tone-based review replies. Farm/lab AI needs the Gemini configuration. Advice is reviewed; it never automatically changes a farm or sends a customer response.

Live Groq requests and TLS authentication to Gmail passed on this desktop. No email was sent during that check. CI uses mocked AI/mail, so each presenting laptop must test its own real provider. Leave MAIL_MAILER=log without an approved private SMTP configuration; reset links are then in storage/logs/laravel.log.

Problem	Check / action
Connection refused (2002)	Start the MySQL server; check host/port. php artisan serve does not start MySQL.
Access denied (1045)	Your .env DB username/password must match your own database. Then config:clear.
Missing users or tables	migrate updates the schema. A NEW demo database also needs db:seed.
Wrong PHP / missing extension	Check php -v and php --ini; select PHP 8.4 and run composer check-platform-reqs.
Missing/stale CSS or JavaScript	npm.cmd ci then npm.cmd run build; reload the browser.
AI unavailable	Check private provider key/model, internet, quota and rate limits. Manual work must remain available.

Use **php artisan test** for the default isolated test suite. **php scripts/test-mysql.php** requires a separate olivetrace_testing schema; it must never point at your real project database.

6. DevOps handover and remaining actions

Implemented: production Dockerfile; separate local Docker/MySQL stack; persistent upload/database volumes; runtime caches; database-aware /up; reverse-proxy HTTPS support; GitHub tests/coverage/SonarQube/Docker checks; Railway configuration; recovery guide; this PDF and the professor's PDF.

Still pending or restricted: Finish the new CI run and Railway deployment; verify any trial network restrictions. The full local project is ready for the module demonstrations.

Useful Docker commands - optional

Docker Desktop must be running. Native Windows setup remains supported and is the quickest way to demonstrate all module features.

```
Copy-Item docker/variables.example .env.docker
notepad .env.docker
docker compose --env-file .env.docker up -d --build mysql
docker compose --env-file .env.docker run --rm --build app `
  php artisan migrate --force
docker compose --env-file .env.docker up -d app
docker compose --env-file .env.docker logs --tail=50 app
docker compose --env-file .env.docker stop
```

Fill APP_KEY and both database passwords in .env.docker; generate a new key with php artisan key:generate --show. This is a separate database and initially has no demo data. See docs/devops.md for the tested one-off local seed command. Never use down -v unless you intend to delete the container environment's volumes.

Before the 14:00 validation

1. Pull main and run the update commands.
2. Confirm your local login and module workflow.
3. Test AI from the actual presenting laptop.
4. Open CI, SonarQube and the hosted URL; keep the complete local app running.
5. Send OliveTraceDevops.pdf to the teacher before the session. This handover is for the team.

If something needs Sofiene: leave the command, exact error and your branch/commit in the group. Do not post .env contents, API keys, SMTP passwords or database exports. No additional module feature has been assigned as part of the DevOps work.

Detailed deployment/recovery guide | Professor document | Latest main revision