



100 Ampere to 125 Ampere Metered Power Outlet With or Without Circuit Breaker and Receptacles



| | | | | | |
|-------------------------------|---|---|---|---|--|
| Catalog Number | TEST-U5101-XL | TEST-U4721-O-BL-ALT | TEST-U5136-O-75-FMG | TEST-101012-GHC1-NK | TEST-363612-CT3RXA-SP1 |
| UPC | 984572271999 | 984572596559 | 984572320611 | 984572281660 | 984572525092 |
| Marketing Product Description | 4 Terminal Ringless Small Closing Plate Surface Mount | 4 Terminal Ringless Plain Top Lever Bypass 9-16 In Barrel Lock With Bracket Provision Alliant Energy | 4 Terminal Ringless Plain Top 1-Main Breaker Provision 1450 TT30 520GR Single Pedestal Direct Bury Florida Meter Group | 10x12x10 Hinge Cover Wireway Type 1 UL Listed Steel No Knockouts ANSI 61 Gray | 36x12x36 Hinge Cover Type 3R UL Listed Aluminum No Knockouts No Paint Padlocking 3 Point Handle Louvers Both Sides |
| Length (IN) | 5.188 | 5.75 | 10.195 | 12 | 12 |
| Width (IN) | 8.875 | 16 | 9.195 | 10 | 36 |
| Height (IN) | 25 | 22 | 80 | 10 | 36 |
| Weight (LB) | 23 | 29 | 79 | 12 | 118 |
| Brand Name | Milbank | Milbank | Milbank | MilBank | Milbank |
| Type | Load Center | Bolt On Meter Socket | Bolt On Meter Socket | Load Center | Load Center |
| Special Features | 104 Terminal Ringless Small Closing Plate Surface Mount | 104 Terminal Ringless Plain Top Lever Bypass 9-16 In Barrel Lock With Bracket Provision Alliant Energy 4 Terminal Ringless Plain Top Lever Bypass 9-16 In Barrel Lock With Bracket Provision Alliant Energy | Terminal Ringless Plain Top 1-Main Breaker Provision 1450 TT30 520GR Single Pedestal Direct Bury Florida Meter Group Terminal Ringless Plain Top 1-Main Breaker Provision 1450 TT30 520GR Single Pedestal Direct Bury Florida Meter Group | 10x12x10 Hinge Cover Wireway Type 1 UL Listed Steel No Knockouts ANSI 61 Gray | 36x12x36 Hinge Cover Type 3R UL Listed Aluminum No Knockouts No Paint Padlocking 3 Point Handle Louvers Both Sides 36x12x36 Hinge Cover Type 3R UL Listed Aluminum No Knockouts No Paint Padlocking 3 Point Handle Louvers Both Sides 36x12x36 Hinge Cover Type 3R UL Listed Aluminum No Knockouts No Paint Padlocking 3 Point Handle Louvers Both Sides |
| Application | Meter Socket | Meter Socket | Meter Socket With Load Center | Meter Socket | Meter Socket With Load Center |
| Standard | UL Listed | UL Listed | UL Listed | Non UL Listed | UL Listed |
| Voltage Rating | 240 Volts Alternating Current | 120/208 Volts Alternating Current | 120/208 Volts Alternating Current | 120/240 Volts Alternating Current | 120/208 Volts Alternating Current |
| Amperage Rating | 200 Ampere | 100 Ampere | 100 Ampere | 80 Continuous Ampere | 200 Ampere |
| Phase | 1 Phase | 1 Phase | 3 Phase | 3 Phase | 3 Phase |



Utility requirements for this equipment may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.

Utility requirements for this equipment may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.



100 Ampere to 125 Ampere Metered Power Outlet With or Without Circuit Breaker and Receptacles



| | | | | | |
|---------------------------|--|---|--|---|-------------------------------------|
| Frequency Rating | 60 Hertz | 60 Hertz | 60 Hertz | 60 Hertz | 60 Hertz |
| Wattage | 96 | 106.4 | 60 | | 15 |
| Number Of Cutouts | 1 | 1 | 1 | 1 | 2 |
| Cutout Size | Breaker Provision | Breaker Provision | Breaker Provision | Breaker Provision | Four Single Pole 20 Ampere Breakers |
| Cable Entry | Overhead or Underground | Overhead | Overhead and Underground and Side Wireway | Overhead and Underground and Side Wireway | Overhead or Underground |
| Terminal | Lay in | 1/2 Inch Stud Line Side | 1/2 Inch Stud Line Side | 1/2 Inch Stud Line Side;3/8 Inch Stud | 3/8 Inch Stud |
| Insulation | Fiberglass with Resin | Fiberglass with Resin | Fiberglass with Resin | Haysite | Fiberglass with Resin |
| Mounting | Flush Mount | Direct Bury | Direct Bury | Direct Bury | Flush Mount with Flange |
| Operating Temperature | 100C | 103 | 105 | | 451 |
| Enclosure | G90 Galvanized Steel with Powder Coat Finish | 304 Stainless Steel with Powder Coat Finish | G90 Galvanized Steel with Powder Coat Finish | 304 Stainless Steel with Powder Coat Finish | Aluminum with Powder Coat Finish |
| Jaw Quantity | 5 Terminal | 4 Terminal | 5 Terminal | 4 Terminal | 6 Terminal |
| Bypass Type | Horn Bypass | Auto Bypass | Horn Bypass | Horn Bypass | Lever Bypass |
| Number of Meter Positions | 2 Positions | 1 Position | 1 Position | 2 Positions | 2 Positions |
| Equipment Ground | 2 Barrel Ground Lug and Ground Bar | 2 Barrel Ground Lug | 2 Barrel Ground Lug and Ground Bar | 2 Barrel Ground Lug | 2 Barrel Ground Lug |
| Hub Opening | 1 Inch Hub | 1 Inch Hub | 1 1/4 Inch Hub | 1 Inch Hub | 1 Inch Hub |
| Line Side Wire Range | 1/0 - 250 kcmil | 1/0 - 250 kcmil | | 1/0 - 250 kcmil;1/0 AWG - 350kcmil | 1/0 - 250 kcmil |



Utility requirements for this equipment may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.

Utility requirements for this equipment may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.



Type 3R Hinged Single and Double Door Lockable Enclosures



| | | | | | |
|-------------------------------|--|---|--|---|--|
| Catalog Number | TEST-484816-CT3R | TEST-CL200 | TEST-101060-GSC3R | TEST-U2864-X | TEST-8818-GSC1 |
| UPC | 984572188181 | 984572248564 | 984572100398 | 984572136336 | 984572109223 |
| Marketing Product Description | 48x16x48 Hinge Cover Type 3R Steel No Knockouts ANSI 61 Gray Double Doors Padlocking 3 Point Handle Back Panel Weld Studs Drip Shield No Center Post | 200 Ampere Form 2S EZ Mechanical Reconditioned Meter | 10x60x10 Screw Cover Wireway Type 3R UL Listed Steel Knockouts ANSI 61 Gray Quad D Knockout For Lock | Test 8 Terminal Ringless Large Closing Plate 4 Position 4-200 Ampere Main Breaker Provision Double Connector 4-600kcmil | 8x18x8 Screw Cover Wireway Type 1 UL Listed Steel Knockouts ANSI 61 Gray |
| Length (IN) | 16 | 7 | 60 | 5.844 | 18 |
| Width (IN) | 48 | 5 | 10 | 37 | 8 |
| Height (IN) | 48 | 7 | 10 | 30 | 8 |
| Weight (LB) | 220 | 4.5 | 48 | 97 | 13 |
| Brand Name | Milbank | milbank | milbank | milbank | milbank test |
| Sub Brand | | | | | |
| Type | Fifth Terminal Kit | Fifth Terminal Kit | Fifth Terminal Kit | Fifth Terminal Kit | Fifth Terminal Kit |
| Special Features | 3 OClock Position;6 OClock Position;9 OClock Position | 3 OClock Position;6 OClock Position;9 OClock Position | 6 OClock Position | 3 OClock Position | 3 OClock Position;6 OClock Position;9 OClock Position |
| Application | Metering Accessory | Metering Accessory | Metering Accessory | Metering Accessory | Metering Accessory |
| Standard | milbank | test | test | test | test x18x8 Screw Cover Wireway Type 1 UL Listed Steel Knockouts ANSI 61 Gray x18x8 Screw Cover Wireway Type 1 UL Listed Steel Knockouts ANSI 61 Gray x18x8 Screw Cover Wireway Type 1 UL Listed Steel Knockouts ANSI 61 Gray |
| Connection | Lug | Wire | Wire | Lug | Bracket |
| Number Of Terminals | 51 | 12 | 12 | 12 | 12 |
| Wire Size | 12 AWG | 14 AWG to 2 AWG | 14 AWG to 2 AWG | 14 AWG to 2 AWG | 14 AWG to 2 AWG |

Type 3R Hinged Single and Double Door Lockable Enclosures



| | | | | | |
|--------------------------|--|---|-------------------------------|-------------------------------|---|
| Terminal Size | .414 x .414 x .625 | .414 x .414 x .625 | .414 x .414 x .5 | .414 x .414 x .625 | .414 x .414 x .313 |
| Spacing | 12 | 120 | 120 | 120 | 120 |
| Amperage Rating | 26 | 120 | 120 | 120 | 120 |
| Voltage Rating | 240 Volts Alternating Current | 480 Volts Alternating Current | 240 Volts Alternating Current | 240 Volts Alternating Current | 120 Volts Alternating Current |
| Material | Copper | Copper | Copper | Copper | Copper |
| Color | blue | red | red | red | green |
| Mounting | Bolt In | Plug In | Plug In | Bolt In | Plug In |
| Environmental Conditions | Environmental Conditions Point Handle Back Panel Weld Studs Drip Double Doors Padlocking Shield No Center Post | Test Ampere Form 2S EZ Mechanical product marketing | 65 | 65 | Screw Cover Wireway Type 1 UL Listed Steel Knockouts ANSI 61 Gray Screw Cover Wireway Type 1 UL Listed Steel Knockouts ANSI 61 Gray Screw Cover Wireway Type 1 UL Listed Steel Knockouts ANSI 61 Gray |
| Wattage | Wattage | 65 | 65 | 65 | 45 |



Utility requirements for this equipment may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.

Utility requirements for this equipment may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.



200 Ampere Metered 2 to 6 Multi-Position Units With Breaker Provision



| | | | | | |
|-------------------------------|---|--|---|--------------------------------------|--|
| Catalog Number | TEST-CP3B11115A22 | TEST-CP3B11115ASS | TEST-CP3B11115A42 | TEST-MR-2SS | TEST-K1815 |
| UPC | 984572269699 | 984572243743 | 984572272941 | 984572199293 | 984572113398 |
| Marketing Product Description | Ring Type 100 Amperes 240 Volt 4 Terminal Main Circuit-breaker 16 Circuit Loadcenter 22k Mint Green | Ring Type 100 Amperes 240 Volt 4 Terminal Main Circuit-breaker 16 Circuit Loadcenter Stainless | Ring Type 100 Amperes 240 Volt 4 Terminal Main Circuit-breaker 16 Circuit Loadcenter 42k Mint Green | Sealing Ring Snap-lock Type | Fifth Terminal For Use With 2852-56 And 2862-66 Condo Series |
| Length (IN) | 17 | 17 | 17 | 7.065 | 1.92 |
| Width (IN) | 16 | 16 | 16 | 0.722 | 3.5 |
| Height (IN) | 48 | | 48 | 7.065 | 5 |
| Weight (LB) | 161 | | 186 | 0.09 | 0.33 |
| Brand Name | milbank | milbank | milbank | milbank | milbank |
| Type | Lay In Wireway | Lay In Wireway | Lay In Wireway | Lay In Wireway | Lay In Wireway |
| Special Features | Key Locking Cylinder Latch Provision | Key Locking Cylinder Latch Provision | Key Locking Cylinder Latch Provision | Key Locking Cylinder Latch Provision | Key Locking Cylinder Latch Provision |
| Application | Wireway | Wireway | Wireway | Wireway | Wireway |
| Standard | Non UL Listed | Type 1 | Type 1 | Type 12 | Non UL Listed |
| Cover Type | Clamp Cover | Hinge Cover | Screw Cover | Clamp Cover | Hinge Cover |
| Enclosure | Indoor Enclosure | Outdoor Enclosure | Outdoor Enclosure | Outdoor Enclosure | Indoor Enclosure |
| Nominal Cross Section | 8 | 87 | 54 | tets | Nominal Cross Section |



Utility requirements for this equipment may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.

Utility requirements for this equipment may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.



200 Ampere Metered 2 to 6 Multi-Position Units With Breaker Provision



| | | | | | |
|-------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|
| Straight Section Length | 8 | 87 | 54 | 65 | 45 |
| Non Hazardous Location | 78 | 87 | 45 | usa | Non Hazardous Location |
| Construction | 4 | 78 | 45 | 65 | Construction |
| Material | 316 Stainless Steel | 304 Stainless Steel | 316 Stainless Steel | 304 Stainless Steel | 304 Stainless Steel |
| Finish | ANSI 61 Gray Powder Coat Finish | ANSI 61 Gray Powder Coat Finish | ANSI 61 Gray Powder Coat Finish | ANSI 61 Gray Powder Coat Finish | ANSI 61 Gray Powder Coat Finish |
| Knockouts | True | False | True | False | False |
| Receptacle | Receptacle | Receptacle | Receptacle | Receptacle | Receptacle |



Utility requirements for this equipment may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.

Utility requirements for this equipment may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.

