

# Spring Framework

---

Olivier Liechti & Laurent Prévost  
COMEM Web Services

heig-vd

Haute Ecole d'Ingénierie et de Gestion  
du Canton de Vaud

# What is Spring Framework?

---

- It is a bunch **development libraries**: it provides various modules to develop software components.
- Unlike Java EE, it is **not** an **execution platform**: it **does not** provides an environment to deploy and bring these components “to live”.
- It is not exactly an **enterprise platform**, but it provides support for distributed transactions, security, integration, etc. **Same as J2EE.**
- **Separation of concerns**: "The developer takes care of the business logic. Spring modules take care of the systemic qualities". **Same as J2EE.**



[http://flickr.com/photos/decade\\_null/427124229/sizes/m/#cc\\_license](http://flickr.com/photos/decade_null/427124229/sizes/m/#cc_license)

# Spring Framework

- Spring Framework is not a single library. It's a bunch of libraries where you choose the ones you need (transitive dependencies are managed for you by tools like Maven).
- It brings the **Dependency Injection** also known as **Inversion of Control (IoC)**

*"The question is, what aspect of control are [they] inverting?" Martin Fowler posed this question about **Inversion of Control (IoC)** on his site in 2004. Fowler suggested renaming the principle to make it more self-explanatory and came up with **Dependency Injection**.*

<http://martinfowler.com/articles/injection.html>


- Provide various default implementations to solve problems without having to code them yourself. For example:
  - Spring Security offers Basic Authentication filter to allow your users to authenticate to your service via HTTP basic authentication.

- Spring Framework modules are libraries like any other library. It means that you can add one or more to your classpath and develop your app like any others.
  - Spring Framework modules provide bindings and integrations with most of Java EE Specs:
    - JPA, JMS, ...
- Out of the box, Spring Framework cannot run on its own. The application developed with Spring Framework modules must be deployed in an application server.
  - the container is the **environment** in which we run components;
  - the container **provides services** (transactions, security, etc.) that a Spring Framework can use through the binding modules;
  - the different containers present in Java EE are also available for Spring Framework. In fact, as you develop an app for a container with Spring libraries, you choose which container you want to use.

# Spring Framework Modules




## Spring Framework Runtime



# Spring Framework Modules



## Spring Framework Runtime




Main features that brings you **IoC** and **Dependency Injection**.

# Spring Framework Modules




## Spring Framework Runtime



# Spring Framework Modules



## Spring Framework Runtime






# Spring Framework Modules




## Spring Framework Runtime




# Spring Framework - Example of Integration

<http://docs.spring.io/spring-framework/docs/current/spring-framework-reference/html/overview.html#overview-modules>




# Spring Framework - Example of Integration

<http://docs.spring.io/spring-framework/docs/current/spring-framework-reference/html/overview.html#overview-modules>



# Spring Framework - Example of Integration

<http://docs.spring.io/spring-framework/docs/current/spring-framework-reference/html/overview.html#overview-modules>



# IoC - Dependency Injection

---

*In software engineering, **dependency injection** is a software **design pattern** that implements **inversion of control** for software libraries, where the caller **delegates** to an **external framework** the **control flow** of discovering and importing a service or software module.*

[http://en.wikipedia.org/wiki/Dependency\\_injection](http://en.wikipedia.org/wiki/Dependency_injection)

# IoC - Dependency Injection

---

**Container**

**Class A**

**Class B**


# IoC - Dependency Injection

---




# IoC - Dependency Injection

---







# IoC - Dependency Injection




# IoC - Dependency Injection




# IoC - Dependency Injection




# IoC - Dependency Injection




# IoC - Dependency Injection



# IoC - Dependency Injection




# IoC - Dependency Injection




# IoC - Dependency Injection

---







# IoC - Dependency Injection



# IoC - Dependency Injection



# IoC - Dependency Injection



# Dependency Injection in code with SF

---

```
package ch.heigvd.ptl.sample.ioc.sf;

import org.springframework.stereotype.Service;

@Service
public class ServiceBImpl {
    public String world() {
        return "World!";
    }
}
```

# Dependency Injection in code with SF

---

heig-vd

Haute Ecole d'Ingénierie et de Gestion  
du Canton de Vaud

```
package ch.epfl.lsc.sf;  
  
import org.springframework.stereotype.Service;  
  
@Service  
public class ServiceBImpl {  
    public String world() {  
        return "World!";  
    }  
}
```

Tell the framework  
that is a **service**.

# Dependency Injection in code with SF

```
package ch.heigvd.ptl.sample.ioc.sf;
```

```
import org.springframework.beans.factory.annotation.Autowired;  
import org.springframework.stereotype.Service;
```

```
@Service
```

```
public class ServiceAImpl {
```

```
    @Autowired
```

```
    private ServiceBImpl serviceB;
```

```
    public String hello() {
```

```
        return "Hello " + serviceB.world();
```

```
    }
```

```
}
```

```
package ch
```

```
import org
```

```
@Service
```

```
public class ServiceBImpl {
```

```
    public String world() {
```

```
        return "World!";
```

```
    }
```

```
}
```

Tell the framework  
that is a **service**.

# Dependency Injection in code with SF

```
package ch.heig.vd.sf;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Service;

@Service
public class ServiceAImpl {
    @Autowired
    private ServiceBImpl serviceB;

    public String hello() {
        return "Hello " + serviceB.world();
    }
}
```

Tell the framework  
that is also a  
**service**.

```
package ch.heig.vd.sf;

import org.springframework.stereotype.Service;

@Service
public class ServiceBImpl {
    public String world() {
        return "World!";
    }
}
```

Tell the framework  
that is a **service**.

# Dependency Injection in code with SF

```
package ch.heig.vd.sf;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Service;

@Service
public class ServiceAImpl {
    @Autowired
    private ServiceBImpl serviceB;

    public String world() {
        return "World!";
    }
}
```

Tell the framework  
that is also a  
**service**.

Tell the framework that  
Service A requires an  
instance of Service B.

```
package ch.heig.vd.sf;

import org.springframework.stereotype.Service;

@Service
public class ServiceBImpl {
    public String world() {
        return "World!";
    }
}
```

Tell the framework  
that is a **service**.



# Dependency Injection in code with SF

```
package ch.heig.vd.sf;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Service;

@Service
public class ServiceAImpl {
    @Autowired
    private ServiceBImpl serviceB;

    public String hello() {
        return serviceB.world();
    }
}
```

Tell the framework  
that is also a  
**service**.

Tell the framework that  
Service A requires an  
instance of Service B.

```
package ch.heig.vd.sf;

import org.springframework.stereotype.Service;

@Service
public class ServiceBImpl {
    public String world() {
        return "World!";
    }
}
```

Tell the framework  
that is a **service**.

`serviceAImpl.hello();`



Hello World!

# Dependency Injection in code for Java EE

heig-vd

Haute Ecole d'Ingénierie et de Gestion  
du Canton de Vaud

```
package ch.heigvd.ptl.sample.ioc.j2ee;

import javax.ejb.LocalBean;
import javax.ejb.Stateless;

@Stateless
@LocalBean
public class ServiceBImpl {
    public String world() {
        return "World!";
    }
}
```

# Dependency Injection in code for Java EE

heig-vd

Haute Ecole d'Ingénierie et de Gestion  
du Canton de Vaud

```
package ch.h...c.j2ee;  
  
import javax...  
import javax...  
  
@Stateless  
@LocalBean  
public class ServiceBImpl {  
    public String world() {  
        return "World!";  
    }  
}
```

Tell the container that  
is a **local stateless**  
session bean.

# Dependency Injection in code for Java EE

heig-vd

Haute Ecole d'Ingénierie et de Gestion  
du Canton de Vaud

```
package ch.heigvd.ptl.sample.ioc.j2ee;
```

```
import javax.ejb.EJB;  
import javax.ejb.LocalBean;  
import javax.ejb.Stateless;
```

```
@Stateless
```

```
@LocalBean
```

```
public class ServiceAImpl {  
    @EJB  
    private ServiceBImpl serviceB;  
  
    public String hello() {  
        return "Hello " + serviceB.world();  
    }  
}
```

```
package ch.heigvd.ptl.sample.ioc.j2ee;
```

```
import javax.ejb.EJB;  
import javax.ejb.Stateless;
```

```
@Stateless
```

```
@LocalBean
```

```
public class ServiceBImpl {  
    public String world() {  
        return "World!";  
    }  
}
```

Tell the container that  
is a **local stateless**  
session bean.

# Dependency Injection in code for Java EE

heig-vd

Haute Ecole d'Ingénierie et de Gestion  
du Canton de Vaud

```
package ch.heigvd.ptl.sample.ioc.j2ee;
```

```
import javax.  
import javax.  
import javax.
```

Tell the container that is  
also a **local stateless**  
session bean.

```
@Stateless  
@LocalBean
```

```
public class ServiceAImpl {  
    @EJB  
    private ServiceBImpl serviceB;  
  
    public String hello() {  
        return "Hello " + serviceB.world();  
    }  
}
```

```
package ch.heigvd.ptl.sample.ioc.j2ee;
```

```
import javax.  
import javax.
```

Tell the container that  
is a **local stateless**  
session bean.

```
@Stateless  
@LocalBean
```

```
public class ServiceBImpl {  
    public String world() {  
        return "World!";  
    }  
}
```

# Dependency Injection in code for Java EE

heig-vd

Haute Ecole d'Ingénierie et de Gestion  
du Canton de Vaud

```
package ch.heigvd.ptl.sample.ioc.j2ee;
```

```
import javax.  
import javax.  
import javax.
```

Tell the container that is  
also a **local stateless**  
session bean.

```
@Stateless  
@LocalBean
```

```
public class ServiceAImpl {
```

```
    @EJB
```

```
    private ServiceBImpl serviceB;
```

```
    public void world() {  
        serviceB.world();  
    }  
}
```

Tell the container that  
Service A requires an  
instance of Service B.

```
package ch.heigvd.ptl.sample.ioc.j2ee;
```

```
import javax.  
import javax.
```

Tell the container that  
is a **local stateless**  
session bean.

```
@Stateless  
@LocalBean
```

```
public class ServiceBImpl {
```

```
    public String world() {
```

```
        return "World!";
```

```
    }
```

```
}
```

# Dependency Injection in code for Java EE

```
package ch.heigvd.ptl.sample.ioc.j2ee;
```

```
import javax.  
import javax.  
import javax.
```

Tell the container that is also a **local stateless** session bean.

```
@Stateless  
@LocalBean
```

```
public class ServiceAImpl {
```

```
@EJB
```

```
private ServiceBImpl serviceB;
```

```
public void hello() {  
    serviceB.world();  
}
```

Tell the container that Service A requires an instance of Service B.

```
package ch.heigvd.ptl.sample.ioc.j2ee;
```

```
import javax.  
import javax.
```

Tell the container that is a **local stateless** session bean.

```
@Stateless  
@LocalBean
```

```
public class ServiceBImpl {
```

```
    public String world() {  
        return "World!";  
    }
```

```
serviceAImpl.hello();
```



Hello World!

# Why Spring Framework?

---

- Java EE need new ideas to enrich his specs
- Developers love alternatives
- Spring Source became a reference for various tools and libraries like Spring Security.
- Offers enrichment to develop web applications or enterprise applications.
- Allow integration with Java EE technologies (JPA, JMS, ...) in addition of the libraries used in the app.
- Can be deployed in application servers.
- Big community behind the various libraries that compose the Spring Framework.



# Spring Framework vs. Java EE

---

- Are they concurrent or complementary?
  - No answer like: “Yes” or “No”
  - In fact, they play well together but that really depends what you are building.
- It's really common to use Java EE and one or more libraries from Spring Framework (Ex: Spring Security, Spring MVC, ...)
- Big difference:
  - Java EE is a full package where you choose a profile type to develop your apps;
  - Spring Framework, you pick the libs you need to build what you need and no more.