Appendix A The Compiler Project

There are several general approaches for a compiler project in an academic course on compiler construction. One approach is to give detailed explanations and a complete implementation for a compiler for one source language but then concentrate the project around writing a compiler for a different source language. Another approach is to give explanations and a **partial** implementation for a compiler for a particular source language and then to concentrate the project around finishing the incomplete work and possibly extending the source language or targeting a different computer architecture. This book uses the latter approach.

The overall project of developing a compiler for CPRL is divided into 11 smaller projects (numbered 0-10) as described below. For most of the projects, the GitHub repository has lots of both complete and skeletal code to help you get started plus CPRL test programs that can be used to check your work. For each project you should test your compiler with both correct and incorrect CPRL programs as explained in the project descriptions.

Organizational Structure of the Compiler Project

It is useful to view the source code for the compiler project as being structured into four main organizational units (components) that we refer to as Common, CVM, Assembler, and CPRL. Each of these components has a primary top-level package, and some have one or two subpackages. There are explicit package dependencies among the organizational components as described below. Additionally, there are test classes that are not considered to be part of the main components. We view the test classes as being part of a fifth component named Test. While it is possible to define these components in terms of Java modules, the use of modules is not required for the compiler project.

Following is a description of the five organizational components for the compiler project.

1. The Common Component

This component contains two packages, edu.citadel.common and edu.citadel.common.util. Classes in this component are not directly tied to the CPRL programming language and therefore are useful on other compiler-related projects. Examples include classes such as Position, and Source, and BoundedBuffer defined in package edu.citadel.common, plus utility classes such as ByteUtil and CharUtil defined in package edu.citadel.common.util. This component has no dependencies on the other components.

2. The CVM Component

This component has only one package, edu.citadel.cvm. Two notable classes in this component are CVM, which implements the CPRL virtual machine, and Disassembler, which implements a disassembler for converting CVM object code into CVM assembly language. This component has a dependency only on classes in the Common component as described in item 1 above.

3. The Assembler Component

This component is comprised of three packages, edu.citadel.assembler, edu.citadel.assembler.ast, and edu.citadel.assembler.optimize. The classes in this component implement an assembler for CVM assembly language. The assembler optionally performs several standard optimizations, such as converting an "ADD 1" instruction to an "INC" instruction. This component has a dependency on both the Common and CVM components as described in items 1 and 2 above.

4. The CPRL Component

This component contains the classes that implement the CPRL compiler. There are two packages, edu.citadel.cprl and edu.citadel.cprl.ast. Complete source code is provided for the other three components described above, but only portions of the source code are provided for this component. Although students will need to refer occasionally to classes in the other three components in order to understand the roles those classes play in developing the CPRL compiler, all new development will take place only in this component. Classes in the CPRL component depend only on classes in the Common and CVM component, but it has no dependency on classes the Assembler component; however, knowledge of CVM assembly language is required.

5. The Test Component

There are three classes in this component, class TestSource in package test.common and classes TestScanner and TestParser in package test.cprl. You will use these classes to test your work in the first few projects.

Overview of the Book's GitHub Repository

In addition to the standard license and readme files, the top level of the GitHub Repository at https://github.com/SoftMoore/CPRL-Java-4th contains four directories (a.k.a. folders). The Book directory contains PDF documents of several sections from this book including the Table of Contents, the Preface, and Appendix A. The Handouts directory contains several useful handouts. The PowerPoint directory contains PowerPoint slides that could be useful for college instructors who adopt this book as a course textbook. The slides correspond directly to the book chapters. The Project directory contains all files used for the compiler projects, as described below.

Warning: Several of the source files in the Project directory for latter projects are replacements or enhancements for the same files in earlier projects. For example, there are three versions of class Parser and two versions of class IdTable. Don't try to download the source files and import all of them at the same time into the IDE for your compiler project. Follow the project instructions for each project in the order presented.

Project 0: Getting Started

• This is not a real project but more of an initialization of your working environment for the remaining compiler projects. Expand the green "Code" button on the GitHub Repository page, download the repository as a zip file, and unzip it into a directory on your computer. Under the Project directory you will see 9 subdirectories as follows.

```
Project
- bin
- examples
- src-Assembler
- src-CVM
- src-Compiler
- src-ParserV1
- src-ParserV2
- src-ParserV3
- src-Scanner
```

Directories with names beginning "src..." contain Java source files for the compiler project.

• Directory bin contains sample Bash shell scripts and Windows command scripts for running and testing various stages of the compiler. There are two subdirectories named "bash" and "windows" that contain the Bash and Windows script files, respectively. For each Windows ".cmd" script file there is a corresponding Bash script file without the ".cmd" suffix; e.g., cprlc.cmd and cprlc. Pick the collection of script files for your operating system and programming environment.

As an example of the contents of bin for Windows, there is a script cprlc.cmd that will run the CPRL compiler on a source file whose name is entered via standard input. Similarly, there is a script assemble.cmd for running the assembler on ".asm" files, a script disassemble.cmd for running the disassembler on ".obj" files, and a script cprl.cmd for executing a single compiled/assembled CPRL program on the CVM.

The following will compile all CPRL source files in the current working directory.

```
cprlc *.cprl
```

There are two scripts for testing correct programs. Script testCorrect.cmd can be used to test a single CPRL program, and script testCorrect_all.cmd can be used to test all CPRL programs in the current directory. Both test scripts execute ".obj" files on the CVM and compare the output with expected output. Starting with Project 6 you can also use script testIncorrect_all.cmd to compile all incorrect CPRL programs in the current directory and compare the results to the expected results.

Additionally, there are script files for testing the scanner and parser in the earlier projects.

You will need to edit the file cprl_config.cmd for Windows (or cprl_config for bash) so that the COMPILER_PROJECT_PATH variable "points to" the directories on your computer containing the Java class files for your project.

Most of the other script files use cprl_config.cmd to set the classpath appropriately. For example, my personal setup for Java uses an Eclipse workspace with source files structured in directories based on package names under a "src" subdirectory and class files structured similarly under a "bin" subdirectory. For example; the source code for Parser.java is in subdirectory src\edu\citadel\cprl., and the corresponding class file Parser.class in in subdirectory bin\edu\citadel\cprl. When cprl_config.cmd is executed, it sets COMPILER_PROJECT_PATH to include the bin directory.

Also, you will need to ensure that the directory containing the script files is included in your PATH environment variable so that the operating system can find them when you enter their names on the command line.

You can set the global PATH environment variable permanently for your computer, or you can either execute setPath.cmd (Windows) or source setPath (bash) as appropriate to set the PATH environment variable temporarily for the current terminal session. For windows, simply change to the Windows subdirectory of project folder bin and execute setPath.cmd. For Linux, change to the Bash subdirectory of project folder bin and execute either "source setPath" or ". setPath".

- Directory examples contains examples of correct and incorrect CPRL programs that
 can be used to test various parts of your compiler. There are three subdirectories of
 examples as follows.
 - Subdirectory Correct contains numerous correct CPRL programs. The programs are organized into five subdirectories for testing different projects as you progress though the compiler implementation. For example, there is a subdirectory containing only test programs for CPRL/0, the zero subset of CPRL (no subprograms or composite types) as outlined in Project 6 below. Testing should be performed cumulatively; i.e., you should always retest the CPRL/0 example programs when working on later projects to ensure that you haven't introduced an error that would cause one of the CPRL/0 programs to fail.
 - Subdirectory Incorrect contains numerous incorrect CPRL programs that will be used for testing error detection and recovery. Similar to the correct programs, these programs are organized into five subdirectories for testing different projects as you progress through the compiler implementation.

Subdirectory ScannerTests contains both correct and incorrect files that can be
used for testing your scanner as described in Project 1 below. These are not
necessarily complete CPRL programs. For example, one of the files contains every
valid symbol in CPRL including all reserved words, all operators, and numerous
programmer-defined identifiers and literals.

You are strongly encouraged to develop additional CPRL test programs as you work though the remaining projects described below.

- Directory src-Common contains the source code for the Common component as described above. These classes are used by the other three components, and they are potentially reusable on other compiler projects. All classes in this directory are complete and require no additional work for use on the compiler project. Import the Java source code for this component into your preferred IDE for Java (e.g., Eclipse or IntelliJ IDEA). All code should compile without any errors.
- Directory src-CVM contains classes that implement the CVM, the virtual machine that will be used on subsequent projects to run CPRL programs. These classes are described in the CVM component above. All classes in this directory are complete and require no additional work for use on the compiler project. Import the Java source code for this component into your preferred IDE for Java (e.g., Eclipse or IntelliJ IDEA). All code should compile without any errors.
- Directory src-Assembler contains classes that implement an assembler for CVM assembly language. You will run the assembler on assembly language files generated by your compiler to create machine code files that can be executed on the CVM. These classes are described in the assembler component above. All classes in this directory are complete and require no additional work for use on the compiler project. Import the Java source code for this module into your preferred IDE for Java (e.g., Eclipse or IntelliJ IDEA). All code should compile without any errors.
- To check that source code has been imported successfully and that scrips have been edited correctly, let's test class Source as described in Section 5.2. Directory src-Common contains a test driver named TestSource in package test.common that can be used together with the testSource.cmd (or testSource for bash) script file to "wrap" class Source and run it on any text file. Run testSource.cmd (or testSource) on the file Source.java.

Project 1: Scanner

- Using the concepts from Chapter 5, implement a scanner for CPRL.
- Import the source files from directory src-Scanner into your preferred IDE. Directory src-Scanner contains several classes in package edu.citadel.cprl. It has complete implementations for classes Symbol and Token plus a partial implementation of class Scanner. Directory src-Scanner also contains a test driver named TestScanner in package test.cprl that can be used together with the testScanner.cmd (or

testScanner for bash) script file to "wrap" your scanner and run it against the scanner example test files.

- Complete the implementation for class Scanner.
- Test your scanner with the scanner-specific test examples and multiple correct CPRL examples.

Project 2: Language Recognition

- Using the concepts from Chapter 6, implement a parser that performs language recognition for the full CPRL language (not just the zero subset) based on the language definition and context-free grammar given in Chapter 4, Appendix C, and Appendix D.
- Import the source files from directory src-ParserV1 into your preferred IDE. Directory src-ParserV1 contains complete implementations of classes IdType, IdTable, ScopeLevel, and Scope in package edu.citadel.cprl as described in Chapter 6, and it contains a partial implementation of class Parser that performs only language recognition. Directory src-ParserV1 also contains a test driver named TestParser in package test.cprl that can be used together with the script file testParser.cmd (or testParser for bash) to "wrap" both your scanner and parser together and run them against the example test files. The "incorrect" example subdirectories contain text files showing the results that you should expect when running this version of the parser against the incorrect test examples.
- Complete the implementation for class Parser.
- Do not implement error recovery for this project; i.e., when an error is encountered, simply report the error and exit compilation as described in Chapter 6. Some of the parser methods are fully implemented; study those as examples as guides for the incomplete parser methods.
- Test with all correct and incorrect examples. At this point the parser should accept all correct programs and reject all incorrect programs **except** those with type errors and/or miscellaneous errors. Detection of type errors and miscellaneous errors will be implemented in subsequent projects. Use the text files showing expected results as guides.

Project 3: Error Recovery

- Using the concepts from Chapter 7, add error recovery to your parser.
- Directory src-ParserV2 contains only one class in package edu.citadel.cprl, a partial implementation of class Parser that demonstrates how to add error recovery to the parser methods. Do **not** import this class into your IDE since you already have an implementation for class Parser. Instead, use the class provided in this directory as a guide to manually edit your existing parser in order to add error recovery. Use the test driver and script files from the previous project to run your parser against the example test programs. The "incorrect" example subdirectories contain text files showing the

results that you should expect when running this version of the parser against the incorrect test examples.

- Edit your parser from the previous project to implement error recovery as described in Chapter 7.
- Test with all correct and incorrect examples. At this point the parser should accept and reject exactly the same example programs as for the previous project, but this time your parser should report more than one error for some of the incorrect programs. Use the text files showing expected results as guides.

Project 4: Abstract Syntax Trees

- Using the concepts from Chapter 8, add generation of abstract syntax trees to your
 parser. Most parsing methods should return AST objects or lists of AST objects. From
 now on we will start referring to our implementation as a "compiler" even though it
 doesn't yet generate code.
- Directory src-ParserV3 contains full or partial implementations of more than 40 AST classes in package edu.citadel.cprl.ast. Approximately half of the AST classes are implemented completely, while the remaining AST classes have only partial implementations. You should import the AST classes into your IDE. For now there are empty bodies or partially incomplete bodies for methods checkConstraints() and emit() in the AST classes that are not fully implemented.

Directory src-ParserV3 also contains full or partial implementations of several classes in package edu.citadel.cprl as follows.

- A complete implementation for class Compiler. For this project we will continue to use TestParser, but in the next project you will start using class Compiler instead of TestParser to test your work.
- Complete implementations for classes LoopContext and SubprogramContext. As described in Chapter 8, these classes are used to track entry to and exit from loops and subprograms. Use LoopContext when parsing loop statements and exit statements. Use SubprogramContext when parsing procedure declarations, function declarations, and return statements.
- Complete implementations for classes Scope and IdTable. As described in Chapter 8, IdTable now stores scopes with references to an identifier's declaration. These two classes replace the implementations of Scope and IdTable that we have been using in the previous two projects. Use the complete version of IdTable to check for declaration and scope errors. With this new implementation for IdTable your parser will now be able to detect additional scope errors when we implement subprograms in Project 7.
- A complete implementation for class Type and implementations for its subclasses ArrayType, StringType, and RecordType. The implementations for these three subclasses will compile, but at this point they are not correct. You will correct the implementations for these three classes as part of projects 8, 9, and 10. The correct

- implementations for ArrayType, StringType, and RecordType are straightforward after studying the relevant chapters in the book; i.e., Chapters 14, 15, and 16.
- A partial implementation for class Parser. As described in Chapter 8, most parsing methods now return AST objects or a lists of AST objects. Do **not** import this class into your IDE since you already have an implementation for class Parser. Instead, use the class provided in this directory as a guide to manually edit your existing parser in order to add generation of AST classes.
- Edit your parser from the previous project to add generation of AST classes or lists of AST classes.
- Test your parser with all correct and incorrect examples. The "incorrect" example subdirectories contain text files showing the results that you should expect when running this version of the parser against the incorrect test examples. The major differences in test results between versions 2 and 3 of your parser are that version 3 should also detect exit statements that are not nested within loops.

Project 5: Constraint Analysis for CPRL/0

- Using the concepts from Chapter 9, implement checkConstraints() methods in the AST classes to perform full constraint analysis for the CPRL/0 subset (everything except subprograms and composite types). In addition to the syntax and scope errors previously detected by your compiler, your compiler should also detect all type and miscellaneous errors for the CPRL/0 subset. For this project, do not implement any constraint checks for class Variable. All constraint checks for class Variable involve arrays, strings, or records, which will be covered in subsequent chapters.
- Test with all correct and incorrect CPRL/0 examples. Henceforth you will use Compiler rather than TestParser to test your implementation with the CPRL examples. To invoke the compiler, use script cprlc.cmd or cprlc as appropriate, depending on whether you are developing in a Windows or bash environment. This script is designed to use class Compiler. Recall that you can use "cprlc *.cprl" to compile all files in the current directory. At this point the compiler should accept all correct CPRL/0 examples and reject all incorrect CPRL/0 examples. The "incorrect" example subdirectories contain text files showing the results that you should expect when running this version of the parser against the incorrect test examples.

Here are some tips for working on the remaining projects.

You will eventually want to run the scripts testCorrect_all and testIncorrect_all in the appropriated examples subdirectory, but start by running cprlc *.cprl.

For correct programs, if you don't get a clean compile, then work on each problem example separately. Compile individual examples using something similar to cprlc Correct_101.cprl.

Once you get a clean compile on every file, do the same thing with script assemble; i.e., start with assemble *.asm and use assemble Correct_101.asm (or similar) as needed. If there are problems, compare the .asm files you are generating to the .asm files downloaded from the book's GitHub repository. You can re-download the examples in the event that you overwrote yours when testing your compiler and didn't save copies in a different location.

Once you get a clean compile and a clean assemble, you can run the example's .obj file using something like cprl Correct_101.obj, or you can simply run testCorrect Correct_101.

Project 6: Code Generation for CPRL/0

- Using the concepts from Chapter 11, implement emit() methods in the AST classes to perform code generation for CPRL/0. At this point you are actually generating assembly language for the CVM.
- Use the assembler provided in the Assembler module (see Project o above) and script file assemble.cmd (assemble for bash) to generate machine code for all correct CPRL/0 examples.
- Use script files cprl.cmd, testCorrect.cmd, and testCorrect_all.cmd (or bash equivalents) to run and test all correct CPRL/0 examples. Use script file testIncorrect_all.cmd (or bash equivalent) to test all incorrect CPRL/0 examples.

Project 7: Subprograms

- Using the concepts from Chapter 13, add constraint analysis and code generation for subprograms.
- Correct any remaining errors.
- Test all correct and incorrect Subprogram examples. Retest all correct and incorrect examples from CPRL/0.

Project 8: Arrays

- Using the concepts from Chapter 14, add constraint analysis and code generation for arrays.
- Correct the implementation for class ArrayType plus any remaining errors.
- Test all correct and incorrect Arrays examples. Retest all correct and incorrect examples from CPRL/0 and Subprograms.

Project 9: Strings

- Using the concepts from Chapter 15, add constraint analysis and code generation for strings. Most of the work involved in implementing strings is already provided in the GitHub repository, so this project is relatively simple. Depending on student backgrounds and course prerequisites, instructors might elect to make this the last project and assign project 10 as a reading assignment.
- Correct the implementation for StringType plus any remaining errors.
- Test all correct and incorrect Strings examples. Retest all correct and incorrect examples from CPRL/0, Subprograms, and Arrays.

Project 10: Records

- Using the concepts from Chapter 16, add constraint analysis and code generation for records. Completion of this project results in the final version of your compiler.
- Correct the implementation for RecordType plus any remaining errors.
- Test all correct and incorrect Records examples. Retest all correct and incorrect examples from CPRL/0, Subprograms, Arrays, and Strings.