

Abstract Syntax Trees

©SoftMoore Consulting

Slide 1

1

Abstract Syntax Trees

- We will modify our parser one more time so that, as it parses the source code, it will also generate an intermediate representation of the program known as abstract syntax trees.
- An abstract syntax tree is similar to a parse tree but without extraneous nonterminal and terminal symbols.
- Abstract syntax trees provide an explicit representation of the structure of the source code that can be used for
 - additional constraint analysis (e.g., for type constraints)
 - some optimization (tree transformations)
 - code generation

©SoftMoore Consulting

Slide 2

2

Representing Abstract Syntax Trees

- We will use different classes to represent different node types in our abstract syntax trees. Examples include
 - Program
 - AssignmentStmt
 - Variable
 - ProcedureDecl
 - LoopStmt
 - Expression
- Each AST class has named instance variables (fields) to reference its children. These instance variables provide the “tree” structure.
- Occasionally we also include additional fields to support error handling (e.g., position) and code generation.

Terence Parr refers to this type of AST structure as an irregular (named child fields) heterogeneous (different node types) AST.


©SoftMoore Consulting

Slide 3

3

Abstract Syntax Trees: Example 1

- Consider the grammar for an assignment statement.
assignmentStmt = variable “:=” expression “;” .
- The important parts of an assignment statement are
 - variable (the left side of the assignment)
 - expression (the right side of the assignment)
- We create an AST node for an assignment statement with the following structure:



©SoftMoore Consulting

Slide 4

4

Class AssignmentStmt

```

class AssignmentStmt(private val variable : Variable,
                    private val expr : Expression,
                    private val assignPosition : Position)
: Statement()
{
  ...
}
  
```

position of assignment operator
(for error reporting)


©SoftMoore Consulting

Slide 5

5

Abstract Syntax Trees: Example 2

- Consider the following grammar for a loop statement:
loopStmt = (“while” booleanExpr)?
“loop” statements “end” “loop” “;” .
- Once a loop statement has been parsed, we don’t need to retain the nonterminal symbols. The AST for a loop statement would contain only the statements in the body of the loop and the optional boolean expression (e.g., the reference to the boolean expression could be null).



©SoftMoore Consulting

Slide 6

6

Class LoopStmt

```
class LoopStmt : Statement()
{
    var whileExpr : Expression? = null
    var statements : List<Statement> = emptyList()
    ...
}
```

Note that whileExpr can be null.

©SoftMoore Consulting

Slide 7

7

Abstract Syntax Trees: Example 3


- For binary expressions, part of the grammar exists simply to define operator precedence.
- Once an expression has been parsed, we do not need to preserve additional information about nonterminals that were introduced to define precedence (relation, simpleExpr, term, factor, etc.).
- A binary expression AST would contain only the operator and the left and right operands. The parsing algorithm would build the AST so as to preserve operator precedence.

©SoftMoore Consulting

Slide 8

8

Abstract Syntax Trees: Example 3 (continued)



©SoftMoore Consulting

Slide 9

9

Class BinaryExpr

```
abstract class BinaryExpr(val leftOperand : Expression,
    val operator : Token,
    val rightOperand : Expression)
    : Expression(operator.position)
```

©SoftMoore Consulting

Slide 10

10

Structure of Abstract Syntax Trees

- There is an abstract class AST that serves as the superclass for all other abstract syntax tree classes.
- Class AST contains implementations of methods common to all subclasses plus declarations of abstract methods required by all concrete subclasses.
- All AST classes will be defined in an "...ast" subpackage.

Note the use of AST (in monospaced font) for the specific class and AST (in normal font) as an abbreviation for "abstract syntax tree".

©SoftMoore Consulting

Slide 11

11

Outline of Class AST

```
abstract class AST
{
    ...

    /** Check semantic/contextual constraints. */
    abstract fun checkConstraints()

    /** Emit the object code for the AST. */
    abstract fun emit()
}
```

Methods checkConstraints() and emit() provide a mechanism to "walk" the tree structure using recursive calls to subordinate tree nodes.

©SoftMoore Consulting

Slide 12

12

Subclasses of AST

- We will create a hierarchy of classes, some of which are abstract, that are all direct or indirect subclasses of AST.
- Each node in the abstract syntax tree constructed by the parser will be an object of a class in the AST hierarchy.
- Most classes in the hierarchy will correspond to and have names similar to the nonterminal symbols in the grammar, but not all abstract syntax trees have this property. See, for example, the earlier discussion about binary expressions. We do not need abstract syntax tree classes corresponding to nonterminals `simpleExpr`, `term`, `factor`, etc.

©SoftMoore Consulting

Slide 13

13

Using Collection Classes

- Some parsing methods simply return lists of AST objects.

Examples

```
fun parseInitialDecls() : List<InitialDecl>
fun parseSubprogramDecls() : List<SubprogramDecl>
fun parseIdentifiers() : List<Token>
fun parseStatements() : List<Statement>
fun parseFormalParameters() : List<ParameterDecl>
fun parseExpressions() : List<Expression>
fun parseActualParameters() : List<Expression>
```

©SoftMoore Consulting

Slide 14

14

Naming Conventions for AST

- Most AST classes have names similar to nonterminals in the grammar.
 - Program - FunctionDecl
 - AssignmentStmt - LoopStmt
- The parsing method for that nonterminal will create the corresponding AST object.
 - `parseProgram` returns a `Program` object
 - `parseLoopStmt` returns a `LoopStmt` object
 - etc.
- Parsing methods with plural names will return lists of AST objects.
 - the grammar was written to have this property.

©SoftMoore Consulting

Slide 15

15

Naming Conventions for AST (continued)

Example

```
abstract class Statement : AST() ...
class LoopStmt : Statement() ...
```

- The parsing method `parseLoopStmt()` would be responsible for creating the AST node for `LoopStmt`. Instead of returning `void`, method `parseLoopStmt()` will return an object of class `LoopStmt`.
- Similarly, the parsing method `parseStatements()` will return a list of `Statement` objects, where each `Statement` object is either an `AssignmentStmt`, a `LoopStmt`, an `IfStmt`, etc.

©SoftMoore Consulting

Slide 16

16

Method `parseLiteral()`

- Method `parseLiteral()` is a special case.
- Since literals are tokens returned from the scanner, method `parseLiteral()` simply returns a `Token`. There is no AST class named `Literal`.
- Relevant Grammar Rules


```
literal = intLiteral | charLiteral | stringLiteral
        | booleanLiteral .
booleanLiteral = "true" | "false" .
```
- Method



```
fun parseLiteral() : Token?
// returns null if parsing fails
```

©SoftMoore Consulting

Slide 17

17

Partial AST Inheritance Diagram for the Language CPRL

(names for abstract classes are shown in *italics*)

©SoftMoore Consulting

Slide 18

18

Language Constraints Associated With Identifiers

- A parser built using only the set of parsing rules will not reject programs that violate certain language constraints such as "an identifier must be declared exactly once".
- Examples: Valid syntax but not valid with respect to contextual constraints

```
var x : Integer;      var c : Char;
begin                begin
  y := 5;              c := -3;
end.                  end.
```

©SoftMoore Consulting

Slide 19

19

Class IdTable

- We will extend class IdTable to help track not only of the types of identifiers that have been declared, but also of their declarations.
- Class Declaration is part of the AST hierarchy. A declaration object contains a reference to the identifier token and information about its type. We will use different subclasses of Declaration for kinds of declarations; e.g., ConstDecl, VarDecl, ProcedureDecl, etc.

©SoftMoore Consulting

Slide 20

20

A Property and Selected Methods in the Modified Version of IdTable

```
/**
 * The current scope level.
 */
val scopeLevel : ScopeLevel ← ScopeLevel is an enum
                                class with only two values,
                                PROGRAM and SUBPROGRAM.

/**
 * Opens a new scope for identifiers.
 */
fun openScope()

/**
 * Closes the outermost scope.
 */
fun closeScope()
```

©SoftMoore Consulting

Slide 21

21

A Property and Selected Methods in the Modified Version of IdTable (continued)

```
/**
 * Add a declaration at the current scope level.
 * @throws ParserException if the identifier token associated
 * with the declaration is already
 * defined in the current scope.
 */
fun add(decl : Declaration)

/**
 * Returns the Declaration associated with the identifier
 * token's text. Returns null if the identifier is not found.
 * Searches enclosing scopes if necessary.
 */
operator fun get(idToken : Token) : Declaration?
```

©SoftMoore Consulting

Slide 22

22

Adding Declarations to IdTable

- When an identifier is declared, the parser will attempt to add the declaration to the table within the current scope. (The declaration already contains the identifier token.)
 - throws an exception if a declaration with the same name (same token text) has been previously declared in the current scope.

- Example (in method parseConstDecl())

```
val constId = scanner.token
...
val constDecl = ConstDecl(constId, constType, literal)
idTable.add(constDecl) ←
```

Throws a ParserException if the
identifier token constId is already
defined in the current scope

©SoftMoore Consulting

Slide 23

23

Interface NamedDecl

- Identifiers declared using VarDecl (which we convert to a list of SingleVarDecl as described later) or ParameterDecl have similar uses within CPRL; e.g.,


```
x := y;
```
- Variable x could have been declared in a variable declaration or a parameter declaration.
 - similarly for the named value y
- There is a need to treat both types of declarations uniformly at several points during parsing, which we achieve by creating interface NamedDecl and specifying that SingleVarDecl and ParameterDecl implement this interface.

©SoftMoore Consulting

Slide 24

24

Interface NamedDecl (continued)

- Four properties in interface NamedDecl

```
val type : Type
val size : Int
val scopeLevel : ScopeLevel
var relAddr : Int
```

©SoftMoore Consulting

Slide 25

25

Example: Using Interface NamedDecl

```
// excerpt from parseStatement()
when (scanner.symbol)
{
    Symbol.identifier ->
    {
        val decl = idTable[scanner.token]

        if (decl != null)
        {
            if (decl is NamedDecl)
                stmt = parseAssignmentStmt()
            ...
        }
        ...
    }
}
```

©SoftMoore Consulting

Slide 26

26

Using IdTable to Check Applied Occurrences of Identifiers

- When an identifier is encountered in the statement part of the program or a subprogram (e.g., as part of an expression or subprogram call), the parser will
 - check that the identifier has been declared
 - use the information about how the identifier was declared to facilitate correct parsing (e.g., you can't assign a value to an identifier that was declared as a constant.)

©SoftMoore Consulting

Slide 27

27

Using IdTable to Check Applied Occurrences of Identifiers (continued)

- Example (in method parseVariableExpr())


```
val idToken = scanner.token
match(Symbol.identifier)
val decl = idTable[idToken]

if (decl == null)
    throw error("Identifier \"$idToken\" has not "
        + "been declared.")
else if (decl !is NamedDecl)
    throw error("Identifier \"$idToken\" is not "
        + "a variable.")
```

©SoftMoore Consulting

Slide 28

28

Types in CPRL

- The compiler uses two classes to provide support for CPRL types.
- Class Type encapsulates the language types and their sizes.
 - Predefined types are declared as constants in the companion object.
 - Class Type also contains a method that returns the type of a literal symbol.


```
fun getTypeOf(literal : Symbol): Type
```
- Class ArrayType extends Type to provide additional support for arrays.

©SoftMoore Consulting

Slide 29

29

Class Type

- Class Type encapsulates the language types and sizes (number of bytes) for the programming language CPRL.
- Type sizes are initialized to values appropriate for the CPRL virtual machine.
 - 4 for Integer
 - 1 for Boolean
 - 2 for Character
 - etc.
- Predefined types are declared in the companion object.


```
val Boolean = Type("Boolean", Constants.BYTES_PER_BOOLEAN)
val Integer = Type("Integer", Constants.BYTES_PER_INTEGER)
val Char = Type("Char", Constants.BYTES_PER_CHAR)
val String = Type("String")
val Address = Type("Address", Constants.BYTES_PER_ADDRESS)
val UNKNOWN = Type("UNKNOWN")
```

©SoftMoore Consulting

Slide 30

30

Class ArrayType

- Class `ArrayType` extends class `Type`.
 - therefore array types are also types
- In addition to the total size of the array, class `ArrayType` also keeps track of the number and type of elements.


```
class ArrayType(typeName : String, val numElements : Int,
               val elementType : Type)
    : Type(typeName, numElements*elementType.size)
```
- When the parser parses an array type declaration, the constructor for AST class `ArrayTypeDecl` creates an `ArrayType` object.

©SoftMoore Consulting

Slide 31

31

Example: Parsing a ConstDecl

```
/**
 * Parse the following grammar rule:
 * `constDecl = "const" constId ":@" literal ";"`
 *
 * @return the parsed constant declaration.
 * Returns null if parsing fails.
 */
fun parseConstDecl() : ConstDecl?
{
    try
    {
        match(Symbol.constRw)
        val constId = scanner.token
        match(Symbol.identifier)
    }
}
```

(continued on next slide)

©SoftMoore Consulting

Slide 32

32

Example: Parsing a ConstDecl (continued)

```
match(Symbol.assign)
val literal = parseLiteral()
match(Symbol.semicolon)

var constType = Type.UNKNOWN
if (literal != null)
    constType = Type.getTypeOf(literal.symbol)

val constDecl = ConstDecl(constId, constType, literal)
idTable.add(constDecl)
return constDecl
}
```

(continued on next slide)

©SoftMoore Consulting

Slide 33

33

Example: Parsing a ConstDecl (continued)

```
catch (e : ParseException)
{
    ErrorHandler.reportError(e)
    recover(initialDeclFollowers)
    return null
}
```

©SoftMoore Consulting

Slide 34

34

The Scope Level of a Variable Declaration

- During code generation, when a variable or named value is referenced in the statement part of a program or subprogram, we need to be able to determine where the variable was declared.
- Class `IdTable` contains a property named `scopeLevel` that returns the block nesting level for the current scope.
 - PROGRAM for objects declared at the outermost (program) scope.
 - SUBPROGRAM for objects declared within a subprogram.
- When a variable is **declared**, the declaration is initialized with the current level.


```
val varDecl = VarDecl(identifiers, varType, idTable.scopeLevel)
```

©SoftMoore Consulting

Slide 35

35

Example: Scope Levels

```
var x : Integer; // scope level of declaration is PROGRAM
var y : Integer; // scope level of declaration is PROGRAM

procedure p is // scope level of declaration is PROGRAM
    var x : Integer; // scope level of declaration is SUBPROGRAM
    var b : Integer; // scope level of declaration is SUBPROGRAM
begin
    ... x ... // x was declared at SUBPROGRAM scope
    ... b ... // b was declared at SUBPROGRAM scope
    ... y ... // y was declared at PROGRAM scope
end p;

begin
    ... x ... // x was declared at PROGRAM scope
    ... y ... // y was declared at PROGRAM scope
    ... p ... // p was declared at PROGRAM scope
end.
```

©SoftMoore Consulting

Slide 36

36

VarDecl versus SingleVarDecl

- A variable declaration can declare several identifiers all with the same type, as in

```
var x, y, z : Integer;
```
- This declaration is logically equivalent to declaring each variable separately, as in

```
var x : Integer;
var y : Integer;
var z : Integer;
```
- To simplify constraint checking and code generation, within the AST we will view a variable declaration as a collection of single variable declarations.

©SoftMoore Consulting

Slide 37

37

Class SingleVarDecl

```
class SingleVarDecl(identifier : Token, varType : Type,
    override val scopeLevel : ScopeLevel)
    : InitialDecl(identifier, varType), NamedDecl
{
    ...
}
```

©SoftMoore Consulting

Slide 38

38

Class VarDecl

```
class VarDecl(identifiers : List<Token>, varType : Type,
    scopeLevel : ScopeLevel)
    : InitialDecl(Token(), varType)
{
    // the list of single var decls for the variable declaration
    val singleVarDecls =
        ArrayList<SingleVarDecl>(identifiers.size)

    init
    {
        for (id in identifiers)
            singleVarDecls.add(SingleVarDecl(id, varType,
                scopeLevel))
    }
}
```

A VarDecl is simply a list of SingleVarDecls.

©SoftMoore Consulting

Slide 39

39

Method parseInitialDecls()

- Method `parseInitialDecls()` constructs/returns a list of initial declarations.
- For constant and array type declarations, this method simply adds them to the list.
- For variable declarations (VarDecls), this method extracts the list of single variable declarations (SingleVarDecls) and adds them to the list. The original VarDecl is no longer used after this point.

©SoftMoore Consulting

Slide 40

40

Method parseInitialDecls() (continued)

```
...

val decl = parseInitialDecl()

if (decl is VarDecl)
{
    // add the single variable declarations
    for (singleVarDecl in decl.singleVarDecls)
        initialDecls.add(singleVarDecl)
}
else if (decl != null)
    initialDecls.add(decl)
```

©SoftMoore Consulting

Slide 41

41

Structural References versus Nonstructural References

- Most of the properties of AST classes represent structural references in that they correspond to the edges of the "tree".
 - Class Program has a reference its declarative part and its statement part.
 - Class BinaryExpr has references its left operand, its operator, and its right operand.
- Some AST classes have properties that do not correspond to the edges of the "tree".
 - Class Variable has a reference back to its declaration. Similarly for class NamedValue.
 - Class ExitStmt has a reference its enclosing loop statement.
- These nonstructural references are used during constraint analysis and code generation.

©SoftMoore Consulting

Slide 42

42


Example: Abstract Syntax Tree

```
var x : Integer;
begin
  x := 5;
  writeln x;
end.
```

(AST for this example is on the next slide.)

43

Example: Abstract Syntax Tree (continued)



44

Determining Types of Expressions

- Since CPRL is statically typed, it is possible to determine the type of every expression at compile time, and AST class Expression has a property for the expression type that is inherited by all expression subclasses.
- Where within the compiler should type determination take place? In general, we will determine the type of an expression in the constructor for the expression's AST class.

©SoftMoore Consulting

Slide 45

45

Example: RelationalExpr

- A relational expression is a binary expression where the operator is a relational operator such as "<=" or ">".
- Regardless of the types of the two operands, a relational expression always has type Boolean.

©SoftMoore Consulting

Slide 46

46

Example: RelationalExpr (continued)

- Constructor for RelationalExpr


```
class RelationalExpr(leftOperand : Expression,
                    operator : Token,
                    rightOperand : Expression)
  : BinaryExpr(leftOperand, operator, rightOperand)
  {
    /**
     * Initialize the type of the expression to Boolean.
     */
    init
    {
      type = Type.Boolean
    }
    ...
  }
```

©SoftMoore Consulting

Slide 47

47

Example: AddingExpr

- For most "real" programming languages, determining the type of an adding expression can be somewhat complicated.
 - C and Java have multiple numeric types with rules about automatic conversions (coercions) when an operator has different operand types.
- In CPRL, an adding expression always has type Integer. (Similarly for a multiplying expression in CPRL.)

©SoftMoore Consulting

Slide 48

48

Example: AddingExpr (continued)

- Constructor for AddingExpr

```
class AddingExpr(leftOperand : Expression,
                operator   : Token,
                rightOperand : Expression)
  : BinaryExpr(leftOperand, operator, rightOperand)
{
  /**
   * Initialize the type of the expression to Boolean.
   */
  init
  {
    type = Type.Boolean
  }
  ...
}
```

©SoftMoore Consulting

Slide 49

49

Example: Variable

- The type for a variable (and therefore also for a named value) is initialized to the type specified in the variable's declaration.
- Constructor for Variable

```
open class Variable(val decl : NamedDecl,
                   position : Position,
                   var indexExprs : List<Expression>)
  : Expression(decl.type, position)
```

©SoftMoore Consulting

Slide 50

50

Example: Variable (continued)

- The initialized type for a variable is correct for predefined types such as Integer or Char, but additional work is required for arrays.
- Consider the following declarations:


```
type T1 is array(10) of Integer;
type T2 is array(10) of T1;
var a, b : T2;
```
- While the declared (initialized) type of both a and b is T2, we could have a variable or named value with zero, one, or two index expressions, as in the following:


```
a := b;           // type of var and named val is T2
a[0] := b[0];      // type of var and named val is T1
a[1][6] := b[5][7]; // type of var and named val is Integer
```

©SoftMoore Consulting

Slide 51

51

Example: Variable (continued)

- For arrays, we determine the actual type of a variable or named value in method checkConstraints().

```
for (expr in indexExprs)
{
  expr.checkConstraints()

  if (expr.type != Type.Integer)
    throw error(...)

  if (type is ArrayType)
  {
    val arrayType as ArrayType
    type = arrayType.elementType
  }
  else
    throw error(...);
}
```

©SoftMoore Consulting

Slide 52

52

Maintaining Context During Parsing

- Certain CPRL statements need access to an enclosing context for constraint checking and code generation.
- Example: exit when $n > 10$;
An exit statement has meaning only when nested inside a loop., and code generation for an exit statement requires knowledge of which loop encloses it.
- Similarly, a return statement needs to know which subprogram it is returning from.
- Classes LoopContext and SubprogramContext will be used to maintain contextual information in these cases.

©SoftMoore Consulting

Slide 53

53

Class LoopContext

```
/**
 * The loop statement currently being parsed;
 * null if not currently parsing a loop.
 */
val loopStmt : LoopStmt?

/**
 * Called when starting to parse a loop statement.
 */
fun beginLoop(stmt : LoopStmt)

/**
 * Called when finished parsing a loop statement.
 */
fun endLoop()
```

©SoftMoore Consulting

Slide 54

54

Class SubprogramContext

```
/**
 * The subprogram declaration currently being parsed;
 * null if not currently parsing a subprogram.
 */
var subprogramDecl : SubprogramDecl? = null

/**
 * Called when starting to parse a subprogram declaration.
 */
fun beginSubprogramDecl(subprogDecl : SubprogramDecl)

/**
 * Called when finished parsing a subprogram declaration.
 */
fun endSubprogramDecl()
```

©SoftMoore Consulting

Slide 55

55

Example: Using Context During Parsing

- When parsing a loop statement:


```
val stmt = LoopStmt()
...
loopContext.beginLoop(stmt)
stmt.statements = parseStatements()
loopContext.endLoop()
```
- When parsing an exit statement:


```
val loopStmt = loopContext.loopStmt ?: throw
    error(exitPosition,
        "Exit statement is not nested within a loop.")
match(Symbol.semicolon)
return ExitStmt(whenExpr, loopStmt)
```

©SoftMoore Consulting

Slide 56

56

Version 3 of the Parser (Abstract Syntax Trees)

- Create AST classes in package "...ast"
- Add generation of AST structure; i.e., parsing methods should return AST objects or lists of AST objects.
- Use empty bodies when overriding abstract methods `checkConstraints()` and `emit()`.
- Use complete version of `IdTable` to check for scope errors.
- Use class `Context` to check exit and return statements.

At this point your compiler should accept all legal programs and reject most illegal programs. Some programs with type or other miscellaneous errors will not yet be rejected.

©SoftMoore Consulting

Slide 57

57