Mu Namespace

mu version *0.0.14*

Type keywords

T	type superclass
`:t :nil`	*bool*
`:char`	*char*
`:cons`	*cons, list (cons* or **`:nil`**)
`:fixnum`	*fix,* 61 bit signed integer
`:float`	*float,* 32 bit IEEE float
`:func`	*fn,* function
`:ns`	*ns, symbol* bindings
`:stream`	*stream,* file, string
`:struct`	*struct,* general *vector*
`:symbol`	LISP-1 binding: *symbol, keyword*
`:vector`	*vector, string* (**`:char`**) **`:t :byte :fixnum :float`**

Heap

hp-info	*vector,* of type allocations **`:type :total :alloc :in-use`**

Frame

fr-get *fn*	*struct,* copy frame binding
fr-pop *fn*	*function*, pop frame binding
fr-push *struct*	*struct,* push frame binding
:fr-ref *fix fix'*	*T,* ref frame variable

Reader/Printer

read *stream bool T*	*T,* read stream object
write *T bool stream*	*T,* write escaped object

Structs

struct *type list*	*struct,* from list
st-type *vector*	*keyword,* struct type
st-vec *vector fix*	*vector,* of members

Symbols

boundp *symbol*	*bool,* is *symbol* bound?
keyp *symbol*	*bool, keyword* predicate
keyword *string*	*symbol, keyword* from *string*
symbol *string*	*symbol,* uninterned *symbol*
sy-ns *symbol*	*ns, symbol namespace*
sy-name *symbol*	*string, symbol* name binding
sy-val *symbol*	*T,* value binding

Special Forms

:lambda *list . body*	*function,* anonymous
:quote *T*	*list,* quote form
:if *T T' T"*	*T,* conditional

Core

coerce *T keyword*	*T, coerce* to type keyword
eval *T*	*T,* evaluate form
eq *T T'*	*bool,* are *T* and *T'* identical?
type-of *T*	*keyword*
apply *fn list*	*T,* apply *function* to arg *list*
compile *T*	*T,* library form compiler
tag-of *T*	*fixnum,* of object tag
view *T*	*struct,* vector of object
fix *fn T*	*T,* fixpoint of *function*
:if *T fn fn'*	*T,* **:if** implementation
:frames	*cons,* active frame list
***:gc**	*bool,* garbage collection

Fixnums

fx-mul *fix fix'*	*fixnum,* product
fx-add *fix fix'*	*fixnum,* sum
fx-sub *fix fix'*	*fixnum,* difference
fx-lt *fix fix'*	*bool,* is *fix* less than *fix'?*
fx-div *fix fix*	*fixnum,* quotient
logand *fix fix'*	*fixnum,* bitwise *and*
logor fix fix'	*fixnum,* bitwise *or*

Floats

fl-mul *float float'*	*float,* product
fl-add *float float'*	*float,* sum
fl-sub *float float'*	*float,* difference
fl-lt *float float'*	*bool,* is *float* less than *float'?*
fl-div *float float'*	*float,* quotient

Lists

car *list*	*list,* head of *list*
cdr *list*	*list,* tail of *list*
cons *T T'*	*cons,* from *T* and *T'*
length *list*	*fixnum,* length of *list*
nth *fix list*	*T,* nth *car* of *list*
nthcdr *fix list*	*T,* nth *cdr* of *list*

Vectors

vector *keyword list*
vector, typed vector of list

sv-len *vector*	*fixnum,* length of *vector*
sv-ref *vector fix*	*T, nth* element
sv-type *vector*	*keyword,* type of *vector*

Namespaces

make-ns *string ns*
ns, make *namespace*
map-ns *string* *ns,* map *string* to namespace

intern *ns* `scope` *string value*
symbol, intern bound symbol
`scope` **`:intern :extern`**

ns-find *ns* `scope` *string*
symbol, map *string* to *symbol*
`scope` **`:intern :extern`**

ns-imp *ns*	*ns, namespace's* import
ns-name *ns*	*string, namespace's* name
ns-int *ns*	*list, namespace's* interns
ns-ext *ns*	*list, namespace's* externs

Streams

std-in *symbol,* standard input *stream*
std-out *symbol,* standard output *stream*
err-out *symbol,* standard error *stream*

open *type dir string*
stream, open *stream*
type `:file` | `:string`
dir `:input` | `:output`

close *stream* *bool,* close *stream*
openp *stream* *bool,* is *stream* open?
eof *stream* *bool,* is *stream* at end of file?

flush *stream* *bool,* flush output steam

get-str *stream* *string,*
get *string* from *string stream*

rd-byte *stream bool T*
byte, read *byte* from *stream*
wr-byte *byte stream*
byte, write *byte* to *stream*

rd-char *stream bool T*
char, read *char* from *stream*
wr-char *char stream*
char, write *char* to *stream*
un-char *char stream*
char, push *char* onto *stream*

Exceptions

with-ex *fn fn'* *T,* catch exception
fn `(:lambda (`*T keyword*`) .` *body*`)`
fn' `(:lambda () .` *body*`)`

raise ***T*** *keyword* raise exception with condition

Condition Keywords

```
:arity   :eof    :open   :read
:write   :error  :syntax :type
:unbound :div0   :range  :stream
:except
```

Rust API

```
use crate::mu::core::mu::{
    Exception,
    Extern,
    Mu,
    MuCondition,
    Tag
},

<Mu as Extern>::new(config: String) -> Mu
        config: comma-separated list of
                name:value pairs
        heap:npages
        gc:on|off

&'static str <Mu as Extern>::VERSION

pub trait Export for Mu {
  fn nil() -> Tag

  fn eq(tag: Tag, tag1: Tag) -> bool

  fn apply(&self, func: Tag, args) →
            Exception::Result<Tag>

  fn compile(&self, expr: Tag) ->
            Exception::Result<Tag>

  fn eof(&self, stream: Tag) ->
        Exception::Result<Tag>

  fn eval(&self, expr: Tag) ->
         Exception::Result<Tag>

  fn read_stream(&self, stream: Tag,
                eof: Tag,
                eof_value: Tag) ->
                Exception::Result<Tag>

  fn read_string(&self, expr: String) ->
                Exception::Result<Tag>

  fn write(&self, expr: Tag,
                escape: bool,
                stream: Tag) ->
           Exception::Result<()>

  fn write_string(&self, string: String,
                         stream: Tag) ->
                Exception::Result<()>
}
```

Reader Syntax

`;`	comment to end of line
`#|...|#`	block comment
`(…)`	constant list
`()`	empty list, prints as `:nil`
`` ` ``	quoted form
`"…"`	string/char vector
`#x`	hexadecimal *fixnum*
`#\`	character
`#(:vector-type …)`	*vector*
`#s(:struct-type …)`	*struct*
`#:symbol`	uninterned *symbol*
`\`	single escape in strings
`"`,;`	terminating macro char
`#`	non-terminating macro char

`!$%&*+-.` symbol constituent:
`<>=?@[]|`
`:^_{}~/`
`A..Za..z`
`0..9`
`backspace`
`rubout`

`0x09 tab` whitespace:
`0x0a linefeed`
`0x0c page`
`0x0d return`
`0x20 space`

Runtime

```
runtime: 0.0.10: [-h?psvcedlq] [file...]
  ?: usage message
  h: usage message
  c: [name:value,…]
  d: enable debugging
  e: eval [form] and print result
  l: load [path]
  p: pipe mode
  q: eval [form] quietly
  s: script mode
  v: print version and exit
```